

Course Revision

CS4248 Natural Language Processing

Week 13

Min-Yen KAN

13

Slide Credit: David Bamman (UC Berkeley)

How do you go out and solve **new** problems
involving text?

Slide Credit: David Bamman (UC Berkeley)

1. Language has **structure**

Slide Credit: David Bamman (UC Berkeley)

“... is a film which still causes real, not figurative, chills to run along my spine, and it is certainly the bravest and most ambitious fruit of Coppola's genius”

Roger Ebert, *Apocalypse Now*

“I hated this movie. Hated hated hated hated hated this movie. Hated it. Hated every simpering stupid vacant audience-insulting moment of it. Hated the sensibility that thought anyone would like it.”

Roger Ebert, *North*

Slide Credit: David Bamman (UC Berkeley)

Bag of Words

Representation of text
only as the counts of
words that it contains

	Apocalypse Now	North
the	1	1
of	0	0
hate	0	9
genius	1	0
bravest	1	0
stupid	0	1
like	0	1
...		

Slide Credit: David Bamman (UC Berkeley)


Language Model

“Hillary Clinton seemed to add Benghazi to her already-long list of culprits to blame for her upset loss to Donald _____”


Slide Credit: David Bamman (UC Berkeley)
Source Text: <http://www.foxnews.com/politics/2017/09/13/clinton-laments-how-benghazi-tragedy-hurt-her-politically.html>

POS Tagging

Labeling the tag that is correct **for the context**.



Fruit flies like a banana.



Time flies like an arrow.

Slide Credit: David Bamman (UC Berkeley)

Word Senses

original	It urged that the city take steps to remedy this problem
lemma sense	It urge ¹ that the city ² take ¹ step ¹ to remedy ¹ this problem ²
synset number	It urge ^{2:32:00} that the city ^{1:15:01} take ^{2:41:04} step ^{1:04:02} to remedy ^{2:30:00} this problem ^{1:10:00}

Slide Credit: David Bamman (UC Berkeley)


Thematic Roles

The thematic roles for verbs generally are predictable by the syntactic position of the argument (specific to each verb class). Some allow for consistent alternations:



Slide Credit: David Bamman (UC Berkeley)

Phrase Structure Syntax



Every internal node is a phrase

my pajamas

in my pajamas

elephant in my pajamas

an elephant in my pajamas


shot an elephant in my pajamas

I shot an elephant in my pajamas

Each phrase could be
replaced by another of the
same type of constituent

Slide Credit: David Bamman (UC Berkeley)

Compositional Semantics



Slide Credit: David Bamman (UC Berkeley)

Coreference

LUKE
I'll never join **you!**

VADER
If you only knew the power of the dark side. Obi-Wan never told you what happened to **your father.**

LUKE
He told me enough! It was **you** who killed **him.**

VADER
No. **I** am **your father**

LUKE
No. No. That's not true!
That's impossible!

VADER
Search your feelings. You know it to be true.

LUKE
No! No! No!



Slide Credit: David Bamman (UC Berkeley)

2. Most new problems can be solved with a familiar **class** of algorithms

Slide Credit: David Bamman (UC Berkeley)

- Classification
Counting and normalizing (NB,
PCFG, HMM)
- Sequence Labeling
Loglinear (logistic regression,
MEMM, CRF)
- Trees
Neural (CNN, RNN, LSTM,
seq2seq, attention)
- Graphs

Slide Credit: David Bamman (UC Berkeley)

Classification

Slide Credit: David Bamman (UC Berkeley)

Bayes' Rule

Likelihood: How probable is the data given that our document is a member of y ?

Prior: How probable is a document to be a member of class y seeing any data?

$$P(y|w) = \frac{P(w|y)P(y)}{P(w)}$$

Posterior: How probable is the instance classified as a member of class y ?

Marginal: How probable is the evidence under any class?

Slide adapted from CS3244 Machine Learning

Naïve Bayes Classifier

Training a Naïve Bayes classifier consists of estimating these two quantities from training data for all classes Y

At test time, use those estimated probabilities to calculate the posterior probability of each class y and select the class with the highest probability

$$c_{MAP} = \operatorname{argmax}_{c \in \mathcal{C}} P(c|d)$$

Maximum a posteriori or mostly likely class

$$= \operatorname{argmax}_{c \in \mathcal{C}} \frac{P(d|c)P(c)}{P(d)}$$

Bayes rule

$$= \operatorname{argmax}_{c \in \mathcal{C}} P(d|c)P(c)$$

Dropping the $P(d)$ in the denominator

$$= \operatorname{argmax}_{c \in \mathcal{C}} \overbrace{P(f_1, f_2, \dots, f_n|c)}^{\text{likelihood}} \overbrace{P(c)}^{\text{prior}}$$

Document d represented as features f_1, \dots, f_n (such as word counts) BoW assumption

$$= \operatorname{argmax}_{c \in \mathcal{C}} P(f_1|c)P(f_2|c)\dots P(f_n|c)P(c)$$


Independence Assumption

$$c_{NB} = \operatorname{argmax}_{c \in \mathcal{C}} \boxed{P(c)} \prod_{f \in \mathcal{F}} \boxed{P(f|c)}$$

Equation for NB classifier

Slide Credits: David Bamman (UCB)

Logistic Regression



X = feature vector

W = coefficients

Feature	Value
the	0
and	0
bravest	0
love	0
loved	0
genius	0
not	0
fruit	1
BIAS	1

Feature	W
the	0.01
and	0.03
bravest	1.4
love	3.1
loved	1.2
genius	0.5
not	-3.0
fruit	-0.8
BIAS	-0.1

Slide Credit: David Bamman (UC Berkeley)

Features


As a discriminative classifier, logistic regression doesn't assume features are independent like Naive Bayes does.

Its power partly comes in the ability to create richly expressive features without the burden of independence.

We can represent text through features that are not just the identities of individual words, but any feature that is scoped over **the entirety of the input**.

features
contains <i>like</i>
has word that shows up in positive sentiment dictionary
review begins with " <i>I like</i> "
at least 5 mentions of positive affectual verbs (<i>like</i> , <i>love</i> , etc.)

Slide Credit: David Bamman (UC Berkeley)



We can express y as a function only of the input x
 and the weights W and V

Slide Credit: David Bamman (UC Berkeley)

Sequences

Slide Credit: David Bamman (UC Berkeley)

Sequence Labeling

Sequence labeling problems make a labeling decision at each timestep

B-PER	I-PER	O	O	O	O	B-ORG
Tim	Cook	is	the	CEO	of	Apple

0	1	0	0	0	0	1	0	0	0	0	1	0	0	0	0	0
#	b	l	a	c	k	l	i	v	e	s	m	a	t	t	e	r

Slide Credit: David Bamman (UC Berkeley)

Sequence Labeling

$$X = \{x_1, \dots, x_n\}$$

$$Y = \{y_1, \dots, y_n\}$$

For a set of inputs x with n sequential time steps, one corresponding label y_i for each x_i

Model the structure that exists between within y

Slide Credit: David Bamman (UC Berkeley)

HMM

$$P(x_1, \dots, x_n, y_1, \dots, y_n) \approx \prod_{i=1}^{n+1} P(y_i \mid y_{i-1}) \prod_{i=1}^n P(x_i \mid y_i)$$

Slide Credit: David Bamman (UC Berkeley)

Hidden Markov Model

$$P(x \mid y) = P(x_1, \dots, x_n \mid y_1, \dots, y_n)$$


$$P(x_1, \dots, x_n \mid y_1, \dots, y_n) \approx \prod_{i=1}^N P(x_i \mid y_i)$$

Here again we'll make a strong assumption: the probability of the word we see at a given time step is only dependent on its label

Slide Credit: David Bamman (UC Berkeley)

Recurrent Neural Network

Predict the tag conditioned on the context



Slide Credit: David Bamman (UC Berkeley)

Bidirectional RNN

A powerful alternative is make predictions conditioning both on the **past** and the **future**.

Two RNNs

- One running left-to-right
- One right-to-left

Each produces an output vector at each time step, which we concatenate

Slide Credit: David Bamman (UC Berkeley)

Trees

Slide Credit: David Bamman (UC Berkeley)

PCFG

Probabilistic context-free grammar: each production is also associated with a probability.

This lets us calculate the probability of a parse for a given sentence; for a given parse tree T for sentence S comprised of n rules from R (each $A \rightarrow \beta$):

$$P(T, S) = \prod_i^n P(\beta | A)$$

Slide Credit: David Bamman (UC Berkeley)

Estimating PCFGs

$$\sum_{\beta} P(\beta|A) = \frac{\text{Count}(A \rightarrow \beta)}{\sum_i \text{Count}(A \rightarrow i)}$$

Or equivalently,

$$\sum_{\beta} P(\beta|A) = \frac{\text{Count}(A \rightarrow \beta)}{\text{Count}(A)}$$

Slide Credit: David Bamman (UC Berkeley)

A		β	$P(\beta \mid \text{NP})$
NP	→	NP PP	0.092
NP	→	DT NN	0.087
NP	→	NN	0.047
NP	→	NNS	0.042
NP	→	DT JJ NN	0.035
NP	→	NNP	0.034
NP	→	NNP NNP	0.029
NP	→	JJ NNS	0.027
NP	→	QP -NONE-	0.018
NP	→	NP SBAR	0.017
NP	→	NP PP-LOC	0.017
NP	→	JJ NN	0.015
NP	→	DT NNS	0.014
NP	→	CD	0.014
NP	→	NN NNS	0.013
NP	→	DT NN NN	0.013
NP	→	NP CC NP	0.013

Slide Credit: David Bamman (UC Berkeley)

Natural Language Generation

Slide Credit: David Bamman (UC Berkeley)

Language Model

Language modeling is the task of estimating $P(w)$

- Count and normalize
- Featurized
- Neural (RNN)

Slide Credit: David Bamman (UC Berkeley)

Encoder–Decoder Framework

Language modeling: predict a word given its left context.

How about when there's some prior information?


Conditional Language Model

- Question Answering: predict an answer given its left context **and the source passage.**
- Machine translation: predict a word given its left context **and the full text of the source.**

Basic idea: **encode** some context into a fixed vector; and then **decode** a new sentence from that embedding.

Slide Credit: David Bamman (UC Berkeley)

Encoder–Decoder





Adaptedd from Chris Manning (Stanford) CS224N

Encoder–Decoder with Attention

$$c = h_1 a_1 + h_2 a_2 + h_3 a_3$$


$$s_i = f(s_{i-1}, y_{i-1}, c_i)$$



Slide Credit: David Bamman (UC Berkeley)


3. **Neural** methods are generally* better.


Slide Credit: David Bamman (UC Berkeley)



Zhang and Wallace (2016) [A Sensitivity Analysis of \(and Practitioners' Guide to\) Convolutional Neural Networks for Sentence Classification](#)

Slide Credit: David Bamman (UC Berkeley)






Goldberg (2017)

Slide Credit: David Bamman (UC Berkeley)

Attention




Slide Credit: David Bamman (UC Berkeley)

$$v \in \mathcal{R}^H$$

2.7	3.1	-1.4	-2.3	0.7
-----	-----	------	------	-----

Define v to be a vector to be learned; think of it as an “important word” vector. The dot product here measures how similar each input vector is to that “important word” vector.



Slide Credit: David Bamman (UC Berkeley)

Lexical semantics

“You shall know a word by the company it keeps”

[Firth 1957]

Slide Credit: David Bamman (UC Berkeley)

Distributed Representation

Vector representation that encodes information about the **distribution** of contexts a word appears in

Words that appear in similar contexts have similar representations (and similar meanings, by the **distributional hypothesis**).

Slide Credit: David Bamman (UC Berkeley)

4. Evaluation is critical.

Slide Credit: David Bamman (UC Berkeley)

Interannotator Agreement



Annotator 2

Annotator 1

	puppy	fried chicken
puppy	6	3
fried chicken	2	5

observed agreement = $11/16 = 68.75\%$

Slide Credit: David Bamman (UC Berkeley)
 Source Image: <https://twitter.com/teenybiscuit/status/705232709220769792/photo/1>

Experiment Design

	training	development	testing
size	80%	10%	10%
purpose	training models	model selection	evaluation; never look at it until the very end

Slide Credit: David Bamman (UC Berkeley)

Metrics

- Perplexity
- Accuracy
- Precision/Recall/ F_1
- Parseval ($P/R/F_1$ over labeled constituents)
- Correlation with human judgments
- BLEU Precision / ROUGE Recall

Slide Credit: David Bamman (UC Berkeley)

5. Text is **data**.

Slide Credit: David Bamman (UC Berkeley)

መ 3 2 Δ II ማ ቲ ም ከ

መጽሐፈ፡ልደቱ፡ለእግዚእ
ነ፡አደሱ፡ከርስቶስ፡ወል
ደ፡ዳዊት፡ወልደ፡አብርሃም፡
አብርሃም፡ወልደ፡ለዮስሐ
ት፡ወደሱሐት፡ወልደ፡ለሃዕ
ቶ፡ወደሃዕቶ፡ወልደ፡
ዮሁዳሃ፡ወአቃዊሁ፡ወደዮሁ
ዳ፡ወልደ፡ፋራስሃ፡ወዘራሃ፡
ወራሽምት፡ወማርቆ፡ወፋራስኒ፡ወ
ልደ፡አስርምሃ፡ወአስርም
ኢናኒ፡ወልደ፡አራምሃ፡ወአራ
ምኒ፡ወልደ፡አሚናና፡ወሃዕ
ወአሚናና፡ወልደ፡ነአሶ

ንሃ፡ወነአሶንኒ፡ወልደ፡ሰ
ልሞንሃ፡ወሰልሞንኒ፡ወል
ደ፡ሶሜዝሃ፡አምራኪ፡ወሶ
ሜዝኒ፡ወልደ፡አዮቢድሃ፡አ
ምነ፡ፋት፡ወአዮቢድኒ፡ወ
ልደ፡ሶሴዮሃ፡ወሶሴድኒ፡ወ
ልደ፡ዳዊትሃ፡ንጉሠ፡ወዳ
ዊትኒ፡ወልደ፡ሰለሞንሃ፡አ
ምነ፡ብእሲተ፡አርዮ፡ወሰ
ለሞንኒ፡ወልደ፡ሮብአምሃ፡
ወሮብአምኒ፡ወልደ፡አብጊ
ሃ፡ወአብጊኒ፡ወልደ፡አሳፍ
ሃ፡ወአሳፍኒ፡ወልደ፡አሃሐ

አቢሚኤ. ነገሩ
ጥሀሚ. ገ፡ም
ሰላ፡ፎ፡ወ፡ጥ
ፎ፡ወ፡ሙሀ
ሰላ፡ገ፡ክ፡ላ፡
ገ፡ወ፡ረ፡ገ፡
ደ፡ወ፡ሙሀ፡
ገ፡ፋ፡ት፡ገ፡አ
ሰላ፡ክ፡ላ፡ወ፡
ገ፡ፋ፡ገ፡አ፡
ሰላ፡፡

οὐ μομένω. ἡ μ
πομιάσ δι φθι
ἡρ ∞ ∞ μ. αὐτοῦ
οι ∞ μοι σι τθ το
Δ οὐ δι τὰ πρ




Slide Credit: David Bamman (UC Berkeley)

Keep in touch with CS4248!



Level up with us!

WING Reading Group (CS6101) Past Semesters People Links



WING.NUS
The reading group for the
WING NUS Research Group

- 📍 Singapore
- 🏫 NUS
- 🌐 Website
- 📧 Email
- 🐙 Github
- 📺 YouTube

Web, IR and NLP Public Reading Group

Our reading group will be conducted as a group seminar, with class participants nominating themselves and presenting the materials and leading the discussion. In the Sem II of AY2020/2021, we will focus on the topics of

Conversational Systems, Recommender Systems and their intersections.

There will be 7 reading sessions, which will be held from 1 pm to 3 pm on Friday biweekly. On alternate Thursdays 1-3 pm, we will have project consultation sessions. Please see the detailed schedule in the table.

[A mandatory discussion group is on Slack.](#) Students and guests, please login when you are free. If you have a @comp.nus.edu.sg, @u.nus.edu, @nus.edu.sg, @a-star.edu.sg, @dsi.a-star.edu.sg or @i2r.a-star.edu.sg. email address you can create your Slack account for the discussion without needing an invite.

For interested public participants, please send Min an email at kanmy@comp.nus.edu.sg if you need an invite to the Slack group. The Slack group is being reused from previous semesters. Once you are in the Slack group, you can consider yourself registered for the group.

<https://wing-nus.github.io/cs6101/>

Goodbye!