

# 261kWh Outdoor Integrated Cabinet

Multidimensional Safety | High Efficiency & Economy | Full-Scene Adaptability



Note: Product color, shape, interface and functions are for reference only. The actual product may vary.

## Multidimensional Safety

- Cell-intrinsic safety certified by IEC/UL9540A prevents thermal runaway propagation.
- Integrated PCS and HV box design optimizes high-voltage circuits to eliminate terminal overheating risks.
- Aerospace-grade aerosol (1s response) plus water fire suppression provide dual redundancy meeting NFPA855 requirements.

## High Efficiency & Economy

- Proprietary high-efficiency 314Ah cells deliver superior system energy density.
- Vertical single-row structural design, reducing the footprint by more than 20%.
- IP65 liquid-cooled PCS ensures reliability with 90%+ system efficiency.
- Suspension-type power cabinets enable five-unit parallel operation and station grouping, saving busbar space.

## Full-Scene Adaptability

- Integrated vertical single-row structure supports plug-and-play deployment and multi-cabinet flexible expansion.
- IP55 + C5H corrosion resistance withstands harsh environments including salt mist and high humidity.
- Precise compliance with US/EU/AU standards ensures full market-specific requirements fulfillment.

# Product Parameter

## Cell

| Item             | Specification |
|------------------|---------------|
| Cell Model       | MB31          |
| Nominal Capacity | 314Ah         |
| Dimension(D*W*H) | 72*174*207mm  |
| Weight           | 5600±300g     |
| Energy Density   | 179 Wh/kg     |
| Rated Voltage    | 3.2V          |
| Voltage Range    | 2.5V~3.65V    |

## Module

| Item                                   | Specification              |
|----------------------------------------|----------------------------|
| Module                                 | P531H202                   |
| Dimension(D*W*H)                       | 1160*780*240 mm            |
| Weight                                 | 345±5 kg                   |
| Configuration                          | 1P52S                      |
| Rated Energy                           | 52.25kWh                   |
| Rated Voltage                          | 130V~189.8V                |
| Voltage Range                          | 166.4V                     |
| Standard Charging and Discharging Rate | 0.5P                       |
| Level of Protection                    | IP67                       |
| Thermal Management                     | Liquid Cooling and Heating |
| Certification                          | UN38.3, UL9540A            |

## System

| Item                                   | Specification                                                         |
|----------------------------------------|-----------------------------------------------------------------------|
| Number of Module                       | 5                                                                     |
| Dimension(D*W*H)                       | 1420*1000*2250mm                                                      |
| Weight                                 | ~2720kg                                                               |
| Configuration                          | 1P260S                                                                |
| Rated Energy                           | 261kWh                                                                |
| Rated Voltage                          | DC 832V                                                               |
| Voltage Range                          | DC 728~949V                                                           |
| Standard Charging and Discharging Rate | ≤0.5P                                                                 |
| Operating Temperature Range            | -20~55°C                                                              |
| Level of Protection                    | IP55                                                                  |
| Thermal Management                     | Liquid Cooling and Heating                                            |
| Fire Suppression System                | Cabinet-level space fire suppression with external water-based backup |
| Anticorrosion Grade                    | C5H                                                                   |
| PCS Power                              | 125KW                                                                 |
| AC-Side Voltage                        | 400/480V                                                              |
| Off-Grid Operation                     | Support                                                               |

Note: The above data are from EVE Laboratory

