```
mysql> SELECT S.STDNAME,A.SCORE FROM STUDENT S JOIN ASSESSMENT
 A ON S.REGNO = A.REGNO WHERE A.SCORE > (SELECT AVG(SCORE) FRO
M ASSESSMENT);
+---------+-------+
| STDNAME | SCORE |
+---------+-------+
| Anish   |    85 |
| Anish   |    90 |
| Ramya   |    95 |
| Priya   |    75 |
+---------+-------+
4 rows in set (0.01 sec)
```

```
mysql> SELECT S.REGNO, S.STDNAME FROM STUDENT S WHERE (SELECT COUNT(*) F
ROM ASSESSMENT A WHERE A.REGNO =S.REGNO ) > 1;
+-------+---------+
| REGNO | STDNAME |
+-------+---------+
| S001  | Anish   |
| S002  | Harish  |
+-------+---------+
2 rows in set (0.01 sec)
```

```
mysql> SELECT FACULTYNAME, DATEOFJOINING FROM FACULTY WHERE DATEOFJOININ
G =(SELECT MAX(DATEOFJOINING) FROM FACULTY );
+-------------+---------------+
| FACULTYNAME | DATEOFJOINING |
+-------------+---------------+
| Kiran       | 2024-08-20    |
+-------------+---------------+
1 row in set (0.00 sec)
```

```
mysql> SELECT A.CourseID, A.Score
    -> FROM ASSESSMENT A
    -> WHERE A.Score > (
    ->     SELECT AVG(B.Score)
    ->     FROM ASSESSMENT B
    ->     WHERE B.CourseID = A.CourseID
    -> );
+----------+-------+
| CourseID | Score |
+----------+-------+
| C001     |    85 |
| C002     |    90 |
| C001     |    95 |
+----------+-------+
3 rows in set (0.00 sec)
```