```
mysql> CREATE TABLE DEPARTMENT (
    ->     DeptID INT PRIMARY KEY,
    ->     DeptName VARCHAR(50) UNIQUE NOT NULL
    -> );
Query OK, 0 rows affected (0.14 sec)

mysql> desc DEPARTMENT;
+----------+-------------+------+-----+---------+-------+
| Field    | Type        | Null | Key | Default | Extra |
+----------+-------------+------+-----+---------+-------+
| DeptID   | int         | NO   | PRI | NULL    |       |
| DeptName | varchar(50) | NO   | UNI | NULL    |       |
+----------+-------------+------+-----+---------+-------+
2 rows in set (0.06 sec)

mysql> INSERT INTO DEPARTMENT VALUES
    -> (1, 'CSE'),
    -> (2, 'ECE'),
    -> (3, 'EEE');
Query OK, 3 rows affected (0.03 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM DEPARTMENT;
+--------+----------+
| DeptID | DeptName |
+--------+----------+
|      1 | CSE      |
|      2 | ECE      |
|      3 | EEE      |
+--------+----------+
3 rows in set (0.00 sec)

mysql>
```

```
mysql> CREATE TABLE FACULTY (
    ->     FacultyID INT PRIMARY KEY,
    ->     FacultyName VARCHAR(50),
    ->     DeptID INT,
    ->     FOREIGN KEY (DeptID) REFERENCES DEPARTMENT(DeptID)
    -> );
Query OK, 0 rows affected (0.05 sec)

mysql> DESC FACULTY;
+-------------+-------------+------+-----+---------+-------+
| Field       | Type        | Null | Key | Default | Extra |
+-------------+-------------+------+-----+---------+-------+
| FacultyID   | int         | NO   | PRI | NULL    |       |
| FacultyName | varchar(50) | YES  |     | NULL    |       |
| DeptID      | int         | YES  | MUL | NULL    |       |
+-------------+-------------+------+-----+---------+-------+
3 rows in set (0.00 sec)

mysql> INSERT INTO FACULTY VALUES
    -> (101, 'Ramesh', 1),
    -> (102, 'Suresh', 2),
    -> (103, 'Priya', 3);
Query OK, 3 rows affected (0.01 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM FACULTY;
+-----------+-------------+--------+
| FacultyID | FacultyName | DeptID |
+-----------+-------------+--------+
|       101 | Ramesh      |      1 |
|       102 | Suresh      |      2 |
|       103 | Priya       |      3 |
+-----------+-------------+--------+
3 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE COURSE (
    ->     CourseID INT PRIMARY KEY,
    ->     CourseName VARCHAR(50),
    ->     DeptID INT,
    ->     FOREIGN KEY (DeptID) REFERENCES DEPARTMENT(DeptID)
    -> );
Query OK, 0 rows affected (0.04 sec)

mysql> DESC COURSE;
+------------+-------------+------+-----+---------+-------+
| Field      | Type        | Null | Key | Default | Extra |
+------------+-------------+------+-----+---------+-------+
| CourseID   | int         | NO   | PRI | NULL    |       |
| CourseName | varchar(50) | YES  |     | NULL    |       |
| DeptID     | int         | YES  | MUL | NULL    |       |
+------------+-------------+------+-----+---------+-------+
3 rows in set (0.00 sec)

mysql> INSERT INTO COURSE VALUES
    -> (201, 'DBMS', 1),
    -> (202, 'Networks', 2),
    -> (203, 'Circuits', 3);
Query OK, 3 rows affected (0.01 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM COURSE;
+----------+------------+--------+
| CourseID | CourseName | DeptID |
+----------+------------+--------+
|      201 | DBMS       |      1 |
|      202 | Networks   |      2 |
|      203 | Circuits   |      3 |
+----------+------------+--------+
3 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE STUDENT2 (
    ->     RegNo INT PRIMARY KEY,
    ->     Name VARCHAR(50),
    ->     DeptID INT,
    ->     FOREIGN KEY (DeptID) REFERENCES DEPARTMENT(DeptID)
    -> );
Query OK, 0 rows affected (0.04 sec)

mysql> DESC STUDENT2;
+--------+-------------+------+-----+---------+-------+
| Field  | Type        | Null | Key | Default | Extra |
+--------+-------------+------+-----+---------+-------+
| RegNo  | int         | NO   | PRI | NULL    |       |
| Name   | varchar(50) | YES  |     | NULL    |       |
| DeptID | int         | YES  | MUL | NULL    |       |
+--------+-------------+------+-----+---------+-------+
3 rows in set (0.00 sec)

mysql> INSERT INTO STUDENT2 VALUES
    -> (1001, 'Anish', 1),
    -> (1002, 'Rahul', 2),
    -> (1003, 'Kiran', 3);
Query OK, 3 rows affected (0.01 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM STUDENT2;
+-------+-------+--------+
| RegNo | Name  | DeptID |
+-------+-------+--------+
|  1001 | Anish |      1 |
|  1002 | Rahul |      2 |
|  1003 | Kiran |      3 |
+-------+-------+--------+
3 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE STUDENT3 (
    ->     StudentID INT PRIMARY KEY,
    ->     RegNo INT,
    ->     Age INT,
    ->     FOREIGN KEY (RegNo) REFERENCES STUDENT2(RegNo)
    -> );
Query OK, 0 rows affected (0.04 sec)

mysql> DESC STUDENT3;
+-----------+------+------+-----+---------+-------+
| Field     | Type | Null | Key | Default | Extra |
+-----------+------+------+-----+---------+-------+
| StudentID | int  | NO   | PRI | NULL    |       |
| RegNo     | int  | YES  | MUL | NULL    |       |
| Age       | int  | YES  |     | NULL    |       |
+-----------+------+------+-----+---------+-------+
3 rows in set (0.00 sec)

mysql> INSERT INTO STUDENT3 VALUES
    -> (1, 1001, 19),
    -> (2, 1002, 20),
    -> (3, 1003, 19);
Query OK, 3 rows affected (0.01 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> SELECT * FROM STUDENT3;
+-----------+-------+------+
| StudentID | RegNo | Age  |
+-----------+-------+------+
|         1 |  1001 |   19 |
|         2 |  1002 |   20 |
|         3 |  1003 |   19 |
+-----------+-------+------+
3 rows in set (0.00 sec)
```