

23VLS1401: Microcontroller and Computer architecture
Lecture 2 (U2)

**Data Transfer instructions and
programming for Microprocessor 8085**

A presentation by

Dr. Shubhangi Rathkanthiwar

Professor

Department of Electronics Engineering, YCCE, Nagpur, India




Session objectives

- To overview various software instructions related to the process of data transfer
- To develop the programming technique in assembly language for given problem statement, store the source data, execute the program and observe the result in destination register or memory location.

Data Transfer instructions

- MOV
- MVI
- LDA
- STA
- LDAX
- STAX
- LXI
- LHLD
- SHLD
- XCHG

Flag register and instructions related to various flags required in decision making



Jump Instructions

Opcode	Operand	Meaning	Explanation	Addressing mode
JMP	16 bits address /Label	Unconditional jump	Jump to the address specified in the instruction	Implicit addressing mode
JC		Jump on carry	Jump to the specified address if carry flag is set	
JNC		Jump on no carry	Jump to the specified address if carry flag is reset	
JZ			Jump to the specified address if Zero flag is set	
JNZ			Jump to the specified address if Zero flag is reset	

Programming Examples

Problem Statement 1: A block of 5 data bytes is stored in memory locations starting at 2501H. Write an Assembly language Program to copy the block from memory locations starting at 2601H.

```
LXI H,2501H
LXI D,2601H
MVI C,05H
L1: MOV A,M
    STAX D
    INX H
    INX D
    DCR C
JNZ L1
HLT
```

Programming Examples

Problem Statement 2: A block of 5 data bytes is stored in memory locations starting at 2501H. Write an Assembly language Program to copy the block from memory locations starting at 2601H in reverse order.

LXI H,2501H

LXI D,2605H

MVI C,05H

L1: MOV A,M

STAX D

INX H

DCX D

DCR C

JNZ L1

HLT

Programming Examples

Problem Statement 3: In a sugar industry, 10 viscosity readings are recorded in 16 bits in microprocessor based system in memory locations starting at 2501H. Higher order 8 bits are stored first, followed by lower order readings. Higher bytes are common for all the readings. Write a program to transfer lower order bytes only in memory locations starting at 2601H.

LXI H,2501H

LXI D,2601 H

MVI C,05H

L1: INX H

MOV A,M

STAX D

INX H

DCX D

DCR C

JNZ L1

HLT

Programming Examples

Problem Statement 4: 10 data bytes are stored from 2501H. WAP to shift the string by 5 positions in order to insert new data from 2501H.

LXI H,250AH

LXI D,260F H

MVI C,05H

L1: MOV A,M

STAX D

DCX H

DCX D

DCR C

JNZ L1

HLT

Thank
you