

Name: Yash Kesharwani

Academic Year: 2021-22

Roll No: 3

Class- MSC CS Part I

Subject:

Design and implementation of Modern Compilers

INDEX

SR NO	TITLE
1	Write a program to construct NDFA
2	Write a program to convert the given Right linear Grammar to Left Linear Grammar.
3	Write a code to generate DAG for input arithmetic expression.
4	Write a code to for triples.
5	Write a code for postfix evaluation.
6	Write a code to generate 3 address code
7	Write a code to demonstrate loop jamming for the given code sequence containing loop.
8	Write a code to demonstrate loop unrolling for the given code sequence containing loop.


Practical NO 1

Aim : Write a program to construct NDFA

Install package automata-lib

By using the following command:

```
pip install automata-lib
```



```
D:\Python>
D:\Python>pip install automata-lib
Collecting automata-lib
  Downloading automata_lib-5.0.0-py3-none-any.whl (32 kB)
Collecting pydot
  Downloading pydot-1.4.2-py2.py3-none-any.whl (21 kB)
Collecting pyparsing>=2.1.4
  Downloading pyparsing-3.0.7-py3-none-any.whl (98 kB)
----- 98.0/98.0 KB 622.8 kB/s eta 0:00:00
Installing collected packages: pyparsing, pydot, automata-lib
Successfully installed automata-lib-5.0.0 pydot-1.4.2 pyparsing-3.0.7
```

Code:

```
from automata.fa.nfa import NFA
```

```
class NDFA:
```

```
    def __init__(self):
```

```
        state_set = set(input("Enter state set>\t")) input_symbols =
```

```
set(input("Enter input symbol set>\t")) initial_state =
```

```
input("Enter the initial state>\t") final_states =
```

```
set(input("Enter the final state(s)>\t"))
```

```
    rule_count = int(input("Enter the number of rules you
want to add>\t"))
```

```
    rules = []
```

```
for counter in range(rule_count):  
    rules.append(input("Enter rule " + str(counter + 1) +  
">\t").replace(" ", ""))  
rules = self.get_transitions(rules)
```

```
self.nfa = NFA(  
    states = state_set,  
    input_symbols = input_symbols,  
    transitions = rules,  
    initial_state = initial_state,  
    final_states = final_states  
)  
del state_set, input_symbols, initial_state, final_states,  
rules.
```

```
def get_transitions(self, rules):  
    rules = [i.split("-") for i in rules]  
    rules_dict = {}  
  
    for rule in rules:  
        if rule[0] not in rules_dict:  
            rules_dict[rule[0]] = {rule[1][1]:rule[1][0]}
```

```
print("If:", rules_dict)
else:
    rules_dict[rule[0]][rule[1][0]] = rule[1][1]
print("Else:", rules_dict)
return rules_dict
```

```
def print_stats(self):
    print("\n\nSet of states are > ", self.nfa.states)
    print("Input symbols are > ", self.nfa.input_symbols)
    print("Transitions are > ")
    for transition in self.nfa.transitions:
        print(transition, self.nfa.transitions[transition])
    print("Initial state > ", self.nfa.initial_state)
    print("Final states > ", self.nfa.final_states)
    def print_transition_table(self):
        input_symbols = list(self.nfa.input_symbols)
        transitions = self.nfa.transitions
```

```
print("\n\nTransition table is > ")
```

```
#print(f"States\t\t{input_symbols[0]}\t\t{input_symbols[1]}")
print("States\t\t" + str(input_symbols[0]) + "\t\t" +
```

```

str(input_symbols[1]))
for transition in transitions:
    for input_symbol in input_symbols:
        try:
            temp = transitions[transition][input_symbol] del temp
        except KeyError:
            transitions[transition][input_symbol] = "-"

#print(f"{transition}\t\t{transitions[transition][input_symbols
[0]]}\t\t{transitions[transition][input_symbols[1]]}")

print(transition + "\t\t" +
transitions[transition][input_symbols[0]] + "\t\t" +
transitions[transition][input_symbols[1]])

del input_symbols, transitions

if __name__ == "__main__":
    ndfa = NDFA()
    ndfa.print_stats()
    ndfa.print_transition_table()
Output:

```

```

Enter state set> WAM
Enter input symbol set> 01
Enter the initial state> W
Enter the final state(s)> M
Enter the number of rules you want to add> 3
Enter rule 1> W - 0A
Enter rule 2> A - 1M
Enter rule 3> M - 0W
If: {'W': {'0': 'A'}}
If: {'W': {'0': 'A'}, 'A': {'1': 'M'}}
If: {'W': {'0': 'A'}, 'A': {'1': 'M'}, 'M': {'0': 'W'}}
Set of states are > {'W', 'A', 'M'}
Input symbols are > {'1', '0'}
Transitions are >
W {'0': 'A'}
A {'1': 'M'}
M {'0': 'W'}
Initial state > W
Final states > {'M'}
Transition table is >
States      1      0
W           -      A
A           M      -
M           -      W

```

PRACTICAL NO 2

Aim: Write a program to convert the given Right linear grammar to Left Linear Grammar form.

CODE:

```

def get_transitions(rules):

    my_dict={}

    Id=""

    res=dict()

    r=""

    for i in rules:

        my_dict[i[0]]=[[i[1][1],i[1][0]]

```

```

for sub in my_dict:
    if isinstance(my_dict[sub],list):
        res[sub]=ld.join([str(ele) for ele in my_dict[sub]])
print("Left linear grammar is:")

for item in res:
    r+=item+"-"+str(res[item])+"\n"

print(str(r))


rule_count=int(input("Enter rule count>\t"))
rules=[]

for i in range(rule_count):
    rules.append(input("Enter right linear grammar"+">\t"))

rules=[i.split("->") for i in rules]

print(rules)

get_transitions(rules)

```

OUTPUT:

```
= RESTART: C:\Users\Admin\Desktop\MSC CS\SEM 2\Compiler\Practicals\Practical 2(A
).py
Enter rule count> 2
Enter right linear grammar> S->uP
Enter right linear grammar> T->qW
[['S', 'uP'], ['T', 'qW']]
Left linear grammar is:
Left linear grammar is:
S-Pu
T-Wq
```

PRACTICAL NO 3

Aim: Write a code to generate DAG for input arithmetic expression.

CODE:

```
def funct1(x):

    main=[]

    for i in range(0,x):

        y=input()

        main.append(y)

        print("Label Operator left Right")

        for i in range(0,x):

            q=main[i]

            if q[0] not in res:

                res.append(q[0])

            if(len(q)>3):
```



```
print(" ",q[0]," ",q[3]," ",q[2]," ",q[4]) else:
print(" ",q[0]," ",q[1]," ",q[2]," ")
print(main)

print(res)
print("Enter number of 3 address code")

x=input()
x=int(x)

res=[]

funct1(x)
```

Output:

```

= RESTART: C:/Users/Admin/Desktop/Msc CS/
Enter number of 3 address code
4
t=a-b
r=a-c
o=t*r
q=o
Label Operator left Right
      t      -      a      b
      r      -      a      c
      o      *      t      r
      q      =      o
['t=a-b', 'r=a-c', 'o=t*r', 'q=o']
['t', 'r', 'o', 'q']

```

PRACTICAL NO 4

Aim: Write a code for triples.

Code:

```
def funct1(x):
```

```
    main=[]
```

```
    for i in range(0,x):
```

```
        y=input()
```

```
        main.append(y)
```

```
        print("Address operator argument 1 argument2")
```

```
    for i in range(0,x):
```

```
        g=main[i]
```

```

if g[0] not in res:
    res.append(g[0])
    e=funct2(g[2])
    if(len(g)>3):
        r=funct2(g[4])
        print("(",i,")", " ",g[3], " ",e, " ",r) else:
            print("(",i,")", " ",g[1], " ",e, " ")
    print(main)

print(res)

def funct2(g):
    try:
        z=res.index(g)
        return(z)
    except:
        return(g)

print("Enter number of
production") x=input()

x=int(x)

res=[]

```

funct1(x)

Output:

```
y
Enter number of production
4
t=a-b
u=a-c
w=t*u
e=w
Address operator argument 1 argument2
( 0 )      -      a      b
( 1 )      -      a      c
( 2 )      *      0      1
( 3 )      =      2
['t=a-b', 'u=a-c', 'w=t*u', 'e=w']
['t', 'u', 'w', 'e']
|
```

PRACTICAL NO 5

Aim: Write the code for Postfix Evaluation

CODE:

```
def postfix_evaluation(s):
```

```
    s=s.split()
```

```
    n=len(s)
```

```
    stack=[]
```

```
    for i in range(n):
```

```
        if s[i].isdigit():
```

```
stack.append(int(s[i]))  
elif s[i]=="+":  
    a=stack.pop()  
    b=stack.pop()  
    stack.append(int(a)+int(b)) elif  
s[i]=="*":  
    a=stack.pop()  
    b=stack.pop()  
    stack.append(int(a)*int(b)) elif  
s[i]=="/":  
    a=stack.pop()  
    b=stack.pop()  
    stack.append(int(a)/int(b))  
elif s[i]=="-":  
    a=stack.pop()  
    b=stack.pop()  
    stack.append(int(a)-int(b))  
return stack.pop()
```

```
s="8 7 8 * + 4 -"  
val=postfix_evaluation(s)  
print(val)
```

OUTPUT:

```
Y  
-60  
|
```

PRACTICAL NO 6

Aim: Write a code to generate 3 address code

Code:


```
postfix=input("Enter postfix expression").split()  
operators=['+', '-', '/', '*', '^']  
stack=[]  
result=""  
str1=""  
count=0  
print("3 address code")
```

```

for i in postfix:
    if i not in operators:
        stack.append(i)
        print("Stack-",stack)
    else:
        op1=stack.pop()
        op2=stack.pop()
        result=op2+i+op1
        str1='T'+str(count)
        stack.append(str1)
        print("T",count,"=",result)
        count+=1

```

Output:



```

y
Enter postfix expression a b c + / d *
3 address code
Stack- ['a']
Stack- ['a', 'b']
Stack- ['a', 'b', 'c']
T 0 = b+c
T 1 = a/T0
Stack- ['T1', 'd']
T 2 = T1*d
>

```

PRACTICAL NO 7

Aim: Write a program to demonstrate loop jamming for given code sequence containing loop.

Code: Loop Jamming

```
import time
```

```
from datetime import datetime
```

```
def func1(arr1,arr2,arr3):
```

```
    t1=datetime.now()
```

```
    start=time.time()
```

```
    print(t1.minute,":",t1.second,":",t1.microsecond)
```



```
for i in range (0,10000000):  
  
    sum=0  
  
    for j in range(0,len(arr1)):  
  
        sum=sum+arr1[j]  
  
        for k in range(0,len(arr2)):  
  
            sum=sum+arr2[k]  
  
            for l in range(0,len(arr3)):  
  
                sum=sum+arr3[l]  
  
            if(sum!=210):  
                print(false)  
  
  
  
tm=datetime.now()  
  
done=time.time()  
  
elapsed=done-start  
  
print(t1.minute,":",t1.second,":",t1.microsecond)  
print("First loop Difference",elapsed)  
  
  
start=time.time()
```

```
for i in range(0,10000000):  
  
    sum=0  
  
    for j in range(0,len(arr1)):  
  
        sum=sum+arr1[j]  
  
        sum=sum+arr2[j]  
  
        sum=sum+arr3[j]  
  
    if(sum!=210):  
  
        print(false)  
  
    tn=datetime.now()  
    done=time.time()  
  
    elapsed=done-start  
  
    print(t1.minute,":",t1.second,":",t1.microsecond)  
  
    print("second loop Diffrence",elapsed)
```

```
arr1=[10,20,30]  
  
arr2=[20,10,30]  
  
arr3=[40,40,10]  
  
func1(arr1,arr2,arr3)
```

OUTPUT:

```
Python 3.10.3 (tags/v3.10.3:a342a49, Mar 16 2022, 13:07:40) [MSC v.
AMD64] on win32
Type "help", "copyright", "credits" or "license()" for more inform
= RESTART: C:/Users/Admin/Desktop/Msc CS/SEM 2/Compiler/Practicals,
)-Loop Jamming.py

= RESTART: C:/Users/Admin/Desktop/Msc CS/SEM 2/Compiler/Practicals,
)-Loop Jamming.py
53 : 14 : 254787
53 : 14 : 254787
First loop Difference 21.988343715667725
53 : 14 : 254787
second loop Difference 10.30445909500122
|
```

PRACTICAL NO 8

Aim: Write a program to demonstrate loop unrolling for given code sequence containing loop.

Loop Unrolling

Code:

```
import time
```

```
from datetime import datetime
```

```
def funct1():
```

```
    arr=[]
```

```
arr1=[]  
  
t1=datetime.now()  
  
start=t1.microsecond  
  
print(start)  
  
for i in range(0,1000):  
    arr.insert(0,i)  
  
print(arr)  
  
t2=datetime.now()  
  
end1=t2.microsecond  
  
print(end1)  
for i in range(0,1000,4):  
    arr1.insert(0,i)  
  
    arr1.insert(0,i+1)  
  
    arr1.insert(0,i+2)  
  
    arr1.insert(0,i+3)  
  
print(arr1)  
  
t3=datetime.now()  
  
end2=t3.microsecond
```

```
print(end2)
```

```
print("Before unrolling:",end1-start)
```

```
print("After unrolling:",end2-end1)
```

```
func1()
```

OUTPUT:

```
----- RESTART: C:\Users\ADMIN\DO
833747
Squeezed text (54 lines).
112643
Squeezed text (54 lines).
369812
Before unrolling: -721104
After unrolling: 257169
```