```c
#include <stdio.h>
#include <stdlib.h>

struct Employee {
    int empId;
    char empName[50];
    float empSalary;
};

int main() {
    FILE *filePtr;
    struct Employee emp;

    // Open file in binary read/write mode
    filePtr = fopen("employee.dat", "rb+");

    // If file does not exist, create it
    if (filePtr == NULL) {
        filePtr = fopen("employee.dat", "wb+");
        if (filePtr == NULL) {
            printf("Error creating the file.\n");
            return 1;
        }
    }

    int choice;

    do {
        printf("\n===== Employee Database Menu =====\n");
        printf("1. Add Employee\n");
        printf("2. Display Employee Details\n");
        printf("3. Update Employee Details\n");
        printf("4. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);

        switch (choice) {
```

```c

        case 1:
            printf("Enter Employee ID: ");
            scanf("%d", &emp.empId);

            printf("Enter Employee Name: ");
            scanf("%s", emp.empName);

            printf("Enter Employee Salary: ");
            scanf("%f", &emp.empSalary);

            // Move to correct position using random access
            fseek(filePtr, (emp.empId - 1) * sizeof(struct Employee), SEEK_SET);

            fwrite(&emp, sizeof(struct Employee), 1, filePtr);

            printf("Employee details added successfully.\n");
            break;

        case 2:
            printf("Enter Employee ID to display: ");
            scanf("%d", &emp.empId);

            fseek(filePtr, (emp.empId - 1) * sizeof(struct Employee), SEEK_SET);

            if (fread(&emp, sizeof(struct Employee), 1, filePtr) == 1) {
                printf("Employee ID: %d\n", emp.empId);
                printf("Employee Name: %s\n", emp.empName);
                printf("Employee Salary: %.2f\n", emp.empSalary);
            } else {
                printf("Record not found.\n");
            }
            break;

        case 3:
            printf("Enter Employee ID to update: ");
            scanf("%d", &emp.empId);
```

```c

            fseek(filePtr, (emp.empId - 1) * sizeof(struct Employee), SEEK_SET);

            if (fread(&emp, sizeof(struct Employee), 1, filePtr) == 1) {
                printf("Enter New Employee Name: ");
                scanf("%s", emp.empName);

                printf("Enter New Employee Salary: ");
                scanf("%f", &emp.empSalary);

                fseek(filePtr, (emp.empId - 1) * sizeof(struct Employee), SEEK_SET);
                fwrite(&emp, sizeof(struct Employee), 1, filePtr);

                printf("Employee details updated successfully.\n");
            } else {
                printf("Record not found.\n");
            }
            break;

        case 4:
            printf("Exiting program...\n");
            break;

        default:
            printf("Invalid choice. Please try again.\n");
        }

    } while (choice != 4);

    fclose(filePtr);
    return 0;
}
```

```
Employee Database Menu:
1. Add Employee
2. Display Employee Details
3. Update Employee Details
4. Exit
Enter your choice: 1
Enter Employee ID: 567
Enter Employee Name: sasi
Enter Employee Salary: 50000
Employee details added successfully.

Employee Database Menu:
1. Add Employee
2. Display Employee Details
3. Update Employee Details
4. Exit
Enter your choice:
```