

MINGW64:/c/Users/hp/git-demo1

```
hp@Dharanidhar MINGW64 ~
$ pwd
/c/Users/hp

hp@Dharanidhar MINGW64 ~
$ mkdir git-demo1

hp@Dharanidhar MINGW64 ~
$ cd git-demo1

hp@Dharanidhar MINGW64 ~/git-demo1
$ vim hi.py

hp@Dharanidhar MINGW64 ~/git-demo1
$ cat hi.py
print("this is devops democlass version1")

hp@Dharanidhar MINGW64 ~/git-demo1
$ git config --global user.name "pavithra"

hp@Dharanidhar MINGW64 ~/git-demo1
$ git config --global user.mail "machhapavithra@gmail.com"

hp@Dharanidhar MINGW64 ~/git-demo1
$ git congig --list
git: 'congig' is not a git command. See 'git --help'.

The most similar command is
    config

hp@Dharanidhar MINGW64 ~/git-demo1
$ git config --list
diff.astextplain.textconv=astextplain
filter.lfs.clean=git-lfs clean -- %f
filter.lfs.smudge=git-lfs smudge -- %f
filter.lfs.process=git-lfs filter-process
filter.lfs.required=true
http.sslbackend=schannel
core.autocrlf=true
core.fscache=true
core.symlinks=false
pull.rebase=false
credential.helper=manager
credential.https://dev.azure.com.usehttppath=true
init.defaultbranch=master
user.name=pavithra
user.email=machhapavithra@gmail.com
user.mail=machhapavithra@gmail.com
```

MINGW64:/c/Users/hp/git-demo1

```
hp@Dharanidhar MINGW64 ~/git-demo1
$ git init
Initialized empty Git repository in C:/Users/hp/git-demo1/.git/

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ ls -la
total 21
drwxr-xr-x 1 hp 197121  0 Jun 20 16:25 ./
drwxr-xr-x 1 hp 197121  0 Jun 20 16:23 ../
drwxr-xr-x 1 hp 197121  0 Jun 20 16:25 .git/
-rw-r--r-- 1 hp 197121 43 Jun 20 16:21 hi.py

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git add hi.py
warning: in the working copy of 'hi.py', LF will be replaced by CRLF the next time Git touches it

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
        new file:   hi.py

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git commit -m "this is commit1"
[master (root-commit) 266b7f1] this is commit1
 1 file changed, 1 insertion(+)
 create mode 100644 hi.py

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ vim hi.py

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ cat hi.py
print("this is devops democlass version1")
print("this is devops democlass version2")

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git add hi.py
warning: in the working copy of 'hi.py', LF will be replaced by CRLF the next time Git touches it

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git status
On branch master

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   hi.py
```

```
hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git commit -m"this is commit2"
[master 5eb50a0] this is commit2
1 file changed, 1 insertion(+)

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git log --oneline
5eb50a0 (HEAD -> master) this is commit2
266b7f1 this is commit1

hp@Dharanidhar MINGW64 ~/git-demo1 (master)
$ git checkout 266b7f1
Note: switching to '266b7f1'.

You are in 'detached HEAD' state. You can look around, make experimental
changes and commit them, and you can discard any commits you make in this
state without impacting any branches by switching back to a branch.

If you want to create a new branch to retain commits you create, you may
do so (now or later) by using -c with the switch command. Example:

    git switch -c <new-branch-name>

Or undo this operation with:

    git switch -

Turn off this advice by setting config variable advice.detachedHead to false

HEAD is now at 266b7f1 this is commit1

hp@Dharanidhar MINGW64 ~/git-demo1 ((266b7f1...))
$ cat hi.py
print("this is devops democlass version1")

hp@Dharanidhar MINGW64 ~/git-demo1 ((266b7f1...))
$ |
```