PROJECT: ASHBY MILL LOFTS | OWNER: Ashbey Mill Owner LLC | ARCHITECT: HOLLINS AND READE ARCHITECTS | ISSUE: JULY 20, 2023

Scope of Work and Specifications

Issued for construction

1. The project converts the former Ashby Mill into 84 apartments and 2 ground-floor commercial suites, with a leasing office and resident amenities on the ground floor.

2. Apartment area: 78,650 rentable SF across floors 1 to 5. Gross building area is shown on the code analysis sheet.

3. Floors 1 to 3 will be completed first and may be occupied before floors 4 and 5 are complete, subject to a temporary certificate of occupancy.

4. All work shall comply with the approved Part 2 application and its conditions.

Section 01 10 00 - Summary of work

5. Rehabilitation of a five-story mill building for residential use with ground-floor commercial suites, in accordance with the approved Part 2 application.

6. Remove non-historic partitions, dropped ceilings and abandoned mechanical equipment. Protect historic timber framing and flooring during demolition.

Section 04 01 20 - Masonry restoration

7. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.

8. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

Section 07 50 00 - Membrane roofing

9. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

10. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

Section 09 64 00 - Wood flooring

11. Retain and refinish existing maple flooring. Patch with salvaged boards where possible.

12. Provide wet-pipe sprinkler system. Exposed piping shall be painted to match the ceiling.

Section 23 00 00 - HVAC

13. Provide individual heat pump systems for each apartment. Ductwork shall run in corridor soffits.

14. Conceal new wiring in partitions. Surface conduit is not permitted on historic masonry walls.

Section 01 10 00 - Summary of work

15. Rehabilitation of a five-story mill building for residential use with ground-floor commercial suites, in accordance with the approved Part 2 application.

16. Remove non-historic partitions, dropped ceilings and abandoned mechanical equipment. Protect historic timber framing and flooring during demolition.

Section 04 01 20 - Masonry restoration

17. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.

18. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

Section 07 50 00 - Membrane roofing

19. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

20. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

Section 08 52 00 - Wood windows

1. Wood windows replicating original profiles, with true divided lites matching the historic muntin pattern and profile.

2. Repair existing sash where the window survey shows it can be repaired. Replace only sash documented as deteriorated.

3. Submit shop drawings and a full-size sample for review before fabrication. Shop drawings shall also be sent to the State Historic Preservation Office for NPS review.

4. Exterior finish: factory-primed and field-painted to the approved color.

Section 26 00 00 - Electrical

5. Conceal new wiring in partitions. Surface conduit is not permitted on historic masonry walls.

6. Provide individual heat pump systems for each apartment. Ductwork shall run in corridor soffits.

Section 21 13 00 - Fire suppression

7. Provide wet-pipe sprinkler system. Exposed piping shall be painted to match the ceiling.

8. Retain and refinish existing maple flooring. Patch with salvaged boards where possible.

Section 09 29 00 - Gypsum board

9. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

10. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

Section 06 10 00 - Rough carpentry

11. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

12. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.

Section 02 41 19 - Selective demolition

13. Remove non-historic partitions, dropped ceilings and abandoned mechanical equipment. Protect historic timber framing and flooring during demolition.

14. Rehabilitation of a five-story mill building for residential use with ground-floor commercial suites, in accordance with the approved Part 2 application.

Section 26 00 00 - Electrical

15. Conceal new wiring in partitions. Surface conduit is not permitted on historic masonry walls.

16. Provide individual heat pump systems for each apartment. Ductwork shall run in corridor soffits.

Section 21 13 00 - Fire suppression

17. Provide wet-pipe sprinkler system. Exposed piping shall be painted to match the ceiling.

18. Retain and refinish existing maple flooring. Patch with salvaged boards where possible.

Section 09 29 00 - Gypsum board

19. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

20. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

Section 06 10 00 - Rough carpentry

21. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

22. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.

Section 02 41 19 - Selective demolition

23. Remove non-historic partitions, dropped ceilings and abandoned mechanical equipment. Protect historic timber framing and flooring during demolition.

24. Rehabilitation of a five-story mill building for residential use with ground-floor commercial suites, in accordance with the approved Part 2 application.

Section 26 00 00 - Electrical

25. Conceal new wiring in partitions. Surface conduit is not permitted on historic masonry walls.

26. Provide individual heat pump systems for each apartment. Ductwork shall run in corridor soffits.

Section 21 13 00 - Fire suppression

27. Provide wet-pipe sprinkler system. Exposed piping shall be painted to match the ceiling.

28. Retain and refinish existing maple flooring. Patch with salvaged boards where possible.

Section 09 29 00 - Gypsum board

29. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

30. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

Section 06 10 00 - Rough carpentry

31. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

32. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.

Section 02 41 19 - Selective demolition

33. Remove non-historic partitions, dropped ceilings and abandoned mechanical equipment. Protect historic timber framing and flooring during demolition.

34. Rehabilitation of a five-story mill building for residential use with ground-floor commercial suites, in accordance with the approved Part 2 application.

Section 26 00 00 - Electrical

35. Conceal new wiring in partitions. Surface conduit is not permitted on historic masonry walls.

36. Provide individual heat pump systems for each apartment. Ductwork shall run in corridor soffits.

Section 21 13 00 - Fire suppression

37. Provide wet-pipe sprinkler system. Exposed piping shall be painted to match the ceiling.

38. Retain and refinish existing maple flooring. Patch with salvaged boards where possible.

Section 09 29 00 - Gypsum board

39. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

40. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

Section 06 10 00 - Rough carpentry

41. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

42. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.

Section 02 41 19 - Selective demolition

43. Remove non-historic partitions, dropped ceilings and abandoned mechanical equipment. Protect historic timber framing and flooring during demolition.

44. Rehabilitation of a five-story mill building for residential use with ground-floor commercial suites, in accordance with the approved Part 2 application.

Section 26 00 00 - Electrical

45. Conceal new wiring in partitions. Surface conduit is not permitted on historic masonry walls.

46. Provide individual heat pump systems for each apartment. Ductwork shall run in corridor soffits.

Section 21 13 00 - Fire suppression

47. Provide wet-pipe sprinkler system. Exposed piping shall be painted to match the ceiling.

48. Retain and refinish existing maple flooring. Patch with salvaged boards where possible.

Section 09 29 00 - Gypsum board

49. Partitions shall stop short of exposed timber beams and columns as shown on the drawings.

50. Provide a fully adhered membrane roof system with tapered insulation. Rooftop equipment shall be set back from the parapet.

Section 06 10 00 - Rough carpentry

51. Sister damaged timber members with new material of matching species where available. Do not remove sound historic members.

52. Repoint with lime-based mortar matched to the original. Do not use power tools to remove mortar from historic joints.