

Deep Generative Models

Changyou Chen


Department of Computer Science and Engineering
University at Buffalo, SUNY
`changyou@buffalo.edu`

March 28, 2019

Supervised vs. Unsupervised Learning¹

Supervised Learning

- **Data** (\mathbf{x}, y): \mathbf{x} is data, y is label/output.
- **Goal**: Learn a function to map $\mathbf{x} \rightarrow y$.



¹ Partially adapted from http://cs231n.stanford.edu/slides/2017/cs231n_2017_lecture13.pdf

Supervised vs. Unsupervised Learning¹

Supervised Learning

- **Data (x, y):** x is data, y is label/output.
- **Goal:** Learn a function to map $x \rightarrow y$.



1. A park with a clock tower in the background
2. A place with a tall building in the background
3. A park with a tall tree in the middle

¹ Partially adapted from http://cs231n.stanford.edu/slides/2017/cs231n_2017_lecture13.pdf

Supervised vs. Unsupervised Learning

Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.

Supervised vs. Unsupervised Learning

Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.




Figure: Kmeans

Supervised vs. Unsupervised Learning

Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.




Figure: Principal component analysis (dimension reduction)

Supervised vs. Unsupervised Learning

Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.




Figure: Autoencoders (feature learning)

Supervised vs. Unsupervised Learning

Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.




Figure: Autoencoders (feature learning)

Supervised vs. Unsupervised Learning


Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.



Figure copyright Ian Goodfellow, 2016. Reproduced with permission.

1-d density estimation



2-d density estimation

Supervised vs. Unsupervised Learning



Unsupervised Learning

- **Data x :** no labels.
- **Goal:** Learn some underlying hidden structure of the data:
 - Define different objective functions for different models.



Figure copyright Ian Goodfellow, 2016. Reproduced with permission.

1-d density estimation




2-d density estimation

⇒

Generative adversarial networks
(GAN)

Generative Models

Generate new samples from the same data distribution.




training data $\sim p_{\text{data}}(\mathbf{x})$ generated samples $\sim p_{\text{model}}(\mathbf{x})$

- Goal is to learn $p_{\text{model}}(\mathbf{x})$ such that it is close to $p_{\text{data}}(\mathbf{x})$.

Generative Models

Generate new samples from the same data distribution.



training data $\sim p_{\text{data}}(\mathbf{x})$ generated samples $\sim p_{\text{model}}(\mathbf{x})$

- Goal is to learn $p_{\text{model}}(\mathbf{x})$ such that it is close to $p_{\text{data}}(\mathbf{x})$.

Several flavors

- Explicit density estimation: explicitly define and solve for $p_{\text{model}}(\mathbf{x})$:
 - e.g., variational autoencoder (VAE) (in this case, \mathbf{x} refers to the latent representation of the data)
- Implicit density estimation: learn a model that can sample from $p_{\text{model}}(\mathbf{x})$ w/o explicitly defining it:
 - e.g., generative adversarial nets (GAN)

Why Generative Models?

- ① Realistic samples for artwork, super-resolution, colorization etc.



- ② Generative models of time-series data can be used for simulation and planning ⇒ reinforcement learning applications.
- ③ Training generative models can also enable inference of latent representations that can be useful as general features.
- ④ Effective use of unlabeled data.

Taxonomy of Generative Models




Figure copyright and adapted from Ian Goodfellow, Tutorial on Generative Adversarial Networks, 2017.

Taxonomy of Generative Models




Figure copyright and adapted from Ian Goodfellow, Tutorial on Generative Adversarial Networks, 2017.