

Experiment 3.3

Student Name: Yash Gupta
Branch: BE-CSE
Semester: 6
Subject Name: CC LAB

UID: 20BCS5009
Section/Group: 20BCS_DM-716 B
Date of Performance: 08/05/23
Subject Code: 20CSP_351

1. Aim:

To implement the concept of dynamic programming.

2. Objective:

- The objective is to build problem solving capability and to learn the basic concepts of data structures.
- Understand the problem and find out better approach to solve particular problem

3. LeetCode code and output:

• Decode Ways

The screenshot shows the LeetCode interface for the problem '91. Decode Ways'. It includes the problem title, difficulty level (Medium), and a description of the problem. The description states that a message containing letters from A-Z can be encoded into numbers using a specific mapping. It provides a mapping table: 'A' -> '1', 'B' -> '2', ..., 'Z' -> '26'. It then explains that to decode an encoded message, all the digits must be grouped and mapped back into letters using the reverse of the mapping. An example is given: '11106' can be mapped into 'AAJF' with grouping (1 1 10 6) or 'KJF' with grouping (11 10 6). It notes that the grouping (1 11 06) is invalid because '06' cannot be mapped into 'F' since '6' is different from '06'. The problem asks to return the number of ways to decode a string 's' containing only digits. The test cases are generated so that the answer fits in a 32-bit integer. An example is provided: Input: s = '12', Output: 2, Explanation: '12' could be decoded as 'AB' (1 2) or 'L' (12).

```

class Solution:
    def numDecodings(self, s: str) -> int:
        self.memo = {}
        return self.helper(s)

    def helper(self, s: str) -> int:
        if len(s) == 0: return 1
        if s in self.memo: return self.memo[s]

        takeOne = takeTwo = 0

        if int(s[:1]) >= 1 and int(s[:1]) <= 9:
            takeOne = self.helper(s[1:])

        if int(s[:2]) >= 10 and int(s[:2]) <= 26:
            takeTwo = self.helper(s[2:])

        self.memo[s] = takeOne + takeTwo

        return self.memo[s]

```

Yash Gupta202

May 13, 2023 23:19

[Details](#)
[+ Solution](#)

Python3

Runtime

50 ms

Beats

14.19%

Memory

16.3 MB

Beats

11.5%

Click the distribution chart to view more details

Notes

Write your notes here

Related Tags

Select tags 0/5

```

class Solution:
    def numDecodings(self, s: str) -> int:
        self.memo = {}
        return self.helper(s)

    def helper(self, s: str) -> int:
        if len(s) == 0: return 1
        if s in self.memo: return self.memo[s]

        takeOne = takeTwo = 0

        if int(s[:1]) >= 1 and int(s[:1]) <= 9:
            takeOne = self.helper(s[1:])

        if int(s[:2]) >= 10 and int(s[:2]) <= 26:
            takeTwo = self.helper(s[2:])

        self.memo[s] = takeOne + takeTwo

        return self.memo[s]

```

Console ^

Run

Submit

• Maximum Subarray

[Description](#) [Editorial](#) [Solutions \(10.3K\)](#) [Submissions](#)

53. Maximum Subarray

Medium ✓ 👍 29.5K 💬 1.3K ☆ 🔄

🔒 Companies

Given an integer array `nums`, find the **subarray** with the largest sum, and return *its sum*.

Example 1:

Input: `nums = [-2,1,-3,4,-1,2,1,-5,4]`

Output: 6

Explanation: The subarray `[4,-1,2,1]` has the largest sum 6.

Example 2:

Input: `nums = [1]`

Output: 1

Explanation: The subarray `[1]` has the largest sum 1.

Example 3:

Input: `nums = [5,4,-1,7,8]`

Output: 23

Explanation: The subarray `[5,4,-1,7,8]` has the largest sum 23.

Constraints:

- `1 <= nums.length <= 105`
- `-104 <= nums[i] <= 104`

Follow up: If you have figured out the `O(n)` solution, try coding another solution using the **divide and conquer** approach, which is more subtle.

```
class Solution:
    def maxSubArray(self, nums: List[int]) -> int:
        max_sum=nums[0]
        temp=0
        for i in range(len(nums)):
            if temp<0:
                temp=0
            temp+=nums[i]
            if temp>max_sum:
                max_sum=temp
        return max_sum
```




Yash_Gupta202
May 13, 2023 23:25

Details

+ Solution

Python3



Click the distribution chart to view more details

Notes

Write your notes here

Related Tags

Select tags

0/5

```
class Solution:
    def maxSubArray(self, nums: List[int]) -> int:
        max_sum=nums[0]
        temp=0
        for i in range(len(nums)):
            if temp<0:
                temp=0
            temp+=nums[i]
            if temp>max_sum:
                max_sum=temp
        return max_sum
```

Console ^



Run

Submit