

Face Attendance — 2 APIs

Zegar app • Backend: PHP Laravel • Base URL: <https://zedgift.viaaratech.com/api>

We need only **2 endpoints**: (1) **Register face** and (2) **Mark attendance by face**.

On every request send: Authorization: Bearer <token> , Company-ID: <id>

In responses use **date** = **DD-MM-YYYY** and **time** = **12-hour** (e.g. 09:05 AM).

1) Register Face

UPDATE

Admin saves an employee's face. (This endpoint exists; just make the server read & store the face from the image itself.)

Request

```
POST /attendance/face/register
Content-Type: multipart/form-data

employee_id : 1038          (required)
face_image  : <photo file>  (required, jpg/png)
```

Response

```
{
  "success": true,
  "message": "Face registered.",
  "data": { "employee_id": 1038 }
}
```

2) Mark Attendance by Face

NEW

The phone sends a live photo. The server finds who it is from the registered faces and saves the punch (auto IN / OUT) with the time.

Request

```
POST /attendance/face/punch
Content-Type: multipart/form-data

face_image : <live photo file>  (required)
type       : face                (optional)
```

Server should do

1. Read face from face_image.
2. Compare with ALL registered faces (same library as register).
3. Best match ≥ 0.60 similarity = that employee.

4. Save punch with current timestamp; first punch of day = IN, next = OUT.
5. No good match = "not recognized".

Response — success

```
{
  "success": true,
  "message": "Attendance marked.",
  "data": {
    "employee_id": 1038,
    "name": "Yash Patel",
    "punch_status": "in",          // "in" or "out"
    "date": "09-06-2026",         // DD-MM-YYYY
    "time": "09:05 AM",          // 12-hour
    "confidence": 0.83
  }
}
```

Response — face not found

```
{ "success": false, "message": "Face not recognized.", "data": null }
```

Note: all face matching is done on the **server** (PHP face library, or a small Python service the Laravel app calls). The app only sends a photo and shows the result — so it works from any phone.