

# Face Attendance — API Spec

Zegar app • Backend: PHP Laravel + MySQL • Base URL: <https://zedgift.viaaratech.com/api>

Setup: ONE shared phone (kiosk). **Face recognition is done in the app** (ML Kit + MobileFaceNet). The **server** only needs to (1) **store** each employee's face embeddings, and (2) **save the punch** (attendance).

**Headers on every request:** Authorization: Bearer <token>, Company-ID: <id>, Accept: application/json

**Response formats:** date = **DD-MM-YYYY**, time = **12-hour** (e.g. 09:05 AM).

## 1) Register Face NEW

Admin enrolls an employee. The app captures 5 angles, makes one embedding per angle, and sends them. The server stores them for that employee.

### Endpoint

POST /attendance/face/register (Content-Type: multipart/form-data)

### Request fields — with data types

| Field       | Type           | Required | Description                                                 |
|-------------|----------------|----------|-------------------------------------------------------------|
| employee_id | integer        | Yes      | the employee's id (from /employees)                         |
| embeddings  | JSON string    | Yes      | array of vectors; each vector = 192 decimal numbers (float) |
| face_image  | file (jpg/png) | No       | one photo, kept on record only                              |

### Mock example — request

```
POST /attendance/face/register
employee_id = 1038
embeddings = [
  [0.0123, -0.0821, 0.1140, 0.0335, ... total 192 numbers ...],
  [0.0201, -0.0772, 0.1002, 0.0419, ... total 192 numbers ...],
  [0.0098, -0.0810, 0.1185, 0.0288, ... total 192 numbers ...]
]
face_image = yash_face.jpg
```

### Mock example — response

```
{
  "success": true,
  "message": "Face registered successfully.",
  "data": {
    "employee_id": 1038,
    "embeddings_count": 3
  }
}
```

## 2) Mark Attendance (Punch) EXISTS - confirm

After the app recognizes the employee (on the phone), it sends a punch. The server saves it and auto-decides IN or OUT (first punch of the day = IN, next = OUT).

## Endpoint

POST /attendance/punch (Content-Type: multipart/form-data)

## Request fields — with data types

| Field       | Type              | Required | Description                                       |
|-------------|-------------------|----------|---------------------------------------------------|
| employee_id | integer           | Yes      | recognized employee's id                          |
| type        | string            | No       | "face"                                            |
| timestamp   | string (datetime) | No       | format: YYYY-MM-DD HH:MM:SS (24h, server time ok) |

## Mock example — request

```
POST /attendance/punch
employee_id = 1038
type        = face
timestamp   = 2026-06-09 09:05:00
```

## Mock example — response (IN)

```
{
  "success": true,
  "message": "Attendance marked.",
  "data": {
    "employee_id": 1038,
    "custom_employee_id": 12,
    "name": "Yash Patel",
    "punch_status": "in",
    "date": "09-06-2026",
    "time": "09:05 AM"
  }
}
```

## Mock example — response (evening, OUT)

```
{
  "success": true,
  "message": "Attendance marked.",
  "data": {
    "employee_id": 1038,
    "punch_status": "out",
    "date": "09-06-2026",
    "time": "06:40 PM"
  }
}
```

## Data types — quick reference

| Name | Type | Example |
|------|------|---------|
|------|------|---------|

|              |                              |                           |
|--------------|------------------------------|---------------------------|
| employee_id  | integer                      | 1038                      |
| embeddings   | JSON array of arrays (float) | [[0.01, -0.08, ...], ...] |
| face_image   | file                         | yash_face.jpg             |
| type         | string                       | "face"                    |
| timestamp    | string                       | "2026-06-09 09:05:00"     |
| punch_status | string                       | "in" / "out"              |
| date         | string (DD-MM-YYYY)          | "09-06-2026"              |
| time         | string (12-hour)             | "09:05 AM"                |
| confidence   | float (0-1)                  | 0.83                      |

**Summary for developer:** Build endpoint #1 (store embeddings), confirm endpoint #2 (save punch, auto IN/OUT). Face matching is on the app. Use **DD-MM-YYYY** for date and **12-hour** for time in responses.