

	Room Area (m²)	Tiles	Pixels	SNR (dB)		Score
				Average	Composite	
(a) SNR by Configuration	100	25	4	16	12.2	0.60
		25	4	36	12.0	0.52
		25	4	64	14.1	0.50
		25	4	100	15.2	0.47
		25	4	144	18.3	0.48
		25	4	196	15.5	0.41
		25	4	256	17.6	0.42
		25	9	16	12.9	0.53
		25	9	36	16.5	0.49
		25	9	64	14.9	0.41
		25	9	100	13.7	0.35
		25	9	144	15.3	0.34
		25	9	196	18.9	0.36
		25	9	256	20.4	0.37
		25	16	16	14.2	0.48
		25	16	36	11.9	0.37
		25	16	64	11.4	0.30
		25	16	100	13.7	0.30
		25	16	144	16.7	0.31
		25	16	196	17.4	0.30
		25	16	256	21.9	0.35
		25	25	16	10.4	0.38
		25	25	36	12.4	0.32
		25	25	64	11.6	0.26
		25	25	100	16.8	0.30
		25	25	144	21.3	0.34
		25	25	196	17.4	0.28
		25	25	256	17.0	0.26
		25	36	16	9.6	0.33
		25	36	36	11.3	0.27
		25	36	64	16.0	0.29
		25	36	100	11.5	0.21
		25	36	144	15.8	0.25
		25	36	196	15.8	0.24
		25	36	256	18.9	0.28
		25	49	16	14.0	0.35
		25	49	36	9.7	0.23
		25	49	64	13.8	0.25
		25	49	100	18.5	0.29
		25	49	144	15.4	0.24
		25	49	196	17.1	0.25
		25	64	16	16.9	0.36
		25	64	36	9.9	0.21
		25	64	64	12.8	0.22
		25	64	100	19.4	0.29
		25	64	144	20.8	0.30
(b) SNR by Configuration	50	50	4	16	8.2	0.55
		50	4	36	12.3	0.53
		50	4	64	11.1	0.46
		50	4	100	10.0	0.40
		50	4	144	11.8	0.39
		50	4	196	15.2	0.41
		50	4	256	15.5	0.39
		50	9	16	8.4	0.47
		50	9	36	9.4	0.40
		50	9	64	11.2	0.36
		50	9	100	7.3	0.27
		50	9	144	13.4	0.32
		50	9	196	14.2	0.30
		50	9	256	16.2	0.31
		50	16	16	8.1	0.40
		50	16	36	13.9	0.39
		50	16	64	10.1	0.29
		50	16	100	8.6	0.23
		50	16	144	9.4	0.21
		50	16	196	17.7	0.30
		50	16	256	13.7	0.24
		50	25	16	4.5	0.30
		50	25	36	9.5	0.29
		50	25	64	10.5	0.25
		50	25	100	10.5	0.22
		50	25	144	11.9	0.22
		50	25	196	11.3	0.20
		50	25	256	15.4	0.24
		50	36	16	8.4	0.31
		50	36	36	6.9	0.21
		50	36	64	10.8	0.22
		50	36	100	12.1	0.22
		50	36	144	11.8	0.20
		50	36	196	16.0	0.25
		50	36	256	14.6	0.22
		50	49	16	9.8	0.30
		50	49	36	12.7	0.27
		50	49	64	6.8	0.15
		50	49	100	8.7	0.16
		50	49	144	12.9	0.20
		50	49	196	12.2	0.19
		50	64	16	8.1	0.25
		50	64	36	9.7	0.21
		50	64	64	11.3	0.20
		50	64	100	11.0	0.18
		50	64	144	9.2	0.15
(c) SNR by Configuration	100	100	4	16	4.1	0.49
		100	4	36	2.6	0.40
		100	4	64	3.5	0.36
		100	4	100	7.5	0.37
		100	4	144	5.4	0.31
		100	4	196	8.9	0.32
		100	4	256	10.2	0.32
		100	9	16	7.3	0.45
		100	9	36	8.6	0.39
		100	9	64	2.6	0.25
		100	9	100	6.3	0.26
		100	9	144	13.8	0.32
		100	9	196	11.8	0.27
		100	9	256	11.4	0.25
		100	16	16	3.5	0.34
		100	16	36	6.5	0.29
		100	16	64	5.5	0.22
		100	16	144	6.6	0.18
		100	16	196	12.0	0.23
		100	16	256	11.7	0.21
		100	25	16	1.2	0.26
		100	25	36	6.3	0.24
		100	25	64	5.1	0.18
		100	25	100	5.5	0.15
		100	25	144	6.9	0.15
		100	25	196	7.8	0.15
		100	25	256	10.2	0.17
		100	36	16	4.0	0.25
		100	36	36	3.3	0.17
		100	36	64	5.6	0.16
		100	36	100	8.3	0.17
		100	36	144	7.4	0.14
		100	36	196	6.1	0.11
		100	36	256	6.8	0.12
		100	49	16	-3.1	0.13
		100	49	36	9.0	0.22
		100	49	64	3.6	0.11
		100	49	100	2.6	0.08
		100	49	144	9.5	0.16
		100	49	196	7.4	0.12
		100	64	16	3.3	0.18
		100	64	36	4.1	0.13
		100	64	64	4.6	0.11
		100	64	100	7.6	0.13
		100	64	144	7.1	0.12
		(d) Configuration Summary	200	200	4	16
200	4			36	-5.3	0.29
200	4			64	0.9	0.32
200	4			100	3.7	0.32
200	4			144	2.6	0.27
200	4			196	4.6	0.27
200	4			256	5.3	0.25
200	9			16	-2.2	0.32
200	9			36	-3.8	0.22
200	9			64	-1.5	0.20
200	9			100	-2.2	0.14
200	9			144	3.9	0.19
200	9			196	0.8	0.12
200	9			256	0.5	0.10
200	16			16	1.6	0.31
200	16			36	2.3	0.24
200	16			64	0.4	0.16
200	16			100	3.6	0.16
200	16			144	2.3	0.12
200	16			196	6.8	0.16
200	16			256	1.9	0.08
200	25			16	-4.5	0.18
200	25			36	-1.9	0.13
200	25			64	-2.3	0.08
200	25			100	-0.2	0.08
200	25			144	-0.9	0.05
200	25			196	2.5	0.08
200	25			256	6.9	0.13
200	36			16	4.7	0.26
200	36			36	-2.3	0.09
200	36			64	-0.1	0.08
200	36			100	-1.9	0.03
200	36			144	0.9	0.05
200	36			196	1.4	0.05
200	36			256	4.0	0.08
200	49			16	0.7	0.18
200	49			36	-2.2	0.07
200	49			64	2.9	0.10
200	49			100	1.1	0.06
200	49			144	2.9	0.07
200	49			196	2.1	0.05
200	64			16	-5.6	0.07
200	64			36	-1.5	0.06
200	64			64	0.6	0.06
200	64			100	-0.8	0.02
200	64			144	3.0	0.06
(e) Configuration Summary	400	400	4	16	-6.3	0.35
		400	4	36	-4.6	0.30
		400	4	64	-5.6	0.24
		400	4	100	-5.8	0.19
		400	4	144	-3.8	0.18
		400	4	196	-4.2	0.15
		400	4	256	0.0	0.18
		400	9	16	-10.5	0.21
		400	9	36	-4.5	0.21
		400	9	64	-9.7	0.09
		400	9	100	-0.8	0.16
		400	9	144	-6.9	0.05
		400	9	196	-4.4	0.05
		400	9	256	-2.7	0.06
		400	16	16	-4.4	0.23
		400	16	36	-7.2	0.11
		400	16	64	-3.2	0.11
		400	16	100	-5.4	0.04
400	16	144	-7.5	-0.01		
400	16	196	-5.9	-0.01		
400	16	256	-2.7	0.02		
400	25	16	-11.5	0.09		
400	25	36	-8.5	0.04		
400	25	64	-4.6	0.05		
400	25	100	-0.1	0.08		
400	25	144	-3.5	0.01		
400	25	196	-4.4	-0.01		
400	25	256	-2.1	0.01		
400	36	16	-9.9	0.07		
400	36	36	-7.5			