

selenide_in_2h.py

@yashaka



AUTOMICIAN

10.2021

Agenda

Raw Library (Selenium) VS Wrapper

Selenide Style


When and Why?

Q&A


Preface

There are good practices **in context**,
but there are no best practices.

(c) Cem Kaner, James Bach




... context ?



System Web UI Tests Automation


Tool???



System
Web UI

Tests

Automation



implicit waits
dynamic elements

assertion matchers
errors, logs

selectors ++

Agenda

Raw Library (Selenium) VS Wrapper ?

Selenide Style

When and Why?

Q&A



ElementNotVisibleException
ElementNotInteractableException
StaleElementReferenceException
...

PageObjects limited to **By.*** or **@FindBy** in Java

limited to

expected_conditions.element

```
★ @element_to_be_clickable selenium.webdriver.support...
@element_to_be_selected selenium.webdriver.support...
@element_located_selection_state_to_be selenium..
@element_located_to_be_selected selenium.webdriv..
@element_selection_state_to_be selenium.webdriv..
@invisibility_of_element selenium.webdriver.sup..
@text_to_be_present_in_element selenium.webdriv..
@invisibility_of_element_located selenium.webdr..
@presence_of_all_elements_located selenium.webd..
@presence_of_element_located selenium.webdriver..
@text_to_be_present_in_element_value selenium.w..
@visibility_of_all_elements_located selenium.we..
@visibility_of_any_elements_located selenium.we..
@visibility_of_element_located selenium.webdriv..
```

^↓ and ^↑ will move caret down and up in the editor [Next Tip](#)

VS
?

implicit waits
dynamic elements

assertion matchers
clear errors, logs

```
driver.find_element_by_xpath(  
    "//*[ @test-id='item']//a[contains(text(), 'selenide.org')]"  
)
```

selectors ++


```
62 * def until(self, method, message=''):
63     """Calls the method provided with the driver as an argument until the \
64     return value is not False."""
65     screen = None
66     stacktrace = None
67
68     end_time = time.time() + self._timeout
69     while True:
70         try:
71             value = method(self._driver)
72             if value:
73                 return value
74         except self._ignored_exceptions as exc:
75             screen = getattr(exc, 'screen', None) # ←
76             stacktrace = getattr(exc, 'stacktrace', None) # ←
77             # ← where is message o_O ?
78             time.sleep(self._poll)
79             if time.time() > end_time:
80                 break
81         raise TimeoutException(message, screen, stacktrace)
82
```

clear errors o_O ?



Agenda

Wrapper !

Selenide Style

When and Why?

Q&A

Agenda

Wrapper !

Selenide Style ?

When and Why?

Q&A

```

new_todo = browser.element("#new-todo")
todos = browser.all("#todo-list>li")

browser.open("http://todomvc.com/examples/emberjs/")

new_todo.type("give talk").press_enter()
new_todo.type("have fun").press_enter()

todos.should(have.te("give talk", "have fun"))

```

lazy, dynamic elements

implicit waits

assertion matchers

```

★ f text(partial_va... selene.support.conditions.have
f texts(partial_values) selene.support.conditions.have
f tabs_number_greater_than_or_equal selene.supp...
f tabs_number_less_than_or_equal selene.support....
f tabs_number_greater_than selene.support.condit...
f exact_text(valu... selene.support.conditions.have
f exact_texts(val... selene.support.conditions.have
f size_less_than_or_equal selene.support.conditi...
f attribute(name,... selene.support.conditions.have
f size_greater_than selene.support.conditions.ha...
f size_greater_than_or_equal selene.support.cond...

```

Press <=> to insert, => to replace Next Tip

```

(
  browser.all("#todo-list>li")
    .filtered_by(have.text("give talk"))
    .element(".toggle")
    .click()
)

```

selectors ++

Agenda

Wrapper !

SeleniDe Style ?

When and Why?


Q&A


```
var newTodo = $("#new-todo");  
var todos = $("#todo-list>li");
```

```
open("http://todomvc.com/examples/emberjs/");
```

```
newTodo.append("give talk").pressEnter();  
newTodo.append("have fun").pressEnter();
```

```
todos.shouldHave("give talk", "have fun");
```



```
$("#todo-list>li")  
  .filter(text("give talk"))  
  $(".toggle")  
  .click();
```

lazy, dynamic elements

implicit waits

assertion matchers

selectors ++

Agenda

Wrapper !

Selenides Style ...

Why & When?

Q&A

Opensource

vs

Bicycle

redundant

opinionated

missing/compromises

delayed

bugs/deprecations

clean

&

tuned

shit-code +

RnD friendly:p

Opensource

simple/routine/common case

limited senior resources

short-term easiness matters

outer scale

Bicycle

complex/integrations/unique domain

skilled team

long-term easiness matters
(simple made easy )

at most inner scale

arguments



Agenda


Wrapper !

Selenides Style ...






Workshop

Q&A

Q&A



Thank you!

yashaka @     

more questions, materials, etc?



t.me/yashaka



AUTOMICIAN

@yashaka

10.2021