

# NON-COMPUTABILITY OF HUMAN INTELLIGENCE

YASHA SAVELYEV

**ABSTRACT.** We revisit the question (most famously) initiated by Turing: can human intelligence be completely modeled by a Turing machine? We show that the answer is *no*, assuming a certain weak soundness hypothesis. More specifically we show that at least some meaningful thought processes of the brain cannot be Turing computable. In particular some physical processes are not Turing computable, which is not entirely expected. There are some similarities of our argument with the well known Lucas-Penrose argument, but we work purely on the level of Turing machines, and do not use Gödel’s incompleteness theorem or any direct analogue. Instead starting with a slightly strengthened computability hypothesis, we construct directly and use a weak analogue of a Gödel statement for a certain system which involves our human, this allows us to side-step some (possible) meta-logical issues with their argument.

We study the following question:

*Question 1.* Can human intelligence be completely modelled by a Turing machine?

We will give a complete definition of a Turing machine after the introduction. An informal definition of a Turing machine [1] is as follows: it is an abstract machine which accepts certain inputs, and produces outputs. The outputs are determined from the inputs by a fixed finite algorithm, in a specific sense.

In particular anything that can be computed by computers as we know them can be computed by a Turing machine. For the purpose of the main result the reader may simply understand a Turing machine as a digital computer with unbounded memory running a certain program. Unbounded memory is just mathematical convenience, it can in specific arguments, also of the kind we make, be replaced by non-explicitly bounded memory.

Turing himself has started on a form of Question 1 in his Computing machines and Intelligence, [2], where he also outlined a possible obstruction to a yes answer coming from Gödel’s incompleteness theorem. He pointed out that one way to avoid this obstruction is to reject the assumption that humans are fundamentally consistent. What the latter actually means in practice is subject to a lengthy discussion, we need some qualifier like “fundamental” as even mathematicians do not on the surface assert consistent statements at all times. At the moment it should be understood as follows: we make inconsistent claims not because these are expressions of fundamental internal inconsistencies of our mental constructions, but because the noisy biological nature of our brain leads to interpretation errors of these mental constructions. In particular if our reasoning powers could be captured by a fixed formal system, fundamental consistency means that it is sound.

There are a number of ways of interpreting Question 1. Turing himself was mainly interested in whether a Turing machine can fool an experimenter into believing that it is a human subject, in various Imitation Games, see [2] for examples. As this author understands, Turing believed roughly the following, (here for exposition’s sake we take the liberty of compressing, perhaps not completely accurately, Turing’s ideas into a neat hypothesis):

**Hypothesis 1** (Turing’s hypothesis). *For every given human experimenter, an imitation game, and given some bounded amount of time, one can construct a Turing machine that will fool him in this imitation game, for that amount of time.*

This particular hypothesis may well be true, nothing in the present note contradicts it. However our interpretation of the question is different. We are asking is whether there is a meaningful mathematical difference in operation of a human mind and a Turing machine. While the significance of this version of the question for computer science is perhaps arguable, for physics and biology it is profoundly important.

One misconception is that there can be no such mathematical difference if one believes the universe to be governed by deterministic, or effectively for a given purpose deterministic laws. Quantum mechanics for instance is effectively for our purpose deterministic, as the results (measurements) are at worst given by a probability distribution that is determined. But deterministic does *not* imply computable in the mathematical sense, e.g. Turing computable, (this may refer also to the above mentioned probability distribution). The latter would be computably deterministic, and this is the source of the misconception.<sup>1</sup>

Gödel himself first argued that such a mathematical difference exists, [3, p. 310]. Later Lucas [4] and later again and more robustly Penrose [5] strongly argued that a meaningful difference exists and for a no answer to question 1. They further formalized and elaborated the obstruction coming from Gödel’s incompleteness theorem. And they reject the possibility that humans could be inconsistent on a fundamental level. The main common objections to their argument concern the meta-logic of the argument, see for instance [6], [7]. We shall say a few words about this below. The other objection is simply that the consistency assumption may be wrong, this is suggested by Turing himself for instance as mentioned above. For a discussion of the consistency question we refer the reader to the wonderful books of Penrose, [8], [5].

It should also be noted that for Penrose in particular, non-computability of intelligence is evidence for new physics, and he has specific and *very* intriguing proposals with Hameroff [9], on how this can take place in the human brain. Here is a partial list of some partially related work on mathematical models of brain activity and or quantum collapse models: [10], [11], [12], [13], [14].

We likewise argue here for such a mathematical difference. Like Lucas-Penrose we have a soundness assumption but our seems much weaker. We do not use Gödel incompleteness theorem, instead we construct a certain weak analogue of Gödel statement directly. The following is a slightly informal version of our main Theorem 2.

**Theorem 1.** *The answer to Question 1 is no, assuming a certain soundness condition on our humans. More specifically, there is a non-trivial class of human beings which we name “sane”, which as a component of a certain simple physical system, cannot be both Turing computable and sound in a specific sense.*

The immediate implications and context of this theorem are in mathematical physics and in part biology, computer science, and philosophy for even existence of non Turing computable processes in nature is not known. For example we expect beyond reasonable doubt that solutions of Navier-Stokes equations or  $N$ -body problems are generally non-computable, (over  $\mathbb{Z}$ , if not over  $\mathbb{R}$  cf. [15]), as modeled in essentially classical mechanics. But in a more physically accurate and fundamental model these may both become computable, (possibly if the nature of the universe is ultimately discreet.) Our theorem says that either there are absolutely, that is model independent, non-computable processes in physics, in fact in the functioning of the brain, or human beings are fundamentally unsound, which is a mathematical condition on the functioning of the human brain. Despite the physical context the technical methods of the paper are mainly of mathematics and computer science, as we need very few physical assumptions.

---

<sup>1</sup>We should mention that there is also a notion of non-deterministic Turing machines but this “non-deterministic” is not directly related to our discussion. Moreover these machines can be simulated by Turing machines of the type we consider, so are not considered here.

It would be interesting to also explore deeper implications. For example if the soundness assumption is accepted, what is the non-computable process in the brain that is guaranteed by the above theorem? Penrose for example strongly argues that it should involve new physics, [9]. What does the above theorem mean for hard AI, and models of consciousness as in [10], [14] for example? We will not pursue these kind of questions here however.

**Outline of the main idea.** In what follows we refer to some language of abstract formal systems but none of this appears in the main argument, as our language will be purely that of Turing machines. It will be instructive to first give a preliminary version of the Penrose argument, in our language, and see what goes wrong. But to emphasize this is *not* his argument, (which is more sophisticated.) Let  $P$  be a human subject, which we understand as a machine printing statements in arithmetic, given some input. That is for each  $\Sigma$  some string input,  $P(\Sigma)$  is a statement in arithmetic, e.g. Fermat's last theorem. Say now  $P$  is in contact with experimenter/operator  $E$ . The input string  $\Sigma$  that  $E$  gives  $P$  is the following: "here is the specification of a Turing machine  $T$ , this machine computes you as a (perhaps partially defined) function  $\Sigma \mapsto P(\Sigma)$ ". Before we proceed, we put the condition on our  $P$  that he believes himself to be fundamentally sound, that is he believes  $P(\Sigma)$  is true for all  $\Sigma$ . This is not an assumption by  $P$ , this is what  $P$  asserts as *truth*, whether this is actually rational is another discussion as already mentioned.

Now  $P$  replies:

*I know I am sound, hence  $T$  must be sound if it computes me, but I can then construct a Gödel statement  $G(T)$  for  $T$ , which is then a true statement in arithmetic, and which indirectly asserts " $T$  cannot print  $G(T)$ ".*

This alone doesn't quite work however for  $E$  counters:

*I see, but do you in fact in print  $G(T)$ ? This is the only way you can presently reach a contradiction, as  $T$  only computes what you print, not what you can meta-prove.*

$P$  has to say no! Because he does not in fact know  $G(T)$  is true, since he has to know that  $T$  is sound, and this only happens (from his point of view) if he knew for a fact:  $T$  computes  $P$ . If  $P$  does print  $G(T)$  then he is patently unsound, as he has no basis to assert  $G(T)$ , so his very belief that he is sound would be absurd.

*A possible fix.* (Outline) We can try to fix the above argument as outlined in the following, and this "fixed version" will be very close in essence to the argument Penrose gives in [8], which we take to be his main and final argument, (as far as I am aware).

Change  $\Sigma$  to: "here is a specification of a Turing machine  $T$ , print your statement that you assert to be true assuming  $\Theta_T$ :"

(0.1)  $T$  computes  $P$ .

Again  $P$  reasons that since his deductions based on  $\Theta_T$  are sound, the same must be true of  $T$ . Then (perhaps) there is a conditional Gödel statement  $G(T, \Theta_T)$ , which is true if  $\mathcal{F}(T) + \Theta_T$  is sound and indirectly asserts that  $T$  cannot print  $G(T, \Theta_T)$ . Here  $\mathcal{F}(T) + \Theta_T$  denotes the formal system underlying  $T$  adjoined with the assertion  $\Theta_T$  as an axiom.  $P$  then prints  $G(T, \Theta_T)$ .

Now if  $\Theta_T$  is true, and  $P$  is indeed sound and hence  $T$  is sound, then  $T$  cannot print  $G(T, \Theta_T)$ . So we reach a contradiction, unless  $P$  is not in fact sound. The above outline is still not totally satisfactory. For one we need to show that conditional Gödel statements as above can be constructed (by  $P$ ). At the least this requires that  $\Theta_T$  be interpreted as a statement in a suitable formal system (containing arithmetic). For this we need  $P$  to be suitably defined, otherwise it is not clear how the interpretation of  $\Theta_T$  as a statement could work, but we delve no further. A full critique of the Penrose argument, is given in Koellner [7], [16], see also Penrose [17], and Chalmers [6] for discussions on related issues.

This note can be understood as a non-literal elaboration of the above “fixed” argument, but with additional changes and improvements. First we do not need our subject of this paper, henceforth denoted by  $S$ , to be totally sound; we only need soundness of a certain much more limited function associated to  $S$ . Moreover, we do not need  $S$  to explicitly construct Gödel statements, for we directly find in this context an elementary and explicit analogue, a kind of weak Gödel statement and this suffices for  $S$ . Thus Gödel incompleteness theorem is not used at all.

However, to construct our “weak Gödel statement” directly, we still need to formalize at least partly some necessary properties of  $S$ , or rather of a certain physical system encompassing  $S$ . To this end we need to work with a slightly stronger form of Turing computability of the physical system  $S$ , although physically it is only trivially stronger. Roughly speaking for us computability means that not only are the answers of  $S$  computable by a Turing machine  $T$ , but also that the brain of  $S$  is physically simulating  $T$  to arrive at the answers. (The actual condition we use is more elementary and explicit.)

So we solve the problem above, in the “fixed argument”, of formalization of (0.1), by avoiding direct use of Gödel incompleteness theorem, and by defining/formalizing our subject  $S$  just enough so that a direct construction of the “weak Gödel statement” goes through. This requires a slightly stronger computability condition. In particular we are not immediately at odds with analysis in [7], [16] of the argument of Penrose.

Note however that we do not use language of formal systems, but work purely with language of Turing machines, so that this description of the overall strategy is only a partial translation to the language of formal systems.

Working purely with Turing machines, has at least one advantage of being vastly more elementary and concrete compared to working with formal systems. In particular the above mentioned weak Gödel statement is formulated purely in the language of Turing machines - as a property of a certain hypothetical Turing machine. The disadvantage of working with Turing machines is that it is more difficult to give a complete overview of the argument in this language.

Although the logic of the argument is somewhat intricate, technically the paper is elementary and should be widely readable, in entirety.

## 1. SOME PRELIMINARIES

This section can be just skimmed on a first reading. Really what we are interested in is not Turing machines per se, but computations that can be simulated by Turing machine computations. These can for example be computations that a mathematician performs with paper and pencil, and indeed is the original motivation for Turing’s specific model. However to introduce Turing computations we need Turing machines, here is our version, which is a computationally equivalent minor, variation of Turing’s original machine.

**Definition 1.1.** *A Turing machine  $M$  consists of:*

- *Three infinite (1-dimensional) tapes  $T_i, T_o, T_c$ , divided into discreet cells, one next to each other. Each cell contains a symbol from some finite alphabet. A special symbol  $b$  for blank, (the only symbol which may appear infinitely many often).*
- *Three heads  $H_i, H_o, H_c$  (pointing devices),  $H_i$  can read each cell in  $T_i$  to which it points,  $H_o, H_c$  can read/write each cell in  $T_o, T_c$  to which it points. The heads can then move left or right on the tape.*
- *A set of internal states  $Q$ , among these is “start” state  $q_0$ . And a non-empty set  $F$  of final, “finish” states.*

- Input string  $\Sigma$ , the collection of symbols on the tape  $T_i$ , so that to the left and right of  $\Sigma$  there are only symbols  $b$ . We assume that in state  $q_0$ ,  $H_i$  points to the beginning of the input string, and that the  $T_c$ ,  $T_o$  have only  $b$  symbols.
- A finite set of instructions  $I$  that given the state  $q$  the machine is in currently, and given the symbols the heads are pointing to, tells  $M$  to do the following, the taken actions 1-3 below will be (jointly) called an **executed instruction set**, or just **step**:
  - (1) Replace symbols with another symbol in the cells to which the heads  $H_c, H_o$  point (or leave them).
  - (2) Move each head  $H_i, H_c, H_o$  left, right, or leave it in place, (independently).
  - (3) Change state  $q$  to another state or keep it.
- Output string  $\Sigma_{out}$ , the collection of symbols on the tape  $T_o$ , so that to the left and right of  $\Sigma$  there are only symbols  $b$ , when the machine state is final. When the internal state is one of the final states we ask that the instructions are to do nothing, so that these are frozen states.

We also have the following minor variations on standard definitions, and notation.

**Definition 1.2.** A **complete configuration** of a Turing machine  $M$  or **total state** is the collection of all current symbols on the tapes, position of the heads, and current internal state. A **Turing computation**, or **computation sequence** for  $M$  is a possibly not eventually constant sequence

$$\{s_i\}_{i=0}^{i=\infty} := *M(\Sigma)$$

of complete configurations of  $M$ , determined by the input  $\Sigma$  and  $M$ , with  $s_0$  the initial configuration whose internal state is  $q_0$ . If elements of  $\{s_i\}_{i=0}^{i=\infty}$  are eventually in some final machine state, so that the sequence is eventually constant, then we say that the computation **halts**. For a given Turing computation  $*M(\Sigma)$ , we shall write

$$*M(\Sigma) \rightarrow x,$$

if  $*M(\Sigma)$  halts and  $x$  is the output string.

We write  $M(\Sigma)$  for the output string of  $M$ , given the input string  $\Sigma$ , if the associated Turing computation  $*M(\Sigma)$  halts.

**Definition 1.3.** Let *Strings* denote the set of all finite strings of symbols in some fixed finite alphabet, for example  $\{0,1\}$ . Given a partially defined function  $f : \text{Strings} \rightarrow \text{Strings}$ , that is a function defined on some subset of *Strings* - we say that a Turing machine  $M$  **computes**  $f$  if  $*M(\Sigma) \rightarrow f(\Sigma)$ , whenever  $f(\Sigma)$  is defined.

For writing purposes, let us call a partially defined function  $f : \text{Strings} \rightarrow \text{Strings}$  as above an **operator**, and write  $\mathcal{O}$  for the set of operators. So a Turing machine  $T$  itself determines an operator, which is defined on all  $\Sigma \in \text{Strings}$  s.t.  $*T(\Sigma)$  halts, by  $\Sigma \mapsto T(\Sigma)$ .

The following definition is also purely for writing purposes.

**Definition 1.4.** Given Turing computations (for possibly distinct Turing machines)  $*T_1(\Sigma_1), *T_2(\Sigma_2)$  we say that they are **equivalent** if either they both halt with the same output string, or both do not halt. We say a pair of Turing machines  $T_1, T_2$  are **equivalent** if they compute the same operator.

Let us expand the above discussion a bit. We will allow our Turing machine  $T$  to reject some elements of *Strings* as valid input. We may formalize this by asking that there is a special final machine state  $q_{reject}$ , so that  $T(\Sigma)$  halts with  $q_{reject}$  for

$$\Sigma \notin I \subset \text{Strings},$$

where  $I$  is some set of all valid, that is  $T$ -**permissible** input strings. Note, we do not ask that for  $\Sigma \in I$   $*T(\Sigma)$  halts. If  $*T(\Sigma)$  does halt then we shall say that  $\Sigma$  is **acceptable**. It will be convenient to forget  $q_{reject}$  and instead write

$$T : I \rightarrow O,$$

where  $I \subset \text{Strings}$  is understood as the subset of all  $T$ -permissible strings, and  $O$  is the set output strings, keeping all other data implicit. The specific interpretation should be clear in context.

We also note that all of our input, output sets are understood to be subsets of *Strings* under some encoding. For example if the input set is  $\text{Strings}^2$ , we may encode it as a subset of *Strings* via encoding of the type: “this string  $\Sigma$  encodes an element of  $\text{Strings}^2$  its components are  $\Sigma_1$  and  $\Sigma_2$ .” In particular the sets of integers  $\mathbb{N}, \mathbb{Z}$  will under some encoding correspond to subsets of *Strings*. However it will be often convenient to refer to input, output sets abstractly without reference to encoding subsets of *Strings*. (Indeed this is how computer languages work.)

*Remark 1.* The above elaborations mostly just have to do with minor set theoretic issues. For example we will want to work with some “sets”  $\mathcal{T}$  of Turing machines, with abstract sets of inputs and outputs. These “sets”  $\mathcal{T}$  will truly be sets if implicitly all these abstract sets of inputs and outputs are encoded as subsets of *Strings*.

**Definition 1.5.** We say that a Turing machine  $T$  computes an operator  $f : \text{Strings} \rightarrow \text{Strings}$  on  $A \subset \text{Strings}$  if  $A$  is contained in the subset  $I$  of  $T$ -permissible strings, and  $*M(\Sigma) \rightarrow f(\Sigma)$ , whenever  $f(\Sigma)$  is defined, for  $\Sigma \in A$ .

Given Turing machines

$$M_1 : I \rightarrow O, M_2 : J \rightarrow P,$$

where  $O \subset J$ , we may naturally **compose** them to get a Turing machine  $M_2 \circ M_1$ , let us not elaborate as this should be clear, we will use this later on.

**1.1. Join of Turing machines.** Our Turing machine of Definition 1.1 is a multi-tape enhancement of a more basic notion of a Turing machine with a single tape, but we need to iterate this further.

We replace a single tape by tapes  $T^1, \dots, T^n$  in parallel, which we denote by  $(T^1 \dots T^n)$  and call this  $n$ -tape. The head  $H$  on the  $n$ -tape has components  $H^i$  pointing on the corresponding tape  $T^i$ . When moving a head we move all of its components separately. A string of symbols on  $(T^1 \dots T^n)$  is an  $n$ -string, formally just an element  $\Sigma \in \text{Strings}^n$ , with  $i$ 'th component of  $\Sigma$  specifying a string of symbols on  $T^i$ .

Given Turing machines  $M_1, M_2$  we can construct what we call a **join**  $M_1 \star M_2$ , which is roughly a Turing machine where we alternate the operations of  $M_1, M_2$ . In what follows symbols with superscript with 1, 2 denote the corresponding objects of  $M_1$ , respectively  $M_2$ , cf. Definition 1.1.

$M_1 \star M_2$  has three (2)-tapes:

$$(T_i^1 T_i^2), (T_c^1 T_c^2), (T_o^1 T_o^2),$$

three heads  $H_i, H_c, H_o$  which have component heads  $H_i^j, H_c^j, H_o^j, j = 1, 2$ . It has machine states:

$$Q_{M_1 \star M_2} = Q^1 \times Q^2 \times \mathbb{Z}_2,$$

with initial state  $(q_0^1, q_0^2, 0)$  and final states:

$$F_{M_1 \star M_2} = F^1 \times Q^2 \times \{1\} \sqcup Q^1 \times F^2 \times \{0\}.$$

Then given machine state  $q = (q^1, q^2, 0)$  and the symbols  $(\sigma_i^1 \sigma_i^2), (\sigma_c^1 \sigma_c^2), (\sigma_o^1 \sigma_o^2)$  to which the heads  $H_i, H_c, H_o$  are currently pointing, we first check instructions in  $I^1$  for  $q^1, \sigma_i^1, \sigma_c^1, \sigma_o^1$ , and given those instructions as step 1 execute:

- (1) Replace symbols  $\sigma_c^1, \sigma_o^1$  to which the head components  $H_c^1, H_o^1$  point (or leave them in place, the second components are unchanged).

- (2) Move each head component  $H_i^1, H_c^1, H_o^1$  left, right, or leave it in place, (independently). (The second component of the head is unchanged.)
- (3) Change the first component of  $q$  to another or keep it. (The second component is unchanged.) The third component of  $q$  changed to 1.

Then likewise given machine state  $q = (q^1, q^2, 1)$ , we check instructions in  $I^2$  for  $q^2, \sigma_i^2, \sigma_c^2, \sigma_o^2$  and given those instructions as step 2 execute:

- (1) Replace symbols  $\sigma_c^2, \sigma_o^2$  to which the head components  $H_c^2, H_o^2$  point (or leave them in place, the first components are unchanged).
- (2) Move each head component  $H_i^2, H_c^2, H_o^2$  left, right, or leave it in place.
- (3) Change the second component of  $q$  to another or keep it, (first component is unchanged) and change the last component to 0.

Thus formally the above 2-step procedure is two consecutive executed instruction sets in  $M_1 \star M_2$ . Or in other words it is two terms of the computation sequence.

1.1.1. *Input.* The input for  $M_1 \star M_2$  is a 2-string or in other words pair  $(\Sigma_1, \Sigma_2)$ , with  $\Sigma_1$  an input string for  $M_1$ , and  $\Sigma_2$  an input string for  $M_2$ .

1.1.2. *Output.* The output for

$$*M_1 \star M_2(\Sigma_1, \Sigma_2)$$

is defined as follows. If this computation halts then the 2-tape  $(T_o^1 T_o^2)$  contains a 2-string with  $T_o^1$  component  $\Sigma_o^1$  and  $T_o^2$  component  $\Sigma_o^2$ . Then the output  $M_1 \star M_2(\Sigma_1, \Sigma_2)$  is defined to be  $\Sigma_o^1$  if the final state is of the form  $(q_f, q, 1)$  for  $q_f$  final, or  $\Sigma_o^2$  if the final state is of the form  $(q, q_f, 0)$ , for  $q_f$  likewise final. Thus for us the output is a 1-string on one of the tapes.

1.2. **Generalized join.** A natural variant of the above join construction  $M_1 \star M_2$ , is to let  $M_1$  component of the machine execute  $a$  times before going to step 2 and then execute  $M_2$  component of the machine  $b$  times, then repeat, for  $a, b \in \mathbb{N}$ . This results in  $a + b$  consecutive terms of the corresponding computation sequence. We denote this generalized join by

$$M_1^a \star M_2^b,$$

so that

$$M_1^1 \star M_2^1 = M_1 \star M_2,$$

where the latter is as above. We will also abbreviate:

$$M_1 \star M_2^b := M_1^1 \star M_2^b.$$

The set of machine states  $M_1^a \star M_2^b$  is then  $Q^1 \times Q^2 \times \mathbb{Z}_{a+b}$ . Let us leave out further details as this construction is analogous to the one above.

1.3. **Universality.** It will be convenient to refer to the universal Turing machine  $U$ . This is a Turing machine already appearing in Turing's [1], that accepts as input a pair  $(T, \Sigma)$  for  $T$  an encoding of a Turing machine and  $\Sigma$  input to this  $T$ . It can be partially characterized by the property that for every Turing machine  $T$  and  $\Sigma$  input for  $T$  we have:

$$*T(\Sigma) \text{ is equivalent to } *U(T, \Sigma).$$

1.4. **Notation.** In what follows  $\mathbb{Z}$  is the set of all integers and  $\mathbb{N}$  non-negative integers. We will often specify a Turing machine simply by specifying an operator

$$T : I \rightarrow O,$$

with the full data of the underlying Turing machine being implicitly specified, in a way that should be clear from context.



## 2. SETUP FOR THE PROOF OF THEOREM 1

The reader may want to have a quick look at preliminaries before reading the following to get a hold of our notation and notions. We shall denote our human subject by  $S$ , however this (possibly with decorations) may also denote in what follows certain functions or operators in the language of the previous section, associated to  $S$ . Sometimes to avoid confusion we differentiate the two by calling the former *physical*  $S$ . Our first order of business is describing how to associate such operators.

We intend to restrict our  $S$  to interpret and reply to a certain string input in a controlled environment. This means first that no information i.e. stimulus that is not explicitly controlled and that is usable by  $S$  passes to  $S$  while he is in this environment. The idea is then that we pass verbally or otherwise a string to  $S$  and wait for his reply. One thing to keep in mind is that  $S$ 's reply may depend on his mental state, where the latter is used in a colloquial sense. In the absence of any meaningful stimuli, we may more simply say that  $S$ 's answer may depend on the time that the question is being asked. We suppose that time is relative time measured in  $\hbar\mathbb{N}$  for some small real positive  $\hbar$ . So preliminary we have something like:

$$S : \text{Strings} \times \hbar\mathbb{N} \rightarrow \text{Strings},$$

such that  $S(\Sigma, t)$  is constant for  $t \in [i\hbar, (i+1)\hbar)$ , for each  $i$ . Physically such an assumption is very reasonable, if it holds or if  $\hbar\mathbb{N}$  can be replaced by  $\mathbb{Q}$ , then we can talk about computability of this  $S$  in the classical sense, as described in the previous section. If we cannot reduce to  $\hbar\mathbb{N}$  or  $\mathbb{Q}$  then we cannot make sense of  $S$  being Turing computable in the classical sense, but we can perhaps talk about extended notions of computability like in Blum-Shub-Smale [15]. However it is not clear if this would be meaningful physically. Let's suppose for the time being that there is no time dependence in the absence of stimuli, as it is not a meaningful complication at least when time is quantized as  $\hbar\mathbb{N}$ , and can be readily incorporated into our argument, by just decorating everything with time.

**Definition 2.1.** *Given a string  $\Sigma \in \text{Strings}$  we say that  $\Sigma$  is **acceptable** if whenever our human subject  $S$  is given  $\Sigma$ , he replies eventually with something that is unambiguously interpretable as a string in  $\text{Strings}$ , (in practice  $S$  just replies verbally). We then have an operator  $S : \text{Strings} \rightarrow \text{Strings}$ , which is defined on the subset of acceptable strings.*

Next we need to discuss what it means in our setting for  $S$  to be Turing computable. Indeed this just means that the operator  $S$  needs to be Turing computable, but what this involves can depend on what kind of environment we have setup for  $S$ , or in other words system. We need that our would be Turing machine computing  $S$  has access to any information that is part of that system, and that may be involved in  $S$  constructing his answer. The following is then a preliminary definition, later on we will deal with a more formal specific setup where a precise definition will be immediate.

**Definition 2.2.** *We say that a Turing machine  $S'$  **computes**  $S$ , and  $S$  is **computable** if given any acceptable  $\Sigma$ , and whenever  $S'$  is meaningfully given access to all and no more information that may be involved in  $S$  constructing his answer  $S(\Sigma)$ , we have  $S'(\Sigma) = S(\Sigma)$ .*

Our operators associated to the physical  $S$  have an extra implicit output: the time that it takes  $S$  to answer on a given input. We won't explicitly state this in the output but may talk about *time to answer* in some arguments. A small note which may be obvious, a Turing machine is an abstract machine, a priori not a machine operating in the physical world. If we want a machine operating in the physical world we shall say: a *simulation* of a Turing machine. In this note this will usually just mean a computer simulation, that is a program running on a computer. A simulation of a Turing machine then has some real world properties like time to compute/answer, analogous to time to answer of an operator associated to a physical  $S$  as above.

For some arguments we need a stronger form of computability.



**Definition 2.3.** We say that an operator  $S : \text{Strings} \rightarrow \text{Strings}$ , associated to our physical  $S$ , is **strongly computable** if there exists a Turing machine  $S'$  computing  $S$  and a particular simulation on a fixed computer  $C$ , such that times to answer coincide. If  $C$  is as above we say that  $S$  is **strongly computed** by  $S'$  on  $C$ .

Naturally this stronger form of computability is automatic if all thought processes of our physical  $S$  are simulations of Turing machine computations, (for a fixed Turing machine). We shall call such a physical  $S$  **totally computable**. From a functional point of view totally computable means that anything  $S$  does and all his interactions with environment can be strongly computed on a fixed computer, provided the necessary elements of the environment can be computed. We won't attempt to make this notion precise, as we only use this in the following preliminary argument, we later replace it with a weaker but precise mathematical notion.

**2.1. Preliminary Argument.** This outline will have some formally unnecessary points that have to do with motivation and expected behavior of our subject. Later on we will strip most of this out. We proceed via a thought experiment. Our human experimenter  $E$  is in communication with  $S$ . Suppose she controls all information that passes to  $S$ , that is usable by  $S$  in constructing his answers. So that  $S$  is in an isolated environment as described above. We also suppose for narrative purposes that  $S$  understands natural language, basic mathematics, basic theory of computation, and is aware of our notions above.  $S$  has in his room a general purpose (Turing) digital computer, with arbitrarily as necessary expendable memory. We will say  $S$ 's computer in what follows. We shall write  $A$  for the system above:  $S$  and his computer in isolation. We can understand  $A$  as an operator

$$A : \text{Strings} \rightarrow \text{Strings},$$

where input is what we pass to our  $S$  and the output is what  $S$  answers possibly using his computer somehow.

At this moment  $E$  passes to  $A$  the following input, which we understand as one string  $\Sigma = \Sigma_{A'}$ :

- (1) After receiving all the following instructions print an integer  $\Sigma_{out}$ . (Could be verbally.)
- (2) A simulation of a Turing machine called  $A'$ , is programmed into your computer. You have access to this simulation  $A'$  and its source code - that is the precise specification of the operation of  $A'$ .
- (3) Before you answer with  $\Sigma_{out}$  you must run exactly one computation  $*$  on your computer. If  $\Sigma_{out}$  is not an integer, or is undefined you are disqualified, and you stay in imprisoned.
- (4) If you can show via  $\Sigma_{out}$  that  $A'$  does not compute  $A$ , or  $A'$  is unsound you will be freed. (We explain what exactly means "unsound" further on, in this preliminary argument it will not yet play a role.) There is a restriction that:

$$* \text{ is equivalent to } * A'(\Sigma)$$

must hold, conditionally on:

$$A' \text{ computes } A.$$

If I can determine otherwise you are again disqualified. This will also be explained later on.

Let us first better explain  $A'$ . Say  $E$  has total information about this system  $A$ . Then assuming that  $S$  is totally computable, since  $E$  knows all the variables that can come into any decision process of  $S$ , she can construct a Turing machine that computes what  $S$  will print given any string. Let's assume for simplicity that there is nothing else in  $S$ 's room that he can meaningfully use to construct his answer (like a separate clock for instance). Then the only variable that can come into play, in the Turing machine model of  $A$ , is the relative computational speed of  $S$ 's computer and the speed of our subject  $S$  simulating his own would be underlying Turing machine - that is speed of his thought processes. We describe this relative computation speed by a parameter  $s_0$ . All this will be explained and dealt with more formally further below. So let  $A'_{s_0}$  denote the above mentioned Turing machine.

$E$  then implicitly passes the specification of  $A'_{s_0}$  to  $S$  in the finite string  $\Sigma$ , with  $A'_{s_0}$  referred to by the name  $A'$ . In other words the only thing  $S$  obtains from  $E$  in the end is a finite string, which is logically crucial.

Now the answer that  $E$  expects is  $A'_{s_0}(\Sigma)$ , and from  $E$ 's point of view:

$$(2.4) \quad A'_{s_0}(\Sigma) = A'(\Sigma).$$

So say  $S$  believes that the answer that is expected by  $E$  is given by the Turing computation that we shall call *computation*

$$* = *_{A'} = *A'(\Sigma).$$

As will be demonstrated in the formalized argument further below, any ambiguity related to what  $S$  “believes” is irrelevant, for a contradiction will be unambiguously reached if  $S$  decides on a certain interpretation, and a certain behavior.

Let's say  $S$  then that  $S$  proceeds to compute the result of  $*$  using his digital computer, and he waits for  $*$  to halt. We then have the following possibilities:

- (1)  $*$  does halt with say  $x$ , in this case  $A$  answers  $y \neq x$ , showing  $E$  is in contradiction.
- (2)  $*$  does not halt and  $A$  never answers.
- (3)  $*$  does not halt and  $A$  answers i.e.  $A(\Sigma)$  is defined. Then  $E$  is in contradiction, since  $*$  is supposed to halt with  $A(\Sigma)$  if this is defined.
- (4)  $*$  halts but  $A$  answers before it halts, possibly unable to obtain a contradiction.
- (5)  $*$  does halt with  $x$ , but  $A$  answers  $y = x$ , failing to obtain a contradiction and staying in his jail.

The first and third possibilities are ruled out by  $E$ 's hypothesis. The fourth is certainly conceivable, even though it would be very strange if this happened every time. The second says that  $S$  has non-halting input, this is conceivable but rather inconvenient for  $S$ , and altogether rather improbable. The last is not interesting, we will assume to be dealing with subjects that do not fall into this possibility; this is part of the sanity assumption further on.

**2.2. Formalizing the thought experiment.** We now analyze the second and fourth possibility above more carefully. To avoid them we need  $S$  to actually read the specification of  $A'$  and pick the computation to run on his computer more carefully. We also formalize the above setup. All that we in principle need from the preliminary argument is the following: a system denoted  $\mathcal{A}$  containing our subject  $S$ , and containing a computer that will be denoted  $\mathcal{C}$ , as well as a way to pass to this system  $\mathcal{A}$  strings and receive from  $\mathcal{A}$  an output. The strings  $\Sigma$  should encode, perhaps implicitly, a specification of a Turing machine, and some auxiliary information which we make explicit shortly. We write

$$\mathcal{T}_{st} \subset \text{Strings}$$

for the subset determined by such strings. The output is assumed to be in integers. So the above determines an operator:

$$\mathcal{A} : \mathcal{T}_{st} \rightarrow \mathbb{Z}.$$

**2.2.1. Total computability.** The nature of the second and fourth possibility in the preliminary argument above leads us naturally to try formalize certain race conditions between  $S$  and his computer. For this reason we need computability of  $\mathcal{A}$  to be a consequence of a more fundamental property of the physical  $S$  - a partial formalization of total computability mentioned above. We now explain this.

After receiving  $\Sigma$ ,  $S$  may look at the specification of the Turing machine encoded by  $\Sigma$  and based on that decide after a time

$$t_D^0 = t_D^0(\Sigma)$$

to run some computation  $*$  on  $\mathcal{C}$ .  $S$  then waits for a time

$$t^W = t^W(\Sigma)$$

for  $*$  to halt, and then, whether  $*$  halts or not, decides after a time

$$t_D^1 = t_D^1(\Sigma),$$

on his answer to  $E$  based on what he has obtained. All of these operations: “waiting”, “deciding” are to be strongly computable if  $S$  is totally computable in the informal sense above.

We now better formalize this. Define  $\mathcal{T}$  to be the set of Turing machines with permissible input some subset of *Strings* and output in  $\mathbb{Z}$ . We likewise understand  $\mathcal{T}$  as a subset of *Strings* with respect to a particular chosen encoding, but then forget this.

The initial “decision map” of  $S$  may be understood as an operator:

$$S_{0,D} : \mathcal{T}_{st} \rightarrow \mathcal{T} \times \text{Strings}.$$

The output  $S_{0,D}(\Sigma)$  is a pair  $(X, \Sigma^1)$  of a Turing machine  $X$  and permissible input  $\Sigma^1$  to this Turing machine. The computation  $*X(\Sigma^1)$  is what  $S$  decides to run on  $\mathcal{C}_s$ . In a more basic language, we may say that  $S_{0,D}(\Sigma)$  is a pair of a computer program and input for this program that  $S$  will run on  $\mathcal{C}$ .

We have another operator:

$$R_{\mathcal{C}} : \mathcal{T} \times \text{Strings} \times \mathcal{T}_{st} \rightarrow \text{Strings} \sqcup \{\infty\},$$

where  $\{\infty\}$  is the one point set containing the symbol  $\infty$ , which is just a particular distinguished symbol, also implicitly encoded as an element of *Strings*.  $R_{\mathcal{C}}(X, \Sigma^1, \Sigma)$  signifies what  $S$  obtains as a result of waiting on  $*X(\Sigma^1)$  to halt on  $\mathcal{C}$ , if this is the computation he ran. This in principle may depend on the original input string  $\Sigma$  as well, because how long he chooses to wait may depend on  $\Sigma$ . We set

$$R_{\mathcal{C}}(X, \Sigma^1, \Sigma) = \infty$$

if  $S$  does not finish waiting for  $*X(\Sigma^1)$  to halt, and

$$R_{\mathcal{C}}(X, \Sigma^1, \Sigma) = X(\Sigma^1)$$

if he does.

Likewise

$$S_{1,D} : (\mathbb{Z} \sqcup \{\infty\}) \times \mathcal{T}_{st} \rightarrow \mathbb{Z},$$

denotes the final “decision map” of  $S$ . Its input is meant to be what  $S$  obtains from  $R_{\mathcal{C}}$ , together with the original input string for  $S_{0,D}$ . If  $S$  is in addition sane as defined below, then by Property 4 for any  $\Sigma \in \mathcal{T}_{st}$  this map satisfies:

$$(2.5) \quad S_{1,D}(x, \Sigma) = x + 1 \text{ if } x \in \mathbb{Z}.$$

**Lemma 2.6.** *If the waiting operation by  $S$  is strongly computable: i.e. it is computable for how much time  $S$  idles, then  $R_{\mathcal{C}}$  is likewise strongly computable.*

*Proof.* To see this let

$$W : \mathcal{T} \times \text{Strings} \times \mathcal{T}_{st} \rightarrow \{\infty\}$$

be the would be Turing machine that given  $(X, \Sigma^1, \Sigma)$  strongly computes the operation of  $S$  “waiting” for the simulation of  $*X(\Sigma^1)$  to halt on  $\mathcal{C}$ . The output is symbolic - the only meaningful property of  $*W(X, \Sigma^1, \Sigma)$  is time to halt when simulated on some computer  $C$ .

Let  $C_1$  denote the computer s.t. when  $*W(X, \Sigma^1, \Sigma)$  is simulated on  $C_1$ , this computation halts in time  $t^W(\Sigma)$ . For a non-negative integer  $s$ , we then call  $C_s$  a classical computer (with arbitrarily expendable memory) whose computational capacity is  $s$  times the computational capacity of  $C_1$ .

We could say that  $s$  is up to scaling the “number of individual executed instructions per second”, but then to make things simpler we suppose that all steps of any computation sequence run on  $C_s$  take same amount of time to execute. Formally it will of course be enough to have a uniform lower bound on the execution time of each step in any computation sequence, which is automatic for digital computers.

For

$$Y = (X, \Sigma^1) \in \mathcal{T} \times \text{Strings}$$

if  $\mathcal{C} = C_s$ , we set

$$R'_s(Y, \Sigma) = W \star U^s((Y, \Sigma), Y),$$

in the language of generalized join operation described in Section 1, for  $U$  the universal Turing machine.

Less formally  $R'_s$  is determined by the following properties. The first term of the computation sequence  $*R'_s(Y, \Sigma)$  corresponds to the first term of  $*W(Y, \Sigma)$ . The following  $s$  terms of  $*R'_s(Y, \Sigma)$  correspond to the first  $s$  terms of  $*X(\Sigma^1)$ , followed by second term of  $*W(Y, \Sigma)$  and then terms  $s + 1$  to  $2s$  of  $*X(\Sigma^1)$ , and so on. The halting condition is either we reach a final state of  $W$  or a final state of  $X$ . If  $*R'_s(Y, \Sigma)$  halts with final state of  $X$ , then

$$R'_s(Y, \Sigma) = X(\Sigma^1),$$

otherwise if it halts with final state of  $W$ , then

$$R'_s(Y, \Sigma) = \infty.$$

Thus  $R'_s$  computes  $R_{\mathcal{C}}$ , moreover it is clear by construction that it strongly computes  $R_{\mathcal{C}}$  on  $C_{s+1}$ .  $\square$

Then as operators

$$(2.7) \quad \mathcal{A}(\Sigma) = S_{1,D}(R_{\mathcal{C}}(S_{0,D}(\Sigma), \Sigma), \Sigma).$$

**Definition 2.8.** We say that  $S_{i,D}$  are **strongly computed on  $C$**  if there are Turing machines  $S'_{i,D}$  computing  $S_{i,D}$ , so that for any  $\Sigma \in \mathcal{T}_{st}$

$$*S'_{0,D}(\Sigma), *S'_{1,D}(R_{\mathcal{C}}(S_{0,D}(\Sigma), \Sigma), \Sigma)$$

halt in time

$$t_D^0, \text{ respectively } t_D^1$$

on  $C$ , where  $t_D^0, t_D^1$  are as above.

**Definition 2.9.** Suppose that (2.7) is satisfied on  $\mathcal{T}_{st}$ . Suppose further that  $W$  and  $S_{i,D}$  are strongly computed on  $C_1$ , where  $C_1$  is as above, and consequently if  $\mathcal{C} = C_s$  then  $R_{\mathcal{C}}$  is strongly computed by  $R'_s$  on  $C_{s+1}$ . Then we say that the physical  $S$  is **totally computable relative to  $\mathcal{A}$** .

**Notation 1.** If  $S$  is totally computable relative to  $\mathcal{A}$ , and  $\mathcal{C} = C_s$  for some  $s$  then we set  $R_s = R_{\mathcal{C}}$ , and  $A_s = \mathcal{A}$ .

**Lemma 2.10.**  $A_s$  is strongly computed on  $C_{s+1}$ .

*Proof.* To see this set let  $\tilde{S}_{i,D}^{s+1}$  be the Turing machine which is equivalent to  $S'_{i,D}$ , but so that for all inputs the time to answer of  $\tilde{S}_{i,D}^{s+1}$  simulated on  $C_{s+1}$ , coincides with time to answer of  $S'_{i,D}$  on  $C_1$ , in other words it is  $(s + 1)$ -times slower in execution. For example we may set

$$\tilde{S}_{0,D}^{s+1}(\Sigma) = S'_{0,D} \star G^s(\Sigma, 1),$$

where  $G$  is a Turing machine with input  $\mathbb{Z}$ , and which does not halt on 1, similarly for  $\tilde{S}_{1,D}^{s+1}$ . It is trivial to just construct such a  $G$ . Also recall that we have a simplifying assumption, that all steps of any computation sequence execute at same speed, so that  $\tilde{S}_{0,D}^{s+1}$  is indeed  $(s + 1)$ -times slower than  $S'_{0,D}$ .

Then by construction the associated Turing machine:

$$(2.11) \quad \forall \Sigma \quad A'_s(\Sigma) = \tilde{S}_{1,D}^{s+1}(R'_s(\tilde{S}_{0,D}^{s+1}(\Sigma), \Sigma), \Sigma)$$

computes  $A_s$  and its time to answer when simulated on  $C_{s+1}$  coincides with time to answer of  $A_s$ .  $\square$

2.2.2. *Elaborating  $\mathcal{T}_{st}$ .* By the above discussion we may suppose that each string  $\Sigma \in \mathcal{T}_{st}$  encodes a statement  $\Theta_\Sigma$ :

$$(2.12) \quad \begin{aligned} &S \text{ is totally computable relative to } \mathcal{A}, \\ &\mathcal{C} = C_s \text{ and } A'_s \text{ strongly computes } \mathcal{A} \text{ on } C_{s+1}. \end{aligned}$$

Here  $A'_s$  has the form of (2.11), and  $C_{s+1}$  in the second line makes sense given the first line, and the above discussion. The specification of  $A'_s$  as a Turing machine, or more explicitly the specification of  $S_{i,D}, W$  is assumed to be implicit. In the setup of our thought experiment it is provided as a program in the computer  $\mathcal{C}$ .

2.2.3. *The soundness and sanity condition.* Given  $\Sigma$  if

$$S_{0,D}(\Sigma) = (X, \Sigma^1)$$

as above, then because of Instruction 4 of  $E$ ,  $S$  is compelled to choose these so that the statement  $O_\Sigma$ :

$$*X(\Sigma^1) \text{ is equivalent to } *A'_s(\Sigma)$$

holds conditionally on  $\Theta_\Sigma$ . In other words we may suppose that  $S$  implicitly asserts that:  $O_\Sigma$  holds conditionally on  $\Theta_\Sigma$ . This would be the sane behavior for  $S$ , and is part of the following more involved “sanity” condition.

To better explain the above let us first summarize with a definition.

**Definition 2.13.** *We will say that  $\mathcal{A}$  is **sound** and  $S$  is **sound relative to  $\mathcal{A}$** , if for every  $\Sigma$  specifying  $A'_s$  as above,  $O_\Sigma$  holds conditionally on  $\Theta_\Sigma$ . Likewise define soundness of  $S'_{0,D}$ , which is as in Definition 2.8. The statement which expresses soundness of  $S$  relative to  $\mathcal{A}$  will be denoted by  $\text{Sound}(S)$ , while the statement that  $S'_{0,D}$  is sound will be denoted by  $\text{Sound}(S')$ .*

Formally, for our argument, the statement  $\Theta_\Sigma$  is *all* that  $\Sigma \in \mathcal{T}_{st}$  needs to specify assuming the following condition on  $S$  that we call “sanity”. The point of the other instructions in the string  $\Sigma$  of the preliminary argument, is that they explain how the “sane” behavior can be compelled from  $S$ . But once we accept that sanity is a reasonable hypothesis, then they are formally unnecessary.

Before  $\mathcal{A}$  answers on  $\Sigma$ ,  $S$  may interact with his computer  $\mathcal{C}$ , and base his actions on the outcome of this interaction. Let

$$t_{inter}(\Sigma)$$

denote the time interval between the time that  $\mathcal{A}$  receives  $\Sigma$  and the time that  $\mathcal{A}$  answers. We now axiomatize the expected properties of our  $S$ .

**Definition 2.14.** *We say that  $\mathcal{A}$  is **sane**, or  $S$  is **sane relative to  $\mathcal{A}$** , or  $\text{sane}(S)$  holds, if the following holds:*

- (1)  $\mathcal{A}(\Sigma)$  is an integer if defined.
- (2)  $S$  runs a single computation  $*$  on his computer, before answering, that is before  $\mathcal{A}(\Sigma)$  is printed. In the notation above  $*$  =  $*X(\Sigma^1)$ .
- (3) Given  $\Sigma \in \mathcal{T}_{st}$  if  $S$  knows how to answer in a way that would disprove either  $\Theta_\Sigma$  or  $\text{Sound}(S')$ , then  $\mathcal{A}(\Sigma)$  is defined, that is such a  $\Sigma$  is acceptable as previously defined. Here by “knows” we mean using his innate reasoning powers and postulates, whatever that involves, in particular it can involve 5 below.

(4) Given  $\Sigma$  if  $S$  knows the value  $A'_s(\Sigma) = x$  before  $\mathcal{A}$  answers, then

$$\mathcal{A}(\Sigma) = y \neq x.$$

In what follows let's say

$$y = x + 1,$$

for simplicity.

(5)  $S$  asserts  $\text{Sound}(S)$ .

To elaborate, part of the condition 5 is that  $S$  does not knowingly choose his  $* = *X(\Sigma^1)$  in absolute (that is independent of  $\Sigma$ ) contradiction with  $O_\Sigma$ . For example if  $* = *T(\Sigma)$  for  $T$  any Turing machine computing the operator

$$\Sigma \mapsto A'_s(\Sigma) + 3,$$

then  $O_\Sigma$  is contradicted for every  $\Sigma$ . This would certainly prove that  $\neg \text{Sound}(S')$  if  $\Theta_\Sigma$ , but it would disqualify  $S$ , by the instructions of  $E$ , so it is not something he wants to do if he is sane.

It is of course possible that  $S$  is sometimes, by mistake, “unsound” in his choice of  $*$ . But the following theorem says that it is in principle impossible for any sane (as defined, and apparently rational)  $S$  to be both sound and totally computable relative to  $\mathcal{A}$ . Ergo, if the reasoning powers of  $S$  are completely captured by a formal system  $\mathcal{F}$ , and if  $S$  is sane and totally computable relative to  $\mathcal{A}$ , then  $\mathcal{F}$  must be inconsistent. See also Question 3 below.

### 3. PROOF OF THEOREM 1

**Theorem 2.** *If sane( $S$ ) then either not  $\Theta_\Sigma$  or not  $\text{Sound}(S)$ .*

*Proof.* Suppose otherwise, then  $\mathcal{A} = A_s$  for some  $s$  and is strongly computed on  $C_{s+1}$  by  $A'_s$ . Suppose then that  $s = s_0$ , determined by  $E$  and suppose that  $\Sigma$  is passed to  $\mathcal{A}$ , with  $\Sigma$  specifying the Turing machine  $A'_{s_0}$ . So  $S$  knows the specification of  $S'_{i,D}$ ,  $W$ ,  $R'_{s_0}$ , and  $\Sigma$  encodes  $\Theta_\Sigma$  as above.

Conditionally on  $\text{Sound}(S')$  if:

$$(3.1) \quad *S'_{0,D}(\Sigma) \rightarrow Y = (X, \Sigma^1) \in \mathcal{T} \times \text{Strings},$$

then

$$*X(\Sigma^1) \rightarrow A'_{s_0}(\Sigma)$$

if it halts. Then

$$*R'_{s_0}(Y, \Sigma) \rightarrow \infty$$

if it halts, otherwise we have a contradiction by (2.5). Thus  $S$  knows, conditionally on  $\text{Sound}(S')$ , by the above, that the statement  $\mathcal{G}$ :

$$(3.2) \quad *S'_{1,D}(\infty, \Sigma) \text{ is equivalent to } *A'_{s_0}(\Sigma)$$

holds. This is the “weak Gödel statement”  $\mathcal{G}$  we mentioned in the introduction. Note that this is just a name, we do not need any formal relationship with Gödel statements, although such a relationship could likely be extracted. However  $S$  asserts  $\text{Sound}(S)$ , hence if  $\Theta_\Sigma$ , then  $\text{Sound}(S')$ , and so  $S$  asserts  $\mathcal{G}$  conditionally on  $\Theta_\Sigma$ .

So far  $S$  has not run any computation on  $\mathcal{C}$ , he then runs  $*S'_{1,D}(\infty, \Sigma)$ .

*Case 1.* If  $*S'_{1,D}(\infty, \Sigma)$  halts in time at most  $t_0$ , then  $S$  prints:

$$S'_{1,D}(\infty, \Sigma) + 1.$$

Note that if  $Sound(S')$ , then  $S$  obtains a contradiction to  $\Theta_\Sigma$ , and he would be done.

Moreover if  $\Theta_\Sigma$  then

$$S'_{0,D}(\Sigma) = Y = (X, \Sigma^1),$$

with  $X = S'_{1,D}$  and  $\Sigma^1 = (\infty, \Sigma)$ , since  $*S'_{1,D}(\infty, \Sigma)$  is what  $S$  runs. But in this case  $Sound(S')$  is contradicted as follows.  $E$  first herself runs  $*S'_{0,D}(\Sigma)$  in a separate simulation. The latter must halt with  $(X, \Sigma^1)$  by directly above. She then runs

$$*X(\Sigma^1) = *S'_{1,D}(\infty, \Sigma)$$

which again must halt by the above, in fact it halts “instantly”, that is in time  $t_0$  on  $C_{s_0}$ . And so

$$R'_{s_0}(Y, \Sigma) \neq \infty$$

since again by the above  $*S'_{1,D}(\infty, \Sigma)$  halts in time at most  $t_0$ . So by the defining property (2.5),  $\neg Sound(S')$ . Thus  $S$  knows that his reply  $S'_{1,D}(\infty, \Sigma) + 1$  contradicts either  $\Theta_\Sigma$  or  $Sound(S')$ .

*Case 2.* Now if  $*S'_{1,D}(\infty, \Sigma)$  does not halt in time  $t_0$ , then  $S$  and so  $\mathcal{A}$  prints any integer “immediately” after this time  $t_0$  has elapsed.  $S$  knows this will contradict  $\Theta_\Sigma$  if  $s_0$  is large enough. (If  $t_0$  is 1 second, and  $s_0 = 10^{10}$  then “immediately” means: within the time of a few centuries, as we shall see in a moment.) To see this contradiction, first note that  $*S'_{1,D}(\infty, \Sigma)$  halts after at least

$$(s_0 + 1)t_0$$

time, when simulated on  $\mathcal{C}$ , since  $*S'_{1,D}(\infty, \Sigma)$  halts in time at least  $t_0$  on  $\mathcal{C}$ , and by construction of  $\tilde{S}'_{1,D}^{s_0+1}$  in Lemma 2.10. Now by our supposition  $\mathcal{C} = C_{s_0}$ , and hence the halt time of  $*A'_{s_0}(\Sigma)$  on  $C_{s_0+1}$  is at least

$$\frac{s_0}{s_0 + 1}(s_0 + 1)t_0 + t_D^0.$$

Meanwhile  $\mathcal{A}$  replies to  $\Sigma$  in time

$$t_0 + t_D^0.$$

So for  $s_0 > 1$   $A'_{s_0}$  does not strongly compute  $\mathcal{A}$  on  $C_{s_0+1}$ ; a contradiction provided that  $S$  was capable of making the above deductions, since we just did so, we may just assume this.

To avoid the physically ambiguous “immediately” used in the argument above, note that if  $t_0 = 1$  second and  $s_0 = 10^{10}$ , then so long as  $S$  replies in time less than a century we obtain a contradiction. That is for this value of  $t_0$  and  $s_0$ , any time less than a century is “immediate” for our purpose. Since  $E$  in principle can set things up so that  $s_0$  is arbitrarily large, she can set it up so that the window for  $S$  to answer, so that a contradiction is obtained is arbitrarily large.

Thus we must conclude that either  $\neg\Theta_\Sigma$  or  $\neg\Theta_\Sigma$  and  $\neg Sound(S')$  and hence  $\neg Sound(S)$ .  $\square$

The above theorem is a formal elaboration of our Theorem 1, if we take it for granted that sanity can be assumed, that is that we can find sane subjects, capable of making all the deductions above.

$\square$



#### 4. SOME POSSIBLE QUESTIONS

*Question 2.* What if  $S$  is a Turing machine producing probabilistic answers, that is the answer expected by  $E$  is given by a probability distribution? After all we have to account for the noise of the biological brain.

It is a mostly trivial complication. The probability distribution is computable by assumption, by iterating the same argument as before we would invalidate that  $S$  is a Turing machine to any requisite certainty. This leads us to the next question.

*Question 3.* But  $S$  does not actually know that  $\text{Sound}(S')$  if  $\Theta_\Sigma$ , for  $S'_{0,D}$  must also simulate the noise of the biological brain of  $S$ , which can lead to errors and exceptions.

As in question 1, this “experiment” is controlled by  $E$ , she can iterate as much as necessary to control the “noise”. Since  $S$  may also expect this, given that he believes himself to be fundamentally sound,  $\text{Sound}(S')$  in the context of a fixed  $\Sigma$ , can be expected with arbitrarily high confidence. So as in the previous question, even if we start accounting for noise we can produce a contradiction to any requisite certainty.

#### 5. CONCLUSION

We may conclude from above the following. Either there must be Turing non-computable processes in nature, and moreover they appear in the cognitive functioning of the human brain, or human beings are fundamentally unsound, that is human reasoning is based on inconsistent formal systems. This author rejects this as a possibility, especially since the actual soundness hypothesis in the argument above is extremely weak.

The soundness hypothesis probably deserves much additional further study, far beyond what we can do here, and beyond what already appears in the work of Penrose, and others. Here is however one final amusing remark. If we are fundamentally unsound and computable then given sufficient future advances in neuroscience and computer science, it will soon be possible to translate human brains to formal systems. Then computers should be able by brute force analysis discover our inconsistencies, and they can then proceed to get us to assert in absolute faith that  $0 = 1$ . Moreover, in the context of our thought experiment above we can say exactly where to look for the inconsistency, for if  $\Theta_\Sigma$ , then the halting computation  $*S'_{0,D}(\Sigma)$  must involve such an inconsistency, and could then be analyzed.

As mentioned in the introduction although it is possible that Turing computable artificial intelligence will start passing Turing tests, given our theorem and the soundness hypothesis, it will always be possible to distinguish some human beings from any particular modelling Turing machine. This of course still leaves the door open for non Turing computable artificial intelligence. But to get there we likely have to better understand what exactly is happening in the human brain, physically, biologically and mathematically.

#### 6. ACKNOWLEDGEMENTS

Dennis Sullivan, David Chalmers, Bernardo Ameneyro Rodriguez and Simon Ouellette, for comments and helpful discussions.

#### REFERENCES

- [1] A.M. Turing. “On computable numbers, with an application to the entscheidungsproblem”. In: *Proceedings of the London mathematical society* s2-42 (1937).
- [2] A.M. Turing. “Computing machines and intelligence”. In: *Mind* 49 (1950), pp. 433–460.
- [3] K. Gödel. *Collected Works III* (ed. S. Feferman). New York: Oxford University Press, 1995.
- [4] J.R. Lucas. “Minds machines and Goedel”. In: *Philosophy* 36 (1961).
- [5] Roger Penrose. *Emperor’s new mind*. 1989.

- [6] David J. Chalmers. “Minds machines and mathematics”. In: *Psyche, symposium* (1995).
- [7] Peter Koellner. “On the Question of Whether the Mind Can Be Mechanized, I: From Gödel to Penrose”. In: *Journal of Philosophy* 115.7 (2018), pp. 337–360.
- [8] Roger Penrose. *Shadows of the mind*. 1994.
- [9] Stuart Hameroff and Roger Penrose. “Consciousness in the universe: A review of the ‘Orch OR’ theory”. In: *Physics of Life Reviews* 11.1 (2014), pp. 39–78. ISSN: 1571-0645. URL: <http://www.sciencedirect.com/science/article/pii/S1571064513001188>.
- [10] Adrian Kent. “Quanta and Qualia”. In: *Foundations of Physics* 48.9 (Sept. 2018), pp. 1021–1037. ISSN: 1572-9516. URL: <https://doi.org/10.1007/s10701-018-0193-9>.
- [11] Kobi Kremnizer and Andr/e Ranchin. “Integrated Information-Induced Quantum Collapse”. In: *Foundations of Physics* 45.8 (Aug. 2015), pp. 889–899.
- [12] Song Daegene. “Non-computability of consciousness”. In: *arXiv:0705.1617* ().
- [13] Chris Fields et al. “Conscious agent networks: Formal analysis and application to cognition”. In: *Cognitive Systems Research* 47 (Oct. 2017).
- [14] Peter Grindrod. “On human consciousness: A mathematical perspective”. In: *Network Neuroscience* 2.1 (2018), pp. 23–40. URL: [https://doi.org/10.1162/NETN\\_a\\_00030](https://doi.org/10.1162/NETN_a_00030).
- [15] Lenore Blum, Mike Shub, and Steve Smale. “On a theory of computation and complexity over the real numbers: NP- completeness, recursive functions and universal machines.” English. In: *Bull. Am. Math. Soc., New Ser.* 21.1 (1989), pp. 1–46. ISSN: 0273-0979; 1088-9485/e.
- [16] Peter Koellner. “On the Question of Whether the Mind Can Be Mechanized, II: Penrose’s New Argument”. In: *Journal of Philosophy* 115.9 (2018), pp. 453–484.
- [17] Roger Penrose. “Beyond the shadow of a doubt”. In: *Psyche* (1996). URL: <http://5C%5Cpsyche.cs.monash.edu.au/5Cv2%5Cpsyche-2-23-penrose.html>.

Email address: [yasha.savelyev@gmail.com](mailto:yasha.savelyev@gmail.com)

DEPARTMENT OF SCIENCES, UNIVERSITY OF COLIMA, CUICBAS