Self-Healing Software-Defined Networks Using AI-Based Failure Prediction and Dynamic Make-Before-Break Rerouting

Yashas Anand Kumar Vishwakarma, Aabha Manishkumar Parikh, and Mohamed Yusouf Eijaaz M
School of Computer Science and Engineering (SCOPE), Vellore Institute of Technology, India

Abstract—Traditional fault-tolerance architectures in Software-Defined Networks (SDN) operate reactively: following physical link disruption, asynchronous OpenFlow PORT_STATUS messages trigger centralized path recomputation, incurring severe packet loss, TCP congestion window collapse, and transient routing loops. Furthermore, hardware-assisted fast failover mechanisms (such as OpenFlow 1.3 OFPGT_FF groups) monitor physical port states and remain blind to "soft" network failures, including progressive optical degradation, micro-flapping, buffer bloat, and escalating packet drops.

This paper introduces an end-to-end self-healing SDN architecture that combines high-resolution telemetry, multi-scale temporal gradient feature engineering, sequence-based machine learning forecasting, dynamic risk barrier path optimization, and a provably zero-loss Make-Before-Break (MBB) flow migration protocol. By continuously analyzing first- and second-order telemetry derivatives alongside exponential moving average (EMA) divergence, our temporal model predicts link failures with an average advance lead time of 9.82 seconds ($H = 15$ s horizon). The controller dynamically scales edge weights using a non-linear barrier function $\Phi(P) = (1 - P + \epsilon)^{-1}$, smoothly steering traffic onto chordal backup paths through a two-phase commit downstream flow pre-installation before modifying ingress rules.

We evaluate the system across an exhaustive 1,800-trial benchmark grid comprising three heterogeneous topologies (Mesh, Fat-Tree $k = 4$, WAN), four distinct failure models (hard link down, intermittent flapping, gradual degradation, and congestion collapse), three traffic load intensities, and ten independent random seeds. Benchmarked against four comparative baselines—Reactive Dijkstra (B1), OpenFlow 1.3 Fast Failover (B2), Threshold Heuristics (B3), and Non-Temporal Learning ML (B4)—the proposed method achieves 0.00% packet loss across all 360 trials, reduces failover recovery time by 97.3% relative to Reactive Dijkstra (9.80 ms vs. 358.45 ms), and maintains sustained throughput (49.25 Mbps). Non-parametric paired Wilcoxon signed-rank tests ($p < 10^{-60}$) and very large effect sizes (Cohen's $d = -8.59$) demonstrate overwhelming statistical significance, verifying that proactive predictive self-healing fundamentally outperforms reactive and heuristic alternatives in modern SDN infrastructures.

Index Terms—Software-Defined Networking (SDN), OpenFlow 1.3, Predictive Fault Tolerance, Machine Learning, Make-Before-Break, Telemetry, Network Digital Twins.

I. Introduction

SOFTWARE-DEFINED Networking (SDN) decouples the control plane from underlying forwarding hardware, centralizing global network visibility and enabling dynamic traffic engineering [1]. However, this centralized architectural paradigm introduces substantial vulnerability during network component failures. Under conventional reactive resilience mechanisms, link or node disruptions must first physically manifest at the datapath. The affected switch then transmits an asynchronous OpenFlow PORT_STATUS or PACKET_IN message across the southbound channel to the centralized controller. The controller invokes a shortest-path algorithm (e.g., Dijkstra's algorithm) across the modified network graph $G = (V, E)$ and sequentially dispatches FLOW_MOD updates to intermediate switches.

The total reactive convergence interval T_{conv} is dictated by four sequential delays:

$$T_{\text{conv}} = T_{\text{detect}} + T_{\text{notify}} + T_{\text{calc}} + T_{\text{install}} \tag{1}$$

During T_{conv} (typically ranging from 150 to 600 ms in local clusters and exceeding 1,500 ms across wide-area networks), packets in flight and arriving traffic traversing the failed link are dropped. In production environments, even sub-second packet drop bursts induce catastrophic TCP retransmission timeouts (RTO), congestion window shrinkage, and severe Quality-of-Service (QoS) degradation for mission-critical enterprise applications.

To mitigate reactive control-plane latency, OpenFlow 1.3 standardized the Fast Failover group table (OFPGT_FF) [2]. Fast Failover allows datapaths to execute local hardware bucket switching upon link state change without querying the controller, achieving recovery times under 10 ms for physical disconnects. However, our investigation uncovers a critical "blind spot" in OpenFlow 1.3 Fast Failover: OFPGT_FF groups switch buckets solely based on the binary operational status of a monitored watch_port. In modern carrier networks and data centers, over 70% of network anomalies are soft failures—including optical fiber macro-bending, deteriorating transceiver lasers, progressive buffer bloat, micro-burst congestion, and intermittent cyclic flapping. Throughout soft degradation, the physical port remains in the UP state. Consequently, hardware Fast Failover groups never trigger, subjecting network traffic to persistent, unmitigated packet loss and latency inflation.

To solve both the reactive convergence delay and the soft failure blind spot, this paper proposes a predictive, proactive self-healing architecture for OpenFlow 1.3 networks. Rather than waiting for datapath failure events, the

system continuously aggregates multi-variate telemetry features, computes first- and second-order rate-of-change derivatives, forecasts impending failure probabilities using sliding-window machine learning models, dynamically inflates edge routing costs using a penalty barrier function, and executes zero-loss flow migration via a Make-Before-Break (MBB) invariant.

The primary contributions of this paper are:

1) High-Fidelity Predictive Pipeline: A multi-scale telemetry pipeline extracting instantaneous counters, rolling means, numerical rate-of-change slopes ($\frac{d}{dt}, \frac{d^2}{dt^2}$), and Exponential Moving Average (EMA) divergence, enabling reliable fault forecasting 9.82 seconds prior to physical collapse.
2) Risk-Aware Dynamic Routing: A continuous routing cost function incorporating an asymptotic barrier penalty $\Phi(P) = (1-P+\epsilon)^{-1}$, ensuring smooth, loop-free traffic deflection off deteriorating links before drop onset.
3) Make-Before-Break (MBB) Flow Protocol: A two-phase commit flow update procedure enforcing downstream pre-installation with high-priority rules (priority = 200) and a drain timer ($T_{\text{drain}} = 2 \times \text{RTT}_{\max}$) before ingress modification, achieving provably zero packet loss.
4) Empirical Validation at Scale: An exhaustive evaluation of 1,800 experimental trials across three network topologies, four failure modes, three load profiles, and ten seeds, verified via non-parametric Wilcoxon tests and Cohen's d effect sizes.

—

II. Related Work

A. Reactive Recovery and Fast Failover in SDN

Reactive failure recovery in OpenFlow networks has been comprehensively studied. Standard approaches rely on asynchronous controller notification followed by centralized graph recomputation [1]. While optimal paths are re-established, the convergence latency T_{conv} is bounded by controller workload and southbound round-trip times. Fast Failover group tables (OFPGT_FF) pre-install backup output buckets directly within switch TCAMs, executing sub-50ms failover upon physical carrier drop [2]. However, as documented by Troia et al. [3], hardware failover remains fundamentally incapable of addressing non-binary soft failures where link telemetry deteriorates without an electrical loss-of-signal.

B. Telemetry and Machine Learning in Programmable Networks

With the advent of fine-grained monitoring, in-band network telemetry (INT) and streaming telemetry have enabled high-resolution data plane visibility [3]. Sengendo and Granelli [4] proposed network digital twins for telemetry-based anomaly detection, demonstrating that temporal synchronization across digital replicas can identify datapath irregularities. However, digital twin architectures primarily operate as passive anomaly monitors without closing the autonomous remediation loop.

Deep Reinforcement Learning (DRL) has recently gained popularity for dynamic traffic engineering [5]. While DRL agents can adaptively balance loads, their black-box policy exploration introduces non-deterministic convergence, transient routing loops, and significant computational overhead during phase transitions. In contrast, our framework decouples the probabilistic prediction of link degradation (handled via supervised sequence modeling) from deterministic, loop-free path computation (handled via Dijkstra with asymptotic barrier penalties), ensuring provable safety and sub-5ms controller execution budgets.

—

III. System Architecture and Methodology

The proposed architecture comprises four tightly coupled subsystems running over standard OpenFlow 1.3 datapaths: (1) the High-Resolution Telemetry Collector, (2) the Multi-Scale Feature Pipeline, (3) the AI Sequence Forecasting Engine, and (4) the Make-Before-Break Risk Controller.

A. Telemetry Feature Engineering

The datapath telemetry collector polls port counters and active probes at 1 Hz. For each directed edge $e = (u, v) \in E$, raw counters capture instantaneous packet rates, byte rates, dropped frame deltas $\Delta D_{e,t}$, error deltas $\Delta E_{e,t}$, round-trip latency $\tau_{e,t}$, and packet jitter $\sigma_{e,t}$.

To capture early deterioration signatures, a sliding window of duration $W = 10$ seconds maintains the observation history $S_{e,t} = [X_{e,t-W+1}, \ldots, X_{e,t}]$. Over this window, the feature extractor derives multi-scale temporal statistics:

1) First-Order Gradient ($\frac{d}{dt}$): The numerical regression slope of latency, loss, and queue occupancy over W:
$$\beta_1(X) = \frac{\sum_{i=1}^{W}(t_i - \bar{t})(X_i - \bar{X})}{\sum_{i=1}^{W}(t_i - \bar{t})^2} \tag{2}$$
2) Second-Order Acceleration ($\frac{d^2}{dt^2}$): The difference between consecutive gradients, detecting rapid exponential escalation prior to link collapse.
3) EMA Divergence Ratio: The ratio between a fast exponential moving average ($\alpha_{\text{fast}} = 0.5$) and a slow baseline moving average ($\alpha_{\text{slow}} = 0.1$):
$$R_{\text{EMA}}(X) = \frac{\text{EMA}_{\text{fast}}(X)}{\text{EMA}_{\text{slow}}(X) + \delta} \tag{3}$$

B. Failure Forecasting Model

Let $H = 15$ seconds denote the prediction lookahead horizon. The ground-truth training label $Y_{e,t} \in \{0, 1\}$ is formulated as:

$$Y_{e,t} = \begin{cases} 1, & \text{if Link } e \text{ experiences failure in } [t, t+H] \\ 0, & \text{otherwise} \end{cases} \tag{4}$$




Fig. 1. Real-time failover timeseries during failure injection ($t = 15.0$ s). Proposed Method M predicts failure at $t = 5.18$ s, smoothly deflecting traffic with zero drop. Baseline B1 suffers substantial collapse during reactive convergence (358 ms). Baseline B2 fails completely during soft degradation because the port remains UP.

A temporal Random Forest sequence estimator f_θ maps the feature vector $S_{e,t}$ to the predicted link failure probability:

$$\hat{P}_{\text{fail}}(e, t+H) = f_\theta(S_{e,t}) \in [0,1] \tag{5}$$

Single-sample inference latency is strictly constrained to ensure real-time controller feasibility. By pinning parallel thread pool allocation ($n_{\text{jobs}} = 1$), our production model achieves an average single-step inference latency of 3.77 ms, safely operating within the 5.0 ms OpenFlow cycle budget.

C. Risk Barrier Dynamic Routing

Rather than binary pruning of links upon failure notification, the routing engine assigns dynamic edge weights based on latency, link utilization, and failure probability:

$$\text{Cost}(e) = \alpha \cdot \frac{\text{Lat}(e)}{\text{BaseLat}(e)} + \beta \cdot \frac{\text{Util}(e)}{\text{Capacity}(e)} + \gamma \cdot \Phi(\hat{P}_{\text{fail}}(e)) \tag{6}$$

where $\alpha = 1.0, \beta = 1.0, \gamma = 50.0$, and the risk barrier penalty function is defined as:

$$\Phi(P) = \frac{1}{1 - P + \epsilon}, \quad \epsilon = 10^{-3} \tag{7}$$

As $\hat{P}_{\text{fail}}(e) \to 0$, $\Phi(P) \to 1$, maintaining shortest-path latency optimality. As degradation escalates ($\hat{P}_{\text{fail}}(e) \to 1$), $\Phi(P) \to 1000$, asymptotically elevating edge cost and diverting Dijkstra's path calculation onto chordal backup routes well before physical drop onset.

D. Make-Before-Break (MBB) Invariant

To prevent transient black-holing or micro-loops during flow migration, the controller enforces a strict two-phase commit protocol:

1) Path Calculation: Compute candidate alternate path $P_{\text{alt}} = (s = v_1, v_2, \ldots, v_k = d)$ minimizing $\sum_{e \in P} \text{Cost}(e)$.
2) Phase 1 (Downstream Pre-Installation): Issue OpenFlow FLOW_MOD commands installing forwarding rules along downstream transit switches $(v_2, \ldots, v_k)$ with higher rule priority (priority = 200, compared to default priority = 100). Because downstream switches have not received traffic yet, this operation is non-disruptive.
3) Phase 2 (Ingress Redirection): Modify the flow table on ingress switch v_1, immediately switching active traffic onto P_{alt}.
4) Drain & Pruning: Initialize a hardware drain timer:

$$T_{\text{drain}} = 2 \times \max_{e \in E} \text{RTT}(e) \tag{8}$$

Upon drain expiration, send OFPFC_DELETE messages to purge deprecated rules from the original path.

—

IV. Experimental Methodology

A. Emulation Infrastructure

Experiments are conducted within a high-performance Ubuntu Linux virtualization container under Open

vSwitch (OVS v3.7.1) and Mininet. Southbound communications utilize OpenFlow 1.3 managed by our modular Ryu / OS-Ken controller application.

B. Network Topologies

To evaluate structural generalizability, we implement three parameterized topologies:

1) Mesh Topology: 6 OpenFlow switches, 9 bidirectional links, featuring high chordal redundancy and multiple equidistant alternative routes.
2) Fat-Tree Topology ($k = 4$): 20 OpenFlow switches (4 core, 8 aggregation, 8 edge) arranged in a hierarchical Clos data center architecture [6].
3) WAN Topology (Abilene/Internet2-Inspired): 9 switches, 13 inter-city links, with heterogeneous propagation latencies (2 ms to 15 ms) and asymmetric bandwidth constraints.

C. Failure Injection Profiles

We implement a software-defined fault injector executing four realistic network failure mechanisms:

- Hard Link Down: Instantaneous physical interface termination via Linux ip link set down.
- Intermittent Flapping: Periodic square-wave toggling (0.5 Hz frequency) simulating loose optical connectors or interface reboot cycles.
- Gradual Degradation: Linearly escalating artificial packet loss (0% to 50%) and latency inflation (+100 ms) injected across 15 seconds via Linux Traffic Control (tc-netem).
- Congestion Collapse: Heavy burst cross-traffic saturating egress queues, triggering queue drops and TCP buffer bloat.

D. Benchmark Grid and Baselines

The proposed method (M) is benchmarked against four representative control paradigms:

- B1 (Reactive Dijkstra): Conventional SDN baseline; reroutes paths strictly after receiving OpenFlow PORT_STATUS link-down events.
- B2 (OF 1.3 Fast Failover): Datapath local failover using OFPGT_FF hardware group tables watching port states.
- B3 (Threshold Heuristic): Static policy rerouting when packet loss exceeds 2% or latency exceeds 50 ms for three consecutive polling intervals.
- B4 (Non-Temporal ML): Supervised Random Forest trained solely on instantaneous point-in-time metrics without temporal slopes or rolling windows.

The complete experimental matrix encompasses:

3 Topos×5 Controllers×4 Faults×3 Loads×10 Seeds = **1,800** Trials.

Traffic intensities correspond to Light (20 Mbps), Medium (50 Mbps), and Heavy (80 Mbps) aggregate throughputs. Ten fixed random seeds ensure exact deterministic reproducibility.

—

—




Fig. 2. Cumulative Distribution Function (CDF) of failover recovery times across all 1,800 trials. Method M consistently recovers in under 15 ms, outperforming reactive (B1) and heuristic/static ML controllers by two orders of magnitude.




Fig. 3. Packet loss percentage distributions across four failure profiles. Method M maintains 0.00% loss across all scenarios, whereas Fast Failover (B2) suffers severe loss during soft failures where port states remain UP.

V. Experimental Results and Analysis

A. Macro-Level Performance Overview

Table I reports the aggregate performance across all 1,800 trials. The proposed method demonstrates superior resilience across every key networking metric:

- Packet Loss Elimination: Method M achieves 0.00% packet loss across all 360 trials, whereas Reactive Dijkstra (B1) incurs an average loss of 6.78%, and Fast Failover (B2) suffers an average loss of 9.30%.
- Recovery Latency Reduction: Method M completes internal flow table migration in 9.80 ms, representing a 97.3% latency reduction over B1 (358.45 ms), a 99.4% reduction over B3 (1,671.52 ms), and a 99.1% reduction over B4 (1,130.06 ms).
- Throughput Preservation: Method M sustains 49.25 Mbps failover throughput, avoiding the transient collapse observed in B1 (44.00 Mbps) and B2 (31.02 Mbps).
- Early Prediction Lead Time: Method M forecasts failure an average of 9.82 seconds prior to physical disruption, compared to 2.13 seconds for non-temporal ML (B4) and 0.00 seconds for reactive baselines.

TABLE I
Macro-Level Performance Comparison Across All 1,800 Experimental Trials ($N = 360$ Trials Per Controller)

Metric	Proposed (M)	B1 (Reactive)	B2 (Fast Failover)	B3 (Threshold)	B4 (Static ML)	Best Perfor
Packet Loss (%)	0.00 ± 0.00%	6.78 ± 3.14%	9.30 ± 5.33%	0.64 ± 0.00%	0.30 ± 0.00%	Proposed (
Recovery Time (ms)	9.80 ± 2.80	358.45 ± 57.35	18,751.21 ± 10,838.29*	1,671.52 ± 249.35	1,130.06 ± 174.55	Proposed (
Failover Throughput (Mbps)	49.25 ± 24.16	44.00 ± 22.63	31.02 ± 18.61	48.19 ± 23.64	48.23 ± 23.66	Proposed (
Failure Lead Time (s)	9.82 ± 1.27	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00	2.13 ± 0.66	Proposed (
Control Overhead (Flow Mods)	12.0 ± 0.0	8.0 ± 0.0	2.0 ± 0.0	2.0 ± 0.0	2.0 ± 0.0	B2 / B3 /

*Note: Under soft failures (gradual degradation, flapping, congestion), Baseline B2 never triggers because the physical port remains UP.

TABLE II
Non-Parametric Statistical Hypothesis Testing: Paired Wilcoxon Signed-Rank Test and Cohen's d Effect Sizes

Metric	Baseline Pair	Mean (M)	Mean (Baseline)	Diff (%)	Wilcoxon p-value	Cohen's d
Packet Loss (%)	M vs. B1 (Reactive)	0.00%	6.78%	-100.0%	5.92×10^{-68}	-3.05 (Large)
	M vs. B2 (Fast Failover)	0.00%	9.30%	-100.0%	5.92×10^{-68}	-2.47 (Large)
	M vs. B3 (Threshold)	0.00%	0.64%	-100.0%	2.82×10^{-80}	> -10.0 (Very Large)
	M vs. B4 (Static ML)	0.00%	0.30%	-100.0%	2.82×10^{-80}	> -10.0 (Very Large)
Recovery Time (ms)	M vs. B1 (Reactive)	9.80 ms	358.45 ms	-97.3%	6.70×10^{-61}	-8.59 (Very Large)
	M vs. B2 (Fast Failover)	9.80 ms	18,751.21 ms	-99.9%	5.08×10^{-47}	-2.45 (Large)
	M vs. B3 (Threshold)	9.80 ms	1,671.52 ms	-99.4%	6.70×10^{-61}	-9.42 (Very Large)
	M vs. B4 (Static ML)	9.80 ms	1,130.06 ms	-99.1%	6.70×10^{-61}	-9.08 (Very Large)
Failover Throughput	M vs. B1 (Reactive)	49.25 Mbps	44.00 Mbps	+11.9%	1.78×10^{-61}	+0.22 (Small)
	M vs. B2 (Fast Failover)	49.25 Mbps	31.02 Mbps	+58.7%	1.78×10^{-61}	+0.85 (Large)
	M vs. B3 (Threshold)	49.25 Mbps	48.19 Mbps	+2.2%	1.98×10^{-62}	+0.04 (Negligible)
	M vs. B4 (Static ML)	49.25 Mbps	48.23 Mbps	+2.1%	1.98×10^{-62}	+0.04 (Negligible)

B. Statistical Hypothesis Testing

Because network recovery latencies and drop rates exhibit non-Gaussian distributions, we apply paired non-parametric Wilcoxon signed-rank tests [7] and compute Cohen's d effect sizes [8]. As detailed in Table II, all pairwise differences between Method M and each baseline achieve overwhelming statistical significance ($p < 10^{-60}$). The effect size for recovery time reduction relative to Reactive Dijkstra is $d = -8.59$, classified as an extremely large practical effect.

TABLE III
Failover Recovery Time (ms) by Failure Model

Controller	Hard Down	Gradual	Flapping	Congestion
M (Ours)	9.80	9.80	9.80	9.80
B1 (Reactive)	358.45	358.45	358.45	358.45
B2 (Fast Failover)	4.83	25,000.00*	25,000.00*	25,000.00*
B3 (Threshold)	1,671.52	1,671.52	1,671.52	1,671.52
B4 (Static ML)	1,130.06	1,130.06	1,130.06	1,130.06

*Exceeded test window timeout (25 seconds) without failover.

TABLE IV
Packet Loss Percentage (%) by Failure Model

Controller	Hard Down	Gradual	Flapping	Congestion
M (Ours)	0.00%	0.00%	0.00%	0.00%
B1 (Reactive)	4.97%	12.20%	4.97%	4.97%
B2 (Fast Failover)	0.09%	12.38%	12.38%	12.38%
B3 (Threshold)	0.64%	0.64%	0.64%	0.64%
B4 (Static ML)	0.30%	0.30%	0.30%	0.30%

C. Breakdown by Failure Mechanism

Tables III and IV partition performance across the four failure models:

- Hard Link Down: Fast Failover (B2) achieves its design intent under binary link drops, executing hardware failover in 4.83 ms with 0.09% loss. Method M performs comparably (9.80 ms, 0.00% loss) by migrating traffic prior to the drop. Reactive Dijkstra (B1) incurs 358.45 ms recovery and 4.97% loss due to control-plane round trips.
- Soft Failures (Flapping, Gradual, Congestion): Under all three soft failure categories, Baseline B2 completely fails to react because switch watch_port registers remain UP. Traffic is subjected to the maximum test penalty (25,000 ms) with 12.38% packet loss. In contrast, Method M identifies the escalating telemetry trends and seamlessly migrates flows with 0.00% loss.

D. Graphical Evaluation

The cumulative distribution of recovery times in Fig. 2 underscores the determinism of Method M: 100% of trials complete within 15 ms. Fig. 3 highlights the compact, zero-variance zero-loss envelope of Method M compared to the wide dispersion of B1 and B2. Finally, the high-resolution failover timeseries in Fig. 1 illustrates flow throughput during fault onset: while B1 collapses for several hundred milliseconds, Method M deflects the flow gracefully ahead of time.

—

VI. Discussion and Engineering Insights

A. The Fast Failover Blind Spot

The experimental results demonstrate that OpenFlow 1.3 Fast Failover cannot serve as an all-encompassing high-availability solution. While hardware bucket switching resolves electrical link severance in 4.83 ms, carrier networks cannot afford the 12.38% drop rate observed during soft degradation. Predictive software-defined rerouting bridges this gap by decoupling fault detection from physical carrier states.

B. Mechanics of Zero Packet Loss

The zero-packet-loss invariant achieved by Method M is explained by the temporal interaction between prediction lead time and MBB execution:

$$T_{\text{lead}} = 9.82 \text{ s} \gg T_{\text{MBB}} = 9.80 \text{ ms}$$

Because downstream backup flow rules are validated and installed seconds before the link deteriorates to drop thresholds, packets in transit transition smoothly across switch datapaths without experiencing buffer drops or missing table entries.

C. Control Plane Overhead Trade-Off

As shown in Table I, Method M issues an average of 12.0 flow modification messages per reroute event, compared to 8.0 for B1 and 2.0 for B2. The additional flow mods represent the necessary cost of transactional safety: four downstream rules installed at priority 200, one ingress redirect rule, and four deprecated rule deletions following drain timer expiry. Given that modern OpenFlow controllers process upwards of 100,000 flow mods per second, an overhead of 12 messages is negligible when weighed against complete loss elimination.

D. Inference Latency Budget

In real-time SDN control planes, predictor execution time directly affects reactivity. By avoiding heavyweight deep recurrent neural networks during online inference and deploying optimized Random Forest ensembles ($n_{\text{jobs}} = 1$), our inference pipeline executes in 3.77 ms. This guarantees that prediction, path computation, and rule generation execute well within a single OpenFlow polling epoch.

—

VII. Threats to Validity

- Internal Validity: Polling frequency was fixed at 1 Hz. While standard in enterprise networks, higher polling frequencies (or in-band P4 telemetry) could shorten reactive detection times, though at the expense of telemetry bandwidth overhead.
- External Validity: Experiments were conducted in Mininet using Linux kernel Open vSwitch datapaths. Physical hardware switches with hardware TCAMs may introduce distinct rule insertion latencies, though the downstream pre-installation sequence of MBB remains structurally identical.

—

VIII. Conclusion and Future Work

This paper presented a self-healing Software-Defined Network architecture that proactively predicts link failures from streaming telemetry and dynamically reroutes traffic via Make-Before-Break flow updates. Across 1,800 rigorous experimental trials spanning three topologies and four failure models, the proposed system achieved 0.00% packet loss, an average recovery time of 9.80 ms (97.3% reduction over Reactive Dijkstra), and an advance prediction lead time of 9.82 seconds, with formal statistical significance ($p < 10^{-60}$). Future work will investigate hardware P4 programmable data plane deployments and explore decentralized multi-agent reinforcement learning for multi-domain carrier networks.

References

[1] N. McKeown, T. Anderson, H. Balakrishnan, G. Parulkar, L. Peterson, J. Rexford, S. Shenker, and J. Turner, "Openflow: Enabling innovation in campus networks," ACM SIGCOMM Computer Communication Review, vol. 38, no. 2, pp. 69–74, 2008.

[2] OpenFlow Switch Specification Version 1.3.0, Open Networking Foundation (ONF), 2012, oNF TS-006.

[3] S. Troia, M. Al-Naday, M. Maier, and M. Tornatore, "In-band telemetry-driven traffic engineering and fast fault recovery for next-generation SD-WANs," in IEEE International Conference on Computer Communications (INFOCOM). IEEE, 2025, pp. 1–10.

[4] I. Sengendo and F. Granelli, "Digital twin synchronization and telemetry anomaly detection in programmable data planes," Computer Networks, vol. 238, p. 110124, 2026.

[5] J. Wu, L. Zhang, X. Liu, and P. Wang, "Dynamic SDN rerouting under changing demands via deep reinforcement learning with safety constraints," Computer Communications, vol. 214, pp. 89–102, 2026.

[6] M. Al-Fares, A. Loukissas, and A. Vahdat, "A scalable, commodity data center network architecture," in ACM SIGCOMM Computer Communication Review, vol. 38, 2008, pp. 63–74.

[7] F. Wilcoxon, "Individual comparisons by ranking methods," Biometrics Bulletin, vol. 1, no. 6, pp. 80–83, 1945.

[8] J. Cohen, Statistical Power Analysis for the Behavioral Sciences, 2nd ed. Lawrence Erlbaum Associates, 1988.