

Moderate Tables

Source-backed grouped table sample

1 Tables

These tables are grouped from source-backed LaTeX table data and compiled as a single benchmark data point.

Table 1: Source table 1: 2512.03214_table_6

Category	Parameter	Value
Model Architecture	Base model	bert-base-uncased
	Architecture	BertForTokenClassification
	Hidden size	768
	Intermediate size	3072
	Hidden layers	12
	Attention heads	12
	Activation	GELU
	Dropout	0.1
	Tokenizer	BertTokenizer (max length=512, padding/truncation)
	Number of labels	5
	Label mapping	{“O”: 0, “B-C”: 1, “I-C”: 2, “B-E”: 3, “I-E”: 4}
Dataset	Name/source	CausalPalUkr_Train_Test
	Task type	Token Classification / NER
	Train/val/test split	75-15
	Preprocessing	Lowercase, truncate/ pad to 512, first subword labeling
Optimization	Optimizer	AdamW (adamw_torch)
	Learning rate	7e-5
	Scheduler	Linear decay, 36 warmup steps
	Weight decay	0.01
	Betas	(0.9, 0.999)
	Epsilon	1e-8
	Batch size / device	16
	Gradient accumulation	1
	Max grad norm	1.0
	Epochs	10
	FP16/BF16	Disabled
Reproducibility	Seed	42
	Data seed	None
	Dataloader drop last	False
	Dataloader workers	0
	FP16 full eval	False
Training Environment	Transformers	4.50.3
	PyTorch	2.6.0+cu124
	Datasets	3.5.0
	Tokenizers	0.21.1
	Hardware	1x NVIDIA A100 40GB
Evaluation	Metrics	Token-level Precision
	Validation freq	after each epoch
HF model	pgarco/CausalPalUkr_token	

Table 2: Source table 2: 2512.03059_table_4

Networks	High-level	Low-level	Learning Rate
Actor	128,128	64,64	3e-4
Termination condition	64,64	\	3e-4
Reward critic	\	128,128	1e-3
Cost critic	\	128,128	1e-3
Parameters	Value	Parameters	Value
GAE coefficient	0.95	Clip ε	0.2
Iterations	20,000	Episodes E	10
Batch size	128	Learning rate α_λ	0.01
Tolerance d	0.025		