

CS 4530: Fundamentals of Software Engineering

Module 10.4: Case Studies

Adeel Bhutta, Joydeep Mitra, Mitch Wand
Khoury College of Computer Sciences

Learning Goals for this Lesson

- By the end of this lesson you should be able to:
 - Briefly describe several typical examples of distributed systems
 - Briefly describe how each of them deals with scalability, fault tolerance, etc.

Case Study 1: the Network File System NFS

- NFS is a distributed file system: multiple clients can read/write the same files
- Created in 1984, still widely used
- In a UNIX (POSIX-compliant) operating system, files are stored in a tree from "/"
- Access a remote file by name like
/username@remotehost/path/to/remote/file
- Or you could "mount" a remote filesystem to access it as if it were local.

NFS is a Monolithic Shared Filesystem


- All files are stored on a single server
- To list files in a directory, clients make request to server
- To read or write files, clients make request to server
- Clients might “lock” files to prevent concurrent updates
- Assuming that scale, throughput, fault tolerance requirements are relatively low, this is an acceptable architecture
- This architecture is the *easiest* to build fast and correctly

Case Study 2: GFS (Google File System, ~2010)

- Stated requirements:
- **“High sustained bandwidth is more important than low latency.** Most of our target applications place a premium on **processing data in bulk at a high rate,** while **few have stringent response time requirements for an individual read or write.”**


GFS is a tiered filesystem with two tiers: Metadata and File Chunks

- Example: GFS (Google File System, c 2010)



Case Study 3: Domain Name System (DNS)


- Nodes (hosts) on a network are identified by IP addresses
- E.g.: 142.251.41.4
- We humans prefer something easier to remember: calendar.google.com, facebook.com, www.khoury.northeastern.edu
- We need to keep a directory of domain names and their addresses
- We also need to make sure everybody gets directed to the correct host



<https://a.root-servers.org/metrics>

Requirements for the DNS system

- Need to handle millions of DNS queries per second
- Not immediately obvious how to scale: how do we maintain replication, some measure of consistency?



DNS distributed system requirements

- We need a **scalable** solution
 - New hosts keep being added
 - Number of users increases
 - Need to maintain speed/responsiveness
- We need our service to be **available** and **fault tolerant**
 - It is a crucial basic service
 - A problematic node shouldn't "crash the internet"
 - Reads are more important than writes: far more queries to resolve records than to update them
- Global in scope
 - Domain names mean the same thing everywhere


Strawman solution: Use a local file

- Keep local copy of mapping from all hosts to all IPs (e.g., /etc/hosts)
- Space would be reasonable: a few dozen Gbytes.
- **BUT** hosts change IPs regularly, so need to download file frequently
- Lot of constant internet bandwidth use
- **Not scalable!**

A tiered architecture yields a scalable solution

- Idea: break apart responsibility for each part of a domain name (zone) to a different group of servers
- Each zone is a continuous section of the name space, eg *.northeastern.edu
- Each zone has an associated set of name servers.


DNS partitions responsibility by “layers”.




This is an example of a tiered architecture

- Each server need only needs to know about its immediate descendants in its zone.
- It only processes requests about a single zone.
- Both data and processing are limited to requests about this zone– any other requests are delegated to this server's parent server.

DNS uses Tree
search
algorithm



Updating name servers




But some zones are too big and too busy to be handled by a single server

- Eg, .edu, .com, .gov, etc.
- So these servers are **replicated**.

There is replication even within the root servers

- 13 root servers
 - [a-m].root-servers.org
 - E.g., d.root-servers.org
- But each root server has multiple copies of the database, which need to be kept in sync.
- Somewhere around 1500 replicas in total.




Case Study 4: Reliable Real-Time Chat

- Requirements:
 - Must support real-time text chat for 2,000 users exchanging messages.
 - Must have **best-effort delivery in real-time**
 - Must **guarantee that all messages acknowledged are preserved** in the central database"

Possible solution: use separate processing units for each requirement.

- Allocate separate processing units for these requirements:
 - “Real time” component optimizes for speed and availability (sacrificing fault-tolerance)
 - “Persistence” component optimizes for fault-tolerance, sacrificing speed and availability
 - Event queue service receives events, dispatches to both processing units and is fault tolerant

Block diagram for a real-time chat service



Learning Goals for this Lesson

- By the end of this lesson you should be able to:
 - Briefly describe several typical examples of distributed systems
 - Briefly describe how each of them deals with scalability, fault tolerance, etc.