

AeroFlow X200 Product Specification

The AeroFlow X200 is an industrial dehumidifier engineered for continuous-duty operation in warehouses, production floors, and cold-chain staging areas. It removes up to 200 litres of moisture per day at 30 degrees C and 80 percent relative humidity.

Key Specifications

Rated extraction: 200 L/day. Airflow: 2,000 m³/h. Power draw: 2.4 kW at 230 V. Refrigerant: R-32. Compressor: sealed rotary compressor, model RC-9 series. Net weight: 86 kg. Noise level: 58 dB(A) at 3 m.

Operating Conditions

The X200 is rated for ambient temperatures between 5 degrees C and 40 degrees C. Operation below 5 degrees C can cause coil icing and compressor stress and is outside the supported envelope. Supply voltage must remain within 200-240 V; sustained operation outside this range may damage the compressor relay.

Compressor Subsystem

The sealed rotary compressor is the primary wear component of the X200. It is protected by a thermal cut-out and a start relay (part SR-1142). The compressor assembly is field-replaceable by certified technicians using service kit CK-200.

Maintenance Schedule

Filters should be cleaned every 500 operating hours and replaced every 2,000 hours. The condensate line should be flushed quarterly. An annual inspection of the compressor start relay is recommended for units in continuous duty.