

The '&' Operator

In this lesson, we'll be looking at the ampersand ('&') operator syntax.

WE'LL COVER THE FOLLOWING ^

- Definition
- Example

Definition

The ampersand `&` operator is often used when *nesting* in SASS and is an extremely useful feature.

It can be a great time-saver, especially if you happen to be coding your stylesheets with the [BEM methodology](#), or using any systematic naming convention for your class names.

Example

See the following HTML:

```
<button class = "btn btn--red"> Click me! </button>
```

Typical styling would be something like this:

Output

HTML

CSS (SCSS)

```
.btn {  
  display: inline-block;  
  padding: 15px 32px;  
}  
.btn--red {  
  background-color: #ff0000; // Red
```

```
}  
.btn:hover {  
  
  background-color: #fff; // White  
}
```



With the `&` operator we can be much more efficient:

Output

HTML

CSS (SCSS)

```
.btn {  
  display: inline-block;  
  padding: 15px 32px;  
  &--red {  
    background-color: #ff0000; // Red  
  }  
  &:hover {  
    background-color: #fff; // White  
  }  
}
```



Notice that we've now nested the child selectors that use the same `.btn` name, represented by the `&` operator. name.

When compiled the `&` operator will be replaced by its enclosing selector name!

Next up we'll learn about control directives.