

Search Elements

This lesson will cover the different ways of searching for values using 'find'.

You can search for elements in three different ways.

Returns an element in a range:

```
InpIt find(InpIt first, InpI last, const T& val)
InpIt find(ExePol pol, FwdIt first, FwdIt last, const T& val)

InpIt find_if(InpIt first, InpIt last, UnPred pred)
InpIt find_if(ExePol pol, FwdIt first, FwdIt last, UnPred pred)

InpIt find_if_not(InpIt first, InpIt last, UnPred pre)
InpIt find_if_not(ExePol pol, FwdIt first, FwdIt last, UnPred pre)
```



Returns the first element of a range in a range:

```
FwdIt1 find_first_of(InpIt1 first1, InpIt1 last1, FwdIt2 first2, FwdIt2 last2)
FwdIt1 find_first_of(ExePol pol, FwdIt1 first1, FwdIt1 last1, FwdIt2 first2, FwdIt2 last2)

FwdIt1 find_first_of(InpIt1 first1, InpIt1 last1, FwdIt2 first2, FwdIt2 last2, BiPre pre)
FwdIt1 find_first_of(ExePol pol, FwdIt1 first1, FwdIt1 last1, FwdIt2 first2, FwdIt2 last2, Bi
```



Returns identical, adjacent elements in a range:

```
FwdIt adjacent_find(FwdIt first, FwdIt last)
FwdIt adjacent_find(ExePol pol, FwdIt first, FwdIt last)

FwdIt adjacent_find(FwdIt first, FwdI last, BiPre pre)
FwdIt adjacent_find(ExePol pol, FwdIt first, FwdI last, BiPre pre)
```



The algorithms require input or forward iterators as arguments and return an iterator on the element when successfully found. If the search is not successful, they return an end iterator.

```
#include <iostream>
#include <algorithm>
#include <tests>
```



```

#include <set>
#include <list>
using namespace std;

bool isVowel(char c){
    string myVowels{"aeiouäöü"};
    set<char> vowels(myVowels.begin(), myVowels.end());
    return (vowels.find(c) != vowels.end());
}

int main(){
    list<char> myCha{'a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j'};
    int cha[]= {'A', 'B', 'C'};

    cout << *find(myCha.begin(), myCha.end(), 'g') << endl;           // g
    cout << *find_if(myCha.begin(), myCha.end(), isVowel) << endl;     // a
    cout << *find_if_not(myCha.begin(), myCha.end(), isVowel) << endl; // b

    auto iter= find_first_of(myCha.begin(), myCha.end(), cha, cha + 3);
    if (iter == myCha.end()) cout << "None of A, B or C." << endl;     // None of A, B or C.

    auto iter2= find_first_of(myCha.begin(), myCha.end(), cha, cha+3,
                             [](char a, char b){ return toupper(a) == toupper(b); });
    if (iter2 != myCha.end()) cout << *iter2 << endl;                 // a
    auto iter3= adjacent_find(myCha.begin(), myCha.end());
    if (iter3 == myCha.end()) cout << "No same adjacent chars." << endl;
    // No same adjacent chars.

    auto iter4= adjacent_find(myCha.begin(), myCha.end(),
                             [](char a, char b){ return isVowel(a) == isVowel(b); });
    if (iter4 != myCha.end()) cout << *iter4;                        // b
}

```



std::find, std::find_if, std::find_if_not, std::find_of, and std::adjacent_find