

# Solution Review: Pairs with Sums

This lesson contains the solution review for the challenge of finding pairs in a doubly linked list which sum up to the given number.

## WE'LL COVER THE FOLLOWING ^

- Implementation
- Explanation

Here is an overview of our solution to finding a pair of nodes in a doubly linked list that sums up to a specific number.

## Implementation #

Here is the coding solution in Python for the previous challenge:

```
def pairs_with_sum(self, sum_val):
    pairs = list()
    p = self.head
    q = None
    while p:
        q = p.next
        while q:
            if p.data + q.data == sum_val:
                pairs.append("(" + str(p.data) + "," + str(q.data) + ")")
            q = q.next
        p = p.next
    return pairs
```

## Explanation #

On **line 2**, `pairs` is initialized to an empty Python list. In the next lines (**lines 3-4**), `p` and `q` are set equal to `self.head` and `None` respectively. We will use both these pointers (`p` and `q`) to make pairs out of the doubly linked list by using two `while` loops afterward.

The outer `while` loop on **line 5** will run until `p` becomes equal to `None` while

the inner loop on **line 7** will run for every iteration of the outer loop until `q` becomes `None`.

On **line 6**, we set `q` equal to `p.next` as we have to start pairing nodes from the next node of the current node as we would already have checked the pairing with all previous nodes. Then we'll check if the sum of `p.data` and `q.data` equals `sum_value` or not on **line 8**. If it is, then we append `p.data` and `q.data` to the list we declared at the beginning of the `pairs_with_sum` method. If it does not, we move on to the next node of `q` by updating `q` to `q.next` on **line 10**. In each iteration of the inner loop, we pair the data of `p` with all the data of the nodes after `p` using `q` and then check each of these pairs to see if they sum up to `sum_value`. This process is repeated for every node in the linked list as `p` updates to `p.next` on **line 11** in the outer `while` loop. After the outer loop terminates, `pairs` is returned from the method on **line 12**.

You can play around with all the methods that we have implemented for the `DoublyLinkedList` class in the code widget provided below.

```
class Node:
    def __init__(self, data):
        self.data = data
        self.next = None
        self.prev = None

class DoublyLinkedList:
    def __init__(self):
        self.head = None

    def append(self, data):
        if self.head is None:
            new_node = Node(data)
            new_node.prev = None
            self.head = new_node
        else:
            new_node = Node(data)
            cur = self.head
            while cur.next:
                cur = cur.next
            cur.next = new_node
            new_node.prev = cur
            new_node.next = None

    def prepend(self, data):
        if self.head is None:
            new_node = Node(data)
            new_node.prev = None
            self.head = new_node
        else:
            new_node = Node(data)
            self.head.prev = new_node
            new_node.next = self.head
```



```

        self.head = new_node
        new_node.prev = None

def print_list(self):
    cur = self.head
    while cur:
        print(cur.data)
        cur = cur.next

def add_after_node(self, key, data):
    cur = self.head
    while cur:
        if cur.next is None and cur.data == key:
            self.append(data)
            return
        elif cur.data == key:
            new_node = Node(data)
            nxt = cur.next
            cur.next = new_node
            new_node.next = nxt
            new_node.prev = cur
            nxt.prev = new_node
            return
        cur = cur.next

def add_before_node(self, key, data):
    cur = self.head
    while cur:
        if cur.prev is None and cur.data == key:
            self.prepend(data)
            return
        elif cur.data == key:
            new_node = Node(data)
            prev = cur.prev
            prev.next = new_node
            cur.prev = new_node
            new_node.next = cur
            new_node.prev = prev
            return
        cur = cur.next

def delete(self, key):
    cur = self.head
    while cur:
        if cur.data == key and cur == self.head:
            # Case 1:
            if not cur.next:
                cur = None
                self.head = None
                return

            # Case 2:
            else:
                nxt = cur.next
                cur.next = None
                nxt.prev = None
                cur = None
                self.head = nxt
                return

        elif cur.data == key:
            # Case 3:

```

```

        if cur.next:
            nxt = cur.next
            prev = cur.prev

            prev.next = nxt
            nxt.prev = prev
            cur.next = None
            cur.prev = None
            cur = None
            return

        # Case 4:
    else:
        prev = cur.prev
        prev.next = None
        cur.prev = None
        cur = None
        return
    cur = cur.next

def delete_node(self, node):
    cur = self.head
    while cur:
        if cur == node and cur == self.head:
            # Case 1:
            if not cur.next:
                cur = None
                self.head = None
                return

            # Case 2:
            else:
                nxt = cur.next
                cur.next = None
                nxt.prev = None
                cur = None
                self.head = nxt
                return

        elif cur == node:
            # Case 3:
            if cur.next:
                nxt = cur.next
                prev = cur.prev
                prev.next = nxt
                nxt.prev = prev
                cur.next = None
                cur.prev = None
                cur = None
                return

            # Case 4:
            else:
                prev = cur.prev
                prev.next = None
                cur.prev = None
                cur = None
                return
        cur = cur.next

def reverse(self):
    tmp = None
    cur = self.head

```

```

        while cur:
            tmp = cur.prev
            cur.prev = cur.next

            cur.next = tmp
            cur = cur.prev
        if tmp:
            self.head = tmp.prev

    def remove_duplicates(self):
        cur = self.head
        seen = dict()
        while cur:
            if cur.data not in seen:
                seen[cur.data] = 1
                cur = cur.next
            else:
                nxt = cur.next
                self.delete_node(cur)
                cur = nxt

    def pairs_with_sum(self, sum_val):
        pairs = list()
        p = self.head
        q = None
        while p:
            q = p.next
            while q:
                if p.data + q.data == sum_val:
                    pairs.append("(" + str(p.data) + "," + str(q.data) + ")")
                q = q.next
            p = p.next
        return pairs

dllist = DoublyLinkedList()
dllist.append(1)
dllist.append(2)
dllist.append(3)
dllist.append(4)
dllist.append(5)

print(dllist.pairs_with_sum(5))

```



Now this lesson marks an end to the content on linked lists. Get ready to solve problems using another data structure in the next chapter!