

Template Arguments

In this lesson, we'll learn about template arguments.

WE'LL COVER THE FOLLOWING



- Template Arguments
- Template Arguments (C++17)
- Argument Deduction
 - Explicit Template Arguments
 - Default Template Arguments

Template Arguments

In general, template arguments can be automatically deduced for function templates. From the user's perspective, function templates feel like functions.

Conversion:

- The compiler uses simple conversions for deducing the template arguments from the function arguments.
- The compiler removes `const` or `volatile` from the function arguments and converts C-arrays and functions to pointers.

Template argument deduction for function templates:

```
template <typename T>
void func(ParamType param);
```

Two datatypes were deduced:

- `T`
- `ParamType`

`ParamType` can be a

- Reference or pointer
- Universal reference(`&&`)
- Value (copy)

1. The parameter type is a reference or a pointer

```
template <typename T>
void func(T& param);
// void func(T* param);
func(expr);
```

- `T` ignores reference or pointer
- Pattern matching on `expr` for `T&` or `T`

2. The parameter type is a universal reference (`&&`)

```
template <typename T>
void func(T&& param);
func(expr);
```

- `expr` is an lvalue: `T` and `param` become lvalue references
- `expr` is an rvalue: `T` is deduced when the `param` is a reference (case 1)

3. Parameter type is a value (copy)

```
template <typename T>
void func(T param);
func(expr);
```

1. `expr` is a reference: the reference (pointer) of the argument is ignored
2. `expr` is `const` or `volatile`: `const` or `volatile` is ignored

Template Arguments (C++17)

The constructor can deduce its template arguments from its function arguments.

Template Argument deduction for a constructor is available since C++17, but for function templates since C++98.

```
std::pair<int, double> myPair(2011, 1.23);  
std::pair myPair(2011, 1.23);
```

Many of the `make_` functions such as `std::make_pair` are not necessary any more:

```
auto myPair = std::make_pair(2011, 1.23);
```

Argument Deduction

The types of function arguments have to be exact, otherwise no conversion takes place.

```
template <typename T>  
bool isSmaller(T fir, T sec){  
    return fir < sec;  
}  
  
isSmaller(1, 5LL); // ERROR int != long long int
```



Providing a second template parameter makes this example work.

```
template <typename T, typename U>  
bool isSmaller(T fir, U sec){  
    return fir < sec;  
}  
  
isSmaller(1, 5LL); // OK
```



Explicit Template Arguments

Unlike in line 5 in the previous example, sometimes the template argument types need to be explicitly specified. This is necessary in the following cases:

Explicit Template Arguments

- if the template argument cannot be deduced from the function argument.
- if a specific instance of a function template is needed.

```
template <typename R, typename T, typename U>  
R add(T fir, U sec){  
    return fir * sec;
```

```
}  
add<long long int>(1000000, 1000000LL);
```

Missing template arguments are automatically derived from the function arguments.

Default Template Arguments

The default for template parameters can be specified for class templates and function templates. If a template parameter has a default parameter, all subsequent template parameters also need a default argument.

```
template <typename T, typename Pred = std::less<T>>  
bool isSmaller(T fir, T sec, Pred pred = Pred()){  
    return pred(fir, sec);  
}
```

To learn more about template arguments, click [here](#).

In the next lesson, we'll take a look at some examples of template arguments.