

Consuming a context in a strongly-typed class component

In this lesson, we'll learn how to use a context in strongly-typed class components

WE'LL COVER THE FOLLOWING

- Trying to use the context hook in a class component
- Using the `context` property
- Explicitly setting the type for the `context` property
- Using the `Consumer` component
- Wrap up

Trying to use the context hook in a class component

We are going to continue using the context we created in the last lesson that allows consumers to share and set a theme. Let's update the `Header` component to be a class component:

```
class Header extends React.Component {
  render() {
    const { theme, setTheme } = useTheme();

    return (
      <div style={{ backgroundColor: theme }}>
        <select
          value={theme}
          onChange={e => setTheme(e.currentTarget.value)}
        >
          <option value="white">White</option>
          <option value="lightblue">Blue</option>
          <option value="lightgreen">Green</option>
        </select>
        <span>Hello!</span>
      </div>
    );
  }
}
```

```
        </div>
    );
}
}
```

Can you spot a problem with this implementation?

 Show Answer

Using the `context` property

React class components have a `context` property that we can use to consume a context. First, we need to tell the class what context it should use with a `static contextType` property and then we can access the `context` property:

```
class Header extends React.Component {
  static contextType = ThemeContext;

  render() {
    const { theme, setTheme } = this.context!;

    return (
      ...
    );
  }
}
```

Notice that we put an exclamation mark(`!`) after the `context` property to tell the TypeScript compiler that it isn't `undefined`.

What types have `theme` and `setTheme` been inferred as?

 Show Answer

Explicitly setting the type for the `context` property

At the moment, the consumed context isn't strongly-typed. We can explicitly define the class's `context` property with a type annotation to make it strongly-

typed:

```
class Header extends React.Component {
  static contextType = ThemeContext;
  context: React.ContextType<typeof ThemeContext>;

  render() {
    const { theme, setTheme } = this.context!;

    return (
      ...
    );
  }
}
```

Notice that we don't use `React.ContextType<ThemeContextType>` as the type annotation for the `context` property because we get a type error if we do so.

A full working implementation is available by clicking the link below. Give it a try and change the theme value to see the background change color.

[Open full implementation](#)

Using the `Consumer` component

There is an alternative approach to consuming a context in a class component if we just need access to it in the JSX. This method is to use the contexts

`Consumer` component:

```
class Header extends React.Component {
  render() {
    return (
      <ThemeContext.Consumer>
        {value => (
          <div style={{ backgroundColor: value!.theme }}>
            <select
              value={value!.theme}
              onChange={e => value!.setTheme(e.currentTarget.value)}
            >
              <option value="white">White</option>
              <option value="lightblue">Blue</option>
              <option value="lightgreen">Green</option>
            </select>
            <span>Hello! </span>
          </div>
        )}
      </ThemeContext.Consumer>
    );
  }
}
```

```
        <span>Hello!</span>
      </div>
    )}
  </ThemeProvider.Consumer>
);
}
}
```

The child of the `Consumer` component is a function that has the value of the context passed into it and returns the JSX we want to render. Notice that we have put an exclamation mark (!) after we reference `value` to tell the TypeScript compiler that this isn't `undefined`.

The benefit of this approach is that the `contextType` static property doesn't need to be implemented. We don't need to declare the `context` property with its type annotation as well.

What do you think the inferred type of the `value` parameter is in the `Consumer` components child function?

 Show Answer

Wrap up

We can use React's context in class components, but we can't use the `useContext` hook.

Using the `Consumer` component is a neat way of getting access to the context in the `render` method, which has its type inferred correctly.

The `context` property can be used in other lifecycle methods to get access to the context. We need to explicitly define a type annotation for the `context` property and specify the specific context in a `contextType` static property.

Next, let's double-check what we have learned from the last few lessons with a quiz.