

PROJECT NAME

SportyShoes.com

Developer Detail's:

Developer Name: Prajval Raju Bhale.

Mail ID: prajwalbhale007@gmail.com

Project Start Date: 19 June 2022

Project End Date: 23 June 2022

Used Technologies:

- **Framework:** Spring Boot, Bootstrap, Hibernate.
- **For Frontend:** HTML, CSS, JSP, JavaScript.
- **For Backend :** Java, JPQL, SQL, Servlet,
- **Database :** MySql Workbench.
- **Testing Tool :** postman & Junit Testing.
- **IDE:** Spring Tool Suit(STS) Version:4.14.1

FROM HERE ALL JAVA CODE:--

Admin.java

```
package com.prajval.phase3;
```

```
import javax.persistence.Entity;
```

```
import javax.persistence.GeneratedValue;
```

```
import javax.persistence.GenerationType;
```

```
import javax.persistence.Id;
```

```
import lombok.Data;
```

```
@Data
```

```
@Entity
```

```
public class Admin {
```

```
    @Id
```

```
    @GeneratedValue(strategy = GenerationType.AUTO)
```

```
    private int ad_id;
```

```
    private String ad_fname;
```

```
    private String ad_lname;
```

```
    private String ad_phone;
```

```
    private String ad_mail;
```

```
    private String ad_dob;
```

```
    private String ad_pass;
```

```
    private String ad_con;
```

```
    private String ad_state;
```

```
        private String ad_dist;

        private String ad_taluka;

        private String ad_pin;

        private String ad_gen;


        @GeneratedValue(strategy = GenerationType.AUTO)

        private String log_date;

    }
```

AdminDao.java

```
package com.prajval.phase3;


import java.util.List;


import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;


@Service

public class AdminDao {


    @Autowired

    AdminRepo ad_repo;


    //REGISTREATION-OF-ADMIN

    public Admin ad_insert(Admin a)
```

```

    {

        return ad_repo.save(a);

    }


//ADMIN LOGIN BY USER-NAME
public Admin ad_login(String ad_fname)
{

    return ad_repo.findbyname(ad_fname);

}


//THIS CODE GIVES RETURN PASSWORD FOR ADMIN USING PHONE NUMBER
public List<Admin> forget_ad_pass(String ad_phone)
{

    return ad_repo.findByAdPhone(ad_phone);

}

}

```

AdminRepo.java

```
package com.prajval.phase3;
```

```
import java.util.List;
```

```
import org.springframework.data.jpa.repository.JpaRepository;
```

```
import org.springframework.data.jpa.repository.Query;
```

```
public interface AdminRepo extends JpaRepository<Admin, Integer>{
```

```
@Query("select admin from Admin admin where admin.ad_fname=?1")
```

```
public Admin findbyname(String ad_fname);
```

```
@Query("select ad from Admin ad where ad.ad_phone=?1")
```

```
public List<Admin> findByAdPhone(String ad_phone);
```

```
}
```

AllController.java

```
package com.prajval.phase3;
```

```
import java.util.Date;
```

```
import java.util.List;
```

```
import javax.servlet.http.HttpServletRequest;
```

```
import javax.servlet.http.HttpServletResponse;
```

```
import org.springframework.beans.factory.annotation.Autowired;
```

```
import org.springframework.stereotype.Controller;
```

```
import org.springframework.web.bind.annotation.PathVariable;
```

```
import org.springframework.web.bind.annotation.RequestMapping;
```

```
import org.springframework.web.bind.annotation.ResponseBody;
```

```
import org.springframework.web.servlet.ModelAndView;
```

```
import org.springframework.web.servlet.view.RedirectView;
```

```
@Controller
```

```
public class AllController {
```

```
    /*HERE WE CREATE REPOSITORY'S OBJECT'S*/
```

```
    @Autowired
```

```
    UserRepo u_repo;
```

```
    @Autowired
```

```
    AdminRepo a_repo;
```

@Autowired

ProductRepo pro_repo;

@Autowired

CartRepo c_repo;

/*HERE WE CREATE DAO OBJECT'S*/

@Autowired

AdminDao a_dao;

@Autowired

UserDao u_dao;

@Autowired

ProductDao pro_dao;

@Autowired

CartDao c_dao;

/*USER OPERATION'S START FROM HERE*/

//USER CAN REGISTER USING THIS CODE

@ResponseBody

@RequestMapping("/user_insert")

public ModelAndView user_insert(HttpServletRequest req, HttpServletResponse res)

{

```

        ModelAndView mv = new ModelAndView();

        User u = new User();

        u.setUser_fname(req.getParameter("user_fname"));
        u.setUser_lname(req.getParameter("user_lname"));
        u.setUser_phone(req.getParameter("user_phone"));
        u.setUser_mail(req.getParameter("user_mail"));
        u.setUser_dob(req.getParameter("user_dob"));
        u.setUser_pass(req.getParameter("user_pass"));
        u.setUser_conpass(req.getParameter("user_conpass"));
        u.setUser_state(req.getParameter("user_state"));
        u.setUser_dist(req.getParameter("user_dist"));
        u.setUser_taluka(req.getParameter("user_taluka"));
        u.setUser_pin(req.getParameter("user_pin"));
        u.setUser_gender(req.getParameter("user_gender"));

        User ss = u_dao.user_insert(u);

        if(ss!=null)
        {
            mv.setViewName("user_reg_succ");
        }

        return mv;
    }

```

//ADMIN CAN SEE LIST OF SIGN-UP USER'S USING THIS CODE

@ResponseBody

@RequestMapping("/user_get")

public ModelAndView user_get(HttpServletRequest req, HttpServletResponse res)


```
{  
  
    ModelAndView mv = new ModelAndView();  
  
    List<User> list = u_dao.user_get();  
  
    mv.setViewName("all_user_list");  
  
    mv.addObject("list", list);  
  
    return mv;  
}
```

//USER LOGIN USING THIS CODE

```
@ResponseBody  
  
@RequestMapping("/user_login")  
  
public String user_login(HttpServletRequest req, HttpServletResponse res)  
{  
  
    String user_fname = req.getParameter("user_fname");  
  
    String user_conpass = req.getParameter("user_conpass");  
  
  
    if(u_repo.findbyname(user_fname)!=null)  
    {  
  
        return "Welcome Back"+" "+ user_fname;  
  
    }else {  
  
        return "Check Credentisls or Register" + " ";  
  
    }  
}
```

//USER CAN FORGET HIS PASSWORD USING THIS CODE

```
@ResponseBody  
  
@RequestMapping("/forget_pass")
```

```

public ModelAndView forget_pass(HttpServletRequest req, HttpServletResponse res)
{
    ModelAndView mv = new ModelAndView();
    String user_phone = req.getParameter("user_phone");
    List<User> u_pass = u_dao.forget_pass(user_phone);
    mv.setViewName("get_user_pass");
    mv.addObject("u_pass",u_pass);
    return mv;
}

```

//USER PROFILE

@ResponseBody

@RequestMapping("/user_profile")

```

public ModelAndView user_profile(HttpServletRequest req, HttpServletResponse res)
{
    ModelAndView mv = new ModelAndView();
    List<User> user_list = u_dao.user_profile();
    mv.setViewName("get_user_profile");
    mv.addObject("user_list",user_list);
    return mv;
}

```

//SHOW ALL AVILABLE PRODUCT'S TO USER

@ResponseBody

@RequestMapping("/aviliablePro")

```

public ModelAndView aviliablePro(HttpServletRequest req, HttpServletResponse res)
{

```

```

        ModelAndView mv = new ModelAndView();

        List<Product> avil_pro = pro_dao.aviliablePro();

        mv.setViewName("avil_product");

        mv.addObject("avil_pro", avil_pro);

        return mv;
    }

    /*USER OPERETION'S END HERE*/


    /*ADMIN OPERATIONS START*/


    //ADMIN CAN APPLY FOR LOGIN CREDENCAL'S HERE

    @ResponseBody
    @RequestMapping("/apply_admin")
    public ModelAndView ad_insert(HttpServletRequest req, HttpServletResponse res)
    {

        ModelAndView mv = new ModelAndView();

        Admin A = new Admin();

        A.setAd_fname(req.getParameter("ad_fname"));

        A.setAd_lname(req.getParameter("ad_lname"));

        A.setAd_phone(req.getParameter("ad_phone"));

        A.setAd_mail(req.getParameter("ad_mail"));

        A.setAd_pass(req.getParameter("ad_pass"));

        A.setAd_con(req.getParameter("ad_con"));

        A.setAd_state(req.getParameter("ad_state"));

        A.setAd_dist(req.getParameter("ad_dist"));
    }

```

```

        A.setAd_taluka(req.getParameter("ad_taluka"));

        A.setAd_pin(req.getParameter("ad_pin"));

        A.setAd_gen(req.getParameter("ad_gen"));

        Admin aa = a_dao.ad_insert(A);

        if(aa!=null)

        {

            mv.setViewName("ad_reg_succ");

        }

        return mv;

    }

//ADMIN LOGIN USING USER NAME

@ResponseBody

@RequestMapping("/ad_login")

public String ad_login(HttpServletRequest req, HttpServletResponse res)

{

    String ad_fname = req.getParameter("ad_fname");

    String ad_con = req.getParameter("ad_con");

    if(a_repo.findbyname(ad_fname)!=null)

    {

        return "Welcome Back "+ " "+ ad_fname;

    }else

    {

        return "Check Credencial's" + " ";

    }

}

}

```

//ADMIN SEARCH USER USING THIS CODE

@ResponseBody

@RequestMapping("/search_user")

public ModelAndView search_user(HttpServletRequest req, HttpServletResponse res)

```
{  
  
    ModelAndView mv = new ModelAndView();  
  
    String user_fname = req.getParameter("user_fname");  
  
    List<User> u_list = u_dao.findByName(user_fname);  
  
    mv.setViewName("search_user_list");  
  
    mv.addObject("u_list", u_list);  
  
    if(u_dao==null)  
    {  
  
        mv.setViewName("search_error");  
  
    }  
  
    return mv;  
}
```

//ADMIN CAN GET REPORT USING THIS CODE

@ResponseBody

@RequestMapping("/get_report")

public ModelAndView report(HttpServletRequest req, HttpServletResponse res)

```
{  
  
    ModelAndView mv = new ModelAndView();  
  
    String sell_date = req.getParameter("sell_date");  
  
    List<Product> r_list = pro_repo.findByDate(sell_date);
```

```

        mv.setViewName("get_report_here");

        mv.addObject("r_list",r_list);

        if(pro_dao==null)
        {
            mv.setViewName("report_error");
        }

        return mv;
    }

```

//ADMIN CAN FORGOT PASSWORD USING REGISTERED MOBILE NUMBER ONLY

```

        @ResponseBody

        @RequestMapping("forget_ad_pass")

        public ModelAndView forget_ad_pass(HttpServletRequest req, HttpServletResponse
res)

        {

            ModelAndView mv = new ModelAndView();

            String ad_phone = req.getParameter("ad_phone");

            List<Admin> pass_list = a_dao.forget_ad_pass(ad_phone);

            mv.setViewName("get_admin_pass");

            mv.addObject("pass_list",pass_list);

            return mv;

        }

```

/*ADMIN OPERATIONS END HERE*/

/*--> PRODUCT OPERATIONS START HERE <--*/

```
//INSERTING PRODUCT CODE
```

```
@ResponseBody
```

```
@RequestMapping("/insert_product")
```

```
public ModelAndView insert_product(HttpServletRequest req, HttpServletResponse res)
```

```
{
```

```
    ModelAndView mv = new ModelAndView();
```

```
    Product p = new Product();
```

```
    p.setPro_code(req.getParameter("pro_code"));
```

```
    p.setPro_name(req.getParameter("pro_name"));
```

```
    p.setPro_brand(req.getParameter("pro_brand"));
```

```
    p.setPro_price(req.getParameter("pro_price"));
```

```
    p.setPro_about(req.getParameter("pro_about"));
```

```
    p.setSell_date(req.getParameter("sell_date"));
```

```
    Product pp = pro_dao.insert_product(p);
```

```
    if(pp!=null)
```

```
    {
```

```
        mv.setViewName("pro_reg_succ");
```

```
    }
```

```
    return mv;
```

```
}
```

```
@ResponseBody
```

```
@RequestMapping("/addcart/{pro_code}")
```

```
public RedirectView addCart(@PathVariable("pro_code") String pro_code,  
HttpServletRequest req, HttpServletResponse res)
```

```
{
```

```
    RedirectView rv = new RedirectView();
```

```
    Cart c = new Cart();
```

```
        c.setPro_code(pro_code);  
        return rv;  
    }  
  
    /*--> PRODUCT OPERATIONS END HERE <--*/  
}
```


Product.java

```
package com.prajval.phase3;
```

```
import java.text.SimpleDateFormat;
```

```
import java.time.LocalDate;
```

```
import java.util.Date;
```

```
import javax.persistence.Entity;
```

```
import javax.persistence.GeneratedValue;
```

```
import javax.persistence.GenerationType;
```

```
import javax.persistence.Id;
```

```
import javax.servlet.jsp.tagext.TryCatchFinally;
```

```
import org.springframework.data.jpa.provider.HibernateUtils;
```

```
import lombok.Data;
```

```
@Data
```

```
@Entity
```

```
public class Product {
```

```
    @Id
```

```
    @GeneratedValue(strategy = GenerationType.AUTO)
```

```
    private int pro_id;
```

```
    private String pro_code;
```

```
    private String pro_name;
```

```
    private String pro_brand;
```

```
        private String pro_price;

        private String pro_about;

        private String sell_date;


//        String pattern = "dd/MM/yyyy";
//        SimpleDateFormat simpleDateFormat = new SimpleDateFormat(pattern);
//        String date = simpleDateFormat.format(new Date());


//        private Date timestamp = new Date(System.currentTimeMillis());

    }
```

ProductDao.java

```
package com.prajval.phase3;
```

```
import java.util.Date;
```

```
import java.util.List;
```

```
import org.springframework.beans.factory.annotation.Autowired;
```

```
import org.springframework.stereotype.Service;
```

```
@Service
```

```
public class ProductDao {
```

```
    @Autowired
```

```
    ProductRepo pro_repo;
```

```
//INSERT PRODUCT HERE
```

```
public Product insert_product(Product p)
```

```
{
```

```
    return pro_repo.save(p);
```

```
}
```

```
//SHOW AVILABLE PRODUCT LIST
```

```
public List<Product> aviliablePro()
```

```
{
```

```
    return pro_repo.findAll();
```

```
}
```

```
//GET REPORT USING PRODUCT CODE
```

```
//    public List<Product> report(Date timestamp)
```

```
//    {
```

```
//        return pro_repo.findBypcode(timestamp);
```

```
//    }
```

```
}
```

```
ProductRepo.java
```

```
package com.prajval.phase3;
```

```
import java.util.List;
```

```
import org.springframework.data.jpa.repository.JpaRepository;

import org.springframework.data.jpa.repository.Query;


public interface ProductRepo extends JpaRepository<Product, Integer>{

    @Query("select pr from Product pr where pr.sell_date=?1")
    public List<Product> findByDate(String sell_date);

}
```

User.java

```
package com.prajval.phase3;
```

```
import javax.persistence.Entity;
```

```
import javax.persistence.GeneratedValue;
```

```
import javax.persistence.GenerationType;
```

```
import javax.persistence.Id;
```

```
import lombok.Data;
```

```
@Data
```

```
@Entity
```

```
public class User {
```

```
    @Id
```

```
    @GeneratedValue(strategy = GenerationType.AUTO)
```

```
    private int user_id;
```

```
    private String user_fname;
```

```
    private String user_lname;
```

```
    private String user_phone;
```

```
    private String user_mail;
```

```
    private String user_dob;
```

```
    private String user_pass;
```

```
    private String user_compass;
```

```
    private String user_state;
```

```
    private String user_dist;
```

```
    private String user_taluka;
```

```
        private String user_pin;

        private String user_gender;

    }
}
```

UserDao.java

```
package com.prajval.phase3;
```

```
import java.util.List;
```

```
import org.springframework.beans.factory.annotation.Autowired;
```

```
import org.springframework.beans.factory.support.SecurityContextProvider;
```

```
import org.springframework.boot.autoconfigure.security.servlet.SecurityFilterAutoConfiguration;
```

```
import org.springframework.stereotype.Service;
```

```
@Service
```

```
public class UserDao {
```

```
    @Autowired
```

```
    UserRepo u_repo;
```

```
    //USER-INSERTION-CODE
```

```
    public User user_insert(User u)
```

```
    {
```

```
        return u_repo.save(u);
```

```
    }
```

```
//GET-REGISTERED-USER'S-LIST
```

```
public List<User> user_get()
{
    return u_repo.findAll();
}
```

```
//SEARCH USER BY FIRST NAME
```

```
public List<User> findByName(String user_fname)
{
    return u_repo.findByName(user_fname);
}
```

```
//THIS CODE GIVES RETURN PASSWORD FOR USER USING PHONE NUMBER
```

```
public List<User> forget_pass(String user_phone)
{
    return u_repo.findByPhone(user_phone);
}
```

```
//SHOW LOGGED USER DATA AS A PROFILE
```

```
public List<User> user_profile()
{
    return u_repo.findAll();
}
```

```
}
```

UserRepo.java

```
package com.prajval.phase3;
```

```
import java.util.List;
```

```
import org.springframework.data.jpa.repository.JpaRepository;
```

```
import org.springframework.data.jpa.repository.Query;
```

```
public interface UserRepo extends JpaRepository<User, Integer>{
```

```
    @Query("select user from User user where user.user_fname=?1")
```

```
    public User findbyname(String user_fname);
```

```
    @Query("select u from User u where u.user_fname=?1")
```

```
    public List<User> findByName(String user_fname);
```

```
    @Query("select up from User up where up.user_phone=?1")
```

```
    public List<User> findByPhone(String user_phone);
```

```
}
```


FROM HERE ALL WEB-PAGES :--

1]. FOLLOWING WEB PAGES IS ACCESSIBLE AFTER LOGIN

AllUserList.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
    <%@ page import="java.util.*" %>
    <%@ page import="com.prajval.phase3.*" %>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
</head>
<body>
<% List<User> u =
(List<User>)request.getAttribute("list"); %>
```

```
<table border="1">
<tr>
    <th>User ID</th>
    <th>First Name</th>
    <th>Last Name</th>
    <th>Phone Number</th>
    <th>E-Mail</th>
    <th>Date Of Birth</th>
    <th>Password</th>
    <th>State</th>
    <th>District</th>
    <th>Taluka</th>
    <th>Pin Code</th>
    <th>Gender</th>
</tr>
```

```
<% for(User uu : u ) { %>
<tr>
    <td><%= uu.getUser_id() %></td>
    <td><%= uu.getUser_fname() %></td>
```

```

        <td><%= uu.getUser_lname() %></td>
        <td><%= uu.getUser_phone() %></td>
        <td><%= uu.getUser_mail() %></td>
        <td><%= uu.getUser_dob() %></td>
        <td><%= uu.getUser_conpass() %></td>
        <td><%= uu.getUser_state() %></td>
        <td><%= uu.getUser_dist() %></td>
        <td><%= uu.getUser_taluka() %></td>
        <td><%= uu.getUser_pin() %></td>
        <td><%= uu.getUser_gender() %></td>
    </tr>
<%} %>

</table>
</body>
</html>

```

AvilProd.jsp

```

<!DOCTYPE html>
<html>
<head>
<%@page import="com.prajval.phase3.Product"%>
<%@page import="java.util.List"%>
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<%@include file="./base.jsp" %>
<%@taglib prefix="c"
uri="http://java.sun.com/jsp/jstl/core" %>

<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
</head>
<body>
<table class="table table-striped">
    <thead>
        <tr>
            <th scope="col">Product ID</th>
            <th scope="col">Product Code</th>
            <th scope="col">Product Name</th>
            <th scope="col">Brand Name</th>
            <th scope="col">About Product</th>

```



```
<% List<Admin> up =  
(List<Admin>)request.getAttribute("pass list"); %>
```

```
<table border="1">  
<tr>  
    <th>Password</th>  
</tr>  
  
<% for(Admin aa : up ) { %>  
<tr>  
    <td><%= aa.getAd_con() %></td>  
</tr>  
<%} %>  
  
</table>  
</body>  
</html>
```

getReportHere.jsp

```
<!DOCTYPE html>  
<html>  
<head>  
<%@page import="com.prajval.phase3.Product"%>  
<%@page import="java.util.List"%>  
<%@include file="./base.jsp" %>  
<%@taglib prefix="c"  
uri="http://java.sun.com/jsp/jstl/core" %>  
  
<meta charset="ISO-8859-1">  
<title>PRAJVAL BHALE</title>  
</head>  
<body>  
<table class="table table-striped">  
    <thead>  
        <tr>  
            <th scope="col"> Product ID </th>  
            <th scope="col">Product Code</th>  
            <th scope="col">Product Name</th>  
            <th scope="col">Brand Name</th>
```

```

        <th scope="col">About Product</th>
        <th scope="col">Product Price</th>
        <th scope="col">Purchased Date</th>
    </tr>
</thead>
<tbody>
<c:forEach items="${r_list}" var="r">
    <tr>
        <th scope="row">PRAJ${r.pro_id}SH</th>
        <td class="font-weight-bold">${r.pro_code}</td>
        <td>${r.pro_name}</td>
        <td>${r.pro_brand}</td>
        <td>${r.pro_about}</td>
        <td class="font-weight-bold">&#x20B9; ${r.pro_price
    }/-</td>
        <td class="font-weight-bold">${r.sell_date}<i
class='fas fa-stopwatch'></td>
    </tr>
</c:forEach>
</tbody>
</table>
</body>
</html>

```

GetUserPass.jsp

```

<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
    <%@ page import="java.util.*" %>
    <%@ page import="com.prajval.phase3.*" %>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
</head>
<body>

```

```
<% List<User> up =  
(List<User>)request.getAttribute("u_pass"); %>
```

```
<table border="1">  
<tr>  
    <th>Password</th>  
</tr>
```

```
<% for (User uu : up ) { %>  
<tr>  
    <td><%= uu.getUser_conpass() %></td>  
</tr>  
<%} %>
```

```
</table>  
</body>  
</html>
```

SearchUser.jsp

```
<%@ page language="java" contentType="text/html;  
charset=ISO-8859-1"  
    pageEncoding="ISO-8859-1"%>  
    <%@ page import="java.util.*" %>  
    <%@ page import="com.prajval.phase3.*" %>  
<!DOCTYPE html>  
<html>  
<head>  
<meta charset="ISO-8859-1">  
<title>PRAJVAL BHALE</title>  
</head>  
<body>  
<% List<User> u =  
(List<User>)request.getAttribute("u_list"); %>
```

```
<table border="1">  
<tr>  
    <th>User ID</th>  
    <th>First Name</th>
```

```

        <th>Last Name</th>
        <th>Phone Number</th>
        <th>E-Mail</th>
        <th>Date Of Birth</th>
        <th>Password</th>
        <th>State</th>
        <th>District</th>
        <th>Taluka</th>
        <th>Pin Code</th>
        <th>Gender</th>
    </tr>

    <% for(User uu : u ) { %>
    <tr>
        <td><%= uu.getUser_id() %></td>
        <td><%= uu.getUser_fname() %></td>
        <td><%= uu.getUser_lname() %></td>
        <td><%= uu.getUser_phone() %></td>
        <td><%= uu.getUser_mail() %></td>
        <td><%= uu.getUser_dob() %></td>
        <td><%= uu.getUser_conpass() %></td>
        <td><%= uu.getUser_state() %></td>
        <td><%= uu.getUser_dist() %></td>
        <td><%= uu.getUser_taluka() %></td>
        <td><%= uu.getUser_pin() %></td>
        <td><%= uu.getUser_gender() %></td>
    </tr>
    <%} %>

</table>
</body>
</html>

```

Base.jsp

```

<%@page
import="com.fasterxml.jackson.annotation.JsonInclude.Include"%>
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>

```

```
<meta name="viewport"
      content="width=device-width, initial-scale=1,
shrink-to-fit=no">
    <%@page isELIgnored="false" %>
    <%@taglib prefix="c"
uri="http://java.sun.com/jsp/jstl/core" %>

<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/cs
s/bootstrap.min.css" integrity="sha384-
Gn5384xqQ1aowXA+058RXPxPg6fy4IWvTNh0E263XmFcJLSAwiGgFAW/dA
iS6JXm" crossorigin="anonymous">

<link rel="stylesheet"
href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/6.1.1/css/all.min.css" integrity="sha512-
KfkfwYDsLkIlwQp6LFnl8zNdLGxu9YAA1QvwINks4PhcELQSVqcyVLLD9a
MhXd13uQjoXtEKNos0WaZqXgel0g==" crossorigin="anonymous"
referrerpolicy="no-referrer" />

<script
      src="https://code.jquery.com/jquery-
3.2.1.slim.min.js"
      integrity="sha384-
KJ3o2DKtIkvYIK3UENzmM7KCKRr/rE9/Qpg6aAZGJwFDMVNA/GpGFF93hX
pG5KkN"
      crossorigin="anonymous">
</script>

<script
      src="https://cdn.jsdelivr.net/npm/popper.js@1.12.9/di
st/umd/popper.min.js"
      integrity="sha384-
ApNbgh9B+Y1QKtv3Rn7W3mgPxhU9K/ScQsAP7hUibX39j7fakFPskvXusv
fa0b4Q"
      crossorigin="anonymous">
</script>

<script
```



```
src="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/js/bootstrap.min.js"
    integrity="sha384-JZR6Spejh4U02d8j0t6vLEHfe/JQGiRRSQQxSfFWpi1MquVdAyjUar5+76PVCmYL"
    crossorigin="anonymous">
</script>

<title><c:out value="${title }"></c:out> </title>
```

1). FOLLOWING WEB PAGES IS ACCESSIBLE TO EVERYONE.

AdGetReport.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
</head>
<h1>collect report from here</h1>
<body>
<form action="get_report">
<input type="date" name="sell_date">
<input type="submit" value="Get Report">
</form>
</body>
</html>
```

AdminLogin.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 750px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
```

```
        overflow: hidden;

        padding : 60px;
        padding-top: 35px;
        padding-bottom : 35px;
    }

    .main{
        background-color: #FFFAFA;
    }

    .btn{
        cursor: pointer;
        padding:5px;
        width: 70px;
        height: 30px;
    }

    .db{
        cursor: pointer;
    }

    .head{
        max-width: 300px;
        border: 2px solid #FFFAFA;
        position: relative;
        margin: auto;
        padding:2px;
        padding-right: 2px;
        font-size: 47px;
    }

    .sh{
        font-family: Garamond;
        font-size:20px;
        color: green;
        padding:1px;
        padding-top:1px;
        max-width:500px;
        margin: 1%;
    }
```

```
.err{
    color: red;
}

.Log{
    color: blue;
}

.admin{
    text-decoration: none;
    color: blue;
}

.forget_pass{
    color: blue;
    text-decoration: none;
}
</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
<hr>
<br><br>
<h1 class="head">Admin <a class="Log">Log
In</a></h1><br><br><br>
<body class="main">
<div class="box">

<form action="ad_login">

    <b>User Name
    :</b>
    <input type="text" name="ad_fname" placeholder="User
    Name">

    <b>Password :</b>
    <input type="password" name="ad_con"
    placeholder="Password">

    </form>
</div>
</body>
</html>
```



```
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 450px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
    padding:5px;
    width: 70px;
    height: 30px;
}

.db{
    cursor: pointer;
}

.head{
    max-width: 475px;
    border: 2px solid #FFFAFA;
    position: relative;
    margin: auto;
    padding:2px;
    padding-right: 2px;
    font-size: 40px;
```

}

```
.sh{
    font-family: Garamond;
    font-size: 20px;
    color: green;
    padding: 1px;
    padding-top: 1px;
    max-width: 500px;
    margin: 1%;
}
```

```
.err{
  color: red;
}
```

```
.search{
  color: blue;
}
```

```
</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
<hr>
<br>
<h1 class="head"><a class="search">Search</a> Sign Up
User's Here</h1><br><br><br>
<body class="main">
<div class="box">
```

```
<form action="search user">
```

```

        <input type="text" name="user_fname" placeholder="Search
        By User Name"><br><br><br><br>
    
```

[illegible]

AdminForgotPass.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 300px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
    padding:5px;
    width: 100px;
```



```
        height: 30px;
        margin: auto;
        margin-right: 10%;
        margin-left: 12%;
    }

    .db{
        cursor: pointer;
    }

    .head{
        max-width: 350px;
        border: 2px solid #FFFAFA;
        position: relative;
        margin: auto;
        padding: 2px;
        padding-right: 2px;
        font-size: 47px;
    }

    .sh{
        font-family: Garamond;
        font-size: 20px;
        color: green;
        padding: 1px;
        padding-top: 1px;
        max-width: 500px;
        margin: 1%;
    }

    .err{
        color: red;
    }

    .Log{
        color: blue;
    }

    .ac{
        text-decoration: none;
    }
```



```
.bx {  
    padding: 0;  
    background-color: black;  
    overflow: hidden;  
    border-radius: 0;  
    height: 150px;  
    max-height: 210px;  
    margin: auto;  
    padding-top: 20px;  
    border-bottom-left-radius: 20px;  
    border-bottom-right-radius: 20px;  
}
```

```
.head{  
    font-family: Garamond;  
    font-size: 30px;  
    color: green;  
    padding: 1px;  
    max-width: 500px;  
    padding-top: 100px;  
}
```

```
.sh {  
    position: absolute;  
    top: 21%;  
    left: 9%;  
    transform: translate(-50%, -50%);  
    font-family: Garamond;  
    color: green;  
    font-size: 27px;  
}
```

```
.active{  
    display :block;  
    text-decoration: none;  
    float: right;  
    padding: 1%;  
    margin: auto;  
    margin-right : 1%;  
    margin-left : 1%;  
    font-size: 27px;  
    font-family: Garamond;
```

```
        color: green;
    }

    .active a:hover {
        background: gray;
    }

    .img{
        position: absolute;
        margin-left: 2%;
        margin-right: 2%;
        max-height: 200px;
        max-width: 400px;
    }

    .info{
        color: black;
        font-family: Garamond;
        float: right;
        padding-right: 15px;
    }
</style>
</head>

<body class="main">

    <div class="bx">
    <div class="container">
    
    <h3 class="sh"></h3>
    </div>
    <br><br>

    <a class="active" href="ad_login.jsp"><b>LOGIN</b></a>
    <a class="active" href="apply_admin.jsp"><b>APPLY</b></a>
    <a class="active" href="Admin_main.jsp"><b>HOME</b></a>
    </div>
    <h4 class="info"><u>Admin</u> Page</h4>
    <br>
</body>
```

```
</html>
```

AfterAdminLogin.jsp

```
<%@ page language="java" contentType="text/html;
charset=UTF-8"
    pageEncoding="UTF-8"%>
```

```
<!DOCTYPE html>
<html>
<head>
<title>PRAJVAL BHALE</title>
<style type="text/css">
```

```
.main{
    margin: 0;
    padding: 0;
    background:#FAF0E6;
    font-family: Sul Sans,Helvetica
Neue,Helvetica,Roboto,Arial,sans-serif;
    font-weight: 400;
    line-height: 1.5;
    color: #FFFAFA;
    -webkit-font-smoothing: antialiased
    background-color: #FFFAFA;
}
```

```
.bx {
    padding: 0;
    background-color: black;
    overflow: hidden;
    border-radius: 0;
    height:150px;
    max-height: 210px;
    margin: auto;
    padding-top: 20px;
    border-bottom-left-radius: 20px;
    border-bottom-right-radius: 20px;
}
```

```
.head{
    font-family: Garamond;
    font-size:30px;
    color: green;
    padding:1px;
    max-width:500px;
    padding-top: 100px;
}
```

```
.sh {
    position: absolute;
    top: 21%;
    left: 9%;
    transform: translate(-50%, -50%);
    font-family: Garamond;
    color: green;
    font-size:27px;
}
```

```
.active{
    display :block;
    text-decoration: none;
    float: right;
    padding: 1%;
    margin: auto;
    margin-right : 1%;
    margin-left : 1%;
    font-size: 22px;
    font-family: Garamond;
    color: green;
}
```

```
.active a:hover {
    background: gray;
}
```

```
.img{
    position: absolute;
    margin-left: 2%;
    margin-right: 2%;
    max-height: 200px;
```

```

        max-width: 400px;
    }

    .pro-img{
        float : right;
        margin-top : -2%;
        margin-left: 2%;
        margin-right: 2%;
        margin-bottom: 2%;
        max-height: 100px;
        max-width: 120px;
        cursor: pointer;
    }
</style>
</head>

<body class="main">

<div class="bx">
<div class="container">

<h3 class="sh"></h3>
</div>
<br><br>
<a href="">

</a>
<a class="active" href="HOME_SCREEN.jsp"><b>LOG
OUT</b></a>
<a class="active"
href="ad_get_report.jsp"><b>REPORT</b></a>
<a class="active" href="ad_search_users.jsp"><b>SEARCH
USER</b></a>
<a class="active" href="/user_get"><b>USER LIST</b></a>
<a class="active" href="insert_product.jsp"><b>ADD
PRODUCT</b></a>

</div>
</body>
</html>

```


AfterUserLogin.jsp

```
<!DOCTYPE html>
<html>
<head>
  <%@ page import="java.util.*" %>
  <%@ page import="com.prajval.phase3.*" %>

  <%@include file="./base.jsp" %>
  <%@taglib prefix="c"
uri="http://java.sun.com/jsp/jstl/core" %>

  <style type="text/css">

    .main{
      margin: 0;
      padding: 0;
      background:#FAF0E6;
      font-family: Sul Sans,Helvetica
Neue,Helvetica,Roboto,Arial,sans-serif;
      font-weight: 400;
      line-height: 1.5;
      color: #FFFAFA;
      -webkit-font-smoothing: antialiased
      background-color: #FFFAFA;

    }

    .bx {
      padding: 0;
      background-color: black;
      overflow: hidden;
      border-radius: 0;
      height:150px;
      max-height: 210px;
      margin: auto;
      padding-top: 20px;
      border-bottom-left-radius: 20px;
      border-bottom-right-radius: 20px;
    }
  </style>
</head>
<body>
```

```
.head{
    font-family: Garamond;
    font-size:30px;
    color: green;
    padding:1px;
    max-width:500px;
    padding-top: 100px;
}

.sh {
    position: absolute;
    top: 21%;
    left: 9%;
    transform: translate(-50%, -50%);
    font-family: Garamond;
    color: green;
    font-size:27px;
}

.active{
    display :block;
    text-decoration: none;
    float: right;
    padding: 1%;
    margin: auto;
    margin-right : 1%;
    margin-left : 1%;
    font-size: 22px;
    font-family: Garamond;
    color: green;
}

.active a:hover {
    background: gray;
}

.img{
    position: absolute;
    margin-left: -4%;
    margin-right: 2%;
}
```

```

        max-height: 200px;
        max-width: 400px;
    }

    .pro-img{
        float : right;
        margin-top : -2%;
        margin-left: 2%;
        margin-right: 2%;
        margin-bottom: 2%;
        max-height: 100px;
        max-width: 120px;
        cursor: pointer;
    }

    .table{
        color: black;
        font-size: 130%;
        font-family: times new roman;
    }
</style>
</head>

<body class="main">
<div class="bx">
<div class="container">

</div>
<br><br>
<a href="user_profile.jsp">

</a>
<a class="active" href="HOME_SCREEN.jsp"><b>LOG
OUT</b></a>
<a class="active" href="#"><b>MY CART</b></a>
<a class="active" href="#"><b>MY ORDER'S</b></a>
<a class="active"
href="/aviliablePro"><b>PRODUCT'S</b></a>
<a class="active"
href="/after_user_login.jsp"><b>HOME</b></a>
</div>

```

```
</body>
</html>
```

ApplyAdmin.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 750px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
}

.db{
    cursor: pointer;
}
```

```
.head{
    max-width: 280px;
    border: 2px solid #FFFAFA;
    position: relative;
    margin: auto;
    padding: 2px;
    padding-right: 2px;
}
```

```
.sh{
    font-family: Garamond;
    font-size: 20px;
    color: green;
    padding: 1px;
    padding-top: 1px;
    max-width: 500px;
    margin: 1%;
}
```

```
.reg{
  color: blue;
}
```

```
</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
<hr>
<br>
<h1 class="head">Apply for <a
class="reg">ADMIN.</a></h1><br>
<body class="main">
<div class="box">
```

```
<form action="apply_admin">
```

```

        <b>First Name
    :</b>
    <input type="text" name="ad_fname" placeholder="First
    Name">

```

[illegible]

```
<b>Phone Number :</b>  
<input type="number" name="ad_phone" placeholder="Phone  
Number">  
  
  
  
  
  
  
  
  
  
  
<b>E-mail  
:</b><br>  
<input type="email" name="ad_mail" placeholder="E-mail  
ID"><br><br><br>
```

```

Date Of Birth :

```

```

    <b>Conform :</b>
    <input type="password" name="ad_con" placeholder="Conform Password">

    <b>State :</b>
    <input type="text" name="ad_state" placeholder="State"><br><br><br>

```

```

District :


```

[illegible]

Pin Code :

```
<b>Gender :</b>  
<input type="text" name="ad_gen"  
placeholder="Gender"><br><br><br>
```

[illegible][illegible]

```
<input class="btn" type="submit" value="Register">
</form>
```

</body>

</html>

Base.jsp

```
import "com.fasterxml.jackson.annotation.JsonInclude.Include" %>
```

```
pageEncoding="ISO-8859-1"%>
```

```
<meta name="viewport"
```

```
        content="width=device-width, initial-scale=1,
shrink-to-fit=no">
        <%@page isELIgnored="false" %>
        <%@taglib prefix="c"
uri="http://java.sun.com/jsp/jstl/core" %>

<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/cs
s/bootstrap.min.css" integrity="sha384-
Gn5384xqQ1aowXA+058RXPxPg6fy4IWvTNh0E263XmFcJLSAwiGgFAW/dA
iS6JXm" crossorigin="anonymous">

<link rel="stylesheet"
href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/6.1.1/css/all.min.css" integrity="sha512-
KfkfwYDsLkIlwQp6LFnl8zNdLGxu9YAA1QvwINks4PhcELQSVqcyVLLD9a
MhXd13uQjoXtEKNos0WaZqXgel0g==" crossorigin="anonymous"
referrerpolicy="no-referrer" />

<script
        src="https://code.jquery.com/jquery-
3.2.1.slim.min.js"
        integrity="sha384-
KJ3o2DKtIkVYIK3UENzmM7KChRr/rE9/Qpg6aAZGJwFDMVNA/GpGFF93hX
pG5KkN"
        crossorigin="anonymous">
</script>

<script
        src="https://cdn.jsdelivr.net/npm/popper.js@1.12.9/di
st/umd/popper.min.js"
        integrity="sha384-
ApNbgh9B+Y1QKtv3Rn7W3mgPxhU9K/ScQsAP7hUibX39j7fakFPskvXusv
fa0b4Q"
        crossorigin="anonymous">
</script>

<script
        src="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dis
t/js/bootstrap.min.js"
```



```
        integrity="sha384-
JZR6Spejh4U02d8jOt6vLEHfe/JQGiRRSQQxSfFWpi1MquVdAyjUar5+76
PVCmYL"
```

```
        crossorigin="anonymous">
</script>
```

```
        <title><c:out value="${title }"></c:out>PRAJVAL
        BHALE</title>
```

HOME_CART.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
```

```
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
```

```
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
```

```
.log{
    text-decoration: none;
    color: blue;
}
```

```
.insert{
    text-decoration: none;
    color: blue;
}
```

```
.main{
    background-color: #FFFAFA;
}
```

```
.sh{
    font-family: Garamond;
    font-size:20px;
    color: green;
    padding:1px;
    padding-top:1px;
    max-width:500px;
```

```

        margin: 1%;
    }
</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
<hr>
<img alt="" src="">
<body class="main">
<h1>No Data to Show.....!</h1>
<h2>Log in to my account<a class="log"
href="user_login.jsp"> User</a> /<a class="log"
href="ad_login.jsp"> Admin</a></h2>
<h3>If you Don't have account then Create Here<a
class="insert" href="insert_user.jsp"> For User</a> & <a
class="insert" href="apply_admin.jsp">For Admin</a></h3>
</body>
</html>

```

HOME.screen

```

<%@ page language="java" contentType="text/html;
charset=UTF-8"
    pageEncoding="UTF-8"%>

```

```

<!DOCTYPE html>
<html>
<head>
<title>PRAJVAL BHALE</title>
<style type="text/css">

```

```

.main{
    margin: 0;
    padding: 0;
    background:#FAF0E6;
    font-family: Sul Sans,Helvetica
Neue,Helvetica,Roboto,Arial,sans-serif;
    font-weight: 400;
    line-height: 1.5;
    color: #FFFAFA;
    -webkit-font-smoothing: antialiased
    background-color: #FFFAFA;
}

```

```
.bx {  
    padding: 0;  
    background-color: black;  
    overflow: hidden;  
    border-radius: 0;  
    height: 150px;  
    max-height: 210px;  
    margin: auto;  
    padding-top: 20px;  
    border-bottom-left-radius: 20px;  
    border-bottom-right-radius: 20px;  
}
```

```
.head{  
    font-family: Garamond;  
    font-size: 30px;  
    color: green;  
    padding: 1px;  
    max-width: 500px;  
    padding-top: 100px;  
}
```

```
.sh {  
    position: absolute;  
    top: 21%;  
    left: 9%;  
    transform: translate(-50%, -50%);  
    font-family: Garamond;  
    color: green;  
    font-size: 27px;  
}
```

```
.active{  
    display :block;  
    text-decoration: none;  
    float: right;  
    padding: 1%;  
    margin: auto;  
    margin-right : 1%;  
    margin-left : 1%;  
    font-size: 22px;
```

```

        font-family: Garamond;
        color: green;
    }

    .active a:hover {
        background: gray;
    }

    .img{
        position: absolute;
        margin-left: 2%;
        margin-right: 2%;
        max-height: 200px;
        max-width: 400px;
    }
</style>
</head>

<body class="main">

<div class="bx">
<div class="container">

<h3 class="sh"></h3>
</div>
<br><br>
<a class="active" href="HOME_CART.jsp"><b>CART</b></a>
<a class="active" href="User_main.jsp"><b>USER</b></a>
<a class="active" href="Admin_main.jsp"><b>ADMIN</b></a>
<a class="active" href="HOME_SCREEN.jsp"><b>HOME</b></a>

</div>
</body>
</html>

```

InsertProduct.jsp

```

<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"

```

```
        pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
    <%@include file="./base.jsp" %>
<style type="text/css">
.box {
    max-width: 750px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
}

.db{
    cursor: pointer;
}

.head{
    max-width: 300px;
    border: 2px solid #FFFAFA;
    position: relative;
    margin: auto;
    padding:2px;
    padding-right: 2px;
}
```

```
.sh{
    font-family: Garamond;
    font-size: 20px;
    color: green;
    padding: 1px;
    padding-top: 1px;
    max-width: 500px;
    margin: 1%;
}
```

```
.reg{
  color: blue;
}
```

```
.Log-in{
    cursor: pointer;
    padding: 15px;
    width: 90px;
    height: 30px;
    text-decoration: none;
}
```

```
</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
<hr>
<br>
<h1 class="head">Insert <a
class="reg">PRODUCT...!</a></h1><br>
<body class="main">
<div class="box">
```

```
<form action="insert_product">
```

```
              <b>Product Code
:</b>              <input type="text" name="pro_code" placeholder="Product
Code"><br><br>
                <b>Product Name
:</b>              
```



```
</html>
```

insertUser.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 750px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
}

.db{
    cursor: pointer;
}

.head{
```



```

        max-width: 490px;
        border: 2px solid #FFFAFA;
        position: relative;
        margin: auto;
        padding: 2px;
        padding-right: 2px;
    }

    .sh{
        font-family: Garamond;
        font-size: 20px;
        color: green;
        padding: 1px;
        padding-top: 1px;
        max-width: 500px;
        margin: 1%;
    }

    .reg{
        color: blue;
    }

    .Log-in{
        cursor: pointer;
        padding: 15px;
        width: 90px;
        height: 30px;
        text-decoration: none;
    }

</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
<hr>
<br>
<h1 class="head">USER <a
class="reg">REGISTRATION...!</a></h1><br>
<body class="main">
<div class="box">

<form action="user_insert">

```


UserForgotPass.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 300px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
    padding:5px;
    width: 100px;
    height: 30px;
    margin: auto;
    margin-right: 10%;
    margin-left: 12%;
}

.db{
    cursor: pointer;
```

```
}

.head{
  max-width: 350px;
  border: 2px solid #FFFAFA;
  position: relative;
  margin: auto;
  padding: 2px;
  padding-right: 2px;
  font-size: 47px;
}

.sh{
  font-family: Garamond;
  font-size: 20px;
  color: green;
  padding: 1px;
  padding-top: 1px;
  max-width: 500px;
  margin: 1%;
}

.err{
  color: red;
}

.log{
  color: blue;
}

.ac{
  text-decoration: none;
}

.forget_pass{
  color: blue;
  text-decoration: none;
}

</style>
</head>
<h3 class="sh">SportyShoes.com</h3>
```



```
<input class="btn" type="submit" value="Get Password">
</form>
</div>
</body>
</html>
```

UserLogin.jsp

```
<%@ page language="java" contentType="text/html;
charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>PRAJVAL BHALE</title>
<style type="text/css">
.box {
    max-width: 750px;
    margin: auto;
    align-content: center;
    border : 1px solid gray;
    border-radius: 15px;
    background-color: white;
    border-width: 2px;
    overflow: hidden;

    padding : 60px;
    padding-top: 35px;
    padding-bottom : 35px;
}

.main{
    background-color: #FFFAFA;
}

.btn{
    cursor: pointer;
    padding:5px;
```

```
        width: 70px;
        height: 30px;
    }

    .db{
        cursor: pointer;
    }

    .head{
        max-width: 300px;
        border: 2px solid #FFFAFA;
        position: relative;
        margin: auto;
        padding: 2px;
        padding-right: 2px;
        font-size: 47px;
    }

    .sh{
        font-family: Garamond;
        font-size: 20px;
        color: green;
        padding: 1px;
        padding-top: 1px;
        max-width: 500px;
        margin: 1%;
    }

    .err{
        color: red;
    }

    .Log{
        color: blue;
    }

    .ac{
        text-decoration: none;
    }

    .forget_pass{
        color: blue;
    }
```


[illegible]


```
    color: #FFFAFA;
    -webkit-font-smoothing: antialiased
    background-color: #FFFAFA;
}

.bx {
    padding: 0;
    background-color: black;
    overflow: hidden;
    border-radius: 0;
    height: 150px;
    max-height: 210px;
    margin: auto;
    padding-top: 20px;
    border-bottom-left-radius: 20px;
    border-bottom-right-radius: 20px;
}

.head{
    font-family: Garamond;
    font-size: 30px;
    color: green;
    padding: 1px;
    max-width: 500px;
    padding-top: 100px;
}

.sh {
    position: absolute;
    top: 21%;
    left: 9%;
    transform: translate(-50%, -50%);
    font-family: Garamond;
    color: green;
    font-size: 27px;
}

.active{
    display :block;
    text-decoration: none;
    float: right;
```

```
padding: 1%;  
margin: auto;  
margin-right : 1%;  
margin-left : 1%;  
font-size: 27px;  
font-family: Garamond;  
color: green;  
}
```

```
.active a:hover {  
    background: gray;  
}
```

```
.img{  
    position: absolute;  
    margin-left: 2%;  
    margin-right: 2%;  
    max-height: 200px;  
    max-width: 400px;  
}
```

```
.info{  
    color: black;  
    font-family: Garamond;  
    float: right;  
    padding-right: 15px;  
}  
</style>  
</head>
```

```
<body class="main">
```

```
<div class="bx">  
<div class="container">  
  
<h3 class="sh"></h3>  
</div>  
<br><br>
```

```
<a class="active" href="HOME_SCREEN.jsp"><b>LOG-  
OUT</b></a>  
<a class="active" href="user_login.jsp"><b>LOGIN</b></a>  
<a class="active"  
href="insert_user.jsp"><b>REGISTER</b></a>  
<a class="active" href="User_main.jsp"><b>HOME</b></a>  
</div>  
<h4 class="info">User Page</h4>  
<br>  
</body>  
</html>
```

This Two Picture's are in Used :---

