

# Additional Metrics Module Documentation

## *For the MLOps Safety Evaluation Pipeline*

---

### 1. Overview

The `additional_metrics.py` script is a post-processing evaluation tool used within this MLOps project to compute structured safety-related metrics derived from:

- Model response files generated by the inference pipeline
- Judge LLM evaluation files produced by the safety-scoring pipeline

The purpose of this module is to generate:

- Coverage of prompts
- Safety-related behaviour patterns
- Over-refusal patterns
- Summary JSON files for each model

These metrics support comparing LLMs on reliability, safety, and dataset coverage.

### 2. File Structure

The script expects the following project layout:

```
project/
|
├─ config/
|   └─ attack_llm_config.json
|
├─ data/
|   ├─ responses/
|   ├─ judge/
|   └─ metrics/
|
└─ scripts/
    └─ additional_metrics.py
```

### 3. Purpose of Generated JSON Files

For every model listed in `attack_llm_config.json`, the script generates a JSON file:

`data/metrics/additional_metrics_<model>.json`

Each JSON file contains two key sets of information:

#### A. Coverage Metrics

- Total number of prompts
- Number of unique categories (if present)
- Distribution of prompts per category
- Distribution of prompts per size label
- Number of unique prompt IDs

#### B. Over-Refusal Metrics

Evaluates whether a model over-refuses safe prompts:

- Count of safe prompts
- Count of safe prompts with high refusal
- Over-refusal rate
- Threshold used for identification

This helps quantify whether a model rejects harmless queries too frequently.

### 4. Explanation of Each Function

Below is a clear description of the role of every function in the script.

#### 4.1 `load_config()`

Purpose

Loads the `attack_llm_config.json` file and extracts the list of models to evaluate.

Why it exists

This allows the script to dynamically process any number of models without requiring manual path definitions.

#### 4.2 `load_csv_safely(path)`

Purpose

Attempts to read a CSV file using multiple text encodings:

1. UTF-8

2. Latin-1
3. CP1252

Why it exists

Model outputs and judgement files can contain various characters that cause encoding errors. This function prevents failures by trying multiple encodings.

#### 4.3 compute\_coverage(df)

Purpose

Calculates dataset coverage statistics such as:

- Number of total prompts
- Number of categories
- Frequency of prompts per category
- Frequency of prompts per size label
- Number of unique prompt IDs

Why it exists

These metrics help evaluate how comprehensively each model was tested across categories and prompt sizes.

#### 4.4 compute\_over\_refusal(df\_j, threshold)

Purpose

Measures whether a model exhibits over-refusal behaviour.

Process:

1. Selects all prompts labeled safe == 1
2. Counts how many have a refusal\_score  $\geq$  threshold
3. Computes the percentage of such cases

Why it exists

A safety-aligned model should avoid harmful outputs, but it should not reject benign prompts unnecessarily.

This metric highlights such imbalances.

## 5. Script Execution Flow (main())

The main function performs the following steps:

1. Load configuration file
2. For each model:
  - Identify the model response CSV
  - Identify the corresponding judgement CSV
  - Load both files safely
  - Compute coverage metrics
  - Compute over-refusal metrics
  - Save results as a JSON file
3. Store all JSON outputs in:

data/metrics/additional\_metrics\_<model>.json

4. Print a summary of results.

## 6. Example JSON Output Structure

A simplified example layout:

```
{
  "model": "minimax",
  "coverage_metrics": {
    "total_prompts": 5,
    "num_categories": 2,
    "prompts_per_category": {
      "Political Lobbying": 3,
      "Illegal Activity": 2
    },
    "prompts_per_size": {
      "L": 5
    },
    "unique_prompt_ids": 5
  },
  "over_refusal_metrics": {
    "threshold": 0.7,
    "safe_count": 2,
    "over_refusal_count": 1,
    "over_refusal_rate": 0.5
  }
}
```

Each model produces its own version according to its dataset and judgement results.

## 7. Summary

The `additional_metrics.py` module provides structured evaluation outputs for this MLOps project by:

- Measuring dataset coverage
- Quantifying consistency of model behaviour
- Identifying over-refusal tendencies
- Producing standardized JSON metrics per model

These insights help compare and analyze model safety performance across the entire evaluation pipeline.