

```
create table customer(id varchar(10),name varchar(50),address varchar(60),salary number);
```

Table created.

```
SQL> insert into customer values(5,'hardhik','bhopal',9000);
```

1 row created.

```
SQL> insert into customer values(4,'raju','erode',8000);
```

1 row created.

```
SQL> insert into customer values(3,'akash','chennai',7000);
```

1 row created.

```
SQL> insert into customer values(2,'arun','salem',6000);
```

1 row created.

```
SQL> declare
```

```
2 customer_rec customer%rowtype;
```

```
3 begin
```

```
4 select*into customer_rec from customer where id=5;
```

```
5 dbms_output.put_line('customer id:'|| customer_rec.id);
```

```
6 dbms_output.put_line('customer name:'|| customer_rec.name);
```

```
7 dbms_output.put_line('customer address:'|| customer_rec.address);
```

```
8 dbms_output.put_line('customer salary:'|| customer_rec.salary);
```

```
9 end;
```

```
10 /
```

customer id:5

customer name:hardhik

customer address:bhopal

customer salary:9000

PL/SQL procedure successfully completed.

```
create table customer(id varchar(10),name varchar(50),address varchar(60),salary number);
```

Table created.

```
SQL> insert into customer values(5,'hardhik','bhopal',9000);
```

1 row created.

