

CS 577- Intro to Algorithms

Network Flow (Part 4)

Dieter van Melkebeek

November 5, 2020

Outline

Outline

Applications of min cut

- ▶ Image segmentation
- ▶ Project selection

Recap

Recap

Network

- ▶ a digraph (V, E)
- ▶ edge capacities $c : E \rightarrow [0, \infty)$
- ▶ the source $s \in V$, which has indegree 0, and
- ▶ the sink $t \in V$, which has outdegree 0.

Recap

Network

- ▶ a digraph (V, E)
- ▶ edge capacities $c : E \rightarrow [0, \infty)$
- ▶ the source $s \in V$, which has indegree 0, and
- ▶ the sink $t \in V$, which has outdegree 0.

st -Cut

A partition (S, T) of V such that $s \in S$ and $t \in T$.

Recap

Network

- ▶ a digraph (V, E)
- ▶ edge capacities $c : E \rightarrow [0, \infty)$
- ▶ the source $s \in V$, which has indegree 0, and
- ▶ the sink $t \in V$, which has outdegree 0.

st -Cut

A partition (S, T) of V such that $s \in S$ and $t \in T$.

Min cut problem

Input: network $N = (V, E, c, s, t)$

Output: st -cut (S, T) such that $c(S, T) \doteq \sum_{e \in S \times T} c(e)$ is minimized

Recap

Network

- ▶ a digraph (V, E)
- ▶ edge capacities $c : E \rightarrow [0, \infty)$
- ▶ the source $s \in V$, which has indegree 0, and
- ▶ the sink $t \in V$, which has outdegree 0.

st -Cut

A partition (S, T) of V such that $s \in S$ and $t \in T$.

Min cut problem

Input: network $N = (V, E, c, s, t)$

Output: st -cut (S, T) such that $c(S, T) \doteq \sum_{e \in S \times T} c(e)$ is minimized

Complexity: time $O(nm)$

Image segmentation

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$
 $f_i \in [0, \infty)$: “likelihood” that i is foreground

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

Output: partition of $[n]$ into foreground F and background B

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

$c \in [0, \infty)$: penalty for separating neighboring pixels

Output: partition of $[n]$ into foreground F and background B

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

$c \in [0, \infty)$: penalty for separating neighboring pixels

Output: partition of $[n]$ into foreground F and background B maximizing

$$\sum_{i \in F} f_i + \sum_{j \in B} b_j - c \cdot |\{(i, j) \in F \times B : i \sim j\}|$$

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

$c \in [0, \infty)$: penalty for separating neighboring pixels

Output: partition of $[n]$ into foreground F and background B maximizing

$$\sum_{i \in F} f_i + \sum_{j \in B} b_j - c \cdot |\{(i, j) \in F \times B : i \sim j\}|$$

Model

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

$c \in [0, \infty)$: penalty for separating neighboring pixels

Output: partition of $[n]$ into foreground F and background B maximizing

$$\sum_{i \in F} f_i + \sum_{j \in B} b_j - c \cdot |\{(i, j) \in F \times B : i \sim j\}|$$

Model

- ▶ Vertex for each pixel, source s , sink t

Image segmentation

Computational problem

Input: grid of pixels $i \in [n]$

$f_i \in [0, \infty)$: “likelihood” that i is foreground

$b_i \in [0, \infty)$: “likelihood” that i is background

$c \in [0, \infty)$: penalty for separating neighboring pixels

Output: partition of $[n]$ into foreground F and background B maximizing

$$\sum_{i \in F} f_i + \sum_{j \in B} b_j - c \cdot |\{(i, j) \in F \times B : i \sim j\}|$$

Model

- ▶ Vertex for each pixel, source s , sink t
- ▶ $S = F \cup \{s\}$ and $T = B \cup \{t\}$

Image Segmentation – rewriting objective

Image Segmentation – rewriting objective

$$\begin{aligned} & \max_{F,B} \left(\sum_{i \in F} f_i + \sum_{j \in B} b_j - \sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c \right) \\ &= - \min_{F,B} \left(\sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c - \sum_{i \in F} f_i - \sum_{j \in B} b_j \right) \\ &= - \min_{F,B} \left(\sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c - \sum_{i \in [n]} f_i + \sum_{i \in B} f_i - \sum_{j \in [n]} b_j + \sum_{j \in F} b_j \right) \\ &= \sum_{i \in [n]} f_i + \sum_{j \in [n]} b_j - \min_{F,B} \left(\sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c + \sum_{i \in B} f_i + \sum_{j \in F} b_j \right) \end{aligned}$$

Image Segmentation – reduction to min cut

Image Segmentation – reduction to min cut

- Need to find partition of $[n]$ into F and B minimizing

$$(*) \doteq \sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c + \sum_{i \in B} f_i + \sum_{j \in F} b_j.$$

Image Segmentation – reduction to min cut

- ▶ Need to find partition of $[n]$ into F and B minimizing

$$(*) \doteq \sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c + \sum_{i \in B} f_i + \sum_{j \in F} b_j.$$

- ▶ Construct network N such that $(*) = c(S, T)$ where $S = F \cup \{s\}$ and $T = B \cup \{t\}$.

Image Segmentation – reduction to min cut

- Need to find partition of $[n]$ into F and B minimizing

$$(*) \doteq \sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c + \sum_{i \in B} f_i + \sum_{j \in F} b_j.$$

- Construct network N such that $(*) = c(S, T)$ where $S = F \cup \{s\}$ and $T = B \cup \{t\}$.





Image Segmentation – reduction to min cut

- Need to find partition of $[n]$ into F and B minimizing

$$(*) \doteq \sum_{\substack{i \sim j \\ (i,j) \in F \times B}} c + \sum_{i \in B} f_i + \sum_{j \in F} b_j.$$

- Construct network N such that $(*) = c(S, T)$ where $S = F \cup \{s\}$ and $T = B \cup \{t\}$.



- Resulting algorithm runs in time $O(n^2)$.

Project Selection

Project Selection

Computational problem

Project Selection

Computational problem

Input: n projects $i \in [n]$

Project Selection

Computational problem

Input: n projects $i \in [n]$
 m tools $j \in [m]$

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

$v_i \in [0, \infty)$: value of project $i \in [n]$ if realized

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

$v_i \in [0, \infty)$: value of project $i \in [n]$ if realized

$c_j \in [0, \infty)$: one-time cost of tool $j \in [m]$ if bought

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

$v_i \in [0, \infty)$: value of project $i \in [n]$ if realized

$c_j \in [0, \infty)$: one-time cost of tool $j \in [m]$ if bought

Output: Set of projects $I \subseteq [n]$ to realize and set of tools $J \subseteq [m]$ to buy maximizing $\sum_{i \in I} v_i - \sum_{j \in J} c_j$ such that $(\forall i \in I) T_i \subseteq J$.

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

$v_i \in [0, \infty)$: value of project $i \in [n]$ if realized

$c_j \in [0, \infty)$: one-time cost of tool $j \in [m]$ if bought

Output: Set of projects $I \subseteq [n]$ to realize and set of tools

$J \subseteq [m]$ to buy maximizing $\sum_{i \in I} v_i - \sum_{j \in J} c_j$

such that $(\forall i \in I) T_i \subseteq J$.

Model

- ▶ Vertex for each project $i \in [n]$ & tool $j \in [m]$; source s , sink t

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

$v_i \in [0, \infty)$: value of project $i \in [n]$ if realized

$c_j \in [0, \infty)$: one-time cost of tool $j \in [m]$ if bought

Output: Set of projects $I \subseteq [n]$ to realize and set of tools

$J \subseteq [m]$ to buy maximizing $\sum_{i \in I} v_i - \sum_{j \in J} c_j$

such that $(\forall i \in I) T_i \subseteq J$.

Model

- ▶ Vertex for each project $i \in [n]$ & tool $j \in [m]$; source s , sink t
- ▶ Project $i \in [n]$ is realized iff $i \in S$.

Project Selection

Computational problem

Input: n projects $i \in [n]$

m tools $j \in [m]$

$T_i \subseteq [m]$: tools needed to realize project $i \in [n]$

$v_i \in [0, \infty)$: value of project $i \in [n]$ if realized

$c_j \in [0, \infty)$: one-time cost of tool $j \in [m]$ if bought

Output: Set of projects $I \subseteq [n]$ to realize and set of tools $J \subseteq [m]$ to buy maximizing $\sum_{i \in I} v_i - \sum_{j \in J} c_j$ such that $(\forall i \in I) T_i \subseteq J$.

Model

- ▶ Vertex for each project $i \in [n]$ & tool $j \in [m]$; source s , sink t
- ▶ Project $i \in [n]$ is realized iff $i \in S$.
- ▶ Side of st -cut determines whether tool $j \in [m]$ is bought.

Project Selection – rewriting objective

Project Selection – rewriting objective

$$\begin{aligned} & \max_{I,J} \left(\sum_{i \in I} v_i - \sum_{j \in J} c_j \right) \\ &= - \min_{I,J} \left(\sum_{j \in J} c_j - \sum_{i \in I} v_i \right) \\ &= - \min_{I,J} \left(\sum_{j \in J} c_j - \sum_{i \in [n]} v_i + \sum_{i \in [n] \setminus I} v_i \right) \\ &= \sum_{i \in [n]} v_i - \min_{I,J} \left(\sum_{j \in J} c_j + \sum_{i \in [n] \setminus I} v_i \right) \end{aligned}$$

Project Selection – reduction to min cut

Project Selection – reduction to min cut

- ▶ Need to find $I \subseteq [n]$ and $J \subseteq [m]$ with $(\forall i \in I) T_i \subseteq J$ minimizing

$$(*) \doteq \sum_{j \in J} c_j + \sum_{i \in [n] \setminus I} v_i.$$

Project Selection – reduction to min cut

- ▶ Need to find $I \subseteq [n]$ and $J \subseteq [m]$ with $(\forall i \in I) T_i \subseteq J$ minimizing

$$(*) \doteq \sum_{j \in J} c_j + \sum_{i \in [n] \setminus I} v_i.$$

- ▶ Construct network N such that $(*) = c(S, T)$ where I are the projects in S .

Project Selection – reduction to min cut

- ▶ Need to find $I \subseteq [n]$ and $J \subseteq [m]$ with $(\forall i \in I) T_i \subseteq J$ minimizing

$$(*) \doteq \sum_{j \in J} c_j + \sum_{i \in [n] \setminus I} v_i.$$

- ▶ Construct network N such that $(*) = c(S, T)$ where I are the projects in S .
- ▶ Enforce condition $(\forall i \in I) T_i \subseteq J$ by including edges (i, j) with $c(i, j) = \infty$ for each $i \in [n]$ and $j \in T_i$, and let J be the tools in S .


Project Selection – reduction to min cut

- ▶ Need to find $I \subseteq [n]$ and $J \subseteq [m]$ with $(\forall i \in I) T_i \subseteq J$ minimizing

$$(*) \doteq \sum_{j \in J} c_j + \sum_{i \in [n] \setminus I} v_i.$$

- ▶ Construct network N such that $(*) = c(S, T)$ where I are the projects in S .
- ▶ Enforce condition $(\forall i \in I) T_i \subseteq J$ by including edges (i, j) with $c(i, j) = \infty$ for each $i \in [n]$ and $j \in T_i$, and let J be the tools in S .
- ▶ Resulting algorithm runs in time $O((n + m)(n + m + \sum_{i \in [n]} |T_i|))$.

Project Selection – reduction to min cut



$$T_1 = \{1, m\}$$