

CS 577- Intro to Algorithms

Reductions

Dieter van Melkebeek

November 10, 2020

Outline

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design
- ▶ NP-completeness

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design
- ▶ NP-completeness

Today

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design
- ▶ NP-completeness

Today

- ▶ Notion

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design
- ▶ NP-completeness

Today

- ▶ Notion
- ▶ Example where A and B have efficient algorithms

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design
- ▶ NP-completeness

Today

- ▶ Notion
- ▶ Example where A and B have efficient algorithms
- ▶ Examples where A and B have no (known) efficient algorithms

Outline

Paradigm

Solve a computational problem A using a blackbox for another computational problem B .

Motivation

- ▶ Modular design
- ▶ NP-completeness

Today

- ▶ Notion
- ▶ Example where A and B have efficient algorithms
- ▶ Examples where A and B have no (known) efficient algorithms: optimization vs search vs decision

Notion

Notion

Let A and B be two computational problems.

Notion

Let A and B be two computational problems.

Definition

A reduction from A to B is an algorithm for A that can make use of a blackbox for B .

Notion

Let A and B be two computational problems.

Definition

A reduction from A to B is an algorithm for A that can make use of a blackbox for B .

Queries

- ▶ On a given input x of problem A , reduction can make multiple queries x' to the blackbox for B .

Notion

Let A and B be two computational problems.

Definition

A reduction from A to B is an algorithm for A that can make use of a blackbox for B .

Queries

- ▶ On a given input x of problem A , reduction can make multiple queries x' to the blackbox for B .
- ▶ For a valid query x' of problem B , the blackbox returns a valid output y' for problem B on input x' .

Notion

Let A and B be two computational problems.

Definition

A reduction from A to B is an algorithm for A that can make use of a blackbox for B .

Queries

- ▶ On a given input x of problem A , reduction can make multiple queries x' to the blackbox for B .
- ▶ For a valid query x' of problem B , the blackbox returns a valid output y' for problem B on input x' .
- ▶ Often times one query suffices.

Bipartite Matching and Integral Max Flow

Bipartite Matching and Integral Max Flow

A : Bipartite Matching

Bipartite Matching and Integral Max Flow

A : Bipartite Matching

Input: bipartite graph $G = (V, E)$
where $V = L \sqcup R$ and $E \subseteq L \times R$

Bipartite Matching and Integral Max Flow

A : Bipartite Matching

Input: bipartite graph $G = (V, E)$
where $V = L \sqcup R$ and $E \subseteq L \times R$

Output: matching M such that $|M|$ is maximized

Bipartite Matching and Integral Max Flow

A : Bipartite Matching

Input: bipartite graph $G = (V, E)$
where $V = L \sqcup R$ and $E \subseteq L \times R$

Output: matching M such that $|M|$ is maximized

B : Integral Max Flow

Bipartite Matching and Integral Max Flow

A : Bipartite Matching

Input: bipartite graph $G = (V, E)$
where $V = L \sqcup R$ and $E \subseteq L \times R$

Output: matching M such that $|M|$ is maximized

B : Integral Max Flow

Input: network $N = (V', E', c, s, t)$

Bipartite Matching and Integral Max Flow

A : Bipartite Matching

Input: bipartite graph $G = (V, E)$
where $V = L \sqcup R$ and $E \subseteq L \times R$

Output: matching M such that $|M|$ is maximized


B : Integral Max Flow

Input: network $N = (V', E', c, s, t)$

Output: integral flow f such that $\nu(f) \doteq f_{\text{out}}(s)$ is maximized

Reduction from Bipartite Matching to Integral Max Flow

Reduction from Bipartite Matching to Integral Max Flow



Correctness of a Reduction

Correctness of a Reduction

Definition

On every valid input x of A :

Correctness of a Reduction

Definition

On every valid input x of A :

- ▶ Each query x' to the blackbox is valid input of B .

Correctness of a Reduction

Definition

On every valid input x of A :

- ▶ Each query x' to the blackbox is valid input of B .
- ▶ Assuming all queries to the blackbox are answered correctly, the reduction produces a correct output y for A on input x .

Correctness of a Reduction

Definition

On every valid input x of A :

- ▶ Each query x' to the blackbox is valid input of B .
- ▶ Assuming all queries to the blackbox are answered correctly, the reduction produces a correct output y for A on input x .

Corollary

Replacing the blackbox for B by a correct algorithm for B yields a correct algorithm for A .

Reducibility

Reducibility

Definition

$A \leq B$ if there exists a reduction from A to B .

Reducibility

Definition

$A \leq B$ if there exists a reduction from A to B .

Properties

Reducibility

Definition

$A \leq B$ if there exists a reduction from A to B .

Properties

- ▶ Reflexive: $A \leq A$

Reducibility

Definition

$A \leq B$ if there exists a reduction from A to B .

Properties

- ▶ Reflexive: $A \leq A$
- ▶ Not symmetric: Bipartite Matching \leq Halting Problem, but not the other way.

Reducibility

Definition

$A \leq B$ if there exists a reduction from A to B .

Properties

- ▶ Reflexive: $A \leq A$
- ▶ Not symmetric: Bipartite Matching \leq Halting Problem, but not the other way.
- ▶ Transitive: $A \leq B$ and $B \leq C$ implies $A \leq C$.

Reducibility

Definition

$A \leq B$ if there exists a reduction from A to B .

Properties

- ▶ Reflexive: $A \leq A$
- ▶ Not symmetric: Bipartite Matching \leq Halting Problem, but not the other way.
- ▶ Transitive: $A \leq B$ and $B \leq C$ implies $A \leq C$.
- ▶ If $A \leq B$ and B can be solved algorithmically, then A can be solved algorithmically.

Running Time of a Reduction

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Case of one query:

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Case of one query:

Running time of reduction consists of:

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Case of one query:

Running time of reduction consists of:

- ▶ Time to construct out of the input x to A the query x' to B .

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Case of one query:

Running time of reduction consists of:

- ▶ Time to construct out of the input x to A the query x' to B .
- ▶ Time to construct out of the answer y' of B to query x' , the answer y for A on input x .

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Case of one query:

Running time of reduction consists of:

- ▶ Time to construct out of the input x to A the query x' to B .
- ▶ Time to construct out of the answer y' of B to query x' , the answer y for A on input x .
- ▶ **Not** time to compute y' out of x' .

Running Time of a Reduction

Definition

Time to run the reduction assuming blackbox queries are answered instantaneously.

Case of one query:

Running time of reduction consists of:

- ▶ Time to construct out of the input x to A the query x' to B .
- ▶ Time to construct out of the answer y' of B to query x' , the answer y for A on input x .
- ▶ **Not** time to compute y' out of x' .

Corollary

Suppose reduction from A to B runs in time t . Replacing the blackbox for B by an algorithm for B that runs in time $t_B(n)$ yields an algorithm for A that runs in time $t + t \cdot t_B(t)$.

Polynomial Time

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

- ▶ binary strings: length

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

- ▶ binary strings: length
- ▶ numbers: length of the binary representation (finite precision)

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

- ▶ binary strings: length
- ▶ numbers: length of the binary representation (finite precision)
- ▶ graphs: $O(n^2)$ for adjacency matrix, $O(n + m \log n)$ for adjacency list

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

- ▶ binary strings: length
- ▶ numbers: length of the binary representation (finite precision)
- ▶ graphs: $O(n^2)$ for adjacency matrix, $O(n + m \log n)$ for adjacency list
- ▶ ...

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

- ▶ binary strings: length
- ▶ numbers: length of the binary representation (finite precision)
- ▶ graphs: $O(n^2)$ for adjacency matrix, $O(n + m \log n)$ for adjacency list
- ▶ ...

Definition

An algorithm/reduction runs in polynomial time if its running time is $O(n^c)$ for some constant c , where $n \doteq$ bit-length of the input.

Polynomial Time

Bit-length

The bit-length of an input x is the number of bits needed to represent x .

- ▶ binary strings: length
- ▶ numbers: length of the binary representation (finite precision)
- ▶ graphs: $O(n^2)$ for adjacency matrix, $O(n + m \log n)$ for adjacency list
- ▶ ...

Definition

An algorithm/reduction runs in polynomial time if its running time is $O(n^c)$ for some constant c , where $n \doteq$ bit-length of the input.

Robustness

Notion turns out to be the same for most (but perhaps not all) reasonable input representations and models of computation.

Polynomial-Time Reducibility

Polynomial-Time Reducibility

Definition

$A \leq^P B$ if there exists a polynomial-time reduction from A to B .

Polynomial-Time Reducibility

Definition

$A \leq^P B$ if there exists a polynomial-time reduction from A to B .

Properties

Polynomial-Time Reducibility

Definition

$A \leq^P B$ if there exists a polynomial-time reduction from A to B .

Properties

- ▶ Reflexive: $A \leq^P A$

Polynomial-Time Reducibility

Definition

$A \leq^P B$ if there exists a polynomial-time reduction from A to B .

Properties

- ▶ Reflexive: $A \leq^P A$
- ▶ Not symmetric

Polynomial-Time Reducibility

Definition

$A \leq^P B$ if there exists a polynomial-time reduction from A to B .

Properties

- ▶ Reflexive: $A \leq^P A$
- ▶ Not symmetric
- ▶ Transitive: $A \leq^P B$ and $B \leq^P C$ implies $A \leq^P C$.

Polynomial-Time Reducibility

Definition

$A \leq^P B$ if there exists a polynomial-time reduction from A to B .

Properties

- ▶ Reflexive: $A \leq^P A$
- ▶ Not symmetric
- ▶ Transitive: $A \leq^P B$ and $B \leq^P C$ implies $A \leq^P C$.
- ▶ If $A \leq^P B$ and B can be solved in polynomial time, then A can be solved in polynomial time.

Independent Set Problems

Independent Set Problems

Definition

An independent set in a graph $G = (V, E)$ is a subset $S \subseteq V$ such that $E \cap S \times S = \emptyset$.

Independent Set Problems

Definition

An independent set in a graph $G = (V, E)$ is a subset $S \subseteq V$ such that $E \cap S \times S = \emptyset$.

Optimization problem

Input: graph G

Output: independent set S of G such that $|S|$ is maximized

Independent Set Problems

Definition

An independent set in a graph $G = (V, E)$ is a subset $S \subseteq V$ such that $E \cap S \times S = \emptyset$.

Optimization problem

Input: graph G

Output: independent set S of G such that $|S|$ is maximized

Search problem

Input: graph G , $k \in \mathbb{N}$

Output: independent set S of G such that $|S| \geq k$, or report that no such set exists

Independent Set Problems

Definition

An independent set in a graph $G = (V, E)$ is a subset $S \subseteq V$ such that $E \cap S \times S = \emptyset$.

Optimization problem

Input: graph G

Output: independent set S of G such that $|S|$ is maximized

Search problem

Input: graph G , $k \in \mathbb{N}$

Output: independent set S of G such that $|S| \geq k$, or report that no such set exists

Decision problem

Input: graph G , $k \in \mathbb{N}$

Output: whether independent set S with $|S| \geq k$ exists in G

Independent Set – Decision \leq^p Search \leq^p Optimization

Independent Set – Decision \leq^p Search \leq^p Optimization

- ▶ Decision \leq^p Search

Independent Set – Decision \leq^P Search \leq^P Optimization

► Decision \leq^P Search

```
1: if Search( $G, k$ ) = “no solution” then  
2:   return “no”  
3: else  
4:   return “yes”
```

Independent Set – $\text{Decision} \leq^P \text{Search} \leq^P \text{Optimization}$

► $\text{Decision} \leq^P \text{Search}$

```
1: if Search( $G, k$ ) = “no solution” then  
2:   return “no”  
3: else  
4:   return “yes”
```

► $\text{Search} \leq^P \text{Optimization}$

Independent Set – $\text{Decision} \leq^P \text{Search} \leq^P \text{Optimization}$

► $\text{Decision} \leq^P \text{Search}$

```
1: if Search( $G, k$ ) = “no solution” then  
2:   return “no”  
3: else  
4:   return “yes”
```

► $\text{Search} \leq^P \text{Optimization}$

```
1:  $I \leftarrow \text{Optimization}(G)$   
2: if  $|I| \geq k$  then  
3:   return  $I$   
4: else  
5:   return “no solution”
```

Independent Set – Optimization \leq^P Search \leq^P Decision

Independent Set – Optimization \leq^P Search \leq^P Decision

- ▶ Optimization \leq^P Search

Independent Set – Optimization \leq^P Search \leq^P Decision

► Optimization \leq^P Search

```
1:  $k \leftarrow 0$   
2: while Search( $G, k$ )  $\neq$  “no solution” do  
3:    $k \leftarrow k + 1$   
4: return Search( $G, k$ )
```

Independent Set – Optimization \leq^P Search \leq^P Decision

► Optimization \leq^P Search

```
1:  $k \leftarrow 0$   
2: while Search( $G, k$ )  $\neq$  “no solution” do  
3:    $k \leftarrow k + 1$   
4: return Search( $G, k$ )
```

Number of queries can be reduced from $O(|V|)$ to $O(\log |V|)$ using binary search.

Independent Set – Optimization \leq^P Search \leq^P Decision

► Optimization \leq^P Search

```
1:  $k \leftarrow 0$ 
2: while Search( $G, k$ )  $\neq$  “no solution” do
3:    $k \leftarrow k + 1$ 
4: return Search( $G, k$ )
```

Number of queries can be reduced from $O(|V|)$ to $O(\log |V|)$ using binary search.

► Search \leq^P Decision: next lecture