

| PROTOCOL / SERVICE NAME                                 | TCP PORT   | UDP PORT |
|---------------------------------------------------------|------------|----------|
| Arbitrary Protocol Node                                 | 2002       | —        |
| <b>FTP</b> (File Transfer Protocol)                     | 21         | —        |
| <b>SSH</b> (Secure Shell)                               | 22         | —        |
| <b>Telnet</b> Terminal Connection                       | 23         | —        |
| <b>SMTP</b> (Simple Mail Transfer Protocol)             | 25         | —        |
| <b>DNS</b> (Domain Name System)                         | 53         | 53       |
| <b>HTTP</b> (Hypertext Transfer Protocol)               | 80         | —        |
| <b>Kerberos-sec</b> Authentication Layer                | 88         | —        |
| <b>POP3</b> (Post Office Protocol v3)                   | 110        | —        |
| <b>RPC</b> (Remote Procedure Call)                      | 135        | —        |
| <b>SMB</b> (NetBIOS Session Protocol)                   | 139        | —        |
| <b>LDAP</b> (Lightweight Directory Access Protocol)     | 389        | —        |
| <b>HTTPS</b> (Hypertext Transfer Protocol Secure)       | 443        | —        |
| <b>SMB</b> (Server Message Block Core)                  | 445        | —        |
| <b>Modbus</b> (Industrial Communication Interface)      | 502        | —        |
| <b>LDAPS</b> (LDAP over SSL/TLS)                        | 636        | —        |
| <b>POP3 Encrypted</b> (Secure Mailbox Access)           | 995        | —        |
| <b>MSSQL</b> (Microsoft SQL Server Database Engine)     | 1433       | —        |
| <b>SNMP</b> (Simple Network Management Protocol)        | —          | 161, 162 |
| <b>MQTT</b> (IoT & OT Messaging Broker)                 | 1833       | —        |
| <b>NFS</b> (Network File System)                        | 2049       | —        |
| <b>Microsoft ADGC</b> (Active Directory Global Catalog) | 3268, 3269 | —        |
| <b>MySQL</b> Database Engine Listener                   | 3306       | —        |
| <b>RDP</b> (Remote Desktop Protocol)                    | 3389       | —        |
| <b>njRAT</b> Default Backdoor Listener                  | 5553       | —        |

| PROTOCOL / SERVICE NAME                        | TCP PORT   | UDP PORT |
|------------------------------------------------|------------|----------|
| <b>ADB</b> (Android Debug Bridge Network Link) | 5555       | —        |
| Default Port of Portable Python HTTP Server    | 8000       | —        |
| Proxy / WAMP Default Web Server Instance       | 8080       | —        |
| <b>RAT Ports</b> (Remote Access Trojans)       | 9871, 6703 | —        |

## 2. REMOTE LOGIN & CONNECTION COMMANDS

Utilize these standardized interactive terminal execution lines to directly connect with target services over active interfaces:

### FTP (File Transfer Protocol)

```
ftp <ip>
```

### SSH (Secure Shell Terminal)

```
ssh user@<ip>
```

### Telnet Connection (Custom Port)

```
telnet <ip> <port>
```

### SMB Client (Share Enumeration & Mounting)

```
smbclient //<ip>/<share>
```

### RDP Client (XFreerdp Terminal Link)

```
xfreerdp /v:<ip>
```

### MySQL Interactive Console Login

```
mysql -h <ip> -u user -p
```

### ADB (Android Debug Bridge Connection)

```
adb connect <ip>:5555
```