



API DOCUMENTATION



Table of Contents

A - DOMAINS	4
1. Check Availability of Specified Domain	4
2. Bulk Domain Check for Multiple domains	4
3. Check Domain Suggestions List	5
4. Check TLD Suggestions List	6
5. Check Domain Price for Multiple Years	6
6. Get all TLD Prices	8
7. Register	9
7.1. Special TLD's requirements for domain registration:	9
7.2. IDN Supported Languages:	10
8. Transfer	17
9. Cancel Transfer	18
10. Validate a Transfer	18
11. Renew	19
12. Getting Details of the Domain using ID	19
13. Getting Details of the Domain using Domain Name	21
14. Search	22
15. Modify Nameserver of Domain	22
16. Modify Authcode of Domain	23
17. Manage Lock on Domain	24
18. Manage Privacy on Domain	25
19. Manage Domain Suspend	25
20. Manage Theft Protection on Domain	26
21. View Domain Secret Key	26
22. Manage DNS Management	27
23. Add DNS Record	27
24. Modify DNS Record	28
25. Delete DNS Record	29
26. View DNS Record	29
27. Modifying Domain Contact	30
28. To move domain from one client to another	31
29. Add SRV Record	31
30. Modify DNS Record for Domain	32
B - CONTACT	33
1. Add Contact	33
2. Modify Contact	34
3. View Contact	35
4. To get Registrant list of specific client	36
5. To Send RAA Verification mail	37
6. Send KYC Email to registrant.	38
C - CLIENT	39
1. Add Client	39
2. Modify Client	40
3. View Client	41
4. Change the Client Password	41
5. To Delete The Client	42
6. To Get A Client List	43
D - HOST	43
1. To Add Child Name Server	43
2. Modify Name Server IP	44
3. To Modify Host Child Name Server	45
4. To Delete Child Name Server	45
5. To Get Child Name Servers of a Domain	46
E - DOMAIN FORWARDING	47
1. To Set Domain Forwarding Details	47
2. To Get Domain Forwarding Details	47



3.	To Update Domain Forwarding Details	48
4.	To Delete Domain Forwarding Details.....	49
F – MISCELLANEOUS		50
1.	Check Reseller Available funds.	50



A - DOMAINS

1. Check Availability of Specified Domain

Checks availability of the specified domain name and basis on domain type show their pricing.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/checkdomainavailable?APIKey=<Your_API_Key>&websiteName=example.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
websiteName	Domain Name that you need to check the availability	Required	String

Response:

responseMsg:

statusCode: If 200 then show domain pricing and 400 not available

message: Indicates the message

responseData:

domainType: Indicates domain type

available: check domain is available or not

registration fees: Indicates registration fee

renewalfees: Indicates renewal fee

transferFees: Indicates transfer fee

2. Bulk Domain Check for Multiple domains

Checks availability of the Multiple domain name and basis on domain type show their pricing.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/bulkDomainCheck?APIKey=<Your_API_Key>&websiteNames=example1.com,example2.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
websiteNames	Multiple Domain Names comma separated. (Max. 200 domains per request)	Required	String

**Response:**

responseMsg:

statusCode: If 200 then show domain pricing and 400 not available

message: Indicates the message

responseData:

websiteName: Domain Name

domainType: Indicates domain type

available: check domain is available or not

registration fees: Indicates registration fee

3. Check Domain Suggestions List

Checks suggested domains of the specified keyword.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/domainSuggestion?APIKey=<Your_API_Key>&keyword=example.com&maxResult=5

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
Keyword	Domain Name keyword that you need to check the suggestions for	Required	String
maxResult	No. Of suggestions to be displayed (Max. Value = 50)	Required	Int

Response:

responseMsg: {

```
"registryDomainSuggestionList": [  
  {  
    "domainName": "example.biz",  
    "price": 5.69  
  },  
  {  
    "domainName": "example.co",  
    "price": 12.29  
  },  
  {  
    "domainName": "Helloexample.com",  
    "price": 10.99  
  },  
  {  
    "domainName": "Getexample.com",  
    "price": 10.99  
  },  
]
```



```
{
  "domainName": "Teamexample.com",
  "price": 10.99
}
```

4. Check TLD Suggestions List

To get any keyword or domain suggestion with multiple TLD's.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/getTldSuggestion?APIKey=<Your_API_Key>&websiteName=example.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
WebsiteName	Domain Name or keyword that you need to get suggestions for	Required	String

Response:

Users will get a response of 25 TLD's using this API. The response will be as follows:

```
{
  "responseMsg": {
    "message": "Success",
    "id": 0,
    "reason": null,
    "statusCode": 200
  },
  "responseData": [
    {
      "websiteName": "example.com",
      "domainType": "Standard",
      "available": true
    },
    {
      "websiteName": "example.org",
      "domainType": "-",
      "available": false
    }
  ]
}
```

5. Check Domain Price for Multiple Years

To check any domain price for multiple years.



Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/checkDomainPrice?APIKey=<Your_API_Key>&websiteName=example.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
WebsiteName	Domain Name that you need to register	Required	String

Response:

```
"responseMsg": {
  "message": "Domain Available for Registration",
  "id": 0,
  "statusCode": 200
},
"responseData": {
  "1": [
    {
      "description": "Registration Price for 1 Year is *****"
    },
    {
      "description": "Registration Price for 2 Year is *****"
    },
    {
      "description": "Registration Price for 3 Year is *****"
    },
    {
      "description": "Registration Price for 4 Year is *****"
    },
    {
      "description": "Registration Price for 5 Year is *****"
    },
    {
      "description": "Registration Price for 6 Year is *****"
    },
    {
      "description": "Registration Price for 7 Year is *****"
    },
    {
      "description": "Registration Price for 8 Year is *****"
    },
    {
      "description": "Registration Price for 9 Year is *****"
    }
  ]
}
```



```
    },  
    {  
      "description": "Registration Price for 10 Year is *****"  
    }  
  ]  
}  
}
```

6. Get all TLD Prices.

To get all TLD prices.

Method: GET

URL: https://api.connectreseller.com/ConnectReseller/ESHOP/tldsync/?APIKey=<Your_API_Key>

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String

Response:

```
"responseMsg":  
{  
  "tld": "TLD Name",  
  "minPeriod": Minimum Year,  
  "maxPeriod": Maximum Year,  
  "registrationPrice": Registration Price,  
  "renewalPrice": Renewal Price,  
  "transferPrice": Transfer Price,  
  "currencyCode": "Currency"  
}
```




7. Register

Registers the domain name.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/domainorder?APIKey=<YOUR_API_KEY>&ProductType=1&WebsiteName=domainexample.com&Duration=1&IsWhoisProtection=true&ns1=nameserver1&ns2=nameserver2&ns3=nameserver3&ns4=nameserver4&Id=00&isEnablePremium=0&lang=xxx

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
ProductType	Value:1 by default	Required	Integer
WebsiteName	Domain Name that you need to register	Required	String
Duration	Number of years for which you wish to register this domain name	Required	Integer
IsWhoisProtection	Adds the privacy protection service for the domain name	Required	Boolean
ns1	The Name Servers 1 of the domain name	Required	String
ns2	The Name Servers 2 of the domain name	Required	String
ns3	The Name Servers 3 of the domain name	Optional	String
ns4	The Name Servers 4 of the domain name	Optional	String
Id	The customer ID for whom you wish to register the domain name	Required	Integer
isEnablePremium	Value: 1 indicates registration of premium domain	Required	Integer
lang	Language code of IDN domains to mentioned as per section 6.2	Optional	String

Response:

responseMsg:

statusCode: If 200 then domain is register and other than 200 if domain is not register

message: Indicates the message and reason if domain is not register.

responseData: Null if domain is not register

creationDate: Indicates creation date of registered domain

expiryDate: Indicates expiry date of registered domain

msg: Indicates registry command message

msgCode: Indicates registry command code.

name: Domain name registered.

7.1. Special TLD's requirements for domain registration:

To Register Below TLD Extra Parameters are required which are as follows:



TLD Name	Required Parameter	Description	Required	Type
.us	isUs	Value should be 1 to successfully register .us domains.	Required	Boolean
	appPurpose	User needs to mention any one of the below purpose code: P1 - Business for profit P2 - Non-Profit P3 - Personal P4 - Educational P5 - Governmental	Required	String
	nexusCategory	User needs to mention any one of the below category code: C11 - US Citizen C12 - Permanent Resident C21 - US Organization C31/CC - Foreign Organization doing business in the US C32/CC - Foreign Organization with US office	Required	String

7.2. IDN Supported Languages:

TLD Name	Supported Language	Language Code
.com	Afrikaans	AFR
	Albanian	ALB
	Arabic	ARA
	Aragonese	ARG
	Armenian	ARM
	Assamese	ASM
	Asturian	AST
	Avestan	AVE
	Awadhi	AWA
	Azerbaijani	AZE
	Balinese	BAN
	Baluchi	BAL
	Basa	BAS
	Bashkir	BAK
	Basque	BAQ
	Belarusian	BEL
	Bengali	BEN
	Bhojpuri	BHO
	Bosnian	BOS
	Bulgarian	BUL
	Burmese	BUR
	Carib	CAR
	Catalan	CAT
	Chechen	CHE
	Chinese	CHI
	Chuvash	CHV
	Coptic	COP



	Corsican	COS
	Croatian	SCR
	Czech	CZE
	Danish	DAN
	Divehi	DIV
	Dogri	DOI
	Dutch	DUT
	English	ENG
	Estonian	EST
	Faroese	FAO
	Fijian	FIJ
	Finnish	FIN
	French	FRE
	Frisian	FRY
	Gaelic	GLA
	Georgian	GEO
	German	GER
	Gondi	GON
	Greek	GRE
	Gujarati	GUJ
	Hebrew	HEB
	Hindi	HIN
	Hungarian	HUN
	Icelandic	ICE
	Indic	INC
	Indonesian	IND
	Ingush	INH
	Irish	GLE
	Italian	ITA
	Japanese	JPN
	Javanese	JAV
	Kashmiri	KAS
	Kazakh	KAZ
	Khmer	KHM
	Kirghiz	KIR
	Korean	KOR
	Kurdish	KUR
	Latvian	LAV
	Lithuanian	LIT
	Luxembourgish	LTZ
	Macedonian	MAC
	Malay	MAY
	Malayalam	MAL
	Maltese	MLT
	Maori	MAO
	Moldavian	MOL
	Mongolian	MON



	Nepali	NEP
	Norwegian	NOR
	Oriya	ORI
	Ossetian	OSS
	Panjabi	PAN
	Persian	PER
	Polish	POL
	Portuguese	POR
	Pushto	PUS
	Rajasthani	RAJ
	Romanian	RUM
	Russian	RUS
	Samoan	SMO
	Sanskrit	SAN
	Sardinian	SRD
	Serbian	SCC
	Sindhi	SND
	Sinhalese	SIN
	Slovak	SLO
	Slovenian	SLV
	Somali	SOM
	Spanish	SPA
	Swahili	SWA
	Swedish	SWE
	Syriac	SYR
	Tajik	TGK
	Tamil	TAM
	Telugu	TEL
	Thai	THA
	Tibetan	TIB
	Turkish	TUR
	Ukrainian	UKR
	Urdu	URD
	Uzbek	UZB
	Vietnamese	VIE
	Welsh	WEL
	Yiddish	YID

Languages	Language Code	TLD supported by languages			
Arabic	ar	.ae.org	.press	.fm	.store
		.art	.protection	.fun	.tech
		.baby	.pw	.host	.theatre
		.cam	.radio.am	.in.net	.us.com
		.ceo	.radio.fm	.tickets	.us.org
		.college	.rent	.monster	.website
		.com.fm	.sa.com	.net.fm	.forum



		.tickets	.security	.online	.org.fm
		.edu.fm	.site	.org.fm	.space
		.eu.com	.best	.storage	
Belarusian	be	.eu.com	.ooo		
Bulgarian	bg	.cam	.ooo		
Bosnian	bs	.cam			
Catalan	ca	.cam			
Czech	cs	.cam	.icu		
Danish	da	.art	.cam	.ceo	.eu.com
		.qpon	.tickets	.icu	.best
German	de	.audio	.auto	.best	.cam
		car	.cars	.ceo	christmas
		dealer	diet	eu.com	flowers
		.game	.guitars	.help	.hosting
		.ICU	.inc	.lol	.london
		.mom	.pics	.qpon	.saarland
		.tickets			
Spanish	es	audio	.auto	.baby	.best
		.cam	.car	.cars	.ceo
		.christmas	dealer	diet	.lat
		.eu.com	.flowers	.game	.guitars
		.help	.hosting	.icu	.inc
		.lol	.london	.mom	.ooo
		.pics	.qpon	.tickets	.uno
Estonian	et	.cam			
Finnish	fi	.best	.cam	.ceo	.qpon
Faroese	fo	.eu.com			
French	fr	.cam	.ceo	.eu.com	.icu
		.london	.ooo	.cars	.christmas
		.audio	.auto	.best	.car
		.dealer	.diet	.flowers	.game
		.hosting	.inc	.lol	.london
		.qpon	.tickets	.guitars	.help
		.mom	.pics		
Hebrew	he	.art	.baby	.cam	.college
		.eu.com	.fm	.fun	.host
		.icu	.in.net	.monster	.online
		.ooo	.press	.protection	.radio.am
		.pw	.radio.fm	.rent	.security
		.site	.space	.storage	.store
		.tech	.theatre	.tickets	.uno



		.us.com	.us.org	.website	.xyz
Hindi	hi	.ceo	.best		
Croatian	hr	.cam	.eu.com	.ooo	
Hungarian	hu	.cam	.ceo	.qpon	.best
Icelandic	is	.best	.cam	.ceo	.icu
		.qpon			
Italian	it	.audio	.auto	.best	.cam
		.car	.cars	.dealer	.diet
		.ceo	.christmas	.flowers	.game
		.guitars	.help	.hosting	.icu
		.inc	.lol	.london	.mom
		.pics	.qpon		
Japanese	ja	.art	.ceo	.college	.in.net
		.fm	.fun	.host	.jp.net
		.jpn.com	.online	.ooo	.press
		.protection	.pw	.radio.am	.radio.fm
		.rent	.security	.storage	.store
		.site	.space	.tech	.theatre
		.us.com	.us.org	.website	.xyz
		.baby	.cam	.icu	.monster
		.auto	.car	.cars	.dealer
		.hair	.makeup	.quest	.skin
		.tickets	.uno	.inc	.mom
		.diet	.flowers	.pics	.diet
		.audio	.beauty	.best	.christmas
		.game	.guitars	.hosting	.lol
		.flowers			
Korean	ko	.art	.baby	.cam	.ceo
		.edu.fm	.fm	.fun	.hair
		.in.net	.uno	.makeup	.monster
		.ooo	.org.fm	.press	.protection
		.college	.com.fm	.rent	.security
		.host	.icu	.store	.tech
		.net.fm	.online	.xyz	.site
		.pw	.qpon	.website	.theatre
		.quest	.radio.am	.radio.fm	.beauty
		.skin	.space	.storage	.best
		.tickets	.uno		
Luxembourgish	lb	.cam	.icu		



Lao	lo	.art	.baby	.college	.fm
		.fun	.host	.icu	.website
		.in.net	.monster	.online	.ooo
		.press	.protection	.pw	.xyz
		.radio.am	.radio.fm	.rent	.security
		.storage	.store	.tech	.theatre
		.site	.space	.tickets	.uno
Lithuanian	lt	.cam	.ceo	.qpon	.best
Latvian	lv	.cam	.ceo	.qpon	.best
Macedonian	mk	.eu.com	.ooo	.cam	
Dutch Flemish	nl	.cam	.ceo	.eu.com	.qpon
		.best			
Norwegian	no	.cam	.ceo	.qpon	.best
Polish	pl	.art	.cam	.ceo	.eu.com
		.ooo	.qpon	.tickets	.best
Portuguese	pt	.cam	.ceo	.eu.com	.icu
		.audio	.auto	.best	.car
		.dealer	.diet	.flowers	.game
		.hosting	.inc	.lol	.mom
		.cars	.christmas	.pics	.qpon
		.guitars	.help		
Romanian	ro	.cam	.icu		
Russian	ru	.art	.audio	.auto	.baby
		.cam	.car	.cars	.ceo
		.beauty	.best	.game	.guitars
		.christmas	.college	.icu	.ru.com
		.diet	.eu.com	.flowers	.security
		.hair	.help	.hosting	.skin
		.lol	.quest	.rent	.tickets
		.makeup	.mom	.monster	.xyz
		.ooo	.pics	.storage	.theatre
		.protection	.qpon		
Slovak	sk	.cam			
Slovene	sl	.cam			
Albanian	sq	.cam			



Serbian	sr	.cam	.eu.com	.ooo	
Swedish	sv	.art	.cam	.ceo	.eu.com
		.ooo	.qpon	.tickets	.best
Thai	th	.art	.college	.fm	.host
		.in.net	.online	.ooo	.press
		.protection	.pw	.radio.am	.radio.fm
		.rent	.security	.site	.space
		.storage	.store	.tech	.theatre
		.website	.xyz	.fun	.tickets
		.baby	.cam	.monster	.uno
Turkish	tr	.cam	.icu		
Ukrainian	uk	.cam	.eu.com	.icu	.ooo
Chinese	zh	.art	.auto	.baby	.dealer
		.car	.cn.com	.college	.inc
		.cars	.ceo	.icu	.in.net
		.fm	.fun	.hair	.host
		.makeup	.monster	.quest	.rent
		.uno	.online	.ooo	.tickets
		.press	.protection	.radio.am	.radio.fm
		.pw	.qpon	.storage	.store
		.security	.site	.skin	.space
		.tech	.theatre	.us.com	.us.org
		.website	.xyz	.diet	.flowers
		.audio	.beauty	.best	.christmas
		.game	.guitars	.help	.hosting
		.pics	.lol	.mom	

Languages	Language Code	TLDs Supported		
Arabic	ar	.biz	.one	شبكة
Belarusian	be	.design	.gay	.tube
Bosnian	bs	.ink	.bank	.com.co
Bulgarian	bg	.bid	.insurance	.net.co
Chinese	zh	.date	.tattoo	.nom.co
Danish	da	.download	.adult	.vip
Finnish	fi	.loan	.boston	.vodka
French	fr	.men	.compare	.wedding
German	de	.party	.lux	.work
Hebrew	he	.stream	.porn	.yoga
Hindi	hi	.trade	.select	
Hungarian	hu	.win	.sex	



Icelandic	is	.faith	.sucks
Italian	it	.racing	.bible
Japanese	ja	.review	.earth
Korean	ko	.science	.osaka
Latvian	lv	.webcam	.moe
Lithuanian	lt	.accountant	.courses
Macedonian	mk	.cricket	.health
Norwegian	no	.buzz	.study
Polish	pl	.club	.xxx
Portuguese	pt	.abogado	.vu
Russian	ru	.beer	.garden
Serbian	sr	.casa	.horse
Spanish	es	.cooking	.law
Swedish	sv	.fashion	.miami
Thai	th	.fishing	.rodeo
Ukrainian	uk	.fit	.surf

8. Transfer

Transfer-in the domain name with us.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/TransferOrder?APIKey=<Your_API_Key>&OrderType=4&WebsiteName=domainexample.com&IsWhoisProtection=true&AuthCode=authcode&Id=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
OrderType	Value:4 by default	Required	Integer
WebsiteName	Domain Name that you need to register	Required	String
IsWhoisProtection	Adds the privacy protection service for the domain name	Required	Boolean
Authcode	EPP Domain Secret	Required	String
Id	The customer ID for whom you wish to register the domain name	Required	Integer

Response:

responseMsg:

statusCode: If 200 then domain is transfer and other than 200 if domain is not transfer

message: Indicates the message and also reason if domain is not transfer

responseData: Null if domain is not transfer



responseMsg:

statusCode: 200 if domain transfer process is completed and it waiting for approval for losing registrar and other than 200 if domain transfer is stall (locked or authcode invalid).

message: Indicates the message and reason for stall.

9. Cancel Transfer

Cancel the domain Transfer-In with us till the order is in stall status.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/CancelTransfer?APIKey=<Your_API_Key>&id=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
Id	The domain ID of the domain that you want to cancel the transfer	Required	Integer

Response:

responseMsg:

statusCode: 200 if transfer cancel is successful and other then 200 if transfer cancel failed.

message: Indicates the message and also reason if domain is not cancel.

responseData: Null

10. Validate a Transfer

Transfer a domain name with us.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/syncTransfer?APIKey=<Your_API_Key>&domainName=domainexample.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainName	Domain that you want to validate the transfer	Required	Integer

Response:

responseMsg:

statusCode: 200 if transfer for the domain was placed and 404 if transfer of domain was not placed.

message: Indicates the message.



responseData:

Status: Indicates Transfer Order status.

Reason: Reason if order is cancelled or stall

expiryDate: New expiry date of domain if order is completed.

11. Renew

Renew a domain name with us.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/RenewalOrder?APIKey=<Your_API_Key>&OrderType=2&Websitename=domainexample.com&IsWhoisProtection=true&Duration=00&Id=00&Expiryyear=2025

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
OrderType	Represents the Order Type (2 for renewal)	Required	Integer
Duration	No. of Years	Required	Integer
Websitename	Domain name you want to renew	Required	String
Id	Represents Customer ID	Required	Integer
IsWhoisProtection	Adds the privacy protection service for the domain name	Optional	Boolean
Expiryyear	Current expiry year of domain name.	Optional	String

Response:

responseMsg:

statusCode: 200 if domain is renewed and 404/400 if domain was not renew

message: Indicates the message.

responseData:

statusCode: Registry Status code.

Message: Message and reason.

expiryDate: New Expiry Date

domainName: Domain Name of renewed domain.

12. Getting Details of the Domain using ID

Getting Registered Domain details with us by ID

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ViewDomainById?APIKey=<Your_API_Key>&id=00



Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
Id	ID of the Domain whose details need to be fetched	Required	Integer

Response:

responseMsg:

statusCode: 200 if domain is available in our records and 404 if not found

message: Indicates the message.

responseData:

domainNameId: domainNameId

websiteName: domain name

orderDate: Order date and time of domain in timestamp

creationDate: Registry Creation Date and time of domain in timestamp

lastUpdatedDate: Domain Modification Date and time of domain in timestamp

expirationDate: Registry Expiry Date and time of domain in timestamp

nameserver1: Nameservers 1

nameserver2: Nameservers 2

nameserver3: Nameservers 3

nameserver4: Nameservers 4

nameserver5: Nameservers 5

nameserver6: Nameservers 6

nameserver7: Nameservers 7

nameserver8: Nameservers 8

nameserver9: Nameservers 9

nameserver10: Nameservers 10

nameserver11: Nameservers 11

nameserver12: Nameservers 12

nameserver13: Nameservers 13

Status: Status under the System (currentstatus) - value will be Inactive, Active, Suspended, Pending Delete Restorable, Deleted.

Authcode: Domain Secret key

isDomainLocked: Domain Lock Status

isThiefProtected: Thief Protection Status

isPrivacyProtection: Privacy Protection Status

isParked: domain Parked Status

customerId: Customer Id to which domain belongs.

registrantContactId: Registrant Contact

adminContactId: Admin Contact

technicalContactId: Technical Contact

billingContactId: Billing Contact

isRegistrantVerification: RAA Verification Status

registrantVerificationDate: RAA verification Date

websiteId: website Id for reference

dnszoneStatus: DNS is active or not

dnszoneId: DNS id



13. Getting Details of the Domain using Domain Name

Getting Registered Domain details with us by Domain Name.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ViewDomain?APIKey=<Your_API_Key>&websiteName=example.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
websiteName	Name of the domain whose details need to be fetched	Required	String

Response:

responseMsg:

statusCode: 200 if domain is available in our records and 404 if not found.

message: Indicates the message.

responseData:

domainNameId: domainNameId

websiteName: domain name

orderDate: Order date and time of domain in timestamp

creationDate: Registry Creation Date and time of domain in timestamp

lastUpdatedDate: Domain Modification Date and time of domain in timestamp

expirationDate: Registry Expiry Date and time of domain in timestamp

nameserver1: Nameservers 1

nameserver2: Nameservers 2

nameserver3: Nameservers 3

nameserver4: Nameservers 4

nameserver5: Nameservers 5

nameserver6: Nameservers 6

nameserver7: Nameservers 7

nameserver8: Nameservers 8

nameserver9: Nameservers 9

nameserver10: Nameservers 10

nameserver11: Nameservers 11

nameserver12: Nameservers 12

nameserver13: Nameservers 13

Status: Status under the System (currentstatus) - value will be Inactive, Active, Suspended, Pending Delete Restorable, Deleted.

Authcode: Domain Secret key

isDomainLocked: Domain Lock Status

isThiefProtected: Thief Protection Status

isPrivacyProtection: Privacy Protection Status

isParked: domain Parked Status



customerId: Customer Id to which domain belongs.
registrantContactId: Registrant Contact
adminContactId: Admin Contact
technicalContactId: Technical Contact
billingContactId: Billing Contact
isRegistrantVerification: RAA Verification Status
registrantVerificationDate: RAA verification Date
websiteId: website Id for reference
dnszoneStatus: DNS is active or not
dnszoneId: DNS id

14. Search

Getting Registered Domain details with us by Domain Name.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/SearchDomainList?APIKey=<Your_API_Key>&page=1&maxIndex=10&searchQuery=test&orderby=WebsiteName&orderType=asc&

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
Page	Page for which details needs to be fetched	Required	Integer
maxIndex	Max no. of records needs to be fetched	Required	Integer
orderby	WebsiteName/ExpirationDate/CustomerId/CreationDate	Optional	String
orderType	ASC/DESC	Optional	String
clientId	Represents Customer ID	Optional	Integer
searchQuery	Filter	Optional	String

Response:

totalCount: Total No of domain Count

record:

Array of domain with following details:

entryId: Domain Id

domainName: example.com

expirationDate: registry expiry date

creationDate: registry creation date

actionStatus: Domain status in system

resellerId: Reseller Id under which domain is registered.

customerId: Customer Id under which domain is registered.

15. Modify Nameserver of Domain

To update Domain Name Server in Registry



Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/UpdateNameServer?APIKey=<Your_API_Key>&domainNameId=1&websiteName=domainexample.com&nameServer1=nameServer1&nameServer2=nameServer2&nameServer3=nameServer3&nameServer4=nameserver4

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
websiteName	Domain Name	Required	String
nameServer1	New Name Servers 1 of the domain name	Optional	String
nameServer2	New Name Servers 2 of the domain name	Optional	String
nameServer3	New Name Servers 3 of the domain name	Optional	String
nameServer4	New Name Servers 4 of the domain name	Optional	String
nameServer5	New Name Servers 5 of the domain name	Optional	String
nameServer6	New Name Servers 6 of the domain name	Optional	String
nameServer7	New Name Servers 7 of the domain name	Optional	String
nameServer8	New Name Servers 8 of the domain name	Optional	String
nameServer9	New Name Servers 9 of the domain name	Optional	String
nameServer10	New Name Servers 10 of the domain name	Optional	String
nameServer11	New Name Servers 11 of the domain name	Optional	String
nameServer12	New Name Servers 12 of the domain name	Optional	String
nameServer13	New Name Servers 13 of the domain name	Optional	String

Response:

responseMsg:

statusCode: If 200 nameserver is modified and other then 200 if nameserver modification failed.

message: Indicates the message and reason if domain is not register.

responseData:

msg: Message from registry

msgCode: Message code from registry

16. Modify Authcode of Domain

To Modify Authcode of registered domain.

Method: GET

URL:



https://api.connectreseller.com/ConnectReseller/ESHOP/updateAuthCode?APIKey=<Your_API_Key>&domainNameId=1&websiteName=domainexample.com&authCode=auth

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
websiteName	Domain Name	Required	String
authCode	New Authcode which you want to assign for domain	Required	String

Response:

responseMsg:

statusCode: If 200 Authcode is modified and other then 200 if Authcode modification failed.

message: Indicates the message and reason if domain is not register.

responseData:

msg: Message from registry

msgCode: Message code from registry

17. Manage Lock on Domain

To allow reseller to manage domain lock status.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDomainLock?APIKey=<Your_API_Key>&domainNameId=1&websiteName=domainexample.com&isDomainLocked=true

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
websiteName	Domain Name	Required	String
isDomainLocked	Lock status for domain	Required	Boolean

Response:

responseMsg:

statusCode: 200 if manage lock action is successful and other than 200 if manage lock action failed.

message: Indicates the message

responseData:



statusCode: 200 if manage lock action is successful and other than 200 if manage lock action failed.

message: Indicates the message

18. Manage Privacy on Domain

To allow Reseller to manage domain privacy protection

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDomainPrivacyProtection?APIKey=<Your_API_Key>&domainNameId=1&iswhoisprotected=true

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
isWhoIsProtected	Privacy status for domain	Required	Boolean

Response:

responseMsg:

statusCode: 200 if manage privacy action is successful and other than 200 if manage privacy action failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if manage privacy action is successful and other than 200 if manage privacy action failed.

message: Indicates the message

19. Manage Domain Suspend

To allow Resellers to manage domain suspend action

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDomainSuspend?APIKey=<Your_API_Key>&domainNameId=1&websiteName=domainexample.com&isDomainSuspend=true

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String



domainNameId	Domain Name ID	Required	Integer
websiteName	Domain Name	Required	String
isDomainSuspend	Privacy status for domain	Required	Boolean

Response:

responseMsg:

statusCode: 200 if domain suspend action is successful and 400 if domain suspend action failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if nameserver suspend action successful and 400 if nameserver suspend action failed.

message: Indicates the message

20. Manage Theft Protection on Domain

To allow Reseller to manage domain theft protection.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ManageTheftProtection?APIKey=<Your_API_Key>&domainNameId=1&websiteName=domainexample.com&isTheftProtection=true

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
websiteName	Domain Name	Required	String
isTheftProtection	Privacy status for domain	Required	Boolean

Response:

responseMsg:

statusCode: 200 if theft protection action on domain is successful and 400 if theft protection action on domain is failed.

Message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if theft protection action on domain is successful and 400 if theft protection action on domain is failed.

Message: Indicates the message and reason if domain is not register

21. View Domain Secret Key

View Domain EPP secret key

Method: GET

**URL:**

https://api.connectreseller.com/ConnectReseller/ESHOP/ViewEPPCode?APIKey=<Your_API_Key>&domainNameId=id

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID of the Domain whose EPP code to be fetched	Required	Integer

Response:

DomainSecretKey

22. Manage DNS Management

To Active DNS for Domain

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDNSRecords?APIKey=<Your_API_Key>&WebsiteId=id

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
websiteId	Refer website ID which we get in view domain response	Required	Integer

Response:

responseMsg:

statusCode: 200 if DNS management action on domain is successful and 400 if DNS management action on domain is failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if DNS management on domain is successful and 400 if the DNS management on domain is failed.

message: Indicates the message and reason if domain is not registered

23. Add DNS Record

To add DNS record for domain



Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/AddDNSRecord?APIKey=<Your_API_Key>&DNSZoneID=00&RecordName=host.example.com&RecordType=A&RecordValue=recordvalue&RecordPriority=0&RecordTTL=43200

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
DNSZoneID	DNS zone ID which we get in view domain response	Required	Integer
recordName	Name for DNS entry	Required	String
recordType	Type for DNS entry	Required	String
recordValue	Value for DNS entry	Optional	String
recordTTL	Time to live	Optional	Integer
recorePriority	Set Priority	Optional	Integer

Response:

responseMsg:

statusCode: 200 if DNS record is added successfully domain is successful and 400 if DNS record is add on domain is failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if DNS record is added successfully domain is successful and 400 if DNS record is add on domain is failed.

message: Indicates the message

24. Modify DNS Record

To Modify DNS record for Domain

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyDNSRecord?APIKey=<Your_API_Key>&DNSZoneID=00&DNSZoneRecordID=00&RecordName=host.example.com&RecordType=A&RecordValue=recordvalue&RecordTTL=43200

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
------------	-------------	-------------------	------



APIKey	Authentication Parameters	Required	String
DNSZoneID	DNS zone ID which we get in view domain response	Required	Integer
DNSZoneRecord	DNS zone record ID for which we want to modify the domain	Required	Integer
recordName	Name for DNS entry	Required	String
recordType	Type for DNS entry	Required	String
recordValue	Value for DNS entry	Optional	String
recordTTL	Time to live	Optional	Integer

Response:

responseMsg:

statusCode: 200 if DNS record is modified successfully and 400 if DNS record modification is failed.

message: Indicates the message

responseData:

statusCode: 200 if DNS record is added successfully and 400 if DNS record modification is failed.

message: Indicates the message

25. Delete DNS Record

To delete DNS record for Domain.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/DeleteDNSRecord?APIKey=<Your_API_Key>&DNSZoneID=00&DNSZoneRecordID=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
DNSZoneID	DNS zone ID which we get in view domain response	Required	Integer
DNSZoneRecordID	DNSzone record ID for hich we want to modify the domain	Required	Integer

Response:

responseMsg:

statusCode: 200 if DNS record is deleted successfully and 400 if DNS record deletion is failed.

message: Indicates the message

responseData:

statusCode: 200 if DNS record is deleted successfully and 400 if DNS record deletion is failed.

26. View DNS Record

To view all DNS records.



Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ViewDNSRecord?APIKey=<Your_API_Key>&WebsiteId=id

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
websiteID	Refer website ID which we get in view domain response	Required	Integer

Response:

responseMsg:

statusCode: 200 if DNS record list is fetched successfully and 400 if DNS record list fetching is failed.

message: Indicates the message

responseData:

statusCode: 200 if DNS management on domain is failed and 400 if theft DNS management on domain is failed.

message: Indicates the message and reason if domain is not registered.

27. Modifying Domain Contact

Modifies contacts of the specified register domain

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/updatecontact?APIKey=<Your_API_Key>&domainNameId=1&websiteName=domainexample.com&adminContactId=1234&billingContactId=4567®istrantContactId=7891&technicalContactId=1235

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
websiteName	Domain Name	Required	String
adminContactId	The contact ID that you want to use as the new admin contact	Required	String
New Billing Contact	The contact ID that you want to use as the new billing contact	Required	String
New Registrant	The contact ID that you want to use as the	Required	String



Contact	new registrant contact		
New Technical Contact	The contact ID that you want to use as the new technical contact	Required	String

Response:

responseMsg:

statusCode: 200 if domain contact updated successfully and 400 if domain contact updation is failed.

message: Indicates the message

responseData:

statusCode: 200 if domain contact updated successfully and 400 if domain contact updation is failed.

message: Indicates the message and reason if domain is not registered.

28. To move domain from one client to another

To move registered domain from one reseller to another

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/movedomain?APIKey=<Your_API_Key>&domainNameId=1&customerId=123&userName=abc@example.com&isCustomerContact=1

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID which need to be moved	Required	Integer
customerId	Client ID in domain which need to be moved	Required	Integer
userName	User name of client in which domain needs to be moved	Required	String
isCustomerContact	1 indicates if we want to use default contact of new client. 0 if we want to use existing Contact	Required	Boolean

Response:

responseMsg:

statusCode: 200 if domain is moved successfully and 400 if domain moving is failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if domain is moved successfully and 400 if domain moving is failed.

message: Indicates the message and reason if domain is not registered.

29. Add SRV Record

To add SRV DNS record for Domain.



Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/addsrvrecord/?APIKey=<Your_API_Key>&DNSZoneID=2173&RecordName=host.test.com&RecordValue=tcp._scp.test.com&RecordPriority=0&RecordTTL=43200&RecordPort=1&RecordWeight=50

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
DNSZoneID	DNS zone ID which we get in view domain response	Required	Integer
recordName	Name for DNS entry	Required	String
recordType	Type for DNS entry	Required	String
recordValue	Value for DNS entry	Optional	String
recordTTL	Time to live	Optional	Integer
recordPriority	Set Priority	Optional	Integer
recordWeight	Set Weight	Required	Integer
recordPort	Set Port	Required	Integer

Response:

responseMsg:

statusCode: 200 if DNS record is added successfully domain is successful and 400 if DNS record is add on domain is failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if DNS record is added successfully domain is successful and 400 if DNS record is add on domain is failed.

message: Indicates the message

30. Modify DNS Record for Domain

To Modify DNS record for Domain.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyDNSRecord?APIKey=<Your_API_Key>&DNSZoneID=00&DNSZoneRecordID=00&RecordName=host.example.com&RecordType=A&RecordValue=recordvalue&RecordTTL=43200&RecordPort=1&RecordWeight=50

Request Parameters: Following table describes the request parameters of the pause object.



Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
DNSZoneID	DNS zone ID which we get in view domain response	Required	Integer
DNSZoneRecordID	DNSzone record ID for which we want to modify the domain	Required	Integer
recordName	Name for DNS entry	Required	String
recordType	Type for DNS entry	Required	String
recordValue	Value for DNS entry	Optional	String
recordTTL	Time to live	Optional	Integer
recordWeight	Set Weight	Required	Integer
recordPort	Set Port	Required	Integer

Response:

responseMsg:

statusCode: 200 if DNS record is modified successfully and 400 if DNS record modification is failed.

message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if DNS record is added successfully and 400 if DNS record modification is failed.

message: Indicates the message

B - CONTACT

1. Add Contact

To add the Contact under Customer

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/AddRegistrantContact?APIKey=<<Your_API_KEY>>&Name=johndeo&EmailAddress=johndeo@example.com&CompanyName=example&Address=exampleaddress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate_Phone_cc=00&Alternate_Phone=&Id=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
Name	Name of the contact	Required	String



emailAddress	Email Address of the contact	Required	String
companyName	Company Name of the contact	Required	String
address	Address of the contact	Required	String
city	City of the contact	Required	String
stateName	State of the contact	Required	String
CountryName	Country of the contact	Required	String
zip	Zip code of the contact	Required	String
phoneNo_cc	Phone no. country code of the contact	Required	String
phoneNo	Phone no. of the contact	Required	String
faxNo_cc	Fax no. country code of the contact	Optional	String
faxNo	Fax no. of the contact	Optional	String
alternatePhone_cc	Alternate phone no. country code of the contact	Optional	String
alternatePhone	Alternate phone no. of the contact	Optional	String
ID	Client id for which you want modify the details of Registrant Contact	Required	Integer

Response:

responseMsg:

statusCode: 200 if contact is modified successfully and 400 if modifying contacts failed.

message: Indicates the message.

responseData:

statusCode: 200 if contact is modified successfully and 400 if modifying contacts failed.

message: Indicates the message.

2. Modify Contact

To modify the contact

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyRegistrantContact?APIKey=<Your API Key>&Name=johndeo&EmailAddress=johndeo@example.com&CompanyName=example&Address=exampleaddress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate Phone_cc=00&Alternate Phone=&RegistrantContactId=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
------------	-------------	-------------------	------



APIKey	Authentication Parameters	Required	String
Name	Name of the contact	Required	String
emailAddress	Email Address of the contact	Required	String
companyName	Company Name of the contact	Required	String
address	Address of the contact	Required	String
city	City of the contact	Required	String
stateName	State of the contact	Required	String
CountryName	Country of the contact	Required	String
zip	Zip code of the contact	Required	String
phoneNo_cc	Phone no. country code of the contact	Required	String
phoneNo	Phone no. of the contact	Required	String
faxNo_cc	Fax no. country code of the contact	Optional	String
faxNo	Fax no. of the contact	Optional	String
alternatePhone_cc	Alternate phone no. country code of the contact	Optional	String
alternatePhone	Alternate phone no. of the contact	Optional	String
registrantContactId	Client id for which you want add the contact	Required	Integer

Response:

responseMsg:

statusCode: 200 if contact is added successfully and 400 if adding contacts failed.

message: Indicates the message.

responseData:

statusCode: 200 if contact is added successfully and 400 if adding contacts failed.

message: Indicates the message.

3. View Contact

To view the contact details

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ViewRegistrant?APIKey=<Your_API_Key>&RegistrantContactId=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
registrantContactId	Client id for which you want to view the	Required	Integer



	contact		
--	---------	--	--

Response:

responseMsg:

statusCode: 200 if contact is available and 400 if contact is not available.

message: Indicates the message.

responseData:

Name: Name of the contact

emailaddress: Email Address of the contact

companyName: Company Name of the contact

address: Email Address of the contact

city: City of the contact

stateName: State of the contact

countryName: Country of the contact

zip: Zip code of the contact

phoneNo_cc: Phone no. country code of the contact

phoneNo: Phone no. of the contact

faxNo_cc: Fax no. country code of the contact

faxNo: Fax no. of the contact

alternatePhone_cc: Alternate phone no. country code of the contact

alternatePhone: Alternate phone no. of the contact

clientId: Customer ID to which contact belongs

4. To get Registrant list of specific client

To get registrant detailed list

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/registrantsearchlist?maxIndex=50&clientId=21459&APIKey=<Your_API_Key>&page=1&searchQuery=p

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
page	Page for which details need to be fetched	Required	Integer
maxIndex	Max no. of records needs to be fetched	Required	Integer
clientId	Customer ID	Required	Integer
searchQuery	Filter	Optional	String

Response:

totalCount: Total no. of registrant counts

records:

Array of Registrant of client with following details

registrantContactId: Registrant Contact ID



emailaddress: Email Address
city: City
countryName: Country Name
stateName: State Name
actionStatus: Action Status
domainCount: Domain Count
Name: First Name of the contact

5. To Send RAA Verification mail

To send RAA verification mail to registrant contact.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/resendRegistrantMail?contactId=00&APIKey=<Your_API_Key>

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
contactId	Registrant Contact ID to send email to	Required	Integer

Response:

```
{  
  "message": "Mail Send Successfully",  
  "id": 680,  
  "reason": null,  
  "statusCode": 200  
}
```



6. Send KYC Email to registrant.

To send KYC email to registrant

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/sendKYCMail?registrantContactId=00&APIKey=<Your_API_Key>

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
registrantContactId	Registrants contact ID	Required	Integer

Response:

responseMsg:

```
{  
  "message": "Mail Send Successfully",  
  "id": 00,  
  "reason": null,  
  "statusCode": 200  
}
```



C - CLIENT

1. Add Client

To add new customer

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/AddClient?APIKey=<Your API Key>&FirstName=johndeo&UserName=johndeo@example.com&Password=password&CompanyName=example&Address1=exampleaddress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate Phone cc=00&Alternate Phone=&Id=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
Name	Name of the client	Required	String
userName	Email Address of the client	Required	String
password	Password of the client	Required	String
companyName	Company Name of the client	Required	String
Address1	Address of the client	Required	String
city	City of the client	Required	String
stateName	State of the client	Required	String
CountryName	Country of the client	Required	String
zip	Zip code of the client	Required	String
phoneNo_cc	Phone no. country code of the client	Required	String
phoneNo	Phone no. of the client	Required	String
faxNo_cc	Fax no. country code of the client	Optional	String
faxNo	Fax no. of the client	Optional	String
alternatePhone_cc	Alternate phone no. country code of the client	Optional	String
alternatePhone	Alternate phone no. of the client	Optional	String

Response:

responseMsg:

statusCode: 200 if client is added successfully and 400 if adding client failed.

message: Indicates the message.

responseData:

statusCode: 200 if client is added successfully and 400 if adding client failed.



message: Indicates the message.

2. Modify Client

To modify client

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyClient?APIKey=<Your API Key>&FirstName=johndeo&UserName=johndeo@example.com&Password=password&CompanyName=example&Address=exampleaddress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate Phone cc=00&Alternate Phone= &Id=00

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
id	Customer ID for which you want to modify the details	Required	Integer
firstName	Name of the client	Optional	String
userName	Email Address of the client	Optional	String
password	Password of the client	Optional	String
companyName	Company Name of the client	Optional	String
Address1	Address of the client	Optional	String
city	City of the client	Optional	String
stateName	State of the client	Optional	String
CountryName	Country of the client	Optional	String
zip	Zip code of the client	Optional	String
phoneNo_cc	Phone no. country code of the client	Optional	String
phoneNo	Phone no. of the client	Optional	String
faxNo_cc	Fax no. country code of the client	Optional	String
faxNo	Fax no. of the client	Optional	String
alternatePhone_cc	Alternate phone no. country code of the client	Optional	String
alternatePhone	Alternate phone no. of the client	Optional	String

Response:

responseMsg:

statusCode: 200 if client is modified successfully and 400 if modifying client failed.

message: Indicates the message.



responseData:

statusCode: 200 if client is modified successfully and 400 if modifying client failed.

message: Indicates the message.

3. View Client

To view client details

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ViewClient?APIKey=<Your_API_Key>&Username=username@example.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
userName	User Name for which you want to view client details	Required	String

Response:

responseMsg:

statusCode: 200 if contact is available and 400 if contact is not available.

message: Indicates the message.

responseData:

clientId: ID of the client

resellerId: Reseller ID to which client belongs

firstName: Name of the client

emailaddress: Email Address of the client

companyName: Company Name of the client

password: Password of the client

address: Address of the client

city: City of the client

stateName: State of the client

countryName: Country of the client

zip: Zip code of the client

phoneNo_cc: Phone no. country code of the client

phoneNo: Phone no. of the client

faxNo_cc: Fax no. country code of the client

faxNo: Fax no. of the client

alternatePhone_cc: Alternate phone no. country code of the client

alternatePhone: Alternate phone no. of the client

4. Change the Client Password

To modify client's password

Method: GET

**URL:**

https://api.connectreseller.com/ConnectReseller/ESHOP/ChangeClientPassword?APIKey=<Your_API_Key>&UserName=johndeo@example.com&OldPassword=password&NewPassword=example

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
userName	Email Address of the client	Required	String
oldPassword	Existing Password of the client	Required	String
password	New Password of the client	Required	String

Response:

responseMsg:

statusCode: 200 if client's password is changed successfully and 400 if client's password change failed.

message: Indicates the message.

responseData:

statusCode: 200 if client's password is changed successfully and 400 if client's password change failed.

message: Indicates the message.

5. To Delete The Client

To delete the client

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/DeleteCustomer?APIKey=<Your_API_Key>&customerId=0000

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
customerId	Client ID which you want to delete	Required	Integer

Response:

responseMsg:

statusCode: 200 if client is deleted successfully and 400 if client deletion failed.

message: Indicates the message.

responseData:

statusCode: 200 if client is deleted successfully and 400 if client deletion failed.

message: Indicates the message.



6. To Get A Client List

To get a client list

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/clientsearchlist?maxIndex=50&APIKey=<Your_API_Key>&page=1

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
page	Page for which details needs to be fetched	Required	Integer
maxIndex	Max no. of records needs to be fetched	Required	Integer
searchQuery	Filter	Optional	String

Response:

responseMsg:

totalCount: Total no. of domain count.

records: Array of clients with following details:

entryId: Client ID

customerName: Customer Name

emailId: Email Address

city: City

country: Country

status: Status

D - HOST

1. To Add Child Name Server

To add Child Name Server

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/AddChildNameServer?APIKey=<Your_API_Key>&domainNameId=domainId&websiteName=example.com&ipAddress=127.0.0.1&hostName=example

Request Parameters: Following table describes the request parameters of the pause object.



Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to add child name server	Required	Integer
websiteId	Domain name of registered domain for which you want to add child name server	Required	String
hostName	Child Name Server which you want to add	Required	String
ipAddress	Ip address which you want to associate with the Child Name Servers	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is added successfully and 400 if child name server addition failed.

message: Indicates the message.

responseData:

statusCode: 200 if child name server is added successfully and 400 if child name server addition failed.

message: Indicates the message.

2. Modify Name Server IP

To modify IP address of child name server.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyChildNameServerIP?APIKey=<Your_API_Key>&domainNameId=domainId&websiteName=example.com&oldIpAddress=127.0.0.1&newIpAddress=127.0.0.2&hostName=example

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to modify child name server	Required	Integer
websiteId	Domain name of registered domain for which you want to modify child name server	Required	String
hostName	Child Name Server which you want to modify	Required	String
newIpAddress	New Ip address which you want to associate with the Child Name Servers	Required	String
oldIpAddress	Old IP Address	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is added successfully and 400 if child name server addition failed.



message: Indicates the message.

responseData:

statusCode: 200 if child name server is added successfully and 400 if child name server addition failed.

message: Indicates the message.

3. To Modify Host Child Name Server

To Modify Child Name Server Host of the domain

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyChildNameServerHost?APIKey=<Your_API_Key>&domainNameId=domainId&websiteName=example.com&oldHostName=example&newHostName=example

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to modify child name server	Required	Integer
websiteId	Domain name of registered domain for which you want to modify child name server	Required	String
oldHostName	Old Child Name Server which you want to modify	Required	String
newHostName	New Child Name Server	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is modified successfully and 400 if child name server modification failed.

message: Indicates the message.

responseData:

statusCode: 200 if child name server is modified successfully and 400 if child name server modification failed.

message: Indicates the message.

4. To Delete Child Name Server

To Delete Child Name Server

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/DeleteChildNameServer?APIKey=<Your_API_Key>&domainNameId=domainId&websiteName=example.com&ipAddress=127.0.0.1&hostname=example



Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to delete child name server	Required	Integer
websiteId	Domain name of registered domain for which you want to delete child name server	Required	String
hostName	Child Name Server which you want to delete	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is deleted successfully and 400 if child name server deletion failed.

message: Indicates the message.

responseData:

statusCode: 200 if child name server is deleted successfully and 400 if child name server deletion failed.

message: Indicates the message.

5. To Get Child Name Servers of a Domain

To get Child Name Servers of a domain.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/getchildnameservers?APIKey=<Your_API_Key>&id=domainId

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to get child name server list	Required	Integer

Response:

responseMsg:

statusCode: 200 if child name server list is fetched successfully and 400 if child name server list fetching is failed.

message: Indicates the message.

responseData:

```
[  
{"hostname":"ns1.example.com","ipAddress":"127.0.0.1"},  
{"hostname":"ns2.example.com","ipAddress":"127.0.0.1"}  
]
```



```
{“hostname”:”ns3.example.com”,”ipAddress”:”127.0.0.1”},  
{“hostname”:”ns4.example.com”,ipAddress”:”127.0.0.1”}  
]
```

E - DOMAIN FORWARDING

1. To Set Domain Forwarding Details

To set domain forwarding registered with us.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/SetDomainForwarding?APIKey=<Your_API_Key>&domainNameId=domainId&websiteId=websiteId&isMasking=1&rewrite=http://www.exampleple.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to set Domain Forwarding	Required	Integer
websiteId	DomainWebsite id of registered domain for which you want to set Domain Forwarding (Refer website Id from view domain response)	Required	String
isMasking	Possible value is 1 or 0. If 1, visitors will see the source URL and not the destination URL	Required	Integer
rewrite	URL where you want to forward your domain	Required	String

Response:

responseMsg:

statusCode: 200 if domain forwarding details are added successfully and 400 if domain forwarding details addition failed.

message: Indicates the message.

responseData:

statusCode: 200 if domain forwarding details are added successfully and 400 if domain forwarding details addition failed.

message: Indicates the message.

2. To Get Domain Forwarding Details

To get domain forwarding details of mentioned website.

Method: GET

**URL:**

https://api.connectreseller.com/ConnectReseller/ESHOP/GetDomainForwarding?APIKey=<Your_API_Key>&websiteId=websiteId

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
websiteId	Domain website ID of registered domain for which you want to get domain forwarding details. (Refer website ID from view domain response)	Required	Integer

Response:

responseMsg:

statusCode: 200 if domain forwarding details are fetched successfully and 400 if domain forwarding details fetch failed.

message: Indicates the message.

responseData:

```
{  
  "websiteName": "example.com", "resellerId": id,  
  "isMasking": 1,  
  "rewrite": redirect URL if masking is disable or null, "proxyPass": redirect URL if masking is enable or null,  
}
```

3. To Update Domain Forwarding Details

To Update Domain Forwarding details of the domain.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/updatedomainforwarding?APIKey=<Your_API_Key>&domainNameId=domainId&websiteId=websiteId&isMasking=1&rewrite=http://www.exampleple.com

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain ID of registered domain for which you want to update Domain Forwarding	Required	Integer
websiteId	Domain website ID of registered domain for which you want to update domain	Required	String



	forwarding. (Refer website ID from view domain)		
isMasking	Possible value is 1 or 0. If 1, visitors will see the source URL and not the destination URL	Required	Integer
rewriteURL	Where you want to forward your domain	Required	String

Response:

responseMsg:

statusCode: 200 if domain forwarding details are updated successfully and 400 if domain forwarding details updation failed.

message: Indicates the message.

responseData:

statusCode: 200 if domain forwarding details are updated successfully and 400 if domain forwarding details updation failed.

message: Indicates the message.

4. To Delete Domain Forwarding Details

To Delete Domain Forwarding details of the domain.

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/deletedomainforwarding?APIKey=<Your_API_Key>&websiteId=websiteId&domainNameId=domainNameId

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain Name ID	Required	Integer
websiteId	Domain website ID of registered domain for which you want to delete domain forwarding details. (Refer website ID from view domain response)	Required	Integer

Response:

responseMsg:

statusCode: 200 if domain forwarding details are deleted successfully and 400 if domain forwarding deletion failed.

message: Indicates the message.

responseData:

statusCode: 200 if domain forwarding details are deleted successfully and 400 if domain forwarding deletion failed.

message: Indicates the message.



F – MISCELLANEOUS

1. Check Reseller Available funds.

To get available funds data in resellers account

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/availablefund?APIKey=<YOUR_API_KEY>&resellerId=<YOUR_ID>

Request Parameters: Following table describes the request parameters of the pause object.

Parameters	Description	Required/ Optional	Type
APIKey	Authentication Parameters	Required	String
resellerId	Reseller ID	Required	Integer

Response:

```
{
  "responseMsg": {
    "message": "Available Fund",
    "id": 0,
    "statusCode": 0
  },
  "responseData": Available_Amount
}
```