

# DB schema

## Entity Relationship Diagram — Database Design Document

Karnataka Police Department

### Color Legend

|                         |                                              |
|-------------------------|----------------------------------------------|
| <b>PK — Primary Key</b> | Uniquely identifies each record in the table |
| <b>FK — Foreign Key</b> | References the Primary Key of another table  |
| <b>Alternate row</b>    | Alternating row shading for readability      |
| <b>Normal column</b>    | Regular data column with no key constraint   |

### Table Definitions

#### CaseMaster

| Column Name         | Type    | Key       | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|---------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CaseMasterID        | INT     | <b>PK</b> | Primary key — unique identifier for each FIR/case                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| CrimeNo             | VARCHAR |           | <p>Crime Number is assigned at the police station level and is linked to the corresponding PoliceStationID. The Crime Number follows a structured format consisting of:<br/>           1 digit Case Category Code + 4 digit District ID + 4 digit Police Station ID (Unit ID) + 4 digit Year + 5 digit Running Serial Number</p> <p>A separate running serial number is maintained for each police station, case category, and year.</p> <p>Examples:</p> <ul style="list-style-type: none"> <li>FIR: 104430006202600001</li> <li>UDR: 304430006202600001</li> <li>Zero FIR: 804430006202600001</li> <li>PAR: 404430006202600001</li> </ul> |
| CaseNo              | VARCHAR |           | <p>The <b>Case Number</b> is generated at the police station level and is associated with the corresponding <b>PoliceStationID</b>. For each case category, a unique serial number is maintained per police station and per year. The format is <b>YYYY + 5-digit running serial number</b> (e.g., <b>202600001</b>). (Last 9 digits from CrimeNo)</p>                                                                                                                                                                                                                                                                                      |
| CrimeRegisteredDate | DATE    |           | Date when the FIR was registered                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| PolicePersonID      | INT     | <b>FK</b> | FK → Employee.EmployeeID — officer who registered the FIR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PoliceStationID     | INT     | <b>FK</b> | FK → Unit.UnitID — police station where FIR is registered                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| CaseCategoryID      | INT     | <b>FK</b> | FK → CaseCategory.CaseCategoryID — category                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| GravityOffenceID    | INT     | <b>FK</b> | FK → GravityOffence.GravityOffenceID — gravity level of the offence                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| CrimeMajorHeadID    | INT     | <b>FK</b> | FK → CrimeHead.CrimeHeadID — major crime head classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| CrimeMinorHeadID    | INT     | <b>FK</b> | FK → CrimeSubHead.CrimeSubHeadID — minor crime sub-head classification                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| CaseStatusID        | INT     | <b>FK</b> | FK → CaseStatusMaster.CaseStatusID — current status of the case                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| CourtID             | INT     | <b>FK</b> | FK → Court.CourtID — court where the case is being heard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

| Column Name        | Type          | Key | Description                                                               |
|--------------------|---------------|-----|---------------------------------------------------------------------------|
| IncidentFromDate   | DATETIME      |     | Start date and time of the incident                                       |
| IncidentToDate     | DATETIME      |     | End date and time of the incident                                         |
| InfoReceivedPSDate | DATETIME      |     | Date and time when police station received information about the incident |
| latitude           | DECIMAL       |     | GPS latitude coordinate of the incident location                          |
| longitude          | DECIMAL       |     | GPS longitude coordinate of the incident location                         |
| BriefFacts         | Nvarchar(Max) |     | Summary of the case                                                       |

## ComplainantDetails

| Column Name          | Type    | Key       | Description                                                        |
|----------------------|---------|-----------|--------------------------------------------------------------------|
| <b>ComplainantID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the complainant                |
| CaseMasterID         | INT     | <b>FK</b> | FK → CaseMaster.CaseMasterID — FIR/case filed by this complainant  |
| ComplainantName      | VARCHAR |           | Full name of the complainant                                       |
| AgeYear              | INT     |           | Age of the complainant                                             |
| OccupationID         | INT     | <b>FK</b> | FK → OccupationMaster.OccupationID — occupation of the complainant |
| ReligionID           | INT     | <b>FK</b> | FK → ReligionMaster.ReligionID — religion of the complainant       |
| CasteID              | INT     | <b>FK</b> | FK → CasteMaster.caste_master_id — caste of the complainant        |
| GenderID             | INT     |           | Gender of the complainant (lookup value)                           |

## ActSectionAssociation

| Column Name    | Type | Key       | Description                                                         |
|----------------|------|-----------|---------------------------------------------------------------------|
| CaseMasterID   | INT  | <b>FK</b> | FK → CaseMaster.CaseMasterID — FIR/case this act-section applies to |
| ActID          | INT  | <b>FK</b> | FK → Act.ActCode — legal act under which charges are framed         |
| SectionID      | INT  | <b>FK</b> | FK → Section.SectionCode — specific section of the act invoked      |
| ActOrderID     | INT  |           | Display/print order of the act within the case                      |
| SectionOrderID | INT  |           | Display/print order of the section under the act                    |

## Victim

| Column Name           | Type    | Key       | Description                                                    |
|-----------------------|---------|-----------|----------------------------------------------------------------|
| <b>VictimMasterID</b> | INT     | <b>PK</b> | Primary key — unique identifier for each victim                |
| CaseMasterID          | INT     | <b>FK</b> | FK → CaseMaster.CaseMasterID — FIR/case this victim belongs to |
| VictimName            | VARCHAR |           | Full name of the victim                                        |
| AgeYear               | INT     |           | Age of the victim in years                                     |
| GenderID              | INT     |           | Gender of the victim (lookup value) like m, f, t               |
| VictimPolice          | VARCHAR |           | If Victim is police then 1 else 0                              |

## Accused

| Column Name            | Type | Key       | Description                                                    |
|------------------------|------|-----------|----------------------------------------------------------------|
| <b>AccusedMasterID</b> | INT  | <b>PK</b> | Primary key — unique identifier for each accused person        |
| CaseMasterID           | INT  | <b>FK</b> | FK → CaseMaster.CaseMasterID — FIR/case this accused is linked |

| Column Name | Type    | Key | Description                              |
|-------------|---------|-----|------------------------------------------|
|             |         |     | to                                       |
| AccusedName | VARCHAR |     | Full name of the accused                 |
| AgeYear     | INT     |     | Age of the accused                       |
| GenderID    | INT     |     | Gender of the accused mentioned as M/F/T |
| PersonID    | VARCHAR |     | Accused Sorting like A1, A2, A3....      |

## ArrestSurrender

| Column Name               | Type | Key       | Description                                                                   |
|---------------------------|------|-----------|-------------------------------------------------------------------------------|
| <b>ArrestSurrenderID</b>  | INT  | <b>PK</b> | Primary key — unique identifier for each arrest/surrender event               |
| CaseMasterID              | INT  | <b>FK</b> | FK → CaseMaster.CaseMasterID — FIR/case linked to this arrest/surrender       |
| ArrestSurrenderTypeID     | INT  |           | Type of event: arrest or voluntary surrender (lookup value)                   |
| ArrestSurrenderDate       | DATE |           | Date of arrest or surrender                                                   |
| ArrestSurrenderStateID    | INT  | <b>FK</b> | FK → State.StateID — state where arrest/surrender occurred                    |
| ArrestSurrenderDistrictID | INT  | <b>FK</b> | FK → District.DistrictID — district where arrest/surrender occurred           |
| PoliceStationID           | INT  | <b>FK</b> | FK → Unit.UnitID — police station handling the arrest                         |
| IOID                      | INT  | <b>FK</b> | FK → Employee.EmployeeID — Investigating Officer who made the arrest          |
| CourtID                   | INT  | <b>FK</b> | FK → Court.CourtID — court before which accused was produced                  |
| AccusedMasterID           | INT  | <b>FK</b> | FK → Accused.AccusedMasterID — accused person linked to this arrest/surrender |
| IsAccused                 | BIT  |           | Flag (0/1): whether the person is the primary accused in the case             |
| IsComplainantAccused      | BIT  |           | Flag (0/1): whether the complainant is also listed as accused                 |

## Act

| Column Name    | Type    | Key       | Description                                                           |
|----------------|---------|-----------|-----------------------------------------------------------------------|
| <b>ActCode</b> | VARCHAR | <b>PK</b> | Primary key — unique code for the legal act (e.g. IPC, NDPS)          |
| ActDescription | VARCHAR |           | Full official name/description of the act                             |
| ShortName      | VARCHAR |           | Abbreviated/common name of the act                                    |
| Active         | BIT     |           | Whether the act is currently active and usable (1=Active, 0=Inactive) |

## Section

| Column Name        | Type    | Key       | Description                                                    |
|--------------------|---------|-----------|----------------------------------------------------------------|
| ActCode            | VARCHAR | <b>FK</b> | FK → Act.ActCode — parent act this section belongs to          |
| SectionCode        | VARCHAR |           | Section number/code (e.g. 302, 307)                            |
| SectionDescription | VARCHAR |           | Full description of the section                                |
| Active             | BIT     |           | Whether the section is currently active (1=Active, 0=Inactive) |

## CrimeHeadActSection

| Column Name | Type | Key       | Description                                                                  |
|-------------|------|-----------|------------------------------------------------------------------------------|
| CrimeHeadID | INT  | <b>FK</b> | FK → CrimeHead.CrimeHeadID — crime head this act-section combination maps to |

| Column Name | Type    | Key | Description                                             |
|-------------|---------|-----|---------------------------------------------------------|
| ActCode     | VARCHAR | FK  | FK → Act.ActCode — legal act linked to this crime head  |
| SectionCode | VARCHAR |     | Section code from the act applicable to this crime head |

## CrimeHead

| Column Name        | Type    | Key | Description                                                   |
|--------------------|---------|-----|---------------------------------------------------------------|
| <b>CrimeHeadID</b> | INT     | PK  | Primary key — unique identifier for the major crime head      |
| CrimeGroupName     | VARCHAR |     | Name of the crime group/major head (e.g. Crimes Against Body) |
| Active             | BIT     |     | Whether this crime head is active (1=Active, 0=Inactive)      |

## CrimeSubHead

| Column Name           | Type    | Key | Description                                                          |
|-----------------------|---------|-----|----------------------------------------------------------------------|
| <b>CrimeSubHeadID</b> | INT     | PK  | Primary key — unique identifier for the crime sub-head               |
| CrimeHeadID           | INT     | FK  | FK → CrimeHead.CrimeHeadID — parent major crime head this belongs to |
| CrimeHeadName         | VARCHAR |     | Name of this crime sub-head (e.g. Murder, Robbery)                   |
| SeqID                 | INT     |     | Display/sort sequence number for ordering sub-heads                  |

## CasteMaster

| Column Name            | Type    | Key | Description                                                                              |
|------------------------|---------|-----|------------------------------------------------------------------------------------------|
| <b>caste_master_id</b> | INT     | PK  | Primary key — unique identifier for each caste. Referenced by ComplainantDetails.CasteID |
| caste_master_name      | VARCHAR |     | Name of the caste                                                                        |

## ReligionMaster

| Column Name       | Type    | Key | Description                                                                                    |
|-------------------|---------|-----|------------------------------------------------------------------------------------------------|
| <b>ReligionID</b> | INT     | PK  | Primary key — unique identifier for each religion. Referenced by ComplainantDetails.ReligionID |
| ReligionName      | VARCHAR |     | Name of the religion (e.g. Hindu, Muslim, Christian)                                           |

## OccupationMaster

| Column Name         | Type    | Key | Description                                                                                        |
|---------------------|---------|-----|----------------------------------------------------------------------------------------------------|
| <b>OccupationID</b> | INT     | PK  | Primary key — unique identifier for each occupation. Referenced by ComplainantDetails.OccupationID |
| OccupationName      | VARCHAR |     | Name of the occupation (e.g. Farmer, Government Employee)                                          |

## CaseStatusMaster

| Column Name         | Type    | Key | Description                                                                                 |
|---------------------|---------|-----|---------------------------------------------------------------------------------------------|
| <b>CaseStatusID</b> | INT     | PK  | Primary key — unique identifier for each case status. Referenced by CaseMaster.CaseStatusID |
| CaseStatusName      | VARCHAR |     | Name of the status (e.g. Under Investigation, Charge Sheeted, Closed)                       |

## Court

| Column Name    | Type    | Key       | Description                                                                                              |
|----------------|---------|-----------|----------------------------------------------------------------------------------------------------------|
| <b>CourtID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the court. Referenced by CaseMaster.CourtID, ArrestSurrender.CourtID |
| CourtName      | VARCHAR |           | Full name of the court                                                                                   |
| DistrictID     | INT     | <b>FK</b> | FK → District.DistrictID — district where the court is located                                           |
| StateID        | INT     | <b>FK</b> | FK → State.StateID — state where the court is located                                                    |
| Active         | BIT     |           | Whether the court is active (1=Active, 0=Inactive)                                                       |

## District

| Column Name       | Type    | Key       | Description                                                                                            |
|-------------------|---------|-----------|--------------------------------------------------------------------------------------------------------|
| <b>DistrictID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the district. Referenced by Court, Unit, Employee, ArrestSurrender |
| DistrictName      | VARCHAR |           | Name of the district                                                                                   |
| StateID           | INT     | <b>FK</b> | FK → State.StateID — state this district belongs to                                                    |
| Active            | BIT     |           | Whether the district record is active (1=Active, 0=Inactive)                                           |

## State

| Column Name    | Type    | Key       | Description                                                                                         |
|----------------|---------|-----------|-----------------------------------------------------------------------------------------------------|
| <b>StateID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the state. Referenced by Court, District, Unit, ArrestSurrender |
| StateName      | VARCHAR |           | Name of the state                                                                                   |
| NationalityID  | INT     |           | Nationality reference ID                                                                            |
| Active         | BIT     |           | Whether the state record is active (1=Active, 0=Inactive)                                           |

## Unit

| Column Name   | Type    | Key       | Description                                                                                                                                     |
|---------------|---------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>UnitID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the police unit. Referenced by CaseMaster.PoliceStationID, Employee.UnitID, ArrestSurrender.PoliceStationID |
| UnitName      | VARCHAR |           | Name of the unit or police station                                                                                                              |
| TypeID        | INT     | <b>FK</b> | FK → UnitType.UnitTypeID — type/category of the unit                                                                                            |
| ParentUnit    | INT     |           | Parent unit ID for hierarchy (self-reference to UnitID)                                                                                         |
| NationalityID | INT     |           | Nationality reference ID                                                                                                                        |
| StateID       | INT     | <b>FK</b> | FK → State.StateID — state the unit belongs to                                                                                                  |
| DistrictID    | INT     | <b>FK</b> | FK → District.DistrictID — district the unit belongs to                                                                                         |
| Active        | BIT     |           | Whether the unit is active (1=Active, 0=Inactive)                                                                                               |

## UnitType

| Column Name       | Type    | Key       | Description                                                                  |
|-------------------|---------|-----------|------------------------------------------------------------------------------|
| <b>UnitTypeID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the unit type. Referenced by Unit.TypeID |
| UnitTypeName      | VARCHAR |           | Name of the unit type (e.g. Police Station, Circle Office)                   |
| CityDistState     | VARCHAR |           | Operational level: City / District / State                                   |

| Column Name | Type | Key | Description                                            |
|-------------|------|-----|--------------------------------------------------------|
| Hierarchy   | INT  |     | Hierarchy level number (lower = higher authority)      |
| Active      | BIT  |     | Whether the unit type is active (1=Active, 0=Inactive) |

## Rank

| Column Name   | Type    | Key       | Description                                                                 |
|---------------|---------|-----------|-----------------------------------------------------------------------------|
| <b>RankID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the rank. Referenced by Employee.RankID |
| RankName      | VARCHAR |           | Name of the police rank (e.g. Constable, Inspector, DSP)                    |
| Hierarchy     | INT     |           | Rank hierarchy level (lower = higher rank)                                  |
| Active        | BIT     |           | Whether the rank is active (1=Active, 0=Inactive)                           |

## Designation

| Column Name          | Type    | Key       | Description                                                                               |
|----------------------|---------|-----------|-------------------------------------------------------------------------------------------|
| <b>DesignationID</b> | INT     | <b>PK</b> | Primary key — unique identifier for the designation. Referenced by Employee.DesignationID |
| DesignationName      | VARCHAR |           | Name of the designation (e.g. Investigating Officer, SHO)                                 |
| Active               | BIT     |           | Whether the designation is active (1=Active, 0=Inactive)                                  |
| SortOrder            | INT     |           | Display sort order for dropdowns/reports                                                  |

## Employee

| Column Name          | Type    | Key       | Description                                                                                                            |
|----------------------|---------|-----------|------------------------------------------------------------------------------------------------------------------------|
| <b>EmployeeID</b>    | INT     | <b>PK</b> | Primary key — unique identifier for the police employee. Referenced by CaseMaster.PolicePersonID, ArrestSurrender.IOID |
| DistrictID           | INT     | <b>FK</b> | FK → District.DistrictID — district the employee is currently posted in                                                |
| UnitID               | INT     | <b>FK</b> | FK → Unit.UnitID — unit/police station the employee is assigned to                                                     |
| RankID               | INT     | <b>FK</b> | FK → Rank.RankID — current rank of the employee                                                                        |
| DesignationID        | INT     | <b>FK</b> | FK → Designation.DesignationID — current designation of the employee                                                   |
| KGID                 | VARCHAR |           | Karnataka Government ID (unique government employee number)                                                            |
| FirstName            | VARCHAR |           | First name of the employee                                                                                             |
| EmployeeDOB          | DATE    |           | Date of birth of the employee                                                                                          |
| GenderID             | INT     |           | Gender of the employee (lookup value)                                                                                  |
| BloodGroupID         | INT     |           | Blood group of the employee (lookup value)                                                                             |
| PhysicallyChallenged | BIT     |           | Flag: whether the employee is physically challenged (1=Yes, 0=No)                                                      |
| AppointmentDate      | DATE    |           | Date of appointment to government service                                                                              |

## CaseCategory

| Column Name           | Type | Key       | Description                                                                                    |
|-----------------------|------|-----------|------------------------------------------------------------------------------------------------|
| <b>CaseCategoryID</b> | INT  | <b>PK</b> | Primary key — unique identifier for the case category. Referenced by CaseMaster.CaseCategoryID |

| Column Name | Type    | Key | Description                     |
|-------------|---------|-----|---------------------------------|
| LookupValue | VARCHAR |     | Category name (FIR, UDR, PAR..) |

GravityOffence

| Column Name      | Type    | Key | Description                                                                                      |
|------------------|---------|-----|--------------------------------------------------------------------------------------------------|
| GravityOffenceID | INT     | PK  | Primary key — unique identifier for the gravity level. Referenced by CaseMaster.GravityOffenceID |
| LookupValue      | VARCHAR |     | Gravity description (e.g. Heinous, Non-Heinous)                                                  |

ChargesheetDetails

| Column Name    | Type     | Key | Description                                                       |
|----------------|----------|-----|-------------------------------------------------------------------|
| CSID           | INT      | PK  | Primary key — unique identifier for the chargesheet               |
| CaseMasterID   | INT      | FK  | FK → CaseMaster.CaseMasterID — FIR/case filed by this complainant |
| csdate         | DATETIME |     | Chargesheeted date                                                |
| cstype         | CHAR     |     | Final report type A-> Chargesheet, B->False Case, C->Undetected   |
| PolicePersonID | INT      | FK  | FK → employeeMaster.employee ID                                   |

Relationship Matrix

Defines all foreign key relationships between tables, including cardinality and a brief description.

| Parent Table | Parent Column | Relationship | Child Table           | Child Column | Description                                       |
|--------------|---------------|--------------|-----------------------|--------------|---------------------------------------------------|
| CaseMaster   | CaseMasterID  | One to Many  | Victim                | CaseMasterID | One FIR can have multiple victims                 |
| CaseMaster   | CaseMasterID  | One to Many  | Accused               | CaseMasterID | One FIR can have multiple accused persons         |
| CaseMaster   | CaseMasterID  | One to Many  | ArrestSurrender       | CaseMasterID | One FIR can have multiple arrest/surrender events |
| CaseMaster   | CaseMasterID  | One to Many  | ComplainantDetails    | CaseMasterID | One FIR can have multiple complainants            |
| CaseMaster   | CaseMasterID  | One to Many  | ActSectionAssociation | CaseMasterID | One FIR can invoke multiple act-sections          |
| CaseMaster   | CaseMasterID  | One to One   | Inv_OccuranceTime     | CaseMasterID | One FIR has one occurrence time/location record   |

| Parent Table               | Parent Column                 | Relationship | Child Table                | Child Column      | Description                                             |
|----------------------------|-------------------------------|--------------|----------------------------|-------------------|---------------------------------------------------------|
| CaseMaster                 | CaseCategoryID                | Many to One  | CaseCategory               | CaseCategoryID    | Many FIRs can share the same category                   |
| CaseMaster                 | GravityOffenceID              | Many to One  | GravityOffence             | GravityOffenceID  | Many FIRs can have the same gravity level               |
| CaseMaster                 | CrimeMajorHeadID              | Many to One  | CrimeHead                  | CrimeHeadID       | Many FIRs can share the same major crime head           |
| CaseMaster                 | CrimeMinorHeadID              | Many to One  | CrimeSubHead               | CrimeSubHeadID    | Many FIRs can share the same crime sub-head             |
| CaseMaster                 | CaseStatusID                  | Many to One  | CaseStatusMaster           | CaseStatusID      | Many FIRs can have the same status                      |
| CaseMaster                 | CourtID                       | Many to One  | Court                      | CourtID           | Many FIRs can be tried in the same court                |
| CaseMaster                 | PolicePersonID                | Many to One  | Employee                   | EmployeeID        | Many FIRs can be registered by the same employee        |
| ArrestSurrender            | AccusedMasterID(via junction) | One to Many  | inv_arrestsurrenderaccused | ArrestSurrenderID | One arrest event can link multiple accused via junction |
| inv_arrestsurrenderaccused | ArrestSurrenderID             | Many to One  | ArrestSurrender            | ArrestSurrenderID | Junction links to the arrest/surrender event            |
| ArrestSurrender            | ArrestSurrenderStateID        | Many to One  | State                      | StateID           | Many arrest events can occur in the same state          |
| ArrestSurrender            | ArrestSurrenderDistrictID     | Many to One  | District                   | DistrictID        | Many arrest events can occur in the same district       |
| ArrestSurrender            | CourtID                       | Many to One  | Court                      | CourtID           | Accused may be produced before a court                  |
| ArrestSurrender            | IOID                          | Many to One  | Employee                   | EmployeeID        | Many arrests can be made by the same IO                 |
| ComplainantDetails         | OccupationID                  | Many to One  | OccupationMaster           | OccupationID      | Many complainants can share the same occupation         |
| ComplainantDetails         | ReligionID                    | Many to One  | ReligionMaster             | ReligionID        | Many complainants can share the same religion           |
| ComplainantDetails         | CastelID                      | Many to One  | CasteMaster                | caste_master_id   | Many complainants can belong to                         |



| Parent Table                 | Parent Column | Relationship | Child Table                | Child Column  | Description                                        |
|------------------------------|---------------|--------------|----------------------------|---------------|----------------------------------------------------|
|                              |               |              |                            |               | the same caste                                     |
| <b>ActSectionAssociation</b> | ActID         | Many to One  | <b>Act</b>                 | ActCode       | Many case-sections can reference the same act      |
| <b>ActSectionAssociation</b> | SectionID     | Many to One  | <b>Section</b>             | SectionCode   | Many cases can use the same section                |
| <b>CrimeSubHead</b>          | CrimeHeadID   | Many to One  | <b>CrimeHead</b>           | CrimeHeadID   | Multiple sub-heads fall under one major crime head |
| <b>CrimeHead</b>             | CrimeHeadID   | One to Many  | <b>CrimeHeadActSection</b> | CrimeHeadID   | One crime head can map to multiple act-sections    |
| <b>Act</b>                   | ActCode       | One to Many  | <b>CrimeHeadActSection</b> | ActCode       | One act can be linked to multiple crime heads      |
| <b>Act</b>                   | ActCode       | One to Many  | <b>Section</b>             | ActCode       | One act contains multiple sections                 |
| <b>Court</b>                 | DistrictID    | Many to One  | <b>District</b>            | DistrictID    | Many courts can be in the same district            |
| <b>District</b>              | StateID       | Many to One  | <b>State</b>               | StateID       | Many districts belong to one state                 |
| <b>Unit</b>                  | TypeID        | Many to One  | <b>UnitType</b>            | UnitTypeID    | Many units share the same unit type                |
| <b>Unit</b>                  | StateID       | Many to One  | <b>State</b>               | StateID       | Many units are located in the same state           |
| <b>Unit</b>                  | DistrictID    | Many to One  | <b>District</b>            | DistrictID    | Many units belong to the same district             |
| <b>Employee</b>              | DistrictID    | Many to One  | <b>District</b>            | DistrictID    | Many employees posted in the same district         |
| <b>Employee</b>              | UnitID        | Many to One  | <b>Unit</b>                | UnitID        | Many employees assigned to the same unit           |
| <b>Employee</b>              | RankID        | Many to One  | <b>Rank</b>                | RankID        | Many employees can hold the same rank              |
| <b>Employee</b>              | DesignationID | Many to One  | <b>Designation</b>         | DesignationID | Many employees can have the same designation       |