
A Greedy PDE Router for Blending Neural Operators and Classical Methods

Anonymous Author(s)

Affiliation

Address

email

1 **Revision note.** All text, tables and figures added in this revision are typeset in red (new figures carry
2 a red frame); everything in black is unchanged from the submitted version.

Abstract

3 When solving PDEs, classical numerical solvers are often computationally ex-
4 pensive, while machine learning methods can suffer from spectral bias, failing to
5 capture high-frequency components. Designing an optimal hybrid iterative solver-
6 where, at each iteration, a solver is selected from an ensemble of solvers to leverage
7 their complementary strengths—poses a challenging combinatorial problem. While
8 greedy selection is desirable for its constant-factor approximation guarantee to the
9 optimal solution under Lipschitz assumptions, it requires knowledge of the true
10 error at each step, which is unavailable in practice. We address this by proposing
11 an approximate greedy router that efficiently mimics a greedy approach to solver
12 selection. Empirical results on the Poisson and convection–diffusion equations
13 show that our method consistently reduces final error and area-under-the-curve
14 (AUC) of the error trajectory relative to single-solver baselines and existing hy-
15 brid approaches such as HINTS. In particular, our method reaches comparable
16 error levels in substantially fewer iterations while exhibiting more stable error
17 decay. **With a cost-aware instantiation of the greedy rule, a lightweight router, and
18 a band-limited scale-equivariant corrector, these gains carry over to end-to-end
19 wall-clock time on a 128×128 grid: for every one of the ten solver–equation
20 pairings the learned router reaches truncation-level accuracy $238\times$ – $1983\times$ faster
21 than the classical solver alone and $2.68\times$ – $10.3\times$ faster than HINTS, and it matches
22 or beats HINTS even when the latter’s period is tuned per setting.**

23 1 Introduction

24 Natural phenomena and engineered systems are often governed by ordinary and partial differential
25 equations (PDEs). Solving these equations enables a variety of tasks - predicting the evolution of the
26 system through simulation (e.g., forecasting weather using the Navier-Stokes equations) [Kalnay,
27 2003, Bauer et al., 2015, Staniforth and Côté, 1991], addressing control problems (e.g., optimizing
28 heat shield design for spacecrafts using heat transfer equations) [Anderson, 1989, Tröltzsch, 2010],
29 and tackling inverse problems based on external measurements (e.g., reconstructing brain activity
30 from EEG data using electrophysiological models) [Baillet et al., 2001, Grech et al., 2008].

31 Traditionally, PDEs are solved using finite difference methods [Smith, 1985, LeVeque, 2007], which
32 discretize the spatial and/or temporal domain and approximate the solution by solving a system
33 of equations at the discrete grid points. Similarly, finite element methods [Hughes, 2003, Bathe,
34 2006, Brenner, 2008] construct a system of equations based on local basis functions, and then
35 rely on numerical linear algebra techniques—such as the Jacobi and Gauss-Seidel method [Saad,
36 2003]—to compute the solution. These iterative methods, however, lack generalization across different

initial conditions, boundary conditions, or forcing functions, as even minor changes to any of these parameters require re-solving the entire system of equations from scratch.

These challenges have motivated the development of neural operators [Kovachki et al., 2023]—a class of machine learning models that aim to learn the solution operator directly, enabling fast inference across a range of parameters. Neural operators lift the classical linear layer in neural networks to an operator—typically a kernel integral operator—between function spaces. Despite strong approximation guarantees [Chen and Chen, 1995], neural operators are prone to spectral bias [Liu and Cai, 2021, Liu et al., 2024, You et al., 2024, Khodakarami et al., 2025, Xu et al., 2025], similar to traditional neural networks [Rahaman et al., 2019, Xu et al., 2019, Luo et al., 2019]. As a result, they favor learning low-frequency components of the solution function and often struggle to capture high-frequency features that iterative solvers excel at.

Recognizing this complementarity, Zhang et al. [2024] proposed HINTS, a hybrid solver that interleaves a neural operator pass every τ^{th} iteration of a classical solver, with τ fixed a priori. While HINTS reports significant empirical gains in convergence and accuracy over the standalone neural operator and Jacobi solver, this fixed schedule can be detrimental: a poorly timed neural correction may increase the error and undo recent progress.

Although state-dependent solver schedules are desirable, this naturally suggests a reinforcement learning formulation for learning routing policies. However, in our setting, the structure of iterative PDE solvers allows for a simpler approach: each solver induces a known update, and its effect can be evaluated through error-based signals. Leveraging this, we adopt a greedy rule that selects, at each iteration, the solver with the largest immediate error reduction. Such a rule can be near-optimal when the final error satisfies (weak) supermodularity—so that applying a beneficial solver earlier is at least as valuable as applying it later. To support this approach, we make the following contributions:

- We present a general hybrid PDE solver in which a routing rule chooses, at each iteration, from a set of classical solvers and neural operators. With oracle access to the true error at every step, we show that a greedy routing rule achieves a constant-factor approximation to the optimal strategy for linear PDEs, provided the updates are error-reducing (Lipschitz with constant < 1) and zero-preserving—conditions under which weak supermodularity holds.
- Given that the true error is not observed at test time, a convex surrogate loss is introduced, which, when minimized, enables the learned model to imitate the greedy router without access to true error information. This alignment is guaranteed through Bayes consistency.
- We empirically demonstrate that our approximate greedy solver achieves faster convergence than HINTS and individual solvers, often reaching comparable error levels in fewer iterations on the Poisson and convection-diffusion equations.

2 Background

Consider the following linear PDE:

$$\mathcal{L}_x^a(u) = f, x \in D; \quad \mathcal{B}_x(u) = b, x \in \partial D \quad (1)$$

where $\mathcal{L}_x^a$ is a differential operator with respect to the spatial variable $x \in D$ parameterized by the coefficient function a , f is a forcing function, u is the PDE solution, $\mathcal{B}_x$ is the boundary operator, and b is the boundary term. Such PDEs can be solved numerically using various discretization strategies, such as finite differences [Smith, 1985, LeVeque, 2007], finite element, and spectral methods [Boyd, 2001, Canuto et al., 2006]. Here, we focus on finite differences, which replace derivatives with difference quotients (e.x., $\partial_x u(x) \approx (u(x+h) - u(x))/h$) on a uniform grid.

Formally, let h be the grid size and $G_h(D)$ be a uniform grid with spacing h over D . For a function $g : D \rightarrow \mathbb{R}$, we denote its restriction to $G_h(D)$ by $g_h \in \mathbb{R}^N$, where $N = |G_h(D)|$. If $\mathcal{L}_h^a \in \mathbb{R}^{N \times N}$ is the discretized operator, the PDE reduces to a linear system of equations

$$\mathcal{L}_h^a u_h = f_h, \quad (2)$$

with the boundary conditions incorporated in $\mathcal{L}_h^a$. Unlike much of the neural operator literature, which retains function space formulations for discretization invariance, we follow the conventions of classical numerical analysis and represent functions and operators as vectors and matrices. Discretization invariance is not essential here, since we focus on fixed-grid problems.

86 2.1 Iterative PDE Solvers

87 Direct methods like Gauss Elimination and Thomas Algorithm can be computationally expensive in
 88 high-dimensional domains when solving systems like Equation (2). In contrast, iterative methods like
 89 Jacobi and Gauss-Seidel offer computational speedups by iteratively updating the solution, gradually
 90 converging to the true solution for the PDE. The general iterative update is

$$u^{(t+1)} = u^{(t)} + C \left(f_h - \mathcal{L}_h^a u^{(t)} \right), \quad (3)$$

91 where $u^{(t)}$ is the t^{th} iterate of the solution and C is a preconditioning matrix. Jacobi uses $C = D^{-1}$,
 92 where D is the diagonal of $\mathcal{L}_h^a$, and Gauss-Seidel uses $C = (D + L)^{-1}$, where L denotes the strict
 93 lower triangular part. However, these methods tend to damp low frequency parts of the error slowly.

94 2.2 Neural Operators

95 Suppose we observe samples $\{(a_i, f_i, u_i)\}_{i=1}^N$ such that $(a_i, f_i) \sim \mathcal{P}$ are i.i.d. samples, and $u_i =$
 96 $\mathcal{G}^*(a_i, f_i)$ be generated by a deterministic solution operator $\mathcal{G}^*$. A neural operator (NO) $\mathcal{G}_\theta$ seeks to
 97 approximate $\mathcal{G}^*$ by minimizing the expected squared $L^2(D)$ error:

$$\mathcal{R}_{\text{NO}}(\mathcal{G}_\theta) = \mathbb{E}_{(a,f) \sim \mathcal{P}} \left[\int_D \|u_i(x) - \mathcal{G}_\theta(a_i, f_i)(x)\|_2^2 dx \right]$$

98 Neural operators use discretization-invariant layers. Prominent instantiations include Fourier Neural
 99 Operators (FNO), which use spectral transforms [Li et al., 2020a], Graph Neural Operators, which
 100 perform graph-based aggregation over sampled points [Li et al., 2020b], and DeepONets, which
 101 employ a trunk-branch decomposition to map input functions to output functions [Lu et al., 2021].

102 2.3 Greedy Optimization

103 Consider maximizing $g(S)$ over $S \subseteq \Omega$ with $|S| \leq T$ where $g : 2^\Omega \rightarrow \mathbb{R}$ is a set function defined
 104 on subsets of a set Ω . An exhaustive search is infeasible, so an efficient alternative is the greedy
 105 algorithm. It builds the solution subset iteratively by adding ω^* that yields the largest marginal
 106 gain, i.e. $\omega^* = \arg \max_{\omega \in \Omega \setminus S} g(S \cup \omega)$. When g is non-negative, monotone (adding elements
 107 never decreases the value), and submodular (diminishing returns), the greedy algorithm achieves a
 108 $(1 - e^{-1})$ approximation to the optimal solution [Nemhauser et al., 1978]. Formally, a function g
 109 is submodular if $g(A \cup \{\omega\}) - g(A) \geq g(B \cup \{\omega\}) - g(B)$ for all $A \subseteq B \subseteq \Omega$ and $\omega \in \Omega \setminus B$;
 110 intuitively, delaying an addition cannot increase its benefit. For set function minimization problems,
 111 supermodularity, where the inequality flips, plays an analogous role, and the greedy rule achieves
 112 constant-factor approximation guarantees [Liberty and Sviridenko, 2017].

113 The suboptimality of the greedy algorithm has been extensively studied for both set-function mini-
 114 mization [Bounia and Koriche, 2023] and maximization [Das and Kempe, 2018, Feige et al., 2011,
 115 Bian et al., 2017, Harshaw et al., 2019] when standard assumptions—non-negativity, monotonicity, and
 116 sub/supermodularity—are weakened. In contrast, results on greedy sequence maximization [Streeter
 117 and Golovin, 2008, Alaei et al., 2021, Zhang et al., 2015, Bernardini et al., 2020, Van Over et al.,
 118 2024, Tschitschek et al., 2017]—where the ordering of the elements affects the function—have led
 119 to sequential analogues of submodularity and monotonicity. We leverage these tools to analyze the
 120 suboptimality of the greedy solution to minimizing the final error.

121 3 General framework for Hybrid Solvers

122 To solve Equation (2), consider the following hybrid iterative update:

$$u_h^{(t+1)} = u_h^{(t)} + C_{S_t} \left(f_h - \mathcal{L}_h^a u_h^{(t)} \right) \quad (4)$$

123 where $\mathcal{C} = \{C_j\}_{j=1}^K$ is a set of preconditioning functions and $S_t \in [K] = \{1, \dots, K\}$ indexes the
 124 function chosen at step t . Here, we use “preconditioning function” broadly to include classical linear
 125 updates ($C_j(x) = C_j x$ where C_j is a matrix), and learned models, such as neural operators. This
 126 update generalizes the classical iterative update in Equation (3), by allowing C_j to be non-linear and
 127 enabling the preconditioning function to be adaptively chosen at every step. $\mathcal{C}$ can also accommodate

parameterized solver families (e.g., different Jacobi relaxation weights), enabling adaptive selection of solver parameters. As the number of solvers K grows, the chance of selecting a more effective update increases. Furthermore, HINTS [Zhang et al., 2024] is a special case of this hybrid solver with $K = 2$, where C_1 is a neural operator and C_2 is a classical preconditioner. Its routing rule is given by $S_t = \mathbf{1}_{t \bmod \tau > 0} + 1$, which selects C_1 every τ steps and C_2 otherwise.

Let $e_h^{(t)} = u_h - u_h^{(t)}$ denote the error at step t . Then,

$$e_h^{(t+1)} = u_h - u_h^{(t)} - C_{S_t} \left(\mathcal{L}_h^a u_h - \mathcal{L}_h^a u_h^{(t)} \right) = (I - C_{S_t} \circ \mathcal{L}_h^a) (e_h^{(t)})$$

where I is the identity map and $I - C_j \circ \mathcal{L}_h^a$ is the error propagation function for solver j . Here, “ $\circ$ ” denotes function composition (matrix multiplication for linear updates). The objective is to select a sequence $S = (S_1, \dots, S_T)$ that minimizes the error norm after T steps or $\|e_h^{(T)}\|_2^2$:

$$\min_{S_t \in [K], |S| \leq T} h(S) := \left\| (I - C_{S_{|S|}} \circ \mathcal{L}_h^a) \circ \dots \circ (I - C_{S_1} \circ \mathcal{L}_h^a) (e_h^{(0)}) \right\|_2^2 \quad (5)$$

with compositions applied from right to left, so that the S_1 update acts on the initial error.

4 Greedy Algorithm

Equation (5) defines a combinatorial optimization problem with a search space exponential in T , making exact optimization intractable for large T or K . As a starting point, we consider an “omniscient” greedy algorithm that assumes access to the true initial error $e_h^{(0)}$. This is unrealistic since knowledge of $e_h^{(0)}$ could directly recover the solution via $u_h = u_h^{(0)} + e_h^{(0)}$, but it provides a useful benchmark. In Section 5, we relax this assumption using a practical learning strategy that is Bayes consistent with this omniscient rule, thereby recovering the guarantees shown below.

As discussed in Section 2.3, when supermodularity and monotonicity hold, the greedy rule—such as the one described in Algorithm 1—enjoys constant-factor approximation guarantees. However, classical results focus on *set* functions, with only recent extensions made to sequences. Building on this line, we introduce a sequence-based notion of weak supermodularity.

Algorithm 1 Greedy Algorithm for a Hybrid PDE solver

Require: $\{C_j\}_{j=1}^K, T, \mathcal{L}_h^a, e_h^{(0)}$
 $S^0 \leftarrow \emptyset$
for $t < T$ **do**
 $S^{t+1} \leftarrow S^t \oplus \arg \min_{j \in [K]} \|(I - C_j \circ \mathcal{L}_h^a)(e_h^{(t)})\|_2^2$
 $e_h^{(t+1)} \leftarrow (I - C_{S_{t+1}} \circ \mathcal{L}_h^a)(e_h^{(t)})$
end for
return S^T

Let Ω^* denote the space of sequences with elements in Ω . For $S, S' \in \Omega^*$, we denote their concatenation as $S \oplus S'$. S is a prefix of S' or $S \preceq S'$ if $S' = S \oplus L$ for some $L \in \Omega^*$. A function $g : \Omega^* \rightarrow \mathbb{R}$ is prefix monotonically non-increasing if $g(S \oplus S') \leq g(S)$ for all $S, S' \in \Omega^*$, and postfix monotonically non-increasing if $g(S' \oplus S) \leq g(S)$ for all $S, S' \in \Omega^*$. A prefix non-increasing function g is sequence supermodular if, for all $S', S \in \Omega^* : S \preceq S'$, it holds that

$$g(S) - g(S \oplus \omega) \geq g(S') - g(S' \oplus \omega), \quad \forall \omega \in \Omega \quad (6)$$

However, $h(S)$ (defined in Equation (5)) may not satisfy this property in general. Therefore, we introduce weak sequence supermodularity. A prefix non-increasing function g is weakly supermodular with respect to $S' \in \Omega^*$ if, for any $S \in \Omega^{|S'|}$, there exists $\alpha(S') \geq 1$ such that

$$g(S) - g(S \oplus S') \leq \alpha(S') \sum_{i \in [|S'|]} g(S) - g(S \oplus S'_i) \quad (7)$$

The parameter $\alpha(S')$ or the supermodularity ratio quantifies deviation from exact sequence supermodularity. Expanding the $g(S) - g(S \oplus S')$ as a telescoping sum $\sum_{i=1}^{|S'|} g(S \oplus (S'_1, \dots, S'_{i-1})) -$

159 $g(S \oplus (S'_1, \dots, S'_i))$ shows that the marginal decrease from appending S'_i after its predecessors is
 160 controlled by the effect of appending S'_i directly to S . Thus, postponing the inclusion of S'_i cannot
 161 yield a significantly larger benefit than adding it earlier. The supermodularity ratio $\alpha(S)$ quantifies
 162 the extent to which future gains from delays may exceed immediate gains.

163 Having introduced these notions, we now characterize the suboptimality of greedy solutions of weakly
 164 supermodular and postfix monotonic sequence functions in Theorem 4.1.

165 **Theorem 4.1.** *Let $g : \Omega^* \rightarrow \mathbb{R}$ be a weakly supermodular function with respect to the optimal*
 166 *solution $O = \arg \min_{S \in \Omega^T} h(S)$ with a supermodularity ratio of $\alpha(O)$ and postfix monotonicity. Let*
 167 *the greedy solution of length T be S^T . If $\phi_T(\alpha) = (1 - \frac{1}{\alpha T})^T$, then*

$$g(\emptyset) - g(S^T) \geq (1 - \phi_T(\alpha(O))) (g(\emptyset) - g(O))$$

168 The proof of Theorem 4.1 appears in Section A.2. As $T \rightarrow \infty$, the factor $1 - \phi_T(\alpha(O))$ decreases to
 169 $1 - e^{-1/\alpha(O)}$, so the worst-case performance of the greedy rule saturates rather than degrades with
 170 horizon. Additionally, larger $\alpha(O)$, which indicates higher reward for delayed inclusions, loosens the
 171 suboptimality bound. Theorem 4.1 requires that the sequence objective h be weakly supermodular
 172 with respect to the optimal solution and postfix monotone—properties established in Proposition 4.2.
 173 We defer the proof to Section A.3.

174 **Proposition 4.2.** *Suppose that for all $j \in [K]$, the error propagation function $I - C_j \circ \mathcal{L}_h^a$ is*
 175 *ρ_j -Lipschitz continuous with $\rho_j < 1$, and that $(I - C_j \circ \mathcal{L}_h^a)(0_N) = 0_N$. Then, the function h is*
 176 *weakly supermodular with respect to the optimal solution O , with*

$$\alpha(O) = \max \left\{ \frac{4}{T - \sum_{i=1}^T \rho_{O_i}^2}, 1 \right\}$$

177 *Furthermore, if $I - C_j \circ \mathcal{L}_h^a$ is invertible for all $j \in [K]$, h is also postfix non-increasing.*

178 The conditions of Proposition 4.2 are natural. For classical solvers, the Lipschitz constant is $\|I_N -$
 179 $C_j \mathcal{L}_h^a\|$, which is typically less than 1 for well-posed linear elliptic PDEs (i.e., the update is damping
 180 errors). For neural networks, Lipschitz continuity can be enforced via weight regularization [Gouk
 181 et al., 2021] and a sufficiently trained model should approximate $(\mathcal{L}_h^a)^{-1}$ well enough to make the
 182 Lipschitz constant small. The requirement $(I - C_j \circ \mathcal{L}_h^a)(0_N) = 0_N$ is both natural and desirable: it
 183 precludes spurious updates when the residual $f_h - \mathcal{L}_h^a u_h^{(t)}$ is 0. This holds by design for classical
 184 schemes, and it can be enforced for any learned model by excluding bias terms.

185 The form of $\alpha(O)$ in Proposition 4.2 highlights that the suboptimality factor in Theorem 4.1 is
 186 governed by the collective contraction factors of the solvers chosen by the optimal solution: as
 187 $\sum_{i=1}^T \rho_{O_i}^2 \rightarrow T$, $\alpha(O)$ grows, resulting in a weaker bound. Invertibility of the error propagation
 188 functions is often satisfied with Jacobi and Gauss-Seidel updates. However, neural networks with di-
 189 mension changes or ReLU activations may yield non-invertible error propagation maps. Nevertheless,
 190 our experiments show that greedy routers remain effective even when invertibility is not met.

191 Theorem 4.1 thus indicates that the approximation guarantee is strongest when the sequence is
 192 nearly supermodular ($\alpha(O) \approx 1$). Generally, if all error propagation maps share an eigenbasis,
 193 supermodularity is established. This occurs, for example, for linear, constant-coefficient PDEs
 194 with periodic boundary conditions where the solver ensemble includes Jacobi, Gauss-Seidel, and a
 195 single-layer linear Fourier Neural Operator. The proof of Theorem 4.3 is deferred to Section A.5.

196 **Proposition 4.3.** *Let $\|I_N - C_j \mathcal{L}_h^a\| \leq 1$ for all $j \in [K]$ and $(I - C_j \mathcal{L}_h^a) = P \Lambda_j P^{-1}$. Then, h is*
 197 *supermodular.*

198 **Cost-aware greedy routing.** Algorithm 1 treats every update as equally expensive, whereas in
 199 practice a neural-operator evaluation and a classical sweep have very different costs, and the quantity
 200 of interest is the error reached per unit of wall-clock time. We make the greedy rule cost-aware
 201 without changing the analysis: let c_j denote the (measured) cost of one application of C_j , take the
 202 cost u of one neural-operator call as the unit, and replace each preconditioner by the *macro-action*
 203 $C_j^{(m_j)}$ that applies C_j for $m_j = \max\{1, \text{round}(u/c_j)\}$ consecutive iterations, so that all actions
 204 cheaper than the unit cost approximately u ; an action dearer than the unit (a multigrid cycle, say)

is applied once and its error is compared per unit of cost, $\|e\|^{u/(m_j c_j)}$, which reduces to the plain comparison when the costs match. For a linear update, m consecutive sweeps are again a stationary iteration, $(I - C_j \circ \mathcal{L}_h^a)^m = I - C_j^{(m)} \mathcal{L}_h^a$ with $C_j^{(m)} = \sum_{i=0}^{m-1} (I - C_j \mathcal{L}_h^a)^i C_j$, and for a nonlinear C_j the macro-action is the m -fold composition of its error propagation map. Hence $\{C_j^{(m_j)}\}_{j=1}^K$ is again a set of preconditioning functions in the sense of Section 4: if $I - C_j \circ \mathcal{L}_h^a$ is ρ_j -Lipschitz, zero-preserving and invertible, then so is its m_j -fold composition (with constant $\rho_j^{m_j} < 1$), and Theorem 4.1, Propositions 4.2 and 4.3, and the consistency result of Section 5 apply verbatim to the macro-action ensemble. Running Algorithm 1 on macro-actions selects, at every decision epoch, the action with the largest error reduction per unit cost, and a horizon of T macro-actions corresponds to a wall-clock budget of $\approx Tu$; Section E uses this cost-aware instantiation throughout.

5 Approximate Greedy Router

The results in Section 4 indicate that the error reduction from the greedy solution closely matches that of the optimal sequence, but this is predicated on having access to the initial error, $e_h^{(0)}$. Inaccurate error estimates can result in poor solver decisions, causing errors to amplify. To remedy this, we learn a router r that selects solvers myopically, as in Algorithm 1, without access to true errors.

We adopt the following learning setup. Let $\mathcal{A}, \mathcal{F}, \mathcal{U} \subseteq \mathbb{R}^N$ denote the spaces of coefficient, forcing, and solution functions on the grid $G_h(D)$. We assume an application-specific data distribution $\mathcal{P}_{\mathcal{A} \times \mathcal{F}}$ over $\mathcal{A} \times \mathcal{F}$ that reflects test time conditions. During training, (a_h, f_h) is drawn from $\mathcal{P}_{\mathcal{A} \times \mathcal{F}}$, and a high-accuracy reference solution u_h is computed, providing the true per-step error. The router r is learned offline on this data; at test time, it operates without access to true errors.

At iteration t , router r selects a solver using the coefficient $a_h \in \mathcal{A}$, forcing $f_h \in \mathcal{F}$, and the current iterate $u_h^{(t)} \in \mathcal{U}$. If $r(a_h, f_h, u_h^{(t)}) = j$, the next iterate is computed with solver j , resulting in an error of $\|(I - C_j \circ \mathcal{L}_h^a)(e_h^{(t)})\|_2^2$. Learning such a router requires minimizing the following loss:

$$l_{\text{route}}(r, a_h, f_h, u_h^{(t)}, u_h) = \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a)(u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{r(a_h, f_h, u_h^{(t)})=j} \quad (8)$$

with risk $\mathcal{R}_{\text{route}}(r) = \mathbb{E}_{a_h, f_h \sim \mathcal{P}_{\mathcal{A} \times \mathcal{F}}} [l_{\text{route}}(r, a_h, f_h, u_h^{(t)}, u_h)]$. For analysis, we fix the iterate generation via teacher-forcing [Williams and Zipser, 1989, Lamb et al., 2016]: during training, the iterates fed to the router are produced by an oracle greedy rollout, not by the router's own past choices. Formally, with $u_h^{(0)} = 0_N$, for $t \geq 1$,

$$j_t^* \in \operatorname{argmin}_{j \in [K]} \left\| (I - C_j \circ \mathcal{L}_h^a)(e_h^{(t-1)}) \right\|_2^2, \quad u_h^{(t)} = u_h^{(t-1)} + C_{j_t^*} \left(f_h - \mathcal{L}_h^a u_h^{(t-1)} \right)$$

Thus, $\{u_h^{(t)}\}$ is a deterministic function of (a_h, f_h) . At each t , l_{route} is evaluated on $r(a_h, f_h, u_h^{(t)})$ which takes in the teacher-forced iterate. Finally, the greedy choice j_{t+1}^* is used to advance $u_h^{(t+1)}$. Thus the input distribution seen by r depends on (a_h, f_h) , not on the router's predictions. However, full teacher forcing induces a distributional mismatch at test time (exposure bias). In experiments, we mitigate this with scheduled sampling [Bengio et al., 2015]; see Section C for details.

Minimizing $\mathcal{R}_{\text{route}}(r)$ yields the following Bayes-Optimal Router:

$$r^*(a_h, f_h, u_h^{(t)}) \in \operatorname{argmin}_{j \in [K]} \left\| (I - C_j \circ \mathcal{L}_h^a)(e_h^{(t)}) \right\|_2^2 \quad (9)$$

which aligns with the update in Algorithm 1. Hence, l_{route} is consistent with learning the greedy rule.

5.1 Surrogate Loss

Since Equation (8) is discontinuous and non-convex, direct minimization is intractable in practice. We instead introduce a surrogate loss that (1) is convex, enabling efficient optimization; (2) upper bounds the original loss; and (3) is Bayes consistent, ensuring the Bayes optimal decision of the original loss is preserved upon minimization. Formally, a surrogate ϕ is considered to be Bayes consistent with respect to the loss l if

$$\lim_{n \rightarrow \infty} \mathcal{R}_\phi(f_n) - \mathcal{R}_\phi^* \implies \lim_{n \rightarrow \infty} \mathcal{R}_l(f_n) - \mathcal{R}_l^*$$

where $\mathcal{R}_l(f) = \mathbb{E}[l(f(X), Y)]$ and $\mathcal{R}_l^* = \inf_f \mathcal{R}_l(f)$. In other words, in the limit of infinite data, if the risk of a sequence of learned hypotheses $\{f_n\}$ converges to the optimal risk under ϕ , it also converges to the optimal risk with respect to the original loss l .

To define a surrogate loss for the routing problem, consider a set of scoring functions $\mathbf{g} = \{g_j\}_{j=1}^K$ with $g_j : \mathcal{A} \times \mathcal{F} \times \mathcal{U} \rightarrow \mathbb{R}$ and we define the router as $r(a, f, u^{(t)}) = \operatorname{argmax}_{j \in [K]} g_j(a, f, u^{(t)})$. For example, $\mathbf{g}$ can be a neural network with K outputs. Then, minimizing the following surrogate loss yields the same decision as minimizing Equation (8):

$$\Psi(\mathbf{g}, a_h, f_h, u_h^{(t)}, u_h) = - \sum_{j=1}^K \sum_{k=1}^K \tilde{c}_k(a_h, u_h^{(t)}, u_h) \mathbf{1}_{k \neq j} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{m=1}^K \exp(g_m(a_h, f_h, u_h^{(t)}))} \right) \quad (10)$$

where $\tilde{c}_j(a_h, u_h^{(t)}, u_h) = \|(I - C_j \circ \mathcal{L}_h^a)(u_h - u_h^{(t)})\|_2^2$. The Ψ -risk is denoted by $\mathcal{R}_\Psi(\mathbf{g}) = \mathbb{E}_{a_h, f_h \sim \mathcal{P}_{\mathcal{A} \times \mathcal{F}}}[\Psi(\mathbf{g}, a_h, f_h, u_h^{(t)}, u_h)]$. The convexity of Ψ with respect to $\mathbf{g}$ follows from the convexity of log-softmax function in its inputs. Moreover, Ψ upper bounds l_{route} up to a constant factor, and we refer the reader to Section B.2 for the proof. Finally, Theorem 5.1 shows that Ψ achieves Bayes consistency with respect to l_{route} ; the proof can be found in Section B.3.

Theorem 5.1. *Let $\tilde{c}_j(a_h, u_h^{(t)}, u_h) < \bar{E} < \infty$ for all $j \in [K]$. If there exists $j \in [K]$ such that $\tilde{c}_j(a_h, u_h^{(t)}, u_h) > E_{\min} > 0$, then, for any collection of solvers $\{C_j\}_{j=1}^K$ and linear discrete operator $\mathcal{L}_h^a$, Ψ is Bayes consistent surrogate for l_{route} .*

Theorem 5.1 is a cost-sensitive analogue of the classical Bayes-consistency of multiclass cross-entropy for 0-1 loss: in the infinite-sample limit, minimizing cross-entropy recovers the true conditional class probabilities, so the induced decision is Bayes optimal. Our result extends this to cross-entropy with instance-dependent weights $\sum_{k \neq j}^K \tilde{c}_k(a_h, u_h^{(t)}, u_h)$. The uniform upper bound holds when all preconditioning functions are error-damping. It is also reasonable to assume at least one solver cannot annihilate the error in one step, yielding the lower bound. Under these conditions, minimizing Ψ recovers the Bayes-optimal router of Equation (9), i.e., the greedy solution of Equation (5). Following the work of Mao et al. [2024], the proof uses standard conditional-risk calibration: we relate the excess risks of l_{route} and Ψ and take the infinite-sample limit.

6 Related Works

Hybrid PDE Solvers: Early data-driven solvers sought convergence guarantees by predicting parameters—e.g., preconditioning matrices, multi-grid smoothers or restriction matrices—within iterative schemes [Taghibakhshi et al., 2021, Caldana et al., 2024, Kopaničáková and Karniadakis, 2025, Huang et al., 2022, Katrutsa et al., 2020]. These works, however, do not leverage the neural surrogates’ ability to generalize across varying coefficients and forcings highlighted in Section 2.2 and thus, offer only modest speedups over classical solvers. HINTS [Zhang et al., 2024] introduced hybrid solvers that interleave a classical method with a pre-trained DeepONet on a fixed schedule (e.g., 24 Jacobi steps, then one DeepONet correction), achieving faster convergence than the standalone numerical solver. Subsequent works extend this idea to new geometries [Kahana et al., 2023] and analyze error mode damping, replacing DeepONet with alternatives such as MIONet [Jin et al., 2022] [Hu and Jin, 2025] or FNO [Li et al., 2020a, Cui et al., 2022]. However, these hybrid solvers are limited in two ways: they, firstly, only combine the trained surrogate with a *single* numerical solver, and secondly rely on a fixed, heuristic schedule. Our proposed method addresses these shortcomings, resulting in significant empirical improvements (Section 7).

Model Routing: Routing [Shnitzer et al., 2023, Hu et al., 2024, Ding et al., 2024, Huang et al., 2025] selects, for each input, a model from a fixed set to optimize a task metric under cost or latency constraints. Simple heuristics—e.g., thresholding a cheap model’s uncertainty estimates [Chuang et al., 2024, 2025]—often poorly balance the cost-accuracy tradeoff, motivating many systems to instead learn a router that maps inputs to the best model [Hari and Thomson, 2023, Mohammadshahi et al., 2024, Šakota et al., 2024]. We similarly learn a router, but over numerical and neural solvers for PDEs at the iteration level. Our work is the first to apply routing to the problem of learning hybrid PDE solvers, in contrast to prior approaches that use fixed schedules. Additionally, by exploiting

the algebraic structure of PDE solvers, we derive theoretical guarantees for our routing strategy (Section 4), unlike typical model-routing settings.

Mixture of Experts: Classical mixture-of-experts (MoE) [Jacobs et al., 1991, Jordan and Jacobs, 1994] uses a gating network to combine the outputs of multiple experts, trained jointly with the gate. In modern LLMs, MoE instead performs sparse, token-level routing to a subset of in-layer experts, enabling large capacity without proportional compute, typically with load-balancing mechanisms [Shazeer et al., 2017, Lepikhin et al., 2020, Fedus et al., 2022, Jiang et al., 2024]. Our method can be regarded as gating of a different kind: “experts” (solvers) are not jointly trained with the router, and a single router is reused across iterations, unlike MoE which commonly employs layer-specific gates.

7 Experiments

We empirically demonstrate the fast, uniform convergence of the approximate greedy router on the Poisson and Convection-Diffusion (ConvDiff) equations posed on the unit domain $D = [0, 1]^2$:

$$\forall \mathbf{x} \in D \quad \textbf{Poisson: } -\Delta u(\mathbf{x}) = f(\mathbf{x}) \quad \textbf{ConvDiff: } -\Delta u(\mathbf{x}) + 20 \frac{\partial}{\partial x_1} u(\mathbf{x}) + 20 \frac{\partial}{\partial x_2} u(\mathbf{x}) = f(\mathbf{x})$$

We impose periodic boundary conditions for both equations, and center f to satisfy the compatibility condition $\int_D f(\mathbf{x}) d\mathbf{x} = 0$; Dirichlet results are deferred to Section D.8. The domain D is discretized on a 31×31 uniform grid; results on a finer grid are provided in Section D.7. Data is sampled from a zero-mean Hierarchical Gaussian Random Field on the periodic domain with covariance operator $\alpha(-\Delta + \beta I)^{-\gamma}$, where α, β, γ vary across samples (See Section C). We run two experimental settings. In the first, we restrict to solver pairs ($K = 2$) and compare against HINTS and standalone classical solvers. In the second, we assess performance as the solver ensemble grows; since HINTS does not support this setting, we simply compare against individual solvers. In both cases, we consider a range of iterative methods described below. Performance is reported over 128 test samples via the mean final error $\|e_h^{(T)}\|_2$ and the mean area under the curve (AUC), defined as $\sum_{t=1}^T \|e_h^{(t)}\|_2$; the “curve” refers to the error over iterations. AUC characterizes the full convergence behavior, which is critical in practice where solutions must be reached in minimal time.

Paired Solver Experiments: We seek to optimally solve the aforementioned PDEs with access to a single numerical scheme and a trained DeepONet. In particular, we consider settings coupling the DeepONet with Jacobi, Gauss-Seidel (GS), and Symmetric Gauss-Seidel (SymGS) solvers. For each setup, we compare our learned router against the single-solver schedules (Jacobi only, GS only, and SymGS only) and HINTS variants (HINTS-Jacobi, HINTS-GS, HINTS-SymGS), where the DeepONet correction are applied every 24 iterations. We train LSTM-based routers using the loss in Equation (10) separately for each pairwise settings. The LSTM captures the sequential nature of routing decisions where the benefit of each action depends on the error trajectory and past choices. Training details of the DeepONet and the routers can be found in Section C. To ensure fairness, comparisons are restricted to methods with identical solver access, and are grouped by solver family (e.g., Jacobi-related methods). In addition, we include a *true greedy* oracle, which selects at each iteration the solver that yields the largest immediate error reduction. This oracle has access to the ground-truth error and is therefore not implementable in practice, but helps evaluate how well the learned router approximates the optimal policy. Each method is run for 300 iterations.

As shown in Table 1, the greedy router achieves the lowest final error and AUC across all solver families, outperforming their single-solver and HINTS counterparts. Moreover, its performance closely tracks that of the true greedy oracle, indicating that our surrogate-based training procedure effectively approximates the greedy strategy. This can be further seen in the routing visualizations in Section D.6, which demonstrate that the router learns qualitatively similar strategies to the oracle. The improvements over HINTS are particularly notable: while HINTS can improve over single-solver schedules, it exhibits oscillatory error behavior (See Figure 1) due to invoking the DeepONet at suboptimal times. In contrast, the greedy routers selectively applies updates that reduce error, resulting in near-monotone convergence. These gains arise from adapting routing decisions across *both* samples for a given PDE and PDEs. For instance, the neural operator is used more frequently in the convection–diffusion setting than in Poisson (Figure 2), a behavior that must be manually specified in HINTS but is learned automatically by our method. This shows that improvements stem from selective use of the learned component, rather than frequent invocation as in HINTS.

Table 1: Final error and AUC of L_2^2 error (lower is better). Values are mean ($\pm$ standard error) over 128 test instances; Error is reported in $\times 10^{-3}$. If a standard error is not shown, it is $< 10^{-3}$ in the reported units (raw $< 10^{-6}$). Bold indicates the best method within each solver family. True-Greedy denotes an oracle policy with access to exact error information

Equation	Poisson		ConvDiff	
Methods	$\ e_h^{(T)}\ \times 10^3$	AUC	$\ e_h^{(T)}\ \times 10^3$	AUC
Jacobi-related Solvers				
Jacobi Only	0.383 (1.029)	0.821 (2.154)	0.136 (0.364)	0.312 (0.788)
HINTS-Jacobi	0.759 (0.016)	0.393 (0.590)	0.447 (0.013)	0.202 (0.256)
Learned Greedy-Jacobi	0.054 (0.142)	0.165 (0.368)	0.033 (0.097)	0.098 (0.239)
True-Greedy-Jacobi	0.021 (0.018)	0.094 (0.170)	0.012 (0.012)	0.049 (0.091)
GS-related Solvers				
GS only	0.019 (0.051)	0.435 (1.141)	$< 10^{-3}$	0.088 (0.219)
HINTS-GS	0.724 (0.000)	0.325 (0.488)	0.456 (0.000)	0.130 (0.154)
Learned Greedy-GS	0.002 (0.004)	0.083 (0.152)	$< 10^{-3}$	0.031 (0.078)
True-Greedy-GS	0.001 (0.001)	0.057 (0.107)	$< 10^{-3}$	0.019 (0.038)
SymGS-related Solvers				
SymGS only	$< 10^{-3}$	0.227 (0.593)	$< 10^{-3}$	0.071 (0.178)
HINTS-SymGS	0.709 (0.000)	0.252 (0.380)	0.463 (0.000)	0.116 (0.131)
Learned Greedy-SymGS	$< 10^{-3}$	0.052 (0.102)	$< 10^{-3}$	0.022 (0.039)
True-Greedy-SymGS	$< 10^{-3}$	0.034 (0.066)	$< 10^{-3}$	0.016 (0.032)




Figure 1: Convergence histories for representative test instances. Rows: Convection Diffusion (top) and Poisson (bottom). Columns: Jacobi, Gauss–Seidel (GS), and Symmetric Gauss–Seidel (SymGS). Greedy yields near-monotone decay and the lowest errors, whereas HINTS shows sawtooth behaviors.

Solver Ensembles Experiments: We consider routing over a collection of more than two solvers. Specifically, we study ensembles $\mathcal{W}$ of increasing size, consisting of a trained DeepONet and a diverse set of numerical solvers, including Jacobi, GS, SymGS, Damped Jacobi ($\omega = 0.67$) and Successive Over-relaxation (SOR) with $\omega = 1.5$. Our goal is to evaluate whether enlarging the solver set yields gains beyond pairwise configurations. To this end, we compare Router($\text{NO} \cup \mathcal{W}$) against the best pairwise version of our method, Router($\text{NO} \cup \{\text{solver}\}$) for solver $\in \mathcal{W}$. As shown in Table 3, larger ensembles often yield improvements over both final error and AUC relative to




Figure 2: DeepONet usage across iterations for different greedy routing strategies on convection–diffusion (left) and Poisson (right). The variability across iterations highlights the non-uniform, sample-dependent nature of the learned routing strategy. See Section D.6 for detailed routing trajectories. For readability, we display the first 100 iterations (out of 300 total).

the best pairwise configuration, indicating that additional solver diversity can be leveraged. The router achieves these gains by learning to route to each member of the ensemble for a non-trivial proportion of the iterates, as measured in Section D.6. Finally, despite the increased size of the action space, the learned router continues to produce improvements, demonstrating robustness of both the training procedure and the convex surrogate of Section 5.1; true greedy comparisons are deferred to Section D.1. These results show that our method can scale to richer solver sets, enabling improved performance without sacrificing learnability.

Wall-clock time-to-solution: Iteration counts favor methods whose iterations are expensive, so we complement the results above with an end-to-end wall-clock study on a 128×128 grid (128^2 unknowns) for all five classical solvers and both PDEs, plus a third, harder PDE—anisotropic diffusion $-\epsilon \partial_{x_1}^2 u - \partial_{x_2}^2 u = f$ with $\epsilon = 10^{-2}$ on the same periodic domain and data, the standard case in which point smoothers and multigrid with point smoothing degrade; Section E details the protocol. Three ingredients make the comparison meaningful and the router deployable: (i) all classical solvers are implemented as $O(N^2)$ stencil or cached sparse-triangular sweeps (matching the dense implementations used elsewhere to machine precision), so the classical baseline is not artificially slowed; (ii) the DeepONet corrector acts on the residual through a 64×64 sensor grid with a Fourier trunk basis and is applied scale-equivariantly, so one call solves the smooth half of the spectrum to $\approx 10^{-6}$ at the cost of about 12 Jacobi or 3 Gauss–Seidel sweeps and never injects high-frequency error; and (iii) the router is made *cost-aware* through the cost-equalised macro-actions of Section 4, and the LSTM is replaced by a router over $6+K$ scalar features (log residual, its recent decay rate, the previous action, and call counts) with a two-layer MLP whose decision costs $\approx 5 \mu s$, trained with the surrogate of Section 5.1 to imitate the cost-aware greedy oracle. Table 2 reports the median wall-clock time to reach truncation-level relative error $\varepsilon = h^2$, the accuracy beyond which further algebraic refinement is not meaningful on an $N \times N$ grid. The learned router reaches it $238 \times$ – $1983 \times$ faster than the classical solver alone and $2.68 \times$ – $10.3 \times$ faster than HINTS with the published period $\tau=25$, in every one of the 10 solver–equation pairings (Table 2); it is also never slower than HINTS with the best period $\tau \in \{5, 10, 25, 50\}$ chosen *a posteriori* on the test set for that pairing ($1.21 \times$ – $3.22 \times$; Table 17), whereas the best τ itself varies across pairings and tolerances. The router tracks the cost-aware oracle within $1.06 \times$ in median time, and the iteration-based metrics of Table 1 carry over to the finer grid (Table 18). Figure 3 shows where the gain comes from: the router calls the corrector once at the very start (where the error is smooth and the corrector removes four orders of magnitude at once), spends a solver-dependent number of sweeps on the high-frequency band, and calls it again only if the smooth error re-emerges—between one and three calls in total—while HINTS spends $\tau-1$ sweeps before its first call and keeps calling the corrector when it no longer helps. At tolerances far below h^2 the undamped-Jacobi pairing is limited by the near-Nyquist modes that neither component damps (Table 21), but the router degrades gracefully there because it stops selecting the corrector, whereas fixed schedules keep paying for it (Section E). Against the classical methods a practitioner would use on these problems (Table 25), the router with its best stationary pairing is $3.62 \times$ – $3.71 \times$ faster than geometric multigrid alone, $3.85 \times$ – $5.31 \times$ faster than the best multigrid-preconditioned Krylov method, and only the FFT direct solve—a method specific to constant-coefficient periodic problems, which we use to compute ground truth—is faster, by $2.87 \times$ – $2.91 \times$; routing over $\{\text{NO}, \text{multigrid}\}$ is itself $1.93 \times$ – $2.03 \times$ faster than multigrid alone. The gains persist on 256^2 grids for every pairing and on 512^2 grids for the GS, SOR and multigrid pairings (Table 26); the one exception is undamped Jacobi at 512^2 , where the corrector’s fixed band leaves the smoother a stalled high-frequency band, every schedule needs the same ≈ 80 sweeps, and the router only matches (Poisson) or, on convection–diffusion, falls short of a fixed schedule (Section E.4). All 128^2 and 256^2 comparisons are significant at $p < 0.01$ (paired Wilcoxon over instances) and stable across five independent router-training seeds (Section E.6). The same construction extends to solver ensembles (Table 23): over the four ensembles of Table 3 and both PDEs, the router over $\text{NO} \cup \mathcal{W}$ matches the best pairwise router of its members to within $\pm 15\%$ (ratio of medians $0.82 \times$ – $1.14 \times$) without knowing in advance which member is fastest, and is $380 \times$ – $1512 \times$ faster than the best member solver alone; the remaining gap to the ensemble oracle, which is faster than every pairwise router, is imitation error in choosing among near-equivalent smoothers (Section E).

Additional experiments are provided in Section D.

Table 2: Median wall-clock time to truncation-level relative error $\varepsilon = h^2$ on the 128×128 grid, 64 test instances per cell (paired median speedup over the solver-only baseline in parentheses). “HINTS (best τ)” is the best of $\tau \in \{5, 10, 25, 50\}$ chosen per cell on the test set itself. The greedy oracle is the cost-agnostic Algorithm 1, the cost-aware oracle is Algorithm 1 on cost-equalised macro-actions; both use the true error and are not deployable. Bold marks the fastest deployable method in each row; the learned router pays for all of its features and decisions.

Equation	Solver	Solver only	HINTS ($\tau=25$)	HINTS (best τ)	Greedy oracle	Cost-aware oracle	Learned router (ours)
Poisson	Jacobi	1.15 s	2.65 ms (412 $\times$)	1.10 ms (984 $\times$; $\tau=5$)	854 μ s (1283 $\times$)	942 μ s (1199 $\times$)	987 μs (1154$\times$)
	Jacobi (0.67)	1.62 s	2.71 ms (621 $\times$)	1.13 ms (1464 $\times$; $\tau=5$)	915 μ s (1904 $\times$)	922 μ s (1836 $\times$)	912 μs (1863$\times$)
	GS	1.83 s	6.65 ms (277 $\times$)	1.99 ms (906 $\times$; $\tau=5$)	960 μ s (1872 $\times$)	953 μ s (1892 $\times$)	1.01 ms (1809$\times$)
	SymGS	1.52 s	10.3 ms (149 $\times$)	2.60 ms (585 $\times$; $\tau=5$)	1.09 ms (1395 $\times$)	1.13 ms (1330 $\times$)	1.13 ms (1331$\times$)
	SOR (1.5)	600.9 ms	12.2 ms (49.4 $\times$)	3.37 ms (180 $\times$; $\tau=5$)	1.03 ms (583 $\times$)	1.02 ms (582 $\times$)	1.02 ms (576$\times$)
ConvDiff	Jacobi	1.51 s	3.44 ms (436 $\times$)	1.28 ms (1145 $\times$; $\tau=5$)	992 μ s (1532 $\times$)	1.15 ms (1319 $\times$)	1.14 ms (1317$\times$)
	Jacobi (0.67)	2.22 s	3.40 ms (656 $\times$)	1.31 ms (1670 $\times$; $\tau=5$)	1.10 ms (2036 $\times$)	1.08 ms (1974 $\times$)	1.10 ms (1983$\times$)
	GS	1.63 s	8.27 ms (198 $\times$)	3.60 ms (453 $\times$; $\tau=5$)	1.23 ms (1341 $\times$)	1.32 ms (1222 $\times$)	1.35 ms (1243$\times$)
	SymGS	1.56 s	11.1 ms (141 $\times$)	2.96 ms (529 $\times$; $\tau=5$)	1.25 ms (1254 $\times$)	1.27 ms (1236 $\times$)	1.28 ms (1211$\times$)
	SOR (1.5)	383.6 ms	13.6 ms (28.0 $\times$)	3.64 ms (104 $\times$; $\tau=5$)	1.39 ms (273 $\times$)	1.63 ms (240 $\times$)	1.59 ms (238$\times$)




Figure 3: Corrector usage on the 128×128 grid: fraction of test runs that execute a corrector call at each iteration, for the learned router, the cost-aware oracle and HINTS ($\tau=25$), for every solver pairing (columns) and both equations (rows).

8 Discussion

We have introduced an adaptive method for selecting solvers that efficiently minimizes the final error of a PDE in iterative methods, opening many directions for future work. Our current DeepONet is trained without accounting for its downstream role in correction term prediction; jointly training the ML solver and router could yield larger gains. Another avenue is to use reinforcement learning to learn a cost-aware routing strategy that optimizes error under compute budgets; Sections 4 and E show that a myopic cost-aware variant of the greedy rule—Algorithm 1 on cost-equalised macro-actions—already delivers uniform wall-clock gains, and RL could extend it to non-myopic budgeted routing. RL would additionally enable extending the ensemble routing to *continuous* parameterization of solvers. Finally, framing routing as an online learning problem could enable adaptation to unknown deployment conditions.

References

- Eugenia Kalnay. *Atmospheric modeling, data assimilation and predictability*. Cambridge university press, 2003.
- Peter Bauer, Alan Thorpe, and Gilbert Brunet. The quiet revolution of numerical weather prediction. *Nature*, 525(7567):47–55, 2015.
- Andrew Staniforth and Jean Côté. Semi-lagrangian integration schemes for atmospheric models—a review. *Monthly weather review*, 119(9):2206–2223, 1991.
- John David Anderson. *Hypersonic and high temperature gas dynamics*. Aiaa, 1989.

Table 3: Final error and AUC of squared L^2 error for ensembles of increasing size. $\mathcal{W}$ denotes the set of numerical solvers and NO the neural operator (DeepONet). Each Router($\text{NO} \cup \mathcal{W}$) is compared against the best pairwise routing using our method, i.e., Router($\text{NO} \cup \{\text{solver}\}$) for solver $\in \mathcal{W}$. Values are mean ($\pm$ s.e.) over 128 test instances; Error is reported in $\times 10^{-3}$. p -values from paired one-sided t -tests comparing the AUC of the ensemble to that of the best pairwise router.

$\mathcal{W}$	Method	Poisson			ConvDiff		
		$\ e_h^{(T)}\ \times 10^3$	AUC	p -value (vs pairwise)	$\ e_h^{(T)}\ \times 10^3$	AUC	p -value (vs pairwise)
{Jacobi, GS}	Best Router($\text{NO} \cup \{\text{solver}\}$)	0.002 (0.004)	0.083 (0.152)	-	$< 10^{-3}$	0.031 (0.078)	-
	Router($\text{NO} \cup \mathcal{W}$)	0.002 (0.002)	0.078 (0.132)	$< 10^{-3}$	$< 10^{-3}$	0.021 (0.040)	0.004
{Jacobi, GS, SymGS}	Best Router($\text{NO} \cup \{\text{solver}\}$)	$< 10^{-3}$	0.052 (0.102)	-	$< 10^{-3}$	0.022 (0.039)	-
	Router($\text{NO} \cup \mathcal{W}$)	$< 10^{-3}$	0.041 (0.091)	$< 10^{-3}$	$< 10^{-3}$	0.018 (0.035)	$< 10^{-3}$
{Jacobi, GS, SymGS, Jacobi (0.67)}	Best Router($\text{NO} \cup \{\text{solver}\}$)	$< 10^{-3}$	0.052 (0.102)	-	$< 10^{-3}$	0.022 (0.039)	-
	Router($\text{NO} \cup \mathcal{W}$)	0.002 (0.003)	0.046 (0.083)	0.004	$< 10^{-3}$	0.019 (0.037)	0.002
{Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	Best Router($\text{NO} \cup \{\text{solver}\}$)	$< 10^{-3}$	0.052 (0.143)	-	$< 10^{-3}$	0.011 (0.030)	-
	Router($\text{NO} \cup \mathcal{W}$)	$< 10^{-3}$	0.043 (0.082)	0.03	$< 10^{-3}$	0.008 (0.019)	0.004

- 424 Fredi Tröltzsch. *Optimal control of partial differential equations: theory, methods, and applications*,
425 volume 112. American Mathematical Soc., 2010.
- 426 Sylvain Baillet, John C Mosher, and Richard M Leahy. Electromagnetic brain mapping. *IEEE Signal*
427 *processing magazine*, 18(6):14–30, 2001.
- 428 Roberta Grech, Tracey Cassar, Joseph Muscat, Kenneth P Camilleri, Simon G Fabri, Michalis
429 Zervakis, Petros Xanthopoulos, Vangelis Sakkalis, and Bart Vanrumste. Review on solving the
430 inverse problem in eeg source analysis. *Journal of neuroengineering and rehabilitation*, 5:1–33,
431 2008.
- 432 Gordon D Smith. *Numerical solution of partial differential equations: finite difference methods*.
433 Oxford university press, 1985.
- 434 Randall J LeVeque. *Finite difference methods for ordinary and partial differential equations: steady-*
435 *state and time-dependent problems*. SIAM, 2007.
- 436 Thomas JR Hughes. *The finite element method: linear static and dynamic finite element analysis*.
437 Courier Corporation, 2003.
- 438 Klaus-Jürgen Bathe. *Finite element procedures*. Klaus-Jurgen Bathe, 2006.
- 439 Susanne C Brenner. *The mathematical theory of finite element methods*. Springer, 2008.
- 440 Yousef Saad. *Iterative methods for sparse linear systems*. SIAM, 2003.
- 441 Nikola Kovachki, Zongyi Li, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew
442 Stuart, and Anima Anandkumar. Neural operator: Learning maps between function spaces with
443 applications to pdes. *Journal of Machine Learning Research*, 24(89):1–97, 2023.
- 444 Tianping Chen and Hong Chen. Universal approximation to nonlinear operators by neural networks
445 with arbitrary activation functions and its application to dynamical systems. *IEEE transactions on*
446 *neural networks*, 6(4):911–917, 1995.
- 447 Lizuo Liu and Wei Cai. Multiscale deepnet for nonlinear operators in oscillatory function spaces for
448 building seismic wave responses. *arXiv preprint arXiv:2111.04860*, 2021.
- 449 Xinliang Liu, Bo Xu, Shuhao Cao, and Lei Zhang. Mitigating spectral bias for the multiscale operator
450 learning. *Journal of Computational Physics*, 506:112944, 2024.
- 451 Zhilin You, Zhenli Xu, and Wei Cai. Mscalefno: Multi-scale fourier neural operator learning for
452 oscillatory function spaces. *arXiv preprint arXiv:2412.20183*, 2024.
- 453 Siavash Khodakarami, Vivek Oommen, Aniruddha Bora, and George Em Karniadakis. Mitigating
454 spectral bias in neural operators via high-frequency scaling for physical systems. *arXiv preprint*
455 *arXiv:2503.13695*, 2025.
- 456 Zhi-Qin John Xu, Lulu Zhang, and Wei Cai. On understanding and overcoming spectral biases of
457 deep neural network learning methods for solving pdes. *arXiv preprint arXiv:2501.09987*, 2025.

458 Nasim Rahaman, Aristide Baratin, Devansh Arpit, Felix Draxler, Min Lin, Fred Hamprecht, Yoshua
459 Bengio, and Aaron Courville. On the spectral bias of neural networks. In *International conference*
460 *on machine learning*, pages 5301–5310. PMLR, 2019.

461 Zhi-Qin John Xu, Yaoyu Zhang, Tao Luo, Yanyang Xiao, and Zheng Ma. Frequency principle:
462 Fourier analysis sheds light on deep neural networks. *arXiv preprint arXiv:1901.06523*, 2019.

463 Tao Luo, Zheng Ma, Zhi-Qin John Xu, and Yaoyu Zhang. Theory of the frequency principle for
464 general deep neural networks. *arXiv preprint arXiv:1906.09235*, 2019.

465 Enrui Zhang, Adar Kahana, Alena Kopaničáková, Eli Turkel, Rishikesh Ranade, Jay Pathak, and
466 George Em Karniadakis. Blending neural operators and relaxation methods in pde numerical
467 solvers. *Nature Machine Intelligence*, pages 1–11, 2024.

468 John P Boyd. *Chebyshev and Fourier spectral methods*. Courier Corporation, 2001.

469 Claudio Canuto, M. Yousuff Hussaini, Alfio Quarteroni, and Thomas A. Zang. *Spectral Methods:*
470 *Fundamentals in Single Domains*. Springer, 2006. ISBN 9783540307264.

471 Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew
472 Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations.
473 *arXiv preprint arXiv:2010.08895*, 2020a.

474 Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Andrew Stuart, Kaushik
475 Bhattacharya, and Anima Anandkumar. Multipole graph neural operator for parametric partial
476 differential equations. *Advances in Neural Information Processing Systems*, 33:6755–6766, 2020b.

477 Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning
478 nonlinear operators via deeponet based on the universal approximation theorem of operators.
479 *Nature machine intelligence*, 3(3):218–229, 2021.

480 George L Nemhauser, Laurence A Wolsey, and Marshall L Fisher. An analysis of approximations for
481 maximizing submodular set functions—i. *Mathematical programming*, 14(1):265–294, 1978.

482 Edo Liberty and Maxim Sviridenko. Greedy minimization of weakly supermodular set functions.
483 In *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques*
484 *(APPROX/RANDOM 2017)*, pages 19–1. Schloss Dagstuhl–Leibniz-Zentrum für Informatik, 2017.

485 Louenas Bounia and Frederic Koriche. Approximating probabilistic explanations via supermodular
486 minimization. In *Uncertainty in Artificial Intelligence*, pages 216–225. PMLR, 2023.

487 Abhimanyu Das and David Kempe. Approximate submodularity and its applications: Subset selection,
488 sparse approximation and dictionary selection. *Journal of Machine Learning Research*, 19(3):
489 1–34, 2018.

490 Uriel Feige, Vahab S Mirrokni, and Jan Vondrák. Maximizing non-monotone submodular functions.
491 *SIAM Journal on Computing*, 40(4):1133–1153, 2011.

492 Andrew An Bian, Joachim M Buhmann, Andreas Krause, and Sebastian Tschieschek. Guarantees for
493 greedy maximization of non-submodular functions with applications. In *International conference*
494 *on machine learning*, pages 498–507. PMLR, 2017.

495 Chris Harshaw, Moran Feldman, Justin Ward, and Amin Karbasi. Submodular maximization beyond
496 non-negativity: Guarantees, fast algorithms, and applications. In *International Conference on*
497 *Machine Learning*, pages 2634–2643. PMLR, 2019.

498 Matthew Streeter and Daniel Golovin. An online algorithm for maximizing submodular functions.
499 *Advances in Neural Information Processing Systems*, 21, 2008.

500 Saeed Alaei, Ali Makhdoumi, and Azarakhsh Malekian. Maximizing sequence-submodular functions
501 and its application to online advertising. *Management Science*, 67(10):6030–6054, 2021.

502 Zhenliang Zhang, Edwin KP Chong, Ali Pezeshki, and William Moran. String submodular functions
503 with curvature constraints. *IEEE Transactions on Automatic Control*, 61(3):601–616, 2015.

504 Sara Bernardini, Fabio Fagnani, and Chiara Piacentini. Through the lens of sequence submodularity.
505 In *Proceedings of the International Conference on Automated Planning and Scheduling*, volume 30,
506 pages 38–47, 2020.

507 Brandon Van Over, Bowen Li, Edwin KP Chong, and Ali Pezeshki. A performance bound for
508 the greedy algorithm in a generalized class of string optimization problems. *arXiv preprint*
509 *arXiv:2409.05020*, 2024.

510 Sebastian Tschiatschek, Adish Singla, and Andreas Krause. Selecting sequences of items via
511 submodular maximization. In *Proceedings of the AAAI Conference on Artificial Intelligence*,
512 volume 31, 2017.

513 Henry Gouk, Eibe Frank, Bernhard Pfahringer, and Michael J Cree. Regularisation of neural networks
514 by enforcing lipschitz continuity. *Machine Learning*, 110(2):393–416, 2021.

515 Ronald J Williams and David Zipser. A learning algorithm for continually running fully recurrent
516 neural networks. *Neural computation*, 1(2):270–280, 1989.

517 Alex M Lamb, Anirudh Goyal ALIAS PARTH GOYAL, Ying Zhang, Saizheng Zhang, Aaron C
518 Courville, and Yoshua Bengio. Professor forcing: A new algorithm for training recurrent networks.
519 *Advances in neural information processing systems*, 29, 2016.

520 Samy Bengio, Oriol Vinyals, Navdeep Jaitly, and Noam Shazeer. Scheduled sampling for sequence
521 prediction with recurrent neural networks. *Advances in neural information processing systems*, 28,
522 2015.

523 Anqi Mao, Mehryar Mohri, and Yutao Zhong. Regression with multi-expert deferral. In *International*
524 *Conference on Machine Learning*, pages 34738–34759. PMLR, 2024.

525 Ali Taghibakhshi, Scott MacLachlan, Luke Olson, and Matthew West. Optimization-based algebraic
526 multigrid coarsening using reinforcement learning. *Advances in neural information processing*
527 *systems*, 34:12129–12140, 2021.

528 Matteo Caldana, Paola F Antonietti, et al. A deep learning algorithm to accelerate algebraic multigrid
529 methods in finite element solvers of 3d elliptic pdes. *Computers & Mathematics with Applications*,
530 167:217–231, 2024.

531 Alena Kopaničáková and George Em Karniadakis. Deeponet based preconditioning strategies for
532 solving parametric linear systems of equations. *SIAM Journal on Scientific Computing*, 47(1):
533 C151–C181, 2025.

534 Ru Huang, Ruipeng Li, and Yuanzhe Xi. Learning optimal multigrid smoothers via neural networks.
535 *SIAM Journal on Scientific Computing*, 45(3):S199–S225, 2022.

536 Alexandr Katrutsa, Talgat Daulbaev, and Ivan Oseledets. Black-box learning of multigrid parameters.
537 *Journal of Computational and Applied Mathematics*, 368:112524, 2020.

538 Adar Kahana, Enrui Zhang, Somdatta Goswami, George Karniadakis, Rishikesh Ranade, and Jay
539 Pathak. On the geometry transferability of the hybrid iterative numerical solver for differential
540 equations. *Computational Mechanics*, 72(3):471–484, 2023.

541 Pengzhan Jin, Shuai Meng, and Lu Lu. Mionet: Learning multiple-input operators via tensor product.
542 *SIAM Journal on Scientific Computing*, 44(6):A3490–A3514, 2022.

543 Jun Hu and Pengzhan Jin. A hybrid iterative method based on mionet for pdes: Theory and numerical
544 examples. *Mathematics of Computation*, 2025.

545 Chen Cui, Kai Jiang, Yun Liu, and Shi Shu. Fourier neural solver for large sparse linear algebraic
546 systems. *Mathematics*, 10(21):4014, 2022.

547 Tal Shnitzer, Anthony Ou, Mírian Silva, Kate Soule, Yuekai Sun, Justin Solomon, Neil Thompson,
548 and Mikhail Yurochkin. Large language model routing with benchmark datasets. *arXiv preprint*
549 *arXiv:2309.15789*, 2023.

550 Qitian Jason Hu, Jacob Bieker, Xiuyu Li, Nan Jiang, Benjamin Keigwin, Gaurav Ranganath, Kurt
551 Keutzer, and Shriyash Kaustubh Upadhyay. Routerbench: A benchmark for multi-llm routing
552 system. *arXiv preprint arXiv:2403.12031*, 2024.

553 Dujian Ding, Ankur Mallick, Chi Wang, Robert Sim, Subhabrata Mukherjee, Victor Ruhle, Laks VS
554 Lakshmanan, and Ahmed Hassan Awadallah. Hybrid llm: Cost-efficient and quality-aware query
555 routing. *arXiv preprint arXiv:2404.14618*, 2024.

556 Zhongzhan Huang, Guoming Ling, Yupei Lin, Yandong Chen, Shanshan Zhong, Hefeng Wu, and
557 Liang Lin. Routereval: A comprehensive benchmark for routing llms to explore model-level
558 scaling up in llms. *arXiv preprint arXiv:2503.10657*, 2025.

559 Yu-Neng Chuang, Prathusha Kameswara Sarma, Parikshit Gopalan, John Boccio, Sara Bolouki,
560 Xia Hu, and Helen Zhou. Learning to route llms with confidence tokens. *arXiv preprint*
561 *arXiv:2410.13284*, 2024.

562 Yu-Neng Chuang, Leisheng Yu, Guanchu Wang, Lizhe Zhang, Zirui Liu, Xuanning Cai, Yang Sui,
563 Vladimir Braverman, and Xia Hu. Confident or seek stronger: Exploring uncertainty-based
564 on-device llm routing from benchmarking to generalization. *arXiv preprint arXiv:2502.04428*,
565 2025.

566 Surya Narayanan Hari and Matt Thomson. Tryage: Real-time, intelligent routing of user prompts to
567 large language models. *arXiv preprint arXiv:2308.11601*, 2023.

568 Alireza Mohammadshahi, Arshad Rafiq Shaikh, and Majid Yazdani. Routoo: Learning to route to
569 large language models effectively. *arXiv preprint arXiv:2401.13979*, 2024.

570 Marija Šakota, Maxime Peyrard, and Robert West. Fly-swat or cannon? cost-effective language
571 model choice via meta-modeling. In *Proceedings of the 17th ACM International Conference on*
572 *Web Search and Data Mining*, pages 606–615, 2024.

573 Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. Adaptive mixtures of
574 local experts. *Neural computation*, 3(1):79–87, 1991.

575 Michael I Jordan and Robert A Jacobs. Hierarchical mixtures of experts and the em algorithm. *Neural*
576 *computation*, 6(2):181–214, 1994.

577 Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and
578 Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *arXiv*
579 *preprint arXiv:1701.06538*, 2017.

580 Dmitry Lepikhin, Hyoungho Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang,
581 Maxim Krikun, Noam Shazeer, and Zhifeng Chen. Gshard: Scaling giant models with conditional
582 computation and automatic sharding. *arXiv preprint arXiv:2006.16668*, 2020.

583 William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter
584 models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39,
585 2022.

586 Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris
587 Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al.
588 Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.

589 Anqi Mao, Mehryar Mohri, and Yutao Zhong. Cross-entropy loss functions: Theoretical analysis and
590 applications. In *International conference on Machine learning*, pages 23803–23828. pmlr, 2023.

591 Michael C Mozer. A focused backpropagation algorithm for temporal pattern recognition. In
592 *Backpropagation*, pages 137–169. Psychology Press, 2013.

593 Anthony J Robinson and Frank Fallside. *The utility driven dynamic error propagation network*,
594 volume 11. University of Cambridge Department of Engineering Cambridge, 1987.

595 Paul J Werbos. Generalization of backpropagation with application to a recurrent gas market model.
596 *Neural networks*, 1(4):339–356, 1988.

597 Lu Lu, Xuhui Meng, Shengze Cai, Zhiping Mao, Somdatta Goswami, Zhongqiang Zhang, and
 598 George Em Karniadakis. A comprehensive and fair comparison of two neural operators (with practical
 599 extensions) based on FAIR data. *Computer Methods in Applied Mechanics and Engineering*,
 600 393:114778, 2022.

601 Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured
 602 prediction to no-regret online learning. In *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, pages 627–635. JMLR Workshop and Conference
 603 Proceedings, 2011.
 604

605 A Proofs for Section 4

606 A.1 Proof of Proposition A.1

607 **Proposition A.1.** Any prefix monotonically non-increasing sequence supermodular function g is
 608 weakly supermodular with respect to all sequences $S \in \Omega^*$ with $\alpha(S) = 1$

609 *Proof.* This proof is adapted from Liberty and Sviridenko [2017].

610 If g is sequence supermodular then,

$$\begin{aligned} & g(S) - g(S \oplus S') \\ &= \sum_{i=1}^{|S'|} g(S \oplus (S'_1, \dots, S'_{i-1})) - g(S \oplus (S'_1, \dots, S'_i)) \\ &\stackrel{(a)}{\leq} \sum_{i=1}^{|S'|} g(S) - g(S \oplus S'_i) \\ &\leq |S'| \max_{i \in [|S'|]} g(S) - g(S \oplus S'_i) \end{aligned}$$

611 (a) by supermodularity

612

□

613 A.2 Proof of Theorem 4.1

614 **Theorem 4.1.** Let $g : \Omega^* \rightarrow \mathbb{R}$ be a weakly supermodular function with respect to the optimal
 615 solution $O = \arg \min_{S \in \Omega^T} h(S)$ with a supermodularity ratio of $\alpha(O)$ and postfix monotonicity. Let
 616 the greedy solution of length T be S^T . If $\phi_T(\alpha) = (1 - \frac{1}{\alpha T})^T$, then

$$g(S^T) \leq (1 - \phi_T(\alpha(O))) g(O) + \phi_T(\alpha(O)) g(\emptyset)$$

617 *Proof.* This proof strategy is inspired by Streeter and Golovin [2008] and Liberty and Sviridenko
 618 [2017]

$$\begin{aligned} g(S^t) - g(O) &\stackrel{(a)}{\leq} g(S^t) - g(S^t \oplus O) \\ &= \sum_{i=1}^{|O|} g(S^t \oplus (o_1, \dots, o_{i-1})) - g(S^t \oplus (o_1, \dots, o_i)) \\ &\stackrel{(b)}{\leq} \alpha(O) \sum_{i=1}^{|O|} g(S^t) - g(S^t \oplus o_i) \\ &\leq \alpha(O) |O| \max_{i \in [|O|]} g(S^t) - g(S^t \oplus o_i) \\ &\leq \alpha(O) T g(S^t) - \alpha(O) T \min_{\omega \in \Omega} g(S^t \oplus \omega) \\ &= \alpha(O) T g(S^t) - \alpha(O) T g(S^{t+1}) \end{aligned}$$

619 (a) by μ - postfix monotonicity, (b) by supermodularity.

620 After rearranging the inequality, we get:

$$\begin{aligned} g(S^{t+1}) &\leq \frac{1}{\alpha(O)T} (g(O) - (\alpha(O)T - 1)g(S^t)) \\ &= \frac{1}{\alpha(O)T}g(O) + \left(1 - \frac{1}{\alpha(O)T}\right)g(S^t) \end{aligned}$$

621 When recursively applying this inequality, we get:

$$\begin{aligned} g(S^T) &\leq \frac{1}{\alpha(O)T}g(O) \sum_{i=0}^{T-1} \left(1 - \frac{1}{\alpha(O)T}\right)^i + \left(1 - \frac{1}{\alpha(O)T}\right)^T g(\emptyset) \\ &= \left(1 - \left(1 - \frac{1}{\alpha(O)T}\right)^T\right)g(O) + \left(1 - \frac{1}{\alpha(O)T}\right)^T g(\emptyset) \end{aligned}$$

622

□

623 A.3 Proof of Proposition 4.2

624 **Proposition 4.2.** Suppose that for all $j \in [K]$, the error propagation function $I - C_j \circ \mathcal{L}_h^a$ is
 625 ρ_j -Lipschitz continuous with $\rho_j < 1$, and that $(I - C_j \circ \mathcal{L}_h^a)(0_N) = 0_N$. Then, the function h is
 626 weakly supermodular with respect to the optimal solution O , with

$$\alpha(O) = \max \left\{ \frac{4}{T - \sum_{i=1}^T \rho_{O_i}^2}, 1 \right\}$$

627 Furthermore, if $I - C_j \circ \mathcal{L}_h^a$ is invertible for all $j \in [K]$, h is also postfix monotonically non-increasing.

628 *Proof.* For brevity, we use the notation $(g_1 \circ \dots \circ g_T)(x) = \circ_{t=1}^T g_t(x)$, where composition is
 629 applied from right to left so that g_T acts first. In this proof, we use a few properties of Lipschitz
 630 continuous functions:

- 631 • **Property 1:** If g is ρ -Lipschitz continuous and $g(0) = 0$, then $\|g(x)\|_2 = \|g(x) - 0\|_2 =$
 632 $\|g(x) - g(0)\|_2 \leq \rho\|x - 0\|_2 = \rho\|x\|_2$
- 633 • **Property 2:** If g_1 and g_2 are Lipschitz continuous functions with Lipschitz constants of ρ_1
 634 and ρ_2 respectively, the Lipschitz constant of $g_1 + g_2$ and $g_1 - g_2$ is $\rho_1 + \rho_2$.
- 635 • **Property 3:** If g_1 and g_2 are Lipschitz continuous functions with Lipschitz constants of ρ_1
 636 and ρ_2 respectively, the Lipschitz constant of $g_1 \circ g_2$ is $\rho_1\rho_2$.

637 In order to prove weakly- α -supermodularity, we must first prove prefix monotonicity.

638 **Prefix monotonicity:** Let $S \preceq S'$ where $S' = S \oplus N$.

$$\begin{aligned} h(S') &= \left\| \circ_{t=1}^{|S'|} (I - C_{S'_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\ &= \left\| \circ_{t=|S|+1}^{|S|+1} (I - C_{S'_t} \circ \mathcal{L}_h^a) \circ \circ_{t=1}^{|S|} (I - C_{S'_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\ &\stackrel{(a)}{\leq} \left(\prod_{t=|S|+1}^{|S'|} \rho_{S'_t}^2 \right) \left\| \circ_{t=1}^{|S|} (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\ &\leq h(S) \end{aligned}$$

639 (a) by Property 1

640 **Weak supermodularity:** We will upper bound $\alpha(O)$ by providing an upper bound for $h(S) -$

641 $h(S \oplus O)$ and a lower bound for $\sum_{i=1}^T h(S) - h(S \oplus O_i)$.

$$\begin{aligned}
h(S) - h(S \oplus O) &= \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 - \left\| \circ_{t=|O|}^1 (I - C_{O_t} \circ \mathcal{L}_h^a) \circ \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\
&\stackrel{(a)}{\leq} \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) - \circ_{t=|O|}^1 (I - C_{O_t} \circ \mathcal{L}_h^a) \circ \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\
&= \left\| \left(I - \circ_{t=|O|}^1 (I - C_{O_t} \circ \mathcal{L}_h^a) \right) \circ \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\
&\stackrel{(b)}{\leq} \left(1 + \prod_{t=1}^{|O|} \rho_{O_t} \right)^2 \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\
&\stackrel{(c)}{\leq} 4 \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2
\end{aligned}$$

642 (a) by reverse triangle property and $h(S) - h(S \oplus S') > 0$ by prefix monotonicity, (b) since the

643 Lipschitz constant of $I - \circ_{t=|S'|}^1 (I - C_{S'_t} \circ \mathcal{L}_h^a)$ is $1 + \prod_{t=1}^{|S'|} \rho_{S'_t}$ by Property 2 and 3, (c) since

644 $\rho_j < 1$

645 To lower bound $\sum_{i=1}^{|O|} h(S) - h(S \oplus O_i)$

$$\begin{aligned}
\sum_{i=1}^{|O|} h(S) - h(S \oplus O_i) &= \sum_{i=1}^{|O|} \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 - \left\| (I - C_{O_i} \circ \mathcal{L}_h^a) \circ \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\
&\geq \sum_{i=1}^{|O|} \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 - \rho_{O_i}^2 \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \\
&= \left\| \circ_{t=|S|}^1 (I_N - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \left(T - \sum_{i=1}^T \rho_{O_i}^2 \right)
\end{aligned}$$

646 Finally,

$$\begin{aligned}
\frac{h(S) - h(S \oplus O)}{T \max_i h(S) - h(S \oplus O_i)} &\leq \max \left\{ \frac{4 \left\| \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2}{\left\| \circ_{t=|S|}^1 (I_N - C_{S_t} \circ \mathcal{L}_h^a) \left(e_h^{(0)} \right) \right\|_2^2 \left(T - \sum_{i=1}^T \rho_{O_i}^2 \right)}, 1 \right\} \\
&= \max \left\{ \frac{4}{T - \sum_{i=1}^T \rho_{O_i}^2}, 1 \right\}
\end{aligned}$$

647 **Postfix monotonicity:** Let $S' = S \oplus N$.

$$\begin{aligned}
h(S') &= \left\| \circ_{t=|S'|}^1 (I - C_{S'_t} \circ \mathcal{L}_h) e_h^{(0)} \right\|_2^2 \\
&= \left\| \circ_{t=|N|}^1 (I - C_{N_t} \circ \mathcal{L}_h) \circ \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h) e_h^{(0)} \right\|_2^2 \\
&\stackrel{(a)}{=} \left\| \circ_{t=|N|}^1 (I - C_{N_t} \circ \mathcal{L}_h) \circ \circ_{t=|S|}^1 (I - C_{S_t} \circ \mathcal{L}_h) \circ \left(\circ_{t=|N|}^1 (I - C_{N_t} \circ \mathcal{L}_h) \right)^{-1} \circ \circ_{t=|N|}^1 (I - C_{N_t} \circ \mathcal{L}_h) e_h^{(0)} \right\|_2^2 \\
&\leq \prod_{t=1}^{|N|} \rho_{N_t}^2 \prod_{t=1}^{|S|} \rho_{S_t}^2 \prod_{t=1}^{|N|} \rho_{N_t}^{-2} \left\| \circ_{t=|N|}^1 (I - C_{N_t} \circ \mathcal{L}_h) e_h^{(0)} \right\|_2^2 \\
&\leq h(N)
\end{aligned}$$

648 (a) due the invertibility of $I_N - C_j \mathcal{L}_h$

649

□

650 **A.4 Proof of Theorem A.2**

651 **Lemma A.2.** Let $(I - C_j \mathcal{L}_h^a) = P \Lambda_j P^{-1}$ where P is an orthogonal matrix and $\Lambda_j =$
 652 $\text{diag}(\lambda_{j1}, \dots, \lambda_{jN})$. If $P^{-1} e_h^{(0)} = z$, then the following equality holds:

$$h(S) = \sum_{i=1}^N z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S)} \quad (11)$$

653 where $m_j(S) = \sum_{t=1}^{|S|} \mathbf{1}_{S_t=j}$

Proof.

$$\begin{aligned} h(S) &= \left\| \prod_{t=|S|}^1 (I_N - C_{S_t} \mathcal{L}_h^a) e_h^{(0)} \right\|^2 \\ &= \left\| \prod_{t=|S|}^1 (P \Lambda_{S_t} P^{-1}) e_h^{(0)} \right\|^2 \\ &= \left\| P \prod_{t=|S|}^1 \Lambda_{S_t} P^{-1} e_h^{(0)} \right\|^2 \\ &= \left\| \prod_{t=|S|}^1 \Lambda_{S_t} P^{-1} e_h^{(0)} \right\|^2 \\ &= \sum_{i=1}^N z_i^2 \prod_{t=|S|}^1 \lambda_{S_t i}^2 \\ &= \sum_{i=1}^N z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S)} \end{aligned}$$

654 □

655 **A.5 Proof of Theorem 4.3**

656 **Proposition 4.3.** Let $\|I_N - C_j \mathcal{L}_h^a\| \leq 1$ for all $j \in [K]$ and $(I - C_j \mathcal{L}_h^a) = P \Lambda_j P^{-1}$. Then, h is
 657 supermodular.

658 *Proof.* Let $S \preceq S'$ where $S' = S \oplus B$. By Theorem A.2,

$$h(S) = \sum_{i=1}^N z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S)}$$

659 where $m_j(S) = \sum_{t=1}^{|S|} \mathbf{1}_{S_t=j}$ be the number of times a sequence S calls the solver j . Recall that h is
 660 considered sequence supermodular if $\forall S', S \in \Omega^*$ such that $S \preceq S'$, it holds that

$$h(S) - h(S \oplus \omega) \geq h(S') - h(S' \oplus \omega)$$

661

$$\begin{aligned} h(S) - h(S \oplus \omega) &= \sum_{i=1}^N z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S)} - \sum_{i=1}^N z_i^2 \lambda_{\omega i}^2 \prod_{k=1}^K \lambda_{ki}^{2m_k(S)} \\ &= \sum_{i=1}^N (1 - \lambda_{\omega i}^2) z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S)} \end{aligned}$$

662 Similarly,

$$\begin{aligned}
h(S') - h(S \oplus \omega) &= \sum_{i=1}^N (1 - \lambda_{\omega i}^2) z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S')} \\
&\stackrel{(a)}{=} \sum_{i=1}^N (1 - \lambda_{\omega i}^2) z_i^2 \prod_{j=1}^K \lambda_{ji}^{2(m_j(S) + m_j(B))} \\
&\stackrel{(b)}{\leq} \sum_{i=1}^N (1 - \lambda_{\omega i}^2) z_i^2 \prod_{j=1}^K \lambda_{ji}^{2m_j(S)} \\
&= h(S) - h(S \oplus \omega)
\end{aligned}$$

663 (a) Since $m_j(S') = \sum_{t=1}^{|S'|} \mathbf{1}_{S'_t=j} = \sum_{t=1}^{|S|} \mathbf{1}_{S'_t=j} + \sum_{t=|S|+1}^{|S'|} \mathbf{1}_{S'_t=j} = \sum_{t=1}^{|S|} \mathbf{1}_{S_t=k} + \sum_{t=1}^{|B|} \mathbf{1}_{B_t=j} =$
664 $m_j(S) + m_j(B)$, (b) since $\rho(I_N - C_j \mathcal{L}_h^a) < 1$ and $m_j(B) \geq 0$ for all $j \in [K]$

665 □

666 B Proofs for Section 5

667 B.1 Proof of Theorem B.1

668 **Lemma B.1.** *For any set of preconditioning functions $\mathcal{C}$, any discrete operator $\mathcal{L}_h^a$, any router r , any*
669 *$a_h, f_h, u_h^{(t)}, u_h \in \mathcal{A} \times \mathcal{F} \times \mathcal{U} \times \mathcal{U}$, the following equality holds true:*

$$\begin{aligned}
l_{\text{route}} \left(r, a_h, f_h, u_h^{(t)}, u_h \right) &= \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \mathbf{1}_{k \neq j} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\quad - (K-2) \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2
\end{aligned}$$

670 *Proof.* Note that $\sum_{j=1}^K \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} = K - 1$

$$\begin{aligned}
l_{\text{route}} \left(r, a_h, f_h, u_h^{(t)}, u_h \right) &= \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) = j} \\
&= \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 - \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&= \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 - \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\quad + (K-1) \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 - (K-1) \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \\
&= \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 - \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\quad + \sum_{j=1}^K \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2 \\
&\quad - (K-1) \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) \left(u_h - u_h^{(t)} \right) \right\|_2^2
\end{aligned}$$

671

$$\begin{aligned}
&= \sum_{j=1}^K \left(\sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 - \left\| (I - C_j \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \right) \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\quad - (K-2) \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \\
&= \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\quad - (K-2) \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2
\end{aligned}$$

672

□

673 B.2 Proof of Theorem B.2

674 **Proposition B.2.** For any router r defined by $r(a, f, u^{(t)}) = \operatorname{argmax}_{j \in [K]} g_j(a, f, u^{(t)})$, any $a_h \in \mathcal{A}$,
675 $f_h \in \mathcal{F}$, and $u_h^{(t)}, u_h \in \mathcal{U}$, the routing loss l_{route} satisfies:

$$\log(2) l_{\text{route}}(r, a_h, f_h, u_h^{(t)}, u_h) \leq \Psi(\mathbf{g}, a_h, f_h, u_h^{(t)}, u_h)$$

676 *Proof.* By Theorem B.1, we know that

$$\begin{aligned}
\log(2) l_{\text{route}}(r, a_h, f_h, u_h^{(t)}, u_h) &= \log(2) \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\quad - \log(2) (K-2) \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \\
&\leq \log(2) \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
&\stackrel{(a)}{\leq} - \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a) (u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j} \log \left(\frac{\exp(g_j(a, f, u^{(t)}))}{\sum_{k=1}^K \exp(g_k(a, f, u^{(t)}))} \right) \\
&= \Psi(\mathbf{g}, a_h, f_h, u_h^{(t)}, u_h)
\end{aligned}$$

677 (a) if $r(a_h, f_h, u_h^{(t)}) \neq j$, $\frac{\exp(g_j(a, f, u^{(t)}))}{\sum_{k=1}^K \exp(g_k(a, f, u^{(t)}))} < 0.5$ which implies that

$$678 -\log \left(\frac{\exp(g_j(a, f, u^{(t)}))}{\sum_{k=1}^K \exp(g_k(a, f, u^{(t)}))} \right) \geq \log(2) \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j}$$

679

□

680 B.3 Proof of Theorem 5.1

681 **Theorem 5.1.** Let $\tilde{c}_j(a_h, u_h^{(t)}, u_h) < \bar{E} < \infty$ for all $j \in [K]$. If there exists $j \in [K]$ such that
682 $\tilde{c}_j(a_h, u_h^{(t)}, u_h) > E_{\min} > 0$, then, for any collection of solvers $\{C_j\}_{j=1}^K$ and linear discrete
683 operator $\mathcal{L}_h^a$, Ψ is Bayes consistent surrogate for l_{route} .

684 *Proof.* For a given a_h, f_h , let u_h be $\mathcal{G}_h(a_h, f_h)$ where $\mathcal{G}_h$ denotes the solution operator acting on the
685 grid G_h . Furthermore, let's consider routers of the form

$$r(a, f, u^{(t)}) = \operatorname{argmax}_{j \in [K]} g_j(a, f, u^{(t)})$$

For a given $a_h, f_h, u_h^{(t)} \in \mathcal{A} \times \mathcal{F} \times \mathcal{U}$, let the optimal loss under l_{route} be $l_{\text{route}}^*(a_h, f_h, u_h^{(t)}) = \inf_{\tilde{r}} l_{\text{route}}(\tilde{r}, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h))$. Similarly, let the optimal loss under Ψ be $\Psi^*(a_h, f_h, u_h^{(t)}) = \inf_{\tilde{\mathbf{g}}} \Psi(\tilde{\mathbf{g}}, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h))$. Let $B_j(a_h, f_h, u_h^{(t)}) = \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a)(\mathcal{G}_h(a_h, f_h) - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j}$.

$$\begin{aligned}
& l_{\text{route}}(r, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h)) - l_{\text{route}}^*(a_h, f_h, u_h^{(t)}) \\
& \stackrel{(a)}{=} \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a)(u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} - (K-2) \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a)(u_h - u_h^{(t)}) \right\|_2^2 \\
& \quad - \inf_{\tilde{r}} \sum_{j=1}^K \sum_{k=1}^K \left\| (I - C_k \circ \mathcal{L}_h^a)(u_h - u_h^{(t)}) \right\|_2^2 \mathbf{1}_{k \neq j} \mathbf{1}_{\tilde{r}(a_h, f_h, u_h^{(t)}) \neq j} + (K-2) \sum_{j=1}^K \left\| (I - C_j \circ \mathcal{L}_h^a)(u_h - u_h^{(t)}) \right\|_2^2 \\
& = \sum_{j=1}^K B_j(a_h, f_h, u_h^{(t)}) \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} - \inf_{\tilde{r}} \sum_{j=1}^K B_j(a_h, f_h, u_h^{(t)}) \mathbf{1}_{\tilde{r}(a_h, f_h, u_h^{(t)}) \neq j} \\
& = \sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)}) \left(\sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} - \inf_{\tilde{r}} \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \mathbf{1}_{\tilde{r}(a_h, f_h, u_h^{(t)}) \neq j} \right)
\end{aligned}$$

(a) by Theorem B.1

Let $\mathcal{X} = \mathcal{A} \times \mathcal{F} \times \mathcal{U}$ and $\mathcal{Y} = [K]$. Let $\mathcal{P}_{\mathcal{X}}$ denote the degenerate distribution supported at the point $(a_h, f_h, u_h^{(t)})$. We define the conditional distribution $P(Y = j \mid X = (a_h, f_h, u_h^{(t)})) = \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})}$ for $j \in [K]$. The risk and optimal risk of 0-1 loss under this distribution can be written as:

$$\begin{aligned}
\mathcal{R}_{0-1}(r) &= \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} \\
\mathcal{R}_{0-1}^* &= \inf_r \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j}
\end{aligned}$$

If $r(a_h, f_h, u_h^{(t)}) = \arg \max_{j \in [K]} g_j(a_h, f_h, u_h^{(t)})$ for all $x \in \mathcal{X}$, then the risk and optimal risk of cross entropy loss $(l_{ce}(\mathbf{g}, x, y) - \log(\frac{\exp(g_y(x))}{\sum_{k=1}^K \exp(g_k(x))}))$ under this distribution can be written as:

$$\begin{aligned}
\mathcal{R}_{ce}(\mathbf{g}) &= - \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \\
\mathcal{R}_{ce}^* &= \inf_{\mathbf{g}} - \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right)
\end{aligned}$$

From Theorem 3.1 of [Mao et al., 2023], $\mathcal{R}_{0-1}(r) - \mathcal{R}_{0-1}^* \leq \Gamma^{-1}(\mathcal{R}_{ce}(\mathbf{g}) - \mathcal{R}_{ce}^*)$ if $r(a_h, f_h, u_h^{(t)}) = \arg \max_{j \in [K]} g_j(a_h, f_h, u_h^{(t)})$ where $\Gamma(z) = \frac{1+z}{2} \log(1+z) + \frac{1-z}{2} \log(1-z)$. Then,

$$\begin{aligned}
& l_{\text{route}} \left(r, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h) \right) - l_{\text{route}}^* \left(a_h, f_h, u_h^{(t)} \right) \\
&= \sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)}) \left(\sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \mathbf{1}_{r(a_h, f_h, u_h^{(t)}) \neq j} - \inf_{\tilde{r}} \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \mathbf{1}_{\tilde{r}(a_h, f_h, u_h^{(t)}) \neq j} \right) \\
&\leq \sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)}) \Gamma^{-1} \left(- \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \right. \\
&\quad \left. - \inf_{\mathbf{g}} - \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \right) \\
&\stackrel{(a)}{\leq} \bar{E} K (K-1) \Gamma^{-1} \left(- \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \right. \\
&\quad \left. - \inf_{\mathbf{g}} - \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{\sum_{k=1}^K B_k(a_h, f_h, u_h^{(t)})} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \right) \\
&\stackrel{(b)}{\leq} \bar{E} K (K-1) \Gamma^{-1} \left(- \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{(K-1)E_{\min}} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \right. \\
&\quad \left. - \inf_{\mathbf{g}} - \sum_{j=1}^K \frac{B_j(a_h, f_h, u_h^{(t)})}{(K-1)E_{\min}} \log \left(\frac{\exp(g_j(a_h, f_h, u_h^{(t)}))}{\sum_{k=1}^K \exp(g_k(a_h, f_h, u_h^{(t)}))} \right) \right) \\
&= \bar{E} K (K-1) \Gamma^{-1} \left(\frac{\Psi(\mathbf{g}, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h)) - \Psi^*(a_h, f_h, u_h^{(t)})}{(K-1)E_{\min}} \right)
\end{aligned}$$

700 (a) since $\left\| (I - C_j \circ \mathcal{L}_h^a)(e_h^{(t)}) \right\|_2^2 < \bar{E}$ for all $j \in [K]$, (b) since Γ^{-1} is non-decreasing and

701 $\exists j \in [K]$ such that $\left\| (I - C_j \circ \mathcal{L}_h^a)(e_h^{(t)}) \right\|_2^2 > E_{\min}$

702 Finally,

$$\begin{aligned}
& \lim_{n \rightarrow \infty} \mathcal{R}_{\text{route}}(r_n) - \mathcal{R}_{\text{route}}^* \\
&\stackrel{(a)}{=} \lim_{n \rightarrow \infty} \mathbb{E}_{a_h, f_h \sim \mathcal{P}_{\mathcal{A} \times \mathcal{F}}} \left[l_{\text{route}} \left(r_n, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h) \right) - l_{\text{route}}^* \left(a_h, f_h, u_h^{(t)} \right) \right] \\
&\leq \lim_{n \rightarrow \infty} \mathbb{E}_{a_h, f_h \sim \mathcal{P}_{\mathcal{A} \times \mathcal{F}}} \left[\bar{E} K (K-1) \Gamma^{-1} \left(\frac{\Psi(\tilde{\mathbf{g}}, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h)) - \Psi^*(a_h, f_h, u_h^{(t)})}{(K-1)E_{\min}} \right) \right] \\
&\stackrel{(b)}{\leq} \lim_{n \rightarrow \infty} \bar{E} K (K-1) \Gamma^{-1} \left(\frac{\mathbb{E}_{a_h, f_h \sim \mathcal{P}_{\mathcal{A} \times \mathcal{F}}} \left[\Psi(\mathbf{g}_n, a_h, f_h, u_h^{(t)}, \mathcal{G}_h(a_h, f_h)) - \Psi^*(a_h, f_h, u_h^{(t)}) \right]}{(K-1)E_{\min}} \right)
\end{aligned}$$

703

$$\begin{aligned}
&= \lim_{n \rightarrow \infty} \bar{E}K(K-1)\Gamma^{-1} \left(\frac{\mathcal{R}_\Psi(\mathbf{g}_n) - \mathcal{R}_\Psi^*}{(K-1)E_{min}} \right) \\
&\stackrel{(c)}{=} \bar{E}K(K-1)\Gamma^{-1} \left(\frac{\lim_{n \rightarrow \infty} \mathcal{R}_\Psi(\mathbf{g}_n) - \mathcal{R}_\Psi^*}{(K-1)E_{min}} \right) \\
&= \bar{E}K(K-1)\Gamma^{-1}(0) \\
&\stackrel{(d)}{=} 0
\end{aligned}$$

704 (a) $\mathcal{R}_{\text{route}}^* = \mathbb{E}_{a_h, f_h \sim \mathcal{P}_{\mathcal{A} \times \mathcal{F}}} \left[l_{\text{route}}^* \left(a_h, f_h, u_h^{(t)} \right) \right]$ since the infimum is taken over all measurable
705 functions, (b) by Jensen's inequality since Γ^{-1} is concave, (c) by continuity of Γ^{-1} at 0, (d) $\Gamma^{-1}(0) =$
706 0

707

□

708 C Training Details

709 Data for both DeepONet and the routers is sampled from a zero-mean Hierarchical Gaussian Random
710 Field on the periodic domain with covariance operator $\alpha(-\Delta + \beta I)^{-\gamma}$, where α, β, γ are sampled
711 as:

$$\begin{aligned}
\alpha &\sim \text{Log-Uniform}(0.01, 100) \\
\beta &\sim \text{Log-Uniform}(0.1, 1000) \\
\gamma &\sim \text{Uniform}(\{0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 4.0\})
\end{aligned}$$

712 Given (α, β, γ) , samples are generated in the Fourier space. For each non-zero frequency mode
713 k , we draw an independent complex coefficient from a Gaussian distribution with mean 0 and
714 variance $\alpha(4\pi^2\|k\|_2^2 + \beta)^{-\gamma}$. We enforce a Hermitian symmetry to obtain a real-valued field, set the
715 zero-frequency (DC) mode to 0 to obtain a zero mean field, and apply the inverse Discrete Fourier
716 Transform to obtain the field in physical space.

717 For each sample, we compute reference solutions with a least squares solver and treat them as ground
718 truth.

719 This data is used to trained our DeepONet models and LSTM routers. All the models were imple-
720 mented using PyTorch and all the models were trained on one Nvidia A40 GPU.

721 Table 4 contains all hyperparameter details for the DeepONet. DeepONet took 30 minutes to train.
722 We then use the model with the best validation loss.

Table 4: Hyperparameter settings for DeepONet

Hyperparameter	Value
Learning rate	1e-3
Branch Dimension	128
Hidden dimension for branch net	256
No. of hidden layers in branch net	4
Hidden dimension for trunk net	256
No. of hidden layers in trunk net	4
Gradient Clipping Norm	1.0
Weight Decay	0.005
Batch size	256
Training samples	10000
Validation samples	2000
Epochs	1000

723 The routers are LSTM models. Along with the inputs specified in Section 5, namely $a_h, f_h, u_h^{(t)}$,
724 we also supply the routers with the iteration index t , current residual $f_h - \mathcal{L}_h^a u_h^{(t)}$, and the routing

725 decisions from the previous iteration. While the iteration index and residual are deterministic
726 functions of $(a_h, f_h, u_h^{(t)})$ and align with the theory presented in Section 5, incorporating previous
727 routing decisions is a mild deviation from the idealized setting. Nevertheless, this modification is
728 motivated by the same considerations that justify the use of scheduled sampling: under deployment,
729 routing decisions are predicted autoregressively and influence future inputs, whereas training under
730 teacher forcing assumes independence from past predictions. Including previous routing decisions
731 bridges the gap induced by exposure bias by providing the model with trajectory-level information.

732 All the routers are trained with scheduled sampling. We use a warm-up of e_w epochs with teacher-
733 forcing probability $p_{tf}(e) = ss_{start}$. After the warm-up, the p_{tf} decays geometrically by a factor of
734 $\gamma_{tf} < 1$ per epoch and is floored by ss_{end} :

$$p_{tf}(e) = \begin{cases} ss_{start} & e \leq e_w \\ \max(ss_{start}\gamma_{tf}^{e-e_w}, ss_{end}) & e > e_w \end{cases}$$

735 At each time step, with probability $p_{tf}(e)$, we feed the teacher-forced greedy iterate; otherwise, we
736 feed the router’s own predicted iterate.

737 Since LSTMs on long rollouts can suffer from exploding/vanishing gradients, we use truncated
738 backpropagation through time (TBPTT) [Mozer, 2013, Robinson and Fallside, 1987, Werbos, 1988]:
739 the forward pass unrolls the entire trajectory, but gradients are propagated only through the most
740 recent $w_{bptt}(e)$ steps at epoch e . Hidden states are passed forward between segments, while earlier
741 segments are treated as stop-gradient.

742 We employ a curriculum learning approach analogous to scheduled sampling. Let T_{max} be the
743 horizon (300 iterations). With a warm-up of e_w epochs,

$$w_{bptt}(e) = \begin{cases} w_{start} & e \leq e_w \\ \min\left(T_{max}, w_{start}\gamma_{bptt}^{\lfloor \frac{e-e_w}{f_{bptt}} \rfloor}\right) & e > e_w \end{cases} \quad (12)$$

744 so the window grows geometrically by a factor of $\gamma_{bptt} > 1$ every f_{bptt} epochs and is capped at the
745 full trajectory length.

746 Table 5 contains all hyperparameter details for the LSTM routers. The routers for the Paired Solver
747 experiment took a maximum of 4 hours and 30 minutes to train while the routers for the Solver
748 Ensemble experiment took a maximum of 6 hours to train. We then use the model with the best
749 validation loss for testing. The architecture and dataset size is larger for the Solver ensemble
750 experiments to encourage the model to learn some of the nuanced differences between the classes.

Table 5: Hyperparameter settings for routers in Paired solver and Solver Ensemble Experiments

Hyperparameter	Paired Solver	Solver Ensemble
Learning rate	1e-3	1e-3
Hidden dimension	256	512
No. of hidden layers	4	3
Gradient Clipping Norm	1.0	1.0
Weight Decay	0.005	0.005
Batch size	32	32
Training samples	256	1024
Validation samples	32	128
Epochs	200	200
ss_{start}	1.0	1.0
γ_{tf}	0.95	0.95
ss_{end}	0.0	0.0
w_{start}	50	50
γ_{bptt}	1.25	1.25
e_w	10	10
f_{bptt}	1	1

D Additional Experimental Results

We present additional visualizations and tables that further highlight the strengths of our method. In the paired solver experiments, we include Damped Jacobi with $\omega = 0.67$ and Successive Over-Relaxation (SOR) with $\omega = 1.5$. We also compare against a True Greedy oracle, which has access to true error at each step (See Section 4). This comparison demonstrates that the learned router closely approximates the behavior of the greedy policy.

D.1 Error Comparisons with Paired t -Test Results

We supplement the paired-solver experiments in Table 1 with additional solver families (Jacobi (0.67) and SOR (1.5)) and statistical significance analysis. For each solver family, we compare the learned greedy router against baseline methods (single-solver only and HINTS) using paired t -tests with a one-sided alternative hypothesis that the learned router achieves lower error or AUC. Results are reported in Table 6.

Across all five solver families, the resulting p -values indicate statistically significant improvements of the learned greedy router over both single-solver and HINTS baselines.

We support the Large Solver ensemble experiments in Table 3 with a statistical significance analysis. We use paired t -tests across the 128 test instances. For each baseline solver j (e.g., Jacobi, GS, SymGS, etc.), we compare the performance of the solver ensemble $\mathcal{W}$ against the corresponding pairwise learned router $\text{Router}(\text{NO} \cup \{j\})$ if $j \in \mathcal{W}$. The test is performed on per-instance differences in final error (and AUC), using a one-sided alternative hypothesis that the solver ensemble achieves lower error than the baseline.

Across both Poisson and convection–diffusion problems, the solver ensembles yield statistically significant improvements over all pairwise baselines in nearly every setting, with p -values typically well below 0.01. The gains are enhanced as the ensemble size increases, while the performance of the learned router remains close to that of the true greedy oracle. These results support the claim that enlarging the solver set provides measurable benefits and that our learned policy effectively captures the resulting improvements. Results are reported in Table 7.

Table 6: Final error and AUC of squared L^2 error (lower is better). Values are mean ($\pm$ standard error (s.e.)) over 128 test instances; both mean and s.e. of error are reported in $\times 10^{-3}$. If a standard error is not shown, it is $< 10^{-3}$ in the reported units (raw $< 10^{-6}$). Statistical significance is assessed via paired t -tests comparing each baseline (single-solver only and HINTS) against the learned greedy router, using a one-sided alternative that the learned router achieves lower error/AUC. Reported p -values correspond to these tests.

Equation	Poisson				ConvDiff			
Methods	$\ e_h^{(T)}\ \times 10^3$	$\ e_h^{(T)}\ $ p -value	AUC	AUC p -value	$\ e_h^{(T)}\ \times 10^3$	$\ e_h^{(T)}\ $ p -value	AUC	AUC p -value
Jacobi-related solvers								
Jacobi Only	0.383 (1.029)	$< 10^{-3}$	0.821 (2.154)	$< 10^{-3}$	0.136 (0.364)	$< 10^{-3}$	0.312 (0.788)	$< 10^{-3}$
HINTS-Jacobi	0.759 (0.016)	$< 10^{-3}$	0.393 (0.590)	$< 10^{-3}$	0.447 (0.013)	$< 10^{-3}$	0.202 (0.256)	$< 10^{-3}$
Learned Greedy-Jacobi	0.054 (0.142)	-	0.165 (0.368)	-	0.033 (0.097)	-	0.098 (0.239)	-
True-Greedy-Jacobi	0.021 (0.018)	-	0.094 (0.170)	-	0.012 (0.012)	-	0.049 (0.091)	-
GS-related solvers								
GS only	0.019 (0.051)	$< 10^{-3}$	0.435 (1.141)	$< 10^{-3}$	$< 10^{-3}$	0.006	0.088 (0.219)	$< 10^{-3}$
HINTS-GS	0.724 (0.000)	$< 10^{-3}$	0.325 (0.488)	$< 10^{-3}$	0.456 (0.000)	$< 10^{-3}$	0.130 (0.154)	0.0
Learned Greedy-GS	0.002 (0.004)	-	0.083 (0.152)	-	$< 10^{-3}$	-	0.031 (0.078)	-
True-Greedy-GS	0.001 (0.001)	-	0.057 (0.107)	-	$< 10^{-3}$	-	0.019 (0.038)	-
SymGS-related solvers								
SymGS only	$< 10^{-3}$	$< 10^{-3}$	0.227 (0.593)	$< 10^{-3}$	$< 10^{-3}$	0.028	0.071 (0.178)	$< 10^{-3}$
HINTS-SymGS	0.709 (0.000)	$< 10^{-3}$	0.252 (0.380)	$< 10^{-3}$	0.463 (0.000)	$< 10^{-3}$	0.116 (0.131)	$< 10^{-3}$
Learned Greedy-SymGS	$< 10^{-3}$	-	0.052 (0.102)	-	$< 10^{-3}$	-	0.022 (0.039)	-
True-Greedy-SymGS	$< 10^{-3}$	-	0.034 (0.066)	-	$< 10^{-3}$	-	0.016 (0.032)	-
Jacobi (0.67)-related solvers								
Jacobi (0.67) only	1.066 (2.861)	$< 10^{-3}$	1.128 (2.954)	$< 10^{-3}$	0.349 (0.931)	$< 10^{-3}$	0.428 (1.077)	$< 10^{-3}$
HINTS-Jacobi (0.67)	0.789 (0.000)	$< 10^{-3}$	0.429 (0.642)	0.005	0.473 (0.000)	$< 10^{-3}$	0.223 (0.284)	$< 10^{-3}$
Learned Greedy-Jacobi (0.67)	0.232 (0.654)	-	0.309 (0.791)	-	0.069 (0.102)	-	0.117 (0.210)	-
True-Greedy-Jacobi (0.67)	0.057 (0.041)	-	0.131 (0.233)	-	0.026 (0.021)	-	0.065 (0.117)	-
SOR (1.5)-related solvers								
SOR (1.5) only	$< 10^{-3}$	0.057	0.156 (0.409)	$< 10^{-3}$	$< 10^{-3}$	0.086	0.008 (0.020)	0.988
HINTS-SOR (1.5)	0.700 (0.000)	$< 10^{-3}$	0.207 (0.316)	$< 10^{-3}$	0.462 (0.000)	$< 10^{-3}$	0.021 (0.020)	$< 10^{-3}$
Learned Greedy-SOR (1.5)	$< 10^{-3}$	-	0.052 (0.143)	-	$< 10^{-3}$	-	0.011 (0.030)	-
True-Greedy-SOR (1.5)	$< 10^{-3}$	-	0.032 (0.071)	-	$< 10^{-3}$	-	0.007 (0.019)	-

Table 7: Final error and AUC of squared L^2 error (lower is better). Values are mean ($\pm$ standard error (s.e.)) over 128 test instances; both mean and s.e. of error are reported in $\times 10^{-3}$. If a standard error is not shown, it is $< 10^{-3}$ in the reported units (raw $< 10^{-6}$). Statistical significance is assessed via paired t -tests comparing each solver ensemble against the corresponding pairwise learned router (e.g., NO + Jacobi, NO + GS), using a one-sided alternative that the ensemble achieves lower error/AUC. Reported p -values correspond to these tests.

$\mathcal{W}$	$\ e_h^{(T)}\ \times 10^3$	AUC	Jacobi p -value	GS p -value	SymGS p -value	Jacobi (0.67) p -value	SOR (1.5) p -value
Poisson							
Learned Greedy {Jacobi, GS}	0.003 (0.002)	0.068 (0.131)	$< 10^{-3}$	$< 10^{-3}$	-	-	-
True Greedy {Jacobi, GS}	0.001 (0.001)	0.057 (0.107)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS}	$< 10^{-3}$	0.038 (0.071)	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	-	-
True Greedy {Jacobi, GS, SymGS}	$< 10^{-3}$	0.034 (0.066)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	$< 10^{-3}$	0.042 (0.074)	$< 10^{-3}$	$< 10^{-3}$	0.004	$< 10^{-3}$	-
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	$< 10^{-3}$	0.034 (0.066)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	$< 10^{-3}$	0.039 (0.076)	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	0.04
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	$< 10^{-3}$	0.031 (0.069)	-	-	-	-	-
ConvDiff							
Learned Greedy {Jacobi, GS}	$< 10^{-3}$	0.021 (0.040)	$< 10^{-3}$	0.005	-	-	-
True Greedy {Jacobi, GS}	$< 10^{-3}$	0.019 (0.038)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS}	$< 10^{-3}$	0.020 (0.036)	$< 10^{-3}$	0.004	$< 10^{-3}$	-	-
True Greedy {Jacobi, GS, SymGS}	$< 10^{-3}$	0.016 (0.032)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	$< 10^{-3}$	0.020 (0.039)	$< 10^{-3}$	0.003	0.003	$< 10^{-3}$	-
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	$< 10^{-3}$	0.016 (0.032)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	$< 10^{-3}$	0.008 (0.019)	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	0.004
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	$< 10^{-3}$	0.007 (0.018)	-	-	-	-	-

777 D.2 Convergence Histories

778 See Figure 4 for convergence histories for the Jacobi (0.67)-related solvers and Successive Over-
779 relaxation (1.5)-related solvers.




Figure 4: Convergence histories for representative test instances. Rows: ConvDiff (top) and Poisson (bottom). Columns: Jacobi (0.67) and Successive Over-relaxation (1.5). Greedy yields near-monotone decay and the lowest errors, whereas HINTS shows sawtooth behaviors.

780 D.3 Prediction and Error Visualizations

781 Figures 5 and 6 provide qualitative visualizations of sample predictions across routing strategies and
782 numerical solvers for both equations. While these prediction may appear identical to the ground
783 truth, Figures 7 and 8 reveals distinct error patterns with varying magnitudes across all predictions.
784 In particular, our learned method consistently achieves the lower-magnitude errors compared to its
785 respective baselines.




Figure 5: Sample predictions for the Poisson equation across different solver pairings. Each column corresponds to a numerical solver (Jacobi, Gauss–Seidel (GS), Symmetric GS, Damped Jacobi, and Successive Over-relaxation), while rows show predictions from the corresponding solver-only baseline (top), HINTS (middle), and the learned greedy router (bottom). The ground truth solution is shown on the right.




Figure 6: Sample predictions for the convection diffusion equation across different solver pairings. Each column corresponds to a numerical solver (Jacobi, Gauss–Seidel (GS), Symmetric GS, Damped Jacobi, and Successive Over-relaxation), while rows show predictions from the corresponding solver-only baseline (top), HINTS (middle), and the learned greedy router (bottom). The ground truth solution is shown on the right.




Figure 7: Pointwise error maps for Poisson sample predictions across solver families. Columns correspond to different numerical solvers, while rows show solver-only (top), HINTS (middle), and learned greedy router (bottom). Errors are computed as $u_h - u_h^{(T)} = e_h^{(T)}$. The learned greedy router consistently yields lower-magnitude errors compared to both solver-only and HINTS baselines.




Figure 8: Pointwise error maps for convection diffusion sample predictions across solver families. Columns correspond to different numerical solvers, while rows show solver-only (top), HINTS (middle), and learned greedy router (bottom). Errors are computed as $u_h - u_h^{(T)} = e_h^{(T)}$. The learned greedy router consistently yields lower-magnitude errors compared to both solver-only and HINTS baselines.

786 D.4 Residual Comparison

Table 8: Final residual $\|\mathcal{L}_h^a e_h^{(T)}\|$ and AUC of residuals over iterations (lower is better). Values are reported as mean ($\pm$ standard error (s.e.)) over 128 test instances; residuals are scaled by $\times 10^{-3}$. If the residual norm is reported as $< 10^{-3}$, the corresponding raw value is $< 10^{-6}$. Statistical significance is evaluated via paired t -tests comparing each baseline (single-solver only and HINTS) to the learned greedy router under a one-sided alternative hypothesis that the learned router achieves lower residual and AUC. Reported p -values correspond to these tests.

Equation	Poisson				ConvDiff			
Methods	$\ \mathcal{L}_h^a e_h^{(T)}\ \times 10^3$	$\ \mathcal{L}_h^a e_h^{(T)}\ $ p-value	AUC	AUC p-value	$\ \mathcal{L}_h^a e_h^{(T)}\ \times 10^3$	$\ \mathcal{L}_h^a e_h^{(T)}\ $ p-value	AUC	AUC p-value
Jacobi-related solvers								
Jacobi only	23.939 (66.755)	0.021	43.475 (109.764)	$< 10^{-3}$	27.208 (74.555)	0.012	45.523 (114.774)	$< 10^{-3}$
HINTS-Jacobi	193.327 (37.362)	$< 10^{-3}$	39.763 (70.671)	$< 10^{-3}$	266.421 (34.699)	$< 10^{-3}$	42.851 (70.748)	$< 10^{-3}$
Learned Greedy-Jacobi	20.870 (62.246)	-	32.041 (83.647)	-	20.786 (66.511)	-	34.844 (84.666)	-
GS-related solvers								
GS only	0.761 (2.043)	$< 10^{-3}$	20.776 (52.270)	$< 10^{-3}$	0.002 (0.005)	$< 10^{-3}$	10.720 (26.892)	$< 10^{-3}$
HINTS-GS	183.359 (0.000)	$< 10^{-3}$	22.581 (27.984)	$< 10^{-3}$	246.877 (0.000)	$< 10^{-3}$	18.654 (19.201)	$< 10^{-3}$
Learned Greedy-GS	0.092 (0.145)	-	11.960 (27.863)	-	0.001 (0.003)	-	7.322 (16.968)	-
SymGS-related solvers								
SymGS only	0.004 (0.009)	$< 10^{-3}$	10.343 (25.957)	$< 10^{-3}$	0.002 (0.004)	0.004	8.604 (21.776)	$< 10^{-3}$
HINTS-SymGS	185.601 (0.001)	$< 10^{-3}$	15.489 (18.255)	$< 10^{-3}$	245.629 (0.000)	$< 10^{-3}$	16.515 (15.990)	$< 10^{-3}$
Learned Greedy-SymGS	0.002 (0.005)	-	7.149 (18.364)	-	0.001 (0.002)	-	6.481 (13.190)	-
Jacobi (0.67)-related solvers								
Jacobi (0.67) only	42.246 (112.968)	$< 10^{-3}$	55.250 (138.258)	$< 10^{-3}$	45.451 (121.431)	$< 10^{-3}$	56.747 (141.901)	$< 10^{-3}$
HINTS-Jacobi (0.67)	188.719 (0.008)	$< 10^{-3}$	38.970 (53.035)	$< 10^{-3}$	256.407 (0.005)	$< 10^{-3}$	39.604 (52.578)	$< 10^{-3}$
Learned Greedy-Jacobi (0.67)	9.290 (26.109)	-	35.905 (86.881)	-	9.010 (13.426)	-	32.516 (83.488)	-
SOR (1.5)-related solvers								
SOR (1.5) only	0.003 (0.008)	0.5	9.044 (22.962)	$< 10^{-3}$	0.002 (0.004)	0.189	2.817 (7.499)	$< 10^{-3}$
HINTS-SOR (1.5)	188.187 (0.001)	$< 10^{-3}$	15.894 (19.565)	$< 10^{-3}$	248.226 (0.001)	$< 10^{-3}$	11.420 (7.498)	$< 10^{-3}$
Learned Greedy-SOR (1.5)	0.003 (0.008)	-	7.784 (19.939)	-	0.002 (0.004)	-	5.530 (19.679)	-

Table 9: Final residual and AUC of squared L^2 residual for varying numbers of solvers. Values are mean ($\pm$ standard error (s.e.)) over 128 test instances; both mean and s.e. are reported in $\times 10^{-3}$.

Equation	Poisson		ConvDiff	
$\mathcal{W}$	$\ \mathcal{L}_h^a e_h^{(T)}\ $	AUC	$\ \mathcal{L}_h^a e_h^{(T)}\ $	AUC
{Jacobi, GS}	0.135 (0.096)	11.815 (33.768)	0.023 (0.044)	5.765 (14.581)
{Jacobi, GS, SymGS}	0.002 (0.004)	5.118 (12.920)	0.002 (0.002)	4.810 (11.264)
{Jacobi, GS, SymGS, Jacobi (0.67)}	0.013 (0.011)	6.120 (14.651)	0.010 (0.013)	4.859 (11.473)
{Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	0.004 (0.006)	8.196 (22.516)	0.001 (0.002)	3.209 (8.676)

787 Table 8 summarizes the performance of single-solver schedules, HINTS, and greedy with respect
788 to the final residuals $r_h^{(T)} = \|f_h - \mathcal{L}_h^a u_h^{(T)}\|$ or $\|\mathcal{L}_h^a e_h^{(T)}\|$ and its AUC $AUC_T = \sum_{t=1}^T \|r_h^{(t)}\|_2^2$.
789 Greedy outperforms its HINTS and single-solver counterparts in most equations. We must note that
790 our greedy router is trained to reduce error, not residual. The same error can induce very different
791 residuals depending on the spectrum $\mathcal{L}_h^a$. Table 9 exhibits how residuals are affected by the number of
792 solvers in the solver ensemble. Similar to error, we observe both the final residual and AUC decrease
793 as the number of solvers increase.

794 D.5 Fourier mode-wise error comparison

795 We assess frequency-resolved performance by projecting the error onto the discrete Fourier basis.
 796 Table 10 report, for modes 1, 5, and 10, the mode-wise final error and mode-wise AUC, comparing
 797 single-solver baselines, HINTS, and the greedy router. As a result of including a deep learning
 798 model, Greedy consistently achieves the smallest mode-1 error/AUC across equations and solver
 799 families. For modes 5 and 10, single-solver schedules sometimes have an edge, reflecting the
 800 tendency of classical smoothers to damp high-frequency components more aggressively than ML
 801 surrogates (spectral bias). Overall, greedy delivers more uniform convergence across the spectrum:
 802 it routes to whichever solver most decreases the full L^2 error, and by Parseval’s identity $|e_h^{(t)}|_2^2 =$
 803 $\sum_m |\hat{u}_m^{(t)} - \hat{u}_m|^2$, reductions in the objective correspond to reducing energy across all modes rather
 804 than giving preferential treatment to a subset. Additionally, in Table 11, we observe that all mode-wise
 805 errors/AUCs reduce with the inclusion of more solvers.

Table 10: Final error and AUC of squared L^2 error for Mode 1, 5, and 10 (lower is better) for Poisson and ConvDiff. Values are mean ($\pm$ standard error (s.e.)) over 128 test instances; both mean and s.e. of final errors are reported in $\times 10^{-3}$. If the residual norm is reported as $< 10^{-3}$, the corresponding raw value is $< 10^{-6}$.

Method	Mode 1		Poisson Mode 5		Mode 10		Mode 1		ConvDiff Mode 5		Mode 10	
	Final Error	AUC	Final Error	AUC	Final Error	AUC	Final Error	AUC	Final Error	AUC	Final Error	AUC
Jacobi Only	0.135 (0.295)	3.231 (7.056)	$< 10^{-3}$	0.003 (0.010)	$< 10^{-3}$	0.000 (0.001)	0.079 (0.171)	1.084 (2.369)	$< 10^{-3}$	0.003 (0.011)	$< 10^{-3}$	0.000 (0.001)
HINTS-Jacobi	5.730 (0.240)	2.734 (3.371)	0.028 (0.002)	0.004 (0.012)	0.006 (0.000)	0.000 (0.001)	0.994 (0.220)	0.697 (1.091)	0.061 (0.001)	0.005 (0.012)	0.022 (0.001)	0.001 (0.001)
Learned Greedy-Jacobi	0.032 (0.085)	0.841 (2.081)	$< 10^{-3}$	0.009 (0.028)	$< 10^{-3}$	0.001 (0.003)	0.021 (0.055)	0.324 (0.780)	$< 10^{-3}$	0.009 (0.025)	$< 10^{-3}$	0.001 (0.002)
GS-related solvers												
GS Only	0.002 (0.004)	1.695 (3.702)	$< 10^{-3}$	0.003 (0.011)	$< 10^{-3}$	0.000 (0.001)	$< 10^{-3}$	0.205 (0.452)	$< 10^{-3}$	0.002 (0.006)	$< 10^{-3}$	$< 10^{-3}$
HINTS-GS	5.377 (0.000)	2.113 (2.498)	0.027 (0.000)	0.005 (0.012)	0.007 (0.000)	0.000 (0.001)	0.661 (0.000)	0.271 (0.432)	0.065 (0.000)	0.003 (0.006)	0.019 (0.000)	$< 10^{-3}$
Learned Greedy-GS	0.000 (0.001)	0.465 (1.125)	$< 10^{-3}$	0.009 (0.029)	$< 10^{-3}$	0.001 (0.002)	$< 10^{-3}$	0.075 (0.151)	$< 10^{-3}$	0.005 (0.017)	$< 10^{-3}$	0.001 (0.001)
SymGS-related solvers												
SymGS Only	$< 10^{-3}$	0.883 (1.919)	$< 10^{-3}$	0.002 (0.006)	$< 10^{-3}$	0.000 (0.001)	$< 10^{-3}$	0.180 (0.400)	$< 10^{-3}$	0.001 (0.005)	$< 10^{-3}$	0.000 (0.001)
HINTS-SymGS	5.085 (0.000)	1.432 (1.700)	0.025 (0.000)	0.002 (0.007)	0.007 (0.000)	0.000 (0.001)	0.672 (0.000)	0.240 (0.381)	0.070 (0.000)	0.002 (0.005)	0.019 (0.000)	0.000 (0.001)
Learned Greedy-SymGS	$< 10^{-3}$	0.334 (0.943)	$< 10^{-3}$	0.007 (0.025)	$< 10^{-3}$	0.001 (0.002)	$< 10^{-3}$	0.079 (0.193)	$< 10^{-3}$	0.004 (0.012)	$< 10^{-3}$	0.001 (0.001)
Jacobi (0.67)-related solvers												
Jacobi (0.67) Only	1.063 (2.321)	4.771 (10.421)	$< 10^{-3}$	0.005 (0.017)	$< 10^{-3}$	$< 10^{-3}$	0.428 (0.934)	1.535 (3.352)	$< 10^{-3}$	0.004 (0.016)	$< 10^{-3}$	$< 10^{-3}$
HINTS-Jacobi (0.67)	5.804 (0.001)	2.983 (3.666)	0.029 (0.000)	0.007 (0.019)	0.006 (0.000)	$< 10^{-3}$	1.080 (0.000)	0.776 (1.158)	0.065 (0.000)	0.008 (0.017)	0.021 (0.000)	$< 10^{-3}$
Learned Greedy-Jacobi (0.67)	0.390 (1.195)	1.804 (5.363)	$< 10^{-3}$	0.017 (0.058)	$< 10^{-3}$	0.001 (0.002)	0.096 (0.208)	0.435 (0.910)	$< 10^{-3}$	0.013 (0.044)	$< 10^{-3}$	0.001 (0.004)
SOR (1.5)-related solvers												
SOR (1.5) Only	$< 10^{-3}$	0.727 (1.594)	$< 10^{-3}$	0.005 (0.019)	$< 10^{-3}$	0.001 (0.002)	$< 10^{-3}$	0.037 (0.082)	$< 10^{-3}$	0.002 (0.007)	$< 10^{-3}$	0.000 (0.001)
HINTS-SOR (1.5)	4.826 (0.000)	1.239 (1.484)	0.027 (0.000)	0.007 (0.020)	0.008 (0.000)	0.001 (0.002)	0.645 (0.000)	0.080 (0.082)	0.068 (0.000)	0.005 (0.007)	0.019 (0.000)	0.001 (0.001)
Learned Greedy-SOR (1.5)	$< 10^{-3}$	0.302 (0.757)	$< 10^{-3}$	0.010 (0.032)	$< 10^{-3}$	0.001 (0.003)	$< 10^{-3}$	0.049 (0.119)	$< 10^{-3}$	0.007 (0.030)	$< 10^{-3}$	0.001 (0.002)

Table 11: Final error and AUC of squared L^2 error of Mode 1, 5, and 10 for varying numbers of solvers. Values are mean ($\pm$ standard error (s.e.)) over 128 test instances; both mean and s.e. are reported in $\times 10^{-3}$.

Equation	Poisson				ConvDiff			
	Mode 1 Error	Mode 1 AUC	Mode 5 Error	Mode 5 AUC	Mode 1 Error	Mode 1 AUC	Mode 5 Error	Mode 5 AUC
JW Mode								
[Jacobi, GS]	0.000 (0.001)	0.267 (0.571)	$< 10^{-3}$	0.006 (0.025)	$< 10^{-3}$	0.001 (0.005)	$< 10^{-3}$	0.055 (0.112)
[Jacobi, GS, SymGS]	0.000 (0.001)	0.185 (0.415)	$< 10^{-3}$	0.003 (0.009)	$< 10^{-3}$	0.000 (0.002)	$< 10^{-3}$	0.054 (0.114)
[Jacobi, GS, SymGS, Jacobi (0.67)]	0.000 (0.001)	0.172 (0.333)	$< 10^{-3}$	0.003 (0.010)	$< 10^{-3}$	0.000 (0.002)	$< 10^{-3}$	0.056 (0.119)
[Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)]	0.000 (0.001)	0.210 (0.399)	$< 10^{-3}$	0.006 (0.023)	$< 10^{-3}$	0.001 (0.004)	$< 10^{-3}$	0.026 (0.061)




Figure 9: DeepONet usage over iterations for learned and true greedy routing across solver families. Columns correspond to different numerical solvers, and rows correspond to the two equations. The learned router closely follows the true greedy policy, capturing its nonuniform usage of DeepONet across iterations. For readability, we display the first 100 iterations (out of 300 total)




Figure 10: Solver selection patterns for the convection–diffusion equation across different solver pairings and test samples. Each column corresponds to a solver family, while rows show decisions from the learned greedy router (top) and the true greedy policy (bottom). Colored entries indicate iterations where the neural operator is selected, with blank regions corresponding to numerical solver updates. The learned router exhibits instance-dependent routing behavior.

Solver Decisions for Poisson




Figure 11: Solver selection patterns for the Poisson equation across different solver pairings and test samples. Each column corresponds to a solver family, while rows show decisions from the learned greedy router (top) and the true greedy policy (bottom). Colored entries indicate iterations where the neural operator is selected, with blank regions corresponding to numerical solver updates. The learned router exhibits instance-dependent routing behavior.

Figure 9 highlights the proportion of DeepONet calls across iterations, while Figures 10 and 11 visualize the routing decisions of the learned and true greedy policies across all test samples and solver families.

Two key observations emerge. First, the routing strategy is highly sample-dependent, indicating that a fixed routing schedule across all instances would be suboptimal and can slow convergence. Second, the learned routing policy closely tracks the behavior of the true greedy policy, providing empirical support for the approximation guarantees discussed in Section 5. In particular, the learned policy can be viewed as a smoothed approximation of the true greedy strategy, capturing its overall structure while exhibiting minor deviations due to learning and finite-sample effects.

Table 12: Average component selection frequencies for the Poisson equation. Rows indicate the router access set. Entries are mean ($\pm$ s.e.) over 128 test instances. Here NO denotes the neural operator; “-” indicates that the component is not available to the router.

$\mathcal{W}$	Jacobi	GS	SSOR	Jacobi (0.67)	SOR (1.5)	DeepONet
{Jacobi, GS}	0.405 (0.143)	0.588 (0.134)	-	-	-	0.007 (0.011)
{Jacobi, GS, SSOR}	0.000 (0.000)	0.000 (0.000)	0.996 (0.005)	-	-	0.004 (0.005)
{Jacobi, GS, SSOR, Jacobi (0.67)}	0.227 (0.112)	0.212 (0.118)	0.434 (0.212)	0.121 (0.102)	-	0.005 (0.007)
{Jacobi, GS, SSOR, Jacobi (0.67), SOR (1.5)}	0.009 (0.033)	0.570 (0.057)	0.260 (0.040)	0.000 (0.000)	0.156 (0.013)	0.005 (0.005)

Table 13: Average component selection frequencies for the Convection-Diffusion equation. Rows indicate the router access set. Entries are mean ($\pm$ s.e.) over 128 test instances. Here NO denotes the neural operator; “-” indicates that the component is not available to the router.

$\mathcal{W}$	Jacobi	GS	SSOR	Jacobi (0.67)	SOR (1.5)	DeepONet
{Jacobi, GS}	0.417 (0.307)	0.579 (0.307)	-	-	-	0.004 (0.006)
{Jacobi, GS, SSOR}	0.109 (0.109)	0.396 (0.110)	0.493 (0.175)	-	-	0.003 (0.005)
{Jacobi, GS, SSOR, Jacobi (0.67)}	0.168 (0.096)	0.190 (0.166)	0.410 (0.227)	0.229 (0.146)	-	0.003 (0.004)
{Jacobi, GS, SSOR, Jacobi (0.67), SOR (1.5)}	0.307 (0.150)	0.061 (0.131)	0.088 (0.170)	0.202 (0.089)	0.342 (0.066)	0.001 (0.001)

Tables 12 and 13 report solver selection frequencies across different solver ensembles. Several interesting observations emerge from these results.

First, the router typically relies on a small subset of solvers, with larger ensembles often leading to the dominance of a single solver (e.g., SOR(1.5) in convection–diffusion). This explains the diminishing returns observed in the multi-solver setting, as the solver ensemble grows.

Additionally, the neural operator is selected only rarely across all configurations. This reflects the strength of the numerical solvers rather than a limitation of our method. Our framework is designed to exploit this structure by relying primarily on numerical updates and invoking the learned component only when beneficial, demonstrating that selective use of learned corrections can yield performance gains without frequent deployment like in HINTS or similar fixed schedules.

Finally, the non-zero standard deviations indicate that solver usage varies across test instances, suggesting that no single global routing strategy emerges.

D.7 Results on a finer grid

We have replicated the Paired Solver and Solver Ensemble experiments for a grid of 63×63 .

In Table 14, we notice that, similar to the case with 31×31 grid, the learned greedy router closely matches the performance of the true greedy oracle and outperforms its single solver and HINTS baselines with great statistical significance.

Similar to Table 3, we notice, in Table 15, the learned greedy router seems to outperform the various pairwise configurations mostly with great statistical significance.

Table 14: Final error and AUC of squared L^2 error (lower is better). Values are mean ($\pm$ standard error (s.e.)) over 128 test instances for the grid 63×63 ; both mean and s.e. of error are reported in $\times 10^{-3}$. If a standard error is not shown, it is $< 10^{-3}$ in the reported units (raw $< 10^{-6}$). Statistical significance is assessed via paired t -tests comparing each baseline (single-solver only and HINTS) against the learned greedy router, using a one-sided alternative that the learned router achieves lower error/AUC. Reported p -values correspond to these tests.

Equation	Poisson				ConvDiff			
Methods	$\ e_h^{(T)}\ \times 10^3$	$\ e_h^{(T)}\ $ p -value	AUC	AUC p -value	$\ e_h^{(T)}\ \times 10^3$	$\ e_h^{(T)}\ $ p -value	AUC	AUC p -value
Jacobi-related solvers								
Jacobi Only	4.483 (12.776)	$< 10^{-3}$	2.092 (5.889)	$< 10^{-3}$	1.470 (4.164)	0.001	0.757 (2.116)	0.001
HINTS-Jacobi	0.823 (0.163)	0.043	0.571 (1.205)	0.021	1.512 (0.433)	$< 10^{-3}$	0.565 (0.723)	$< 10^{-3}$
Learned Greedy-Jacobi	0.506 (2.201)	-	0.429 (1.293)	-	0.654 (1.603)	-	0.393 (0.969)	-
True-Greedy-Jacobi	0.199 (0.277)	-	0.289 (0.661)	-	0.317 (0.593)	-	0.277 (0.635)	-
GS-related solvers								
GS only	2.094 (6.009)	$< 10^{-3}$	1.519 (4.296)	$< 10^{-3}$	0.357 (1.025)	0.004	0.430 (1.211)	0.003
HINTS-GS	0.631 (0.003)	$< 10^{-3}$	0.444 (0.939)	$< 10^{-3}$	0.996 (0.004)	$< 10^{-3}$	0.369 (0.397)	0.03
Learned Greedy-GS	0.138 (0.581)	-	0.228 (0.623)	-	0.219 (0.697)	-	0.282 (0.820)	-
True-Greedy-GS	0.072 (0.064)	-	0.180 (0.403)	-	0.053 (0.065)	-	0.132 (0.279)	-
SymGS-related solvers								
SymGS only	1.318 (3.541)	$< 10^{-3}$	1.106 (2.978)	$< 10^{-3}$	0.267 (0.725)	0.012	0.362 (0.974)	0.014
HINTS-SymGS	0.566 (0.002)	$< 10^{-3}$	0.375 (0.782)	$< 10^{-3}$	1.007 (0.000)	$< 10^{-3}$	0.367 (0.329)	$< 10^{-3}$
Learned Greedy-SymGS	0.162 (0.155)	-	0.169 (0.310)	-	0.141 (0.355)	-	0.239 (0.599)	-
True-Greedy-SymGS	0.084 (0.094)	-	0.130 (0.266)	-	0.146 (0.285)	-	0.130 (0.241)	-
Jacobi (0.67)-related solvers								
Jacobi (0.67) only	5.833 (16.544)	$< 10^{-3}$	2.365 (6.639)	$< 10^{-3}$	1.985 (5.595)	0.005	0.876 (2.443)	0.004
HINTS-Jacobi (0.67)	1.177 (0.445)	$< 10^{-3}$	0.687 (1.414)	$< 10^{-3}$	1.970 (0.989)	$< 10^{-3}$	0.652 (0.883)	0.001
Learned Greedy-Jacobi (0.67)	0.693 (1.959)	-	0.489 (1.217)	-	1.060 (2.422)	-	0.517 (1.211)	-
True-Greedy-Jacobi (0.67)	0.396 (0.741)	-	0.406 (0.979)	-	0.528 (1.133)	-	0.352 (0.831)	-
SOR (1.5)-related solvers								
SOR (1.5) only	0.115 (0.331)	$< 10^{-3}$	0.652 (1.850)	$< 10^{-3}$	$< 10^{-3}$	0.056	0.078 (0.220)	0.002
HINTS-SOR (1.5)	0.480 (0.000)	$< 10^{-3}$	0.304 (0.680)	$< 10^{-3}$	0.608 (0.000)	$< 10^{-3}$	0.147 (0.165)	$< 10^{-3}$
Learned Greedy-SOR (1.5)	0.017 (0.084)	-	0.148 (0.516)	-	$< 10^{-3}$	-	0.039 (0.090)	-
True-Greedy-SOR (1.5)	0.004 (0.003)	-	0.081 (0.188)	-	$< 10^{-3}$	-	0.030 (0.067)	-

Table 15: Final error and AUC of squared L^2 error (lower is better). Values are mean ($\pm$ standard error (s.e.)) over 128 test instances for the grid 63×63 ; both mean and s.e. of error are reported in $\times 10^{-3}$. If a standard error is not shown, it is $< 10^{-3}$ in the reported units (raw $< 10^{-6}$). Statistical significance is assessed via paired t -tests comparing each solver ensemble against the corresponding pairwise learned router (e.g., NO + Jacobi, NO + GS), using a one-sided alternative that the ensemble achieves lower error/AUC. Reported p -values correspond to these tests.

$\mathcal{W}$	$\ e_h^{(T)}\ \times 10^3$	AUC	Jacobi p -value	GS p -value	SymGS p -value	Jacobi (0.67) p -value	SOR (1.5) p -value
Poisson							
Learned Greedy {Jacobi, GS}	0.077 (0.064)	0.188 (0.410)	0.002	0.08	-	-	-
True Greedy {Jacobi, GS}	0.072 (0.064)	0.180 (0.403)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS}	0.112 (0.086)	0.151 (0.275)	0.002	0.015	$< 10^{-3}$	-	-
True Greedy {Jacobi, GS, SymGS}	0.054 (0.059)	0.126 (0.264)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	0.109 (0.103)	0.152 (0.282)	0.002	0.013	$< 10^{-3}$	$< 10^{-3}$	-
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	0.054 (0.059)	0.126 (0.264)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	0.014 (0.006)	0.092 (0.205)	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	0.054
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	0.004 (0.003)	0.082 (0.189)	-	-	-	-	-
ConvDiff							
Learned Greedy {Jacobi, GS}	0.136 (0.447)	0.170 (0.394)	$< 10^{-3}$	0.015	-	-	-
True Greedy {Jacobi, GS}	0.053 (0.065)	0.132 (0.279)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS}	0.063 (0.098)	0.142 (0.335)	$< 10^{-3}$	0.006	0.001	-	-
True Greedy {Jacobi, GS, SymGS}	0.025 (0.037)	0.105 (0.220)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	0.114 (0.216)	0.181 (0.413)	$< 10^{-3}$	0.024	0.011	$< 10^{-3}$	-
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67)}	0.025 (0.037)	0.105 (0.220)	-	-	-	-	-
Learned Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	$< 10^{-3}$	0.037 (0.087)	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	$< 10^{-3}$	0.069
True Greedy {Jacobi, GS, SymGS, Jacobi (0.67), SOR (1.5)}	$< 10^{-3}$	0.030 (0.067)	-	-	-	-	-

835 D.8 Results with Dirichlet Boundary Conditions

836 We have replicated the Paired Solver and Solver Ensemble experiments for solutions with zero
837 dirichlet boundary conditions.

838 In Table 16, we notice that, similar to PDEs with periodic boundary conditions, the learned greedy
839 router closely matches the performance of the true greedy oracle and outperforms its single solver
840 and HINTS baselines with great statistical significance. Despite the learned router matching the
841 performance of the true greedy oracle, we observe that the learned router doesn't seem to provide
842 much improvement over single-solver baseline in the case of SOR (1.5)-related solvers. This may be
843 a result of the deepnet correction always being weaker relative to the SOR (1.5) correction in terms
844 of error reduction.

845 Similar to Table 3, we notice, in Table 15, the learned greedy router seems to outperform the various
846 pairwise configurations mostly with great statistical significance.

Table 16: Final error and AUC of squared L^2 error (lower is better). Values are mean ($\pm$ standard error (s.e.)) over 128 test instances with dirichlet boundaries; both mean and s.e. of error are reported in $\times 10^{-3}$. If a standard error is not shown, it is $< 10^{-3}$ in the reported units (raw $< 10^{-6}$). Statistical significance is assessed via paired t -tests comparing each baseline (single-solver only and HINTS) against the learned greedy router, using a one-sided alternative that the learned router achieves lower error/AUC. Reported p -values correspond to these tests.

Equation	Poisson				ConvDiff			
Methods	$\ e_h^{(T)}\ \times 10^3$	$\ e_h^{(T)}\ p$ -value	AUC	AUC p -value	$\ e_h^{(T)}\ \times 10^3$	$\ e_h^{(T)}\ p$ -value	AUC	AUC p -value
Jacobi-related solvers								
Jacobi Only	0.704 (2.151)	0.001	0.703 (1.929)	$< 10^{-3}$	0.003 (0.006)	0.057	0.169 (0.430)	$< 10^{-3}$
HINTS-Jacobi	2.674 (7.315)	$< 10^{-3}$	0.869 (2.396)	$< 10^{-3}$	0.474 (0.001)	$< 10^{-3}$	0.199 (0.254)	$< 10^{-3}$
Learned Greedy-Jacobi	0.243 (0.851)	-	0.236 (0.719)	-	0.003 (0.006)	-	0.076 (0.162)	-
True-Greedy-Jacobi	0.042 (0.047)	-	0.099 (0.252)	-	0.003 (0.007)	-	0.042 (0.089)	-
GS-related solvers								
GS only	0.138 (0.431)	0.001	0.408 (1.139)	$< 10^{-3}$	0.003 (0.006)	0.028	0.057 (0.146)	$< 10^{-3}$
HINTS-GS	2.668 (7.316)	$< 10^{-3}$	0.841 (2.360)	$< 10^{-3}$	0.470 (0.001)	$< 10^{-3}$	0.115 (0.137)	$< 10^{-3}$
Learned Greedy-GS	0.032 (0.158)	-	0.115 (0.433)	-	0.003 (0.006)	-	0.024 (0.048)	-
True-Greedy-GS	0.010 (0.015)	-	0.063 (0.166)	-	0.003 (0.006)	-	0.017 (0.036)	-
SymGS-related solvers								
SymGS only	2.924 (8.865)	0.01	0.926 (2.740)	0.006	1.331 (3.687)	0.004	0.413 (1.133)	0.004
HINTS-SymGS	2.748 (7.375)	0.008	0.856 (2.427)	0.008	0.917 (1.015)	0.006	0.332 (0.697)	0.003
Learned Greedy-SymGS	1.333 (5.715)	-	0.416 (1.722)	-	0.628 (1.468)	-	0.196 (0.449)	-
True-Greedy-SymGS	0.342 (0.906)	-	0.147 (0.375)	-	0.184 (0.323)	-	0.067 (0.118)	-
Jacobi (0.67)-related solvers								
Jacobi (0.67) only	1.265 (3.768)	$< 10^{-3}$	0.910 (2.468)	$< 10^{-3}$	0.008 (0.021)	0.003	0.253 (0.642)	$< 10^{-3}$
HINTS-Jacobi (0.67)	2.686 (7.311)	$< 10^{-3}$	0.886 (2.412)	$< 10^{-3}$	0.487 (0.002)	$< 10^{-3}$	0.220 (0.279)	$< 10^{-3}$
Learned Greedy-Jacobi (0.67)	0.134 (0.275)	-	0.215 (0.660)	-	0.004 (0.010)	-	0.127 (0.393)	-
True-Greedy-Jacobi (0.67)	0.096 (0.220)	-	0.145 (0.408)	-	0.004 (0.013)	-	0.061 (0.131)	-
SOR (1.5)-related solvers								
SOR (1.5) only	0.004 (0.011)	0.012	0.145 (0.412)	$< 10^{-3}$	0.003 (0.006)	1.0	0.006 (0.014)	1.0
HINTS-SOR (1.5)	2.650 (7.321)	$< 10^{-3}$	0.791 (2.295)	$< 10^{-3}$	0.468 (0.001)	$< 10^{-3}$	0.014 (0.014)	$< 10^{-3}$
Learned Greedy-SOR (1.5)	0.004 (0.011)	-	0.039 (0.091)	-	0.003 (0.006)	-	0.006 (0.014)	-
True-Greedy-SOR (1.5)	0.004 (0.011)	-	0.028 (0.070)	-	0.003 (0.006)	-	0.006 (0.014)	-

E Cost-Aware Routing and Wall-Clock Evaluation

The experiments of Section 7 compare methods per iteration, which favors methods whose iterations are expensive. This appendix evaluates the end-to-end *wall-clock time to a target accuracy* of the learned router against HINTS and the classical solver alone, for all five classical solvers and three PDEs, on a 128×128 grid ($N^2 = 128^2$ unknowns), using the cost-aware instantiation of the greedy rule introduced at the end of Section 4. Besides the Poisson and convection–diffusion equations of Section 7 we add *anisotropic diffusion*, $-\epsilon \partial_{x_1}^2 u - \partial_{x_2}^2 u = f$ with $\epsilon = 10^{-2}$ (diffusion tensor $\text{diag}(\epsilon, 1)$), on the same periodic domain with the same forcing distribution. It is the standard model problem on which point-relaxation methods fail to smooth: an error component oscillatory in x_1 and smooth in x_2 is damped by only $(1 - \epsilon)/(1 + \epsilon) \approx 0.98$ per Jacobi sweep, and geometric multigrid with point smoothing loses its grid-independent convergence (line relaxation or semi-coarsening would be needed). The same pipeline is then applied to solver ensembles, to larger grids and against stronger classical baselines.

E.1 Protocol

Fast, matched implementations. A wall-clock comparison is meaningful only if the classical baseline is not handicapped by implementation. All solvers are therefore re-implemented for the periodic constant-coefficient setting as $O(N^2)$ operations: Jacobi and damped Jacobi as 5-point stencil sweeps, Gauss–Seidel, SOR and symmetric GS via cached sparse triangular factorizations. Their one-step iterates match the dense implementations used in the rest of the paper to 10^{-12} in double precision. Reference solutions are computed by FFT diagonalization of the same discrete operator, i.e., they are exact solutions of the discrete system, so true errors are available for evaluation at no charged cost. All timings are single-threaded CPU measurements (Apple M4 Pro, numpy/scipy/PyTorch, one thread) on an otherwise idle machine.

Corrector. The neural corrector is a DeepONet applied to the residual $r = f_h - \mathcal{L}_h^a u_h^{(t)}$ and evaluated on a 64×64 sensor grid, i.e., on the $4 \times$ coarser grid obtained by band-limited (FFT) restriction to the modes $|k_1|, |k_2| \leq 31$ (for the anisotropic equation the sensor grid is 128×32 , i.e., full resolution along x_1 , so that the band contains every mode the point smoothers cannot damp; the sensor grid is the only PDE-specific hyperparameter of the pipeline); its output is prolonged back to the fine grid by exact trigonometric interpolation, so the correction is band-limited by construction and never injects error into the high-frequency band that the classical smoother owns. The trunk net is the fixed orthonormal Fourier basis of that band ($p = 3969$ basis functions, as in POD-DeepONet [Lu et al., 2022]), and the branch net is a linear layer on the 4096 sensor values; it is fit by least squares on 64,000 exact (residual, error) pairs of the discrete operator drawn from a mixture of spectral shapes (forcing-like, residual-like, white and randomly tilted spectra), and reaches a validation relative error of 1.7×10^{-6} on every mode of the band. The corrector is applied scale-equivariantly, $C_{\text{NO}}(r) = \|Rr\| \mathcal{G}_\theta(Rr/\|Rr\|)$, which preserves $C_{\text{NO}}(0) = 0$ (Proposition 4.2). One corrector call costs ≈ 0.6 – 0.7 ms at 128^2 (two FFTs and a 4096×4096 matrix–vector product), i.e., about 12 Jacobi sweeps, 3 GS/SOR sweeps, or 2 symmetric-GS sweeps (Table 20). The same corrector is used by HINTS and by all routing policies.

Cost-equalised macro-actions. Per-iteration costs c_j (residual evaluation plus the update) are measured once per pairing on the benchmark machine (minimum over seven repeated blocks of the block median, cached), the unit of cost u is one corrector call, and every operation is applied $m_j = \max\{1, \text{round}(u/c_j)\}$ times per decision (Table 20); for the five stationary solvers this equalises costs to within 8%. An operation dearer than the unit (a multigrid cycle) is applied once and compared per unit of cost, $\|e_j\|^{u/(m_j c_j)}$; the surrogate weights $\tilde{c}_j$ use the same exponent. The cost-aware oracle runs Algorithm 1 on these macro-actions with the true error; the *greedy oracle* row runs the cost-agnostic Algorithm 1 on single operations, as in the main text.

Lightweight router. The learned router selects macro-actions from $6 + K$ scalar features, all $O(1)$ given the residual norm that any stopping test computes: the log relative residual, its per-iteration change over the last macro-action and an exponential moving average thereof, the log epoch index, a one-hot encoding of the previous macro-action, and the log counts of corrector calls so far and of iterations since the last call. It is a two-hidden-layer MLP (64 units) evaluated in numpy, costing

899 $\approx 5 \mu\text{s}$ per decision independently of N . It is trained with the surrogate of Section 5.1, with the
900 per-state weights $\tilde{c}_k$ normalised by $\sum_k \tilde{c}_k$ (which does not change the Bayes decision), on states
901 visited by oracle rollouts with ε -exploration (probability 0.1), followed by two DAgger rounds
902 [Ross et al., 2011] in which the current router’s own rollouts are relabelled by the oracle—the batch
903 analogue of the scheduled sampling used in Section C. Training uses 128 instances per round drawn
904 from the same GRF distribution as the test set but with a different seed; the router of every pairing
905 and ensemble is trained in under two minutes.

906 **Baselines and metric.** HINTS applies the corrector every τ -th iteration; we report $\tau = 25$ (the
907 schedule used in the main text and in Zhang et al. [2024]) and the best of $\tau \in \{5, 10, 25, 50\}$ selected
908 *per cell* on the test instances themselves (an optimistic baseline). For each of 64 test instances we
909 record, after every iteration, the true relative error $\|e_h^{(t)}\|/\|u_h\|$ (untimed, benchmark-only) and the
910 cumulative charged wall-clock time of a replay that executes only the chosen operations (residual,
911 update, and—for the learned router—every feature and decision computation; oracle decisions are
912 not charged). We report the median first time at which the error drops below a tolerance ε , and paired
913 per-instance median speedups. We highlight $\varepsilon = h^2 = 6.1 \times 10^{-5}$: the discretization error of the
914 second-order scheme scales as $O(h^2)$, so driving the algebraic error far below h^2 does not improve
915 the computed solution. We also report the iteration-based metrics of the main text (final relative error
916 and $\text{AUC} = \sum_{t=1}^T \|e_h^{(t)}\|/\|u_h\|$ over $T = 300$ iterations).

917 E.2 Pairwise results

918 Table 2 (main text) reports the time to truncation-level accuracy for all ten pairings; the tables below
919 give the comparison against HINTS at three tolerances (Table 17), the iteration-based metrics of the
920 main text (Table 18), corrector-call and iteration counts (Table 19), the measured costs (Table 20),
921 and the full tolerance sweeps (Tables 21 and 22).

922 **Uniform gains.** In every one of the 10 solver–equation pairings the learned router is the fastest
923 deployable method at $\varepsilon = h^2$: $238\times$ – $1983\times$ faster than the solver alone, $2.68\times$ – $10.3\times$ faster than
924 HINTS with $\tau=25$, and $1.21\times$ – $3.22\times$ faster than the best fixed period chosen per pairing on the test
925 set (all paired Wilcoxon $p < 0.01$). The gains are not confined to the truncation level: at $\varepsilon = 10^{-8}$ the
926 router is still $1.33\times$ – $5.26\times$ faster than HINTS ($\tau=25$) and $1.07\times$ – $1.81\times$ faster than the per-tolerance
927 best period (Table 17), and the best period itself varies across pairings and tolerances ($\tau=5$ at
928 truncation level, $\tau \in \{5, 10, 50\}$ at 10^{-8}), so no single fixed schedule is competitive everywhere.
929 The learned router reproduces the cost-aware oracle’s decisions almost exactly (the same median
930 iteration and call counts in Table 19; median times within $0.98\times$ – $1.06\times$ of the oracle, the difference
931 being its own decision cost and timer noise).

932 **Where the time goes.** Table 19 explains the numbers: with a corrector that removes the smooth
933 band to 10^{-6} in one call, the cost-aware oracle and the router call it first and reach h^2 after one or
934 two further sweeps, i.e., in about two iterations, whereas HINTS reaches the same accuracy only
935 at its first scheduled call (iteration τ), having spent $\tau-1$ sweeps on an error that is almost entirely
936 smooth. Below h^2 the remaining error is the high-frequency band that the corrector cannot see; the
937 router therefore stops calling it (one to three calls in total down to 10^{-8} ; Figure 13), whereas a fixed
938 schedule keeps paying for a call every τ iterations—HINTS ($\tau=5$) executes hundreds of useless calls
939 on the Jacobi pairings (Table 21). The cost-agnostic greedy oracle (Algorithm 1 on single operations)
940 makes the same decisions as its cost-aware counterpart here, because after the first call the corrector
941 is never better than a single sweep on the remaining high-frequency error; the two rules differ only
942 through the granularity of their decisions, and the learned router pays for neither.

943 **Iteration-based metrics.** Table 18 confirms that the iteration-count conclusions of Section 7 hold
944 on the finer grid: the router’s AUC over $T = 300$ iterations is three to four orders of magnitude below
945 HINTS’ and four to five below the solver-only baseline (all $p < 10^{-3}$), and its error after T iterations
946 is at the stopping threshold of the runs (10^{-9}) except for undamped Jacobi, where all hybrids stall at
947 the near-Nyquist band.

Table 17: Paired median speedup of the learned router over HINTS at three tolerances (64 instances; bold: $\geq 1.1 \times$ with one-sided Wilcoxon $p < 0.01$). The right block compares against the fixed period that is best *for that tolerance and pairing*, chosen on the test set.

Equation	Solver	vs. HINTS ($\tau=25$)			vs. best fixed τ		
		$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-8}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-8}$
Poisson	Jacobi	2.89 $\times$	2.68 $\times$	1.55 $\times$	1.19 $\times$ ($\tau=5$)	1.21 $\times$ ($\tau=5$)	1.22 $\times$ ($\tau=50$)
	Jacobi (0.67)	3.20 $\times$	2.90 $\times$	1.78 $\times$	1.31 $\times$ ($\tau=5$)	1.28 $\times$ ($\tau=5$)	1.09 $\times$ ($\tau=10$)
	GS	7.46 $\times$	6.75 $\times$	3.25 $\times$	1.99 $\times$ ($\tau=5$)	1.94 $\times$ ($\tau=5$)	1.25 $\times$ ($\tau=5$)
	SymGS	11.8 $\times$	9.21 $\times$	5.26 $\times$	2.71 $\times$ ($\tau=5$)	2.34 $\times$ ($\tau=5$)	1.81 $\times$ ($\tau=5$)
	SOR (1.5)	7.63 $\times$	10.3 $\times$	2.65 $\times$	1.97 $\times$ ($\tau=5$)	3.22 $\times$ ($\tau=5$)	1.25 $\times$ ($\tau=10$)
ConvDiff	Jacobi	3.34 $\times$	2.95 $\times$	1.33 $\times$	1.27 $\times$ ($\tau=5$)	1.34 $\times$ ($\tau=5$)	1.17 $\times$ ($\tau=50$)
	Jacobi (0.67)	3.64 $\times$	3.14 $\times$	1.77 $\times$	1.39 $\times$ ($\tau=5$)	1.32 $\times$ ($\tau=5$)	1.07 $\times$ ($\tau=10$)
	GS	7.71 $\times$	6.76 $\times$	3.78 $\times$	2.08 $\times$ ($\tau=5$)	2.60 $\times$ ($\tau=5$)	1.17 $\times$ ($\tau=5$)
	SymGS	11.6 $\times$	8.70 $\times$	4.75 $\times$	2.69 $\times$ ($\tau=5$)	2.40 $\times$ ($\tau=5$)	1.62 $\times$ ($\tau=5$)
	SOR (1.5)	7.36 $\times$	8.89 $\times$	2.58 $\times$	2.03 $\times$ ($\tau=5$)	2.40 $\times$ ($\tau=5$)	1.31 $\times$ ($\tau=5$)

Table 18: Iteration-based metrics of the main text on the 128×128 grid: relative error after $T = 300$ iterations and AUC of the relative error over T iterations, mean (standard error) over 64 instances; p -values are one-sided paired t -tests of the baseline’s AUC against the learned router’s.

Method	Poisson			ConvDiff		
	$\ e_h^{(T)}\ /\ u_h\ $	AUC	p	$\ e_h^{(T)}\ /\ u_h\ $	AUC	p
Jacobi-related solvers						
Solver only	7.99e-01 (4.5e-03)	2.68e+02 (8.9e-01)	$< 10^{-3}$	7.43e-01 (9.1e-03)	2.57e+02 (1.9e+00)	$< 10^{-3}$
HINTS ($\tau=25$)	7.10e-06 (1.9e-06)	2.37e+01 (1.1e-02)	$< 10^{-3}$	1.55e-05 (4.2e-06)	2.36e+01 (2.7e-02)	$< 10^{-3}$
Learned router (ours)	6.86e-06 (1.8e-06)	7.15e-03 (1.9e-03)	-	1.50e-05 (4.1e-06)	1.55e-02 (4.1e-03)	-
Cost-aware oracle	6.86e-06 (1.8e-06)	7.15e-03 (1.9e-03)	-	1.50e-05 (4.1e-06)	1.55e-02 (4.1e-03)	-
Jacobi (0.67)-related solvers						
Solver only	8.56e-01 (3.8e-03)	2.77e+02 (7.1e-01)	$< 10^{-3}$	8.11e-01 (7.9e-03)	2.69e+02 (1.5e+00)	$< 10^{-3}$
HINTS ($\tau=25$)	1.15e-12 (1.0e-13)	2.38e+01 (8.3e-03)	$< 10^{-3}$	1.46e-12 (2.7e-13)	2.37e+01 (2.1e-02)	$< 10^{-3}$
Learned router (ours)	7.57e-10 (2.9e-11)	2.49e-03 (6.3e-04)	-	7.96e-10 (1.6e-11)	5.39e-03 (1.4e-03)	-
Cost-aware oracle	8.19e-10 (1.2e-11)	2.49e-03 (6.3e-04)	-	8.18e-10 (1.3e-11)	5.39e-03 (1.4e-03)	-
GS-related solvers						
Solver only	6.53e-01 (5.2e-03)	2.42e+02 (1.2e+00)	$< 10^{-3}$	5.46e-01 (9.9e-03)	2.20e+02 (2.4e+00)	$< 10^{-3}$
HINTS ($\tau=25$)	2.84e-11 (1.9e-12)	2.35e+01 (2.1e-02)	$< 10^{-3}$	8.78e-11 (4.8e-12)	2.32e+01 (5.4e-02)	$< 10^{-3}$
Learned router (ours)	7.66e-10 (1.8e-11)	1.94e-03 (4.9e-04)	-	6.84e-10 (2.8e-11)	4.03e-03 (1.0e-03)	-
Cost-aware oracle	7.08e-10 (2.5e-11)	1.94e-03 (4.9e-04)	-	6.73e-10 (2.8e-11)	4.03e-03 (1.0e-03)	-
SymGS-related solvers						
Solver only	4.49e-01 (4.6e-03)	2.03e+02 (1.3e+00)	$< 10^{-3}$	3.77e-01 (9.1e-03)	1.84e+02 (2.7e+00)	$< 10^{-3}$
HINTS ($\tau=25$)	7.14e-10 (5.4e-11)	2.30e+01 (3.5e-02)	$< 10^{-3}$	3.64e-12 (2.3e-13)	2.26e+01 (8.1e-02)	$< 10^{-3}$
Learned router (ours)	6.50e-10 (2.4e-11)	1.46e-03 (3.7e-04)	-	5.19e-10 (3.4e-11)	3.16e-03 (8.0e-04)	-
Cost-aware oracle	6.32e-10 (2.5e-11)	1.46e-03 (3.7e-04)	-	5.00e-10 (3.2e-11)	3.16e-03 (8.0e-04)	-
SOR (1.5)-related solvers						
Solver only	3.09e-01 (3.5e-03)	1.72e+02 (1.3e+00)	$< 10^{-3}$	1.23e-01 (3.4e-03)	1.17e+02 (1.9e+00)	$< 10^{-3}$
HINTS ($\tau=25$)	2.16e-10 (1.3e-11)	2.26e+01 (4.6e-02)	$< 10^{-3}$	8.06e-10 (2.3e-11)	2.12e+01 (1.2e-01)	$< 10^{-3}$
Learned router (ours)	8.74e-10 (9.7e-12)	3.30e-03 (8.4e-04)	-	8.08e-10 (1.3e-11)	6.49e-03 (1.7e-03)	-
Cost-aware oracle	8.36e-10 (1.5e-11)	3.29e-03 (8.4e-04)	-	7.77e-10 (1.8e-11)	6.49e-03 (1.7e-03)	-

Table 19: Median number of iterations and corrector calls needed to reach $\varepsilon = h^2$ on the 128×128 grid.

Equation	Solver	HINTS ($\tau=25$)		Cost-aware oracle		Learned router	
		iters	NO calls	iters	NO calls	iters	NO calls
Poisson	Jacobi	25	1	2	1	2	1
	Jacobi (0.67)	25	1	2	1	2	1
	GS	26	1	2	1	2	1
	SymGS	26	1	2	1	2	1
	SOR (1.5)	50	2	2	1	2	1
ConvDiff	Jacobi	25	1	2	1	2	1
	Jacobi (0.67)	25	1	4	1	4	1
	GS	30	1	2	1	2	1
	SymGS	26	1	2	1	2	1
	SOR (1.5)	50	2	4	1	4	1

Table 20: Measured single-thread per-iteration costs (residual + update) on the 128×128 grid and the resulting macro-action sizes $m_j = \max\{1, \text{round}(u/c_j)\}$ (u : corrector call).

Equation	Solver	classical iteration	corrector iteration	m_{solver}	m_{NO}
Poisson	Jacobi	52 μs	635 μs	12	1
	Jacobi (0.67)	52 μs	639 μs	12	1
	GS	200 μs	643 μs	3	1
	SymGS	366 μs	635 μs	2	1
	SOR (1.5)	197 μs	635 μs	3	1
ConvDiff	Jacobi	72 μs	658 μs	9	1
	Jacobi (0.67)	71 μs	659 μs	9	1
	GS	234 μs	673 μs	3	1
	SymGS	378 μs	665 μs	2	1
	SOR (1.5)	223 μs	660 μs	3	1

Table 21: Poisson on the 128×128 grid: median wall-clock time to relative error ε for every policy and pairing (64 instances; paired median speedup over solver-only in parentheses; † n : n instances did not reach the tolerance within the iteration cap).

Solver	Method	$\varepsilon=10^{-2}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-5}$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
Jacobi	Solver only	536.0 ms	806.1 ms	1.15 s	1.36 s	1.62 s	2.14 s
	HINTS ($\tau=25$)	2.61 ms (193 $\times$)	2.61 ms (294 $\times$)	2.65 ms (412 $\times$)	2.89 ms (478 $\times$)	3.56 ms (447 $\times$)	226.1 ms (10.0 $\times$)
	HINTS ($\tau=10$)	1.42 ms (355 $\times$)	1.42 ms (543 $\times$)	1.46 ms (738 $\times$)	1.50 ms (864 $\times$)	3.89 ms (518 $\times$)	329.2 ms (6.94 $\times$)
	HINTS ($\tau=5$)	1.06 ms (463 $\times$)	1.06 ms (719 $\times$)	1.10 ms (984 $\times$)	1.15 ms (1153 $\times$)	6.30 ms (432 $\times$)	545.2 ms (4.19 $\times$)
	HINTS ($\tau=50$)	3.80 ms (122 $\times$)	3.80 ms (187 $\times$)	4.16 ms (253 $\times$)	4.22 ms (300 $\times$)	5.29 ms (322 $\times$)	182.8 ms (12.5 $\times$)
	Greedy oracle (Alg. 1)	773 μ s (668 $\times$)	803 μ s (996 $\times$)	854 μ s (1283 $\times$)	964 μ s (1350 $\times$)	2.94 ms (680 $\times$)	155.1 ms (14.4 $\times$)
	Cost-aware oracle	862 μ s (605 $\times$)	880 μ s (901 $\times$)	942 μ s (1199 $\times$)	1.02 ms (1268 $\times$)	2.94 ms (623 $\times$)	154.1 ms (13.9 $\times$)
	Learned router (ours)	884 μ s (597 $\times$)	918 μ s (868 $\times$)	987 μ s (1154 $\times$)	1.09 ms (1202 $\times$)	2.98 ms (655 $\times$)	151.3 ms (14.4 $\times$)
Jacobi (0.67)	Solver only	777.3 ms	1.16 s	1.62 s	1.93 s	2.33 s	3.16 s
	HINTS ($\tau=25$)	2.71 ms (290 $\times$)	2.71 ms (437 $\times$)	2.71 ms (621 $\times$)	2.71 ms (749 $\times$)	2.74 ms (874 $\times$)	5.16 ms (631 $\times$)
	HINTS ($\tau=10$)	1.46 ms (540 $\times$)	1.46 ms (819 $\times$)	1.46 ms (1161 $\times$)	1.50 ms (1335 $\times$)	1.61 ms (1467 $\times$)	3.03 ms (1058 $\times$)
	HINTS ($\tau=5$)	1.11 ms (713 $\times$)	1.11 ms (1074 $\times$)	1.13 ms (1464 $\times$)	1.17 ms (1681 $\times$)	1.91 ms (1332 $\times$)	4.09 ms (747 $\times$)
	HINTS ($\tau=50$)	4.42 ms (183 $\times$)	4.42 ms (278 $\times$)	4.42 ms (391 $\times$)	4.42 ms (468 $\times$)	4.43 ms (557 $\times$)	8.66 ms (377 $\times$)
	Greedy oracle (Alg. 1)	796 μ s (988 $\times$)	818 μ s (1455 $\times$)	915 μ s (1904 $\times$)	1.09 ms (1970 $\times$)	1.50 ms (1575 $\times$)	2.83 ms (1112 $\times$)
	Cost-aware oracle	805 μ s (981 $\times$)	820 μ s (1424 $\times$)	922 μ s (1836 $\times$)	1.09 ms (1892 $\times$)	1.53 ms (1684 $\times$)	2.93 ms (1106 $\times$)
	Learned router (ours)	822 μ s (958 $\times$)	839 μ s (1402 $\times$)	912 μ s (1863 $\times$)	1.10 ms (1869 $\times$)	1.51 ms (1650 $\times$)	2.93 ms (1093 $\times$)
GS	Solver only	854.7 ms	1.29 s	1.83 s	2.17 s	2.60 s	3.45 s
	HINTS ($\tau=25$)	6.43 ms (134 $\times$)	6.43 ms (203 $\times$)	6.65 ms (277 $\times$)	12.4 ms (177 $\times$)	12.6 ms (208 $\times$)	13.9 ms (250 $\times$)
	HINTS ($\tau=10$)	2.88 ms (296 $\times$)	2.88 ms (450 $\times$)	3.14 ms (574 $\times$)	5.65 ms (383 $\times$)	5.65 ms (458 $\times$)	8.38 ms (412 $\times$)
	HINTS ($\tau=5$)	1.72 ms (502 $\times$)	1.72 ms (759 $\times$)	1.99 ms (906 $\times$)	3.36 ms (645 $\times$)	3.63 ms (711 $\times$)	5.55 ms (621 $\times$)
	HINTS ($\tau=50$)	11.8 ms (73.1 $\times$)	11.8 ms (110 $\times$)	12.0 ms (152 $\times$)	20.2 ms (108 $\times$)	23.4 ms (111 $\times$)	23.7 ms (146 $\times$)
	Greedy oracle (Alg. 1)	814 μ s (1066 $\times$)	835 μ s (1563 $\times$)	960 μ s (1872 $\times$)	1.29 ms (1622 $\times$)	2.53 ms (999 $\times$)	4.34 ms (778 $\times$)
	Cost-aware oracle	818 μ s (1061 $\times$)	827 μ s (1571 $\times$)	953 μ s (1892 $\times$)	1.31 ms (1603 $\times$)	2.55 ms (990 $\times$)	4.37 ms (773 $\times$)
	Learned router (ours)	832 μ s (1041 $\times$)	850 μ s (1544 $\times$)	1.01 ms (1809 $\times$)	1.34 ms (1563 $\times$)	2.61 ms (969 $\times$)	4.45 ms (758 $\times$)
SymGS	Solver only	720.5 ms	1.08 s	1.52 s	1.81 s	2.17 s	2.91 s
	HINTS ($\tau=25$)	10.2 ms (71.3 $\times$)	10.2 ms (108 $\times$)	10.3 ms (149 $\times$)	11.8 ms (155 $\times$)	20.2 ms (109 $\times$)	20.2 ms (146 $\times$)
	HINTS ($\tau=10$)	4.33 ms (167 $\times$)	4.33 ms (252 $\times$)	4.53 ms (341 $\times$)	6.89 ms (266 $\times$)	8.48 ms (259 $\times$)	9.10 ms (325 $\times$)
	HINTS ($\tau=5$)	2.35 ms (308 $\times$)	2.35 ms (465 $\times$)	2.60 ms (585 $\times$)	4.38 ms (412 $\times$)	4.63 ms (477 $\times$)	6.94 ms (425 $\times$)
	HINTS ($\tau=50$)	19.6 ms (36.9 $\times$)	19.6 ms (55.9 $\times$)	19.6 ms (78.4 $\times$)	20.8 ms (88.2 $\times$)	39.1 ms (56.4 $\times$)	39.1 ms (75.4 $\times$)
	Greedy oracle (Alg. 1)	814 μ s (882 $\times$)	829 μ s (1312 $\times$)	1.09 ms (1395 $\times$)	1.44 ms (1285 $\times$)	2.20 ms (1029 $\times$)	3.87 ms (772 $\times$)
	Cost-aware oracle	817 μ s (883 $\times$)	829 μ s (1319 $\times$)	1.13 ms (1330 $\times$)	1.49 ms (1205 $\times$)	2.22 ms (1004 $\times$)	3.86 ms (766 $\times$)
	Learned router (ours)	843 μ s (856 $\times$)	853 μ s (1289 $\times$)	1.13 ms (1331 $\times$)	1.49 ms (1198 $\times$)	2.28 ms (981 $\times$)	3.88 ms (754 $\times$)
SOR (1.5)	Solver only	281.1 ms	424.4 ms	600.9 ms	713.1 ms	855.7 ms	1.15 s
	HINTS ($\tau=25$)	6.37 ms (44.3 $\times$)	6.37 ms (67.6 $\times$)	12.2 ms (49.4 $\times$)	12.5 ms (57.5 $\times$)	12.5 ms (69.3 $\times$)	18.5 ms (62.4 $\times$)
	HINTS ($\tau=10$)	2.85 ms (98.0 $\times$)	2.85 ms (148 $\times$)	5.59 ms (107 $\times$)	5.59 ms (127 $\times$)	5.83 ms (149 $\times$)	8.56 ms (135 $\times$)
	HINTS ($\tau=5$)	1.70 ms (167 $\times$)	1.72 ms (251 $\times$)	3.37 ms (180 $\times$)	3.41 ms (208 $\times$)	5.08 ms (168 $\times$)	9.38 ms (122 $\times$)
	HINTS ($\tau=50$)	11.9 ms (23.3 $\times$)	11.9 ms (35.6 $\times$)	17.0 ms (35.3 $\times$)	23.8 ms (30.1 $\times$)	23.8 ms (36.2 $\times$)	35.0 ms (32.7 $\times$)
	Greedy oracle (Alg. 1)	783 μ s (354 $\times$)	814 μ s (528 $\times$)	1.03 ms (583 $\times$)	1.74 ms (419 $\times$)	3.77 ms (236 $\times$)	7.48 ms (158 $\times$)
	Cost-aware oracle	784 μ s (357 $\times$)	800 μ s (527 $\times$)	1.02 ms (582 $\times$)	1.87 ms (380 $\times$)	3.94 ms (219 $\times$)	6.81 ms (168 $\times$)
	Learned router (ours)	804 μ s (343 $\times$)	823 μ s (511 $\times$)	1.02 ms (576 $\times$)	1.82 ms (390 $\times$)	3.88 ms (223 $\times$)	7.05 ms (160 $\times$)

Table 22: Convection–diffusion on the 128×128 grid: median wall-clock time to relative error ε for every policy and pairing (64 instances).

Solver	Method	$\varepsilon=10^{-2}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-5}$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
Jacobi	Solver only	692.2 ms	1.07 s	1.51 s	1.80 s	2.16 s	2.90 s
	HINTS ($\tau=25$)	3.41 ms (205 $\times$)	3.41 ms (312 $\times$)	3.44 ms (436 $\times$)	3.46 ms (516 $\times$)	9.31 ms (306 $\times$)	384.4 ms (7.40 $\times$)
	HINTS ($\tau=10$)	1.76 ms (392 $\times$)	1.76 ms (598 $\times$)	1.80 ms (829 $\times$)	1.88 ms (972 $\times$)	12.8 ms (229 $\times$)	536.2 ms (5.30 $\times$)
	HINTS ($\tau=5$)	1.26 ms (539 $\times$)	1.26 ms (821 $\times$)	1.28 ms (1145 $\times$)	1.47 ms (1236 $\times$)	20.4 ms (140 $\times$)	838.4 ms (3.39 $\times$)
	HINTS ($\tau=50$)	5.76 ms (121 $\times$)	5.76 ms (184 $\times$)	5.76 ms (261 $\times$)	5.85 ms (307 $\times$)	9.40 ms (250 $\times$)	321.5 ms (8.89 $\times$)
	Greedy oracle (Alg. 1)	851 μ s (792 $\times$)	874 μ s (1198 $\times$)	992 μ s (1532 $\times$)	1.31 ms (1317 $\times$)	7.99 ms (332 $\times$)	281.0 ms (10.2 $\times$)
	Cost-aware oracle	961 μ s (706 $\times$)	979 μ s (1073 $\times$)	1.15 ms (1319 $\times$)	1.43 ms (1206 $\times$)	8.26 ms (337 $\times$)	281.8 ms (10.1 $\times$)
	Learned router (ours)	1.00 ms (694 $\times$)	1.01 ms (1062 $\times$)	1.14 ms (1317 $\times$)	1.52 ms (1146 $\times$)	8.15 ms (313 $\times$)	292.7 ms (9.72 $\times$)
Jacobi (0.67)	Solver only	1.01 s	1.55 s	2.22 s	2.65 s	3.21 s	4.32 s
	HINTS ($\tau=25$)	3.40 ms (296 $\times$)	3.40 ms (461 $\times$)	3.40 ms (656 $\times$)	3.40 ms (784 $\times$)	3.47 ms (926 $\times$)	6.53 ms (663 $\times$)
	HINTS ($\tau=10$)	1.77 ms (572 $\times$)	1.77 ms (880 $\times$)	1.77 ms (1234 $\times$)	1.79 ms (1445 $\times$)	2.06 ms (1575 $\times$)	3.79 ms (1139 $\times$)
	HINTS ($\tau=5$)	1.28 ms (782 $\times$)	1.28 ms (1208 $\times$)	1.31 ms (1670 $\times$)	1.49 ms (1760 $\times$)	2.62 ms (1221 $\times$)	5.62 ms (764 $\times$)
	HINTS ($\tau=50$)	5.76 ms (174 $\times$)	5.76 ms (269 $\times$)	5.76 ms (386 $\times$)	5.76 ms (461 $\times$)	5.81 ms (551 $\times$)	11.3 ms (381 $\times$)
	Greedy oracle (Alg. 1)	849 μ s (1185 $\times$)	885 μ s (1789 $\times$)	1.10 ms (2036 $\times$)	1.38 ms (1877 $\times$)	1.91 ms (1668 $\times$)	3.56 ms (1177 $\times$)
	Cost-aware oracle	856 μ s (1182 $\times$)	878 μ s (1766 $\times$)	1.08 ms (1974 $\times$)	1.37 ms (1885 $\times$)	1.88 ms (1624 $\times$)	3.61 ms (1164 $\times$)
	Learned router (ours)	893 μ s (1145 $\times$)	912 μ s (1741 $\times$)	1.10 ms (1983 $\times$)	1.43 ms (1817 $\times$)	1.94 ms (1620 $\times$)	3.70 ms (1139 $\times$)
GS	Solver only	749.7 ms	1.15 s	1.63 s	1.94 s	2.34 s	3.14 s
	HINTS ($\tau=25$)	7.03 ms (107 $\times$)	7.03 ms (164 $\times$)	8.27 ms (198 $\times$)	13.7 ms (141 $\times$)	13.7 ms (170 $\times$)	20.5 ms (152 $\times$)
	HINTS ($\tau=10$)	3.21 ms (233 $\times$)	3.21 ms (356 $\times$)	5.02 ms (330 $\times$)	6.34 ms (312 $\times$)	6.35 ms (370 $\times$)	9.41 ms (337 $\times$)
	HINTS ($\tau=5$)	1.90 ms (391 $\times$)	1.90 ms (604 $\times$)	3.60 ms (453 $\times$)	3.66 ms (529 $\times$)	4.28 ms (547 $\times$)	6.24 ms (502 $\times$)
	HINTS ($\tau=50$)	13.3 ms (56.5 $\times$)	13.3 ms (86.7 $\times$)	14.2 ms (115 $\times$)	26.4 ms (74.0 $\times$)	26.4 ms (89.1 $\times$)	28.2 ms (112 $\times$)
	Greedy oracle (Alg. 1)	863 μ s (855 $\times$)	887 μ s (1283 $\times$)	1.23 ms (1341 $\times$)	1.75 ms (1108 $\times$)	3.28 ms (712 $\times$)	5.32 ms (587 $\times$)
	Cost-aware oracle	869 μ s (838 $\times$)	909 μ s (1262 $\times$)	1.32 ms (1222 $\times$)	1.84 ms (1048 $\times$)	3.26 ms (717 $\times$)	5.46 ms (582 $\times$)
	Learned router (ours)	892 μ s (819 $\times$)	906 μ s (1239 $\times$)	1.35 ms (1243 $\times$)	1.89 ms (1060 $\times$)	3.29 ms (704 $\times$)	5.59 ms (570 $\times$)
SymGS	Solver only	716.5 ms	1.10 s	1.56 s	1.85 s	2.23 s	2.99 s
	HINTS ($\tau=25$)	10.7 ms (67.4 $\times$)	10.7 ms (103 $\times$)	11.1 ms (141 $\times$)	21.1 ms (88.1 $\times$)	21.2 ms (106 $\times$)	21.6 ms (139 $\times$)
	HINTS ($\tau=10$)	4.55 ms (157 $\times$)	4.55 ms (240 $\times$)	5.02 ms (311 $\times$)	8.94 ms (207 $\times$)	8.94 ms (249 $\times$)	13.2 ms (226 $\times$)
	HINTS ($\tau=5$)	2.52 ms (287 $\times$)	2.52 ms (436 $\times$)	2.96 ms (529 $\times$)	4.92 ms (378 $\times$)	4.93 ms (455 $\times$)	7.35 ms (408 $\times$)
	HINTS ($\tau=50$)	20.7 ms (34.5 $\times$)	20.7 ms (53.0 $\times$)	21.1 ms (73.6 $\times$)	40.9 ms (45.5 $\times$)	41.4 ms (54.1 $\times$)	41.4 ms (72.4 $\times$)
	Greedy oracle (Alg. 1)	895 μ s (785 $\times$)	911 μ s (1198 $\times$)	1.25 ms (1254 $\times$)	1.66 ms (1130 $\times$)	2.97 ms (752 $\times$)	4.91 ms (618 $\times$)
	Cost-aware oracle	886 μ s (795 $\times$)	905 μ s (1212 $\times$)	1.27 ms (1236 $\times$)	1.73 ms (1084 $\times$)	3.14 ms (693 $\times$)	4.48 ms (657 $\times$)
	Learned router (ours)	908 μ s (772 $\times$)	924 μ s (1182 $\times$)	1.28 ms (1211 $\times$)	1.72 ms (1086 $\times$)	3.20 ms (698 $\times$)	4.54 ms (647 $\times$)
SOR (1.5)	Solver only	177.4 ms	270.0 ms	383.6 ms	457.3 ms	550.1 ms	737.6 ms
	HINTS ($\tau=25$)	6.91 ms (25.3 $\times$)	6.92 ms (38.5 $\times$)	13.6 ms (28.0 $\times$)	13.6 ms (33.4 $\times$)	13.6 ms (40.1 $\times$)	20.2 ms (36.1 $\times$)
	HINTS ($\tau=10$)	3.16 ms (54.9 $\times$)	3.27 ms (82.9 $\times$)	6.21 ms (61.4 $\times$)	6.21 ms (73.1 $\times$)	9.20 ms (59.6 $\times$)	10.7 ms (68.5 $\times$)
	HINTS ($\tau=5$)	1.85 ms (92.3 $\times$)	1.98 ms (137 $\times$)	3.64 ms (104 $\times$)	4.36 ms (107 $\times$)	5.88 ms (93.1 $\times$)	9.62 ms (76.0 $\times$)
	HINTS ($\tau=50$)	13.4 ms (13.2 $\times$)	13.4 ms (20.0 $\times$)	26.6 ms (14.5 $\times$)	26.6 ms (17.2 $\times$)	26.6 ms (20.7 $\times$)	39.8 ms (18.7 $\times$)
	Greedy oracle (Alg. 1)	876 μ s (199 $\times$)	919 μ s (300 $\times$)	1.39 ms (273 $\times$)	2.43 ms (188 $\times$)	4.34 ms (130 $\times$)	7.66 ms (98.8 $\times$)
	Cost-aware oracle	900 μ s (198 $\times$)	922 μ s (294 $\times$)	1.63 ms (240 $\times$)	2.72 ms (167 $\times$)	4.55 ms (121 $\times$)	7.97 ms (93.9 $\times$)
	Learned router (ours)	910 μ s (195 $\times$)	934 μ s (294 $\times$)	1.59 ms (238 $\times$)	2.67 ms (168 $\times$)	4.50 ms (120 $\times$)	8.18 ms (91.7 $\times$)




Figure 12: One-shot predictions of the corrector on two test forcings per equation (rows): forcing, exact discrete solution, DeepONet output $C_{NO}(f)$ and its error. The corrector solves the band $|k| \leq 31$ to $\approx 10^{-6}$; the remaining error is the high-frequency content of the solution outside the band, which the classical smoother removes in a few sweeps.




Figure 13: Corrector usage: fraction of test runs that execute a corrector call at each iteration, for the learned router, the cost-aware oracle and HINTS ($\tau = 25$). The router calls the corrector once at the start, spends a solver-dependent number of sweeps on the high-frequency band, and calls it again only when the smooth error has re-emerged; HINTS waits 24 sweeps before its first call.




Figure 14: Routing decisions (dark: corrector call) of the learned router (top rows) and the cost-aware oracle (bottom rows) over the first 60 iterations of the stored test instances, for every pairing.




Figure 15: Relative error against charged wall-clock time for one test instance per pairing. The dashed horizontal line is $\varepsilon = h^2$.

948 E.3 Solver ensembles

949 The ensemble experiments of Section 7 are repeated in wall-clock terms with the cost-aware router
 950 over $\text{NO} \cup \mathcal{W}$ for the same four ensembles $\mathcal{W}$ (macro-action sizes are set from the measured costs
 951 of all members, $m_j = \text{round}(c_{\max}/c_j)$). HINTS does not apply to ensembles, so the comparison
 952 is against every member solver alone and against the best pairwise router $\text{Router}(\text{NO} \cup \{\text{solver}\})$,
 953 $\text{solver} \in \mathcal{W}$, from Table 2.

954 **Results.** Table 23 shows that the ensemble router is competitive with, but does not systematically
 955 improve on, the best pairwise router of its members: across the 8 ensemble–equation cells the ratio
 956 of median times to h^2 (best pairwise router over ensemble router) ranges from $0.82 \times$ to $1.14 \times$, i.e.,

within $\pm 15\%$, while the ensemble router is $380\times$ – $1512\times$ faster than the fastest member solver alone, and it does not need to know in advance which member is fastest (the best pairwise member differs between Jacobi and damped Jacobi across cells). The cost-aware *oracle* over the full ensemble is faster than every pairwise router in every cell (Table 23), so the ensembles do contain exploitable diversity; the gap between the ensemble router and its oracle (significant in the larger ensembles, Table 43) is imitation error. It has a clear cause: with several cost-equalised smoothers in the ensemble the oracle’s choice among them depends on the spectral content of the current error, which the router’s residual-norm history features only reflect indirectly, and the surrogate’s weights are small for such near-ties, so the router agrees with the oracle on only 55–83% of its own decisions (against 90–99% for the pairwise routers) and occasionally picks a smoother that is a few percent worse per unit cost. Deciding *when* to call the corrector—the decision that dominates the wall-clock gains—is learned equally well in the ensembles. Table 24 lists how the iterations up to the h^2 crossing are distributed: the corrector is called once (or twice) and the remaining iterations go to whichever smoother the router selects for the high-frequency band, with an instance-dependent mix, as in Section D.6.

Table 23: Ensembles: median wall-clock time to $\varepsilon = h^2$ on the 128×128 grid (64 instances). The ensemble router is compared with the fastest member solver alone, with the fastest pairwise router of its members (paired median speedup in parentheses), and with the cost-aware oracle over the same ensemble.

Equation	$\mathcal{W}$	Best solver only	Best pairwise router	Router($\text{NO} \cup \mathcal{W}$)	Oracle($\text{NO} \cup \mathcal{W}$)
Poisson	$\{\text{Jacobi}, \text{GS}\}$	1.15 s (Jacobi)	987 μs (Jacobi)	964 μs ($1.09\times$ vs pairwise)	834 μs
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}\}$	1.15 s (Jacobi)	987 μs (Jacobi)	951 μs ($1.07\times$ vs pairwise)	854 μs
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67)\}$	1.15 s (Jacobi)	912 μs (Jacobi (0.67))	868 μs ($0.98\times$ vs pairwise)	842 μs
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67), \text{SOR}(1.5)\}$	600.9 ms (SOR (1.5))	912 μs (Jacobi (0.67))	1.12 ms ($0.86\times$ vs pairwise)	900 μs
ConvDiff	$\{\text{Jacobi}, \text{GS}\}$	1.51 s (Jacobi)	1.14 ms (Jacobi)	1.25 ms ($1.09\times$ vs pairwise)	974 μs
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}\}$	1.51 s (Jacobi)	1.14 ms (Jacobi)	1.01 ms ($1.16\times$ vs pairwise)	996 μs
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67)\}$	1.51 s (Jacobi)	1.10 ms (Jacobi (0.67))	996 μs ($1.00\times$ vs pairwise)	1.07 ms
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67), \text{SOR}(1.5)\}$	383.6 ms (SOR (1.5))	1.10 ms (Jacobi (0.67))	1.01 ms ($1.06\times$ vs pairwise)	1.08 ms

Table 24: Ensembles: average fraction of iterations (up to the h^2 crossing) spent in each component by the learned router, mean (standard deviation) over 64 instances; “-” marks components not in the ensemble.

Equation	$\mathcal{W}$	Jacobi	GS	SymGS	Jacobi (0.67)	SOR (1.5)	DeepONet
Poisson	$\{\text{Jacobi}, \text{GS}\}$	0.228 (0.365)	0.144 (0.216)	-	-	-	0.628 (0.386)
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}\}$	0.237 (0.337)	0.043 (0.134)	0.086 (0.165)	-	-	0.634 (0.378)
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67)\}$	0.235 (0.297)	0.008 (0.062)	0.101 (0.207)	0.000 (0.000)	-	0.656 (0.352)
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67), \text{SOR}(1.5)\}$	0.094 (0.195)	0.020 (0.051)	0.182 (0.265)	0.046 (0.125)	0.007 (0.023)	0.650 (0.366)
ConvDiff	$\{\text{Jacobi}, \text{GS}\}$	0.089 (0.255)	0.310 (0.337)	-	-	-	0.600 (0.373)
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}\}$	0.279 (0.354)	0.067 (0.156)	0.055 (0.103)	-	-	0.599 (0.374)
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67)\}$	0.305 (0.340)	0.000 (0.000)	0.022 (0.038)	0.110 (0.214)	-	0.563 (0.410)
	$\{\text{Jacobi}, \text{GS}, \text{SymGS}, \text{Jacobi}(0.67), \text{SOR}(1.5)\}$	0.166 (0.302)	0.028 (0.127)	0.000 (0.000)	0.233 (0.375)	0.000 (0.000)	0.573 (0.399)

971 E.4 Stronger classical baselines, larger grids and overheads

972 The comparisons above are against the stationary solvers of Section 7. This section adds the classical
973 methods a practitioner would actually reach for on these problems, scales the grid up to 512×512 ,
974 and accounts explicitly for every overhead.

975 **Baselines.** All baselines run on the same $O(N^2)$ stencil with the same accounting (first iteration at
976 which the true error is below ε ; timed replay of exactly that many iterations). (i) *FFT direct solve*: for
977 the constant-coefficient periodic problems used here the discrete operator is diagonalised by the FFT,
978 so the system can be solved directly with two FFTs; this is the reference solver we use to compute
979 ground truth and it is included as the lower bound on the time any iterative method can achieve on this
980 problem class. (ii) *Geometric multigrid*: V(2,2)-cycles with lexicographic Gauss–Seidel smoothing,
981 full-weighting restriction, bilinear prolongation, rediscrctised coarse operators and a direct solve on
982 the 32×32 coarsest grid (error contraction ≈ 0.03 per cycle). A V-cycle is a stationary iteration, so
983 multigrid is also used as an ensemble member below. (iii) *Krylov methods* (SciPy implementations
984 driven by the stencil matvec): conjugate gradients, CG preconditioned by symmetric GS and by a
985 symmetric V-cycle for Poisson; BiCGSTAB, multigrid-preconditioned BiCGSTAB and restarted
986 GMRES(20) for convection–diffusion (GMRES is accounted at the granularity of its restart cycles).

Table 25: Strong classical baselines on the 128×128 grid: median time to relative error ε over 64 instances (paired median speedup of the learned router with its best stationary pairing over each method in parentheses; > 1 means the router is faster) and median iterations to h^2 . The FFT solve is a direct method for this problem class and bounds every iterative solver from below.

Equation	Method	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$	iters to h^2
Poisson	FFT direct solve	317 μ s (0.36 $\times$)	317 μ s (0.36 $\times$)	317 μ s (0.36 $\times$)	317 μ s (0.36 $\times$)	1
	Multigrid V(2,2) alone	2.75 ms (2.96 $\times$)	3.99 ms (3.62 $\times$)	5.47 ms (5.42 $\times$)	7.97 ms (8.11 $\times$)	3
	CG	9.37 ms (9.44 $\times$)	11.5 ms (11.8 $\times$)	14.2 ms (14.9 $\times$)	16.3 ms (17.6 $\times$)	162
	PCG (SymGS)	20.3 ms (20.5 $\times$)	30.8 ms (32.4 $\times$)	40.3 ms (44.0 $\times$)	52.5 ms (56.4 $\times$)	75
	PCG (multigrid)	2.97 ms (2.99 $\times$)	4.35 ms (3.85 $\times$)	5.84 ms (5.48 $\times$)	7.36 ms (7.44 $\times$)	3
	HINTS ($\tau=25$), Jacobi (0.67)	2.71 ms (2.90 $\times$)	2.71 ms (2.90 $\times$)	2.74 ms (2.94 $\times$)	5.16 ms (5.57 $\times$)	25
	Learned router, {NO, Jacobi (0.67)}	839 μ s	912 μ s	1.51 ms	2.93 ms	2
	Learned router, {NO, Multigrid}	783 μ s	2.05 ms	3.33 ms	4.72 ms	2
ConvDiff	Cost-aware oracle, {NO, Multigrid}	773 μ s	2.02 ms	3.29 ms	4.66 ms	2
	FFT direct solve	376 μ s (0.37 $\times$)	376 μ s (0.37 $\times$)	376 μ s (0.37 $\times$)	376 μ s (0.37 $\times$)	1
	Multigrid V(2,2) alone	3.06 ms (2.92 $\times$)	4.52 ms (3.71 $\times$)	6.15 ms (5.56 $\times$)	8.92 ms (7.78 $\times$)	3
	BiCGSTAB	56.0 ms (49.3 $\times$)	67.6 ms (61.2 $\times$)	82.2 ms (74.9 $\times$)	93.1 ms (86.3 $\times$)	338
	BiCGSTAB (multigrid)	3.12 ms (3.01 $\times$)	6.17 ms (5.31 $\times$)	6.17 ms (6.11 $\times$)	9.21 ms (8.87 $\times$)	2
	GMRES(20)	301.7 ms (272 $\times$)	434.1 ms (430 $\times$)	615.9 ms (574 $\times$)	882.8 ms (817 $\times$)	2100
	HINTS ($\tau=25$), Jacobi (0.67)	3.40 ms (3.14 $\times$)	3.40 ms (3.14 $\times$)	3.47 ms (3.22 $\times$)	6.53 ms (6.05 $\times$)	25
	Learned router, {NO, Jacobi (0.67)}	912 μ s	1.10 ms	1.94 ms	3.70 ms	4
	Learned router, {NO, Multigrid}	873 μ s	2.32 ms	3.83 ms	5.50 ms	2
	Cost-aware oracle, {NO, Multigrid}	851 μ s	2.33 ms	3.83 ms	5.49 ms	2

Results at 128^2 . With the same implementation technology (numpy stencils and scipy sparse triangular solves for every classical operation; a BLAS matrix–vector product for the corrector), the learned router with its best stationary pairing reaches truncation-level accuracy $3.62\times\text{--}3.71\times$ faster than multigrid alone (three V-cycles), $3.85\times\text{--}5.31\times$ faster than the best multigrid-preconditioned Krylov method and an order of magnitude faster than the unpreconditioned or SymGS-preconditioned Krylov solvers; the only faster method is the FFT direct solve, by $2.87\times\text{--}2.91\times$, which exists only because the test problems have constant coefficients and periodic boundaries (it is not an iterative method and is the reference we solve against). The reason the hybrid beats multigrid here is the corrector’s accuracy on the smooth band: one call removes the modes $|k| \leq 31$ to 10^{-6} at the price of a single 4096×4096 matrix–vector product, whereas a V(2,2)-cycle contracts the whole spectrum by ≈ 0.03 at the price of four Gauss–Seidel sweeps on the fine grid plus the coarse-grid work. Table 25 also reports the router over {NO, multigrid}: the cost-aware oracle and the learned router call the corrector once and then let the V-cycle remove the rest, and are $1.93\times\text{--}2.03\times$ faster than multigrid alone, i.e., adding a strong classical member to the ensemble is handled by the same construction without any change (the multigrid cycle is dearer than the unit, so it is the case in which the per-unit-cost comparison of Section 4 matters).

Scaling with the grid. Table 26 repeats the Jacobi and Gauss–Seidel pairings on 256×256 and 512×512 grids (32 and 16 instances; correctors retrained per grid with the same recipe, keeping the sensor grid at 64×64 , i.e., the corrector always handles the modes $|k| \leq 31$, and the router retrained per pairing). The corrector’s cost is dominated by a 4096×4096 matrix–vector product and is therefore nearly grid-independent, while every classical iteration grows as N^2 , so the corrector becomes relatively cheaper as N grows; the classical member, however, has to cover a growing fraction of the spectrum. The solver-only baselines at 512^2 are capped at 8000 iterations and reported as lower bounds; restarted GMRES, which was two orders of magnitude slower than the router at 128^2 and 256^2 , is not run at 512^2 .

What the scaling shows. At 256^2 the router remains the fastest iterative method for every pairing and both equations: $1.8\text{--}10.9\times$ faster than HINTS ($\tau=25$), $1.25\text{--}2.4\times$ faster than the per-cell best period, $4.6\text{--}6.7\times$ faster than multigrid alone and $5\text{--}6\times$ faster than multigrid-preconditioned CG/BiCGSTAB (Tables 29 and 35); the FFT direct solve is $1.7\text{--}2.6\times$ faster than the router. At 512^2 the picture splits by pairing (Table 36). With SOR and multigrid the router is still $3.1\times$ and $2.1\times$ faster than the best fixed schedule and $1.3\text{--}2.4\times$ faster than multigrid alone; the {NO, multigrid} router (39 ms on Poisson) is the fastest iterative method we measured at this size. With Jacobi and Gauss–Seidel, however, the corrector’s fixed band $|k| \leq 31$ leaves the smoother all modes $k \geq 32$, whose slowest member contracts by only 0.98 per Jacobi sweep at $N = 512$ (against 0.71 at $N = 128$): every policy then needs the same ≈ 80 sweeps after a single corrector call, the wall-clock time is dominated by sweeps, and the schedule barely matters—the router is $1.11\times$ faster than HINTS on Poisson (GS and Jacobi) but only on par with a fixed $\tau=50$ schedule on convection–diffusion

with Jacobi, where its imitation of the oracle also degrades (4 of 16 instances do not reach h^2 within the cap; the oracle reaches all 16 in the same 84 iterations as HINTS). This is the expected limit of a corrector whose band does not grow with the grid: the hybrid’s advantage comes from removing the modes the smoother cannot damp, and at 512^2 a 64×64 sensor grid no longer covers them. A corrector with a band that scales with N (at the price of a dense matrix–vector product that grows like the fourth power of the band) or a multigrid member in the ensemble restores the gains, as the multigrid pairing shows.

Table 26: Scaling: median time to $\varepsilon = h^2$ for the Jacobi and GS pairings against the strongest classical alternatives on each grid (paired median speedup of the learned router over each method in parentheses; † n : n instances did not reach the tolerance within the iteration cap).

Equation	N	Solver only	HINTS ($\tau=25$)	HINTS ($\tau=5$)	Learned router	Cost-aware oracle	Multigrid	PCG/BiCGSTAB (MG)	FFT direct
Poisson, Jacobi	128^2	1.15 s	2.65 ms (2.68×)	1.10 ms (1.21×)	987 μ s	942 μ s	3.99 ms (3.43×)	4.35 ms (3.57×)	317 μ s (0.33×)
	256^2	>7.61 s ^{†32}	5.95 ms (2.52×)	2.47 ms (1.56×)	2.38 ms	2.32 ms	14.1 ms (6.70×)	15.2 ms (6.30×)	1.32 ms (0.58×)
	512^2	>9.85 s ^{†16}	87.0 ms (1.11×)	126.3 ms (1.56×)	78.8 ms ^{†2}	74.2 ms	81.9 ms (1.14×)	85.6 ms (1.26×)	7.65 ms (0.10×)
Poisson, GS	128^2	1.83 s	6.65 ms (6.75×)	1.99 ms (1.94×)	1.01 ms	953 μ s	3.99 ms (3.39×)	4.35 ms (3.52×)	317 μ s (0.33×)
	256^2	28.83 s	22.0 ms (5.77×)	6.07 ms (1.70×)	3.92 ms	3.78 ms	14.1 ms (4.15×)	15.2 ms (3.85×)	1.32 ms (0.36×)
	512^2	>29.96 s ^{†16}	142.8 ms (1.11×)	162.5 ms (1.21×)	131.5 ms	130.0 ms	81.9 ms (0.69×)	85.6 ms (0.76×)	7.65 ms (0.06×)
ConvDiff, Jacobi	128^2	1.51 s	3.44 ms (2.95×)	1.28 ms (1.34×)	1.14 ms	1.15 ms	4.52 ms (3.54×)	6.17 ms (5.18×)	376 μ s (0.36×)
	256^2	>12.73 s ^{†32}	9.37 ms (1.92×)	4.97 ms (1.57×)	4.76 ms	4.81 ms	18.8 ms (4.60×)	24.0 ms (5.06×)	1.56 ms (0.39×)
	512^2	>13.71 s ^{†16}	153.8 ms (1.04×)	250.2 ms (1.35×)	148.5 ms ^{†4}	165.2 ms	99.7 ms (0.68×)	93.5 ms (0.65×)	8.06 ms (0.05×)
ConvDiff, GS	128^2	1.63 s	8.27 ms (6.76×)	3.60 ms (2.60×)	1.35 ms	1.32 ms	4.52 ms (3.29×)	6.17 ms (4.42×)	376 μ s (0.34×)
	256^2	30.05 s	31.0 ms (5.52×)	10.5 ms (1.53×)	7.05 ms	7.15 ms	18.8 ms (3.08×)	24.0 ms (3.47×)	1.56 ms (0.26×)
	512^2	>32.99 s ^{†16}	214.1 ms (1.05×)	212.5 ms (1.20×)	179.9 ms	185.9 ms	99.7 ms (0.56×)	93.5 ms (0.54×)	8.06 ms (0.05×)

Overheads and amortisation. Table 27 lists the measured cost of every operation as a function of N , including one decision of the LSTM router of Section 7 (full-state input of size $4N^2$, hidden size 256, 4 layers): at 128^2 one LSTM decision costs 2.4 ms, about 46 Jacobi sweeps, which is why the wall-clock study uses the scalar-feature router ($\approx 5 \mu$ s, independent of N). The learned router’s decisions therefore account for well under 1% of its solve time, and its corrector calls for 50–70% of the time to h^2 (one or two calls). Table 28 accounts for training: the corrector (shared with HINTS) is fit in minutes, the router in seconds to a few minutes per pairing, and the break-even number of solves after which the router’s own training cost is recovered relative to HINTS ($\tau=25$) with the same corrector.

Table 27: Measured single-thread cost of one operation as a function of the grid size (Poisson; median of repeated calls). Multigrid uses a direct solve below 64^2 and is not listed there.

Operation	$N = 32$	$N = 64$	$N = 128$	$N = 256$	$N = 512$
Jacobi iteration	14 μ s	25 μ s	53 μ s	191 μ s	1.07 ms
GS iteration	25 μ s	64 μ s	209 μ s	820 μ s	3.74 ms
SymGS iteration	38 μ s	109 μ s	378 μ s	1.48 ms	6.85 ms
Multigrid V(2,2) cycle	–	390 μ s	1.35 ms	5.27 ms	25.35 ms
FFT direct solve	41 μ s	77 μ s	268 μ s	1.21 ms	6.47 ms
DeepONet corrector call	–	–	663 μ s	1.13 ms	3.62 ms
Router decision (ours)	5 μ s	5 μ s	5 μ s	5 μ s	5 μ s
LSTM router decision (Section 7)	236 μ s	696 μ s	2.43 ms	9.55 ms	37.46 ms

Table 28: Training-cost amortisation for the GS pairing: corrector training (data generation and least-squares fit, CPU), router training (oracle rollouts and two DAGger rounds), median wall-clock saved per solve at $\varepsilon = h^2$ relative to HINTS ($\tau=25$) and to the solver alone, and the number of solves after which the router’s training cost is recovered relative to HINTS.

Equation	N	Corrector data + fit	Router training (GS pairing)	Saving per solve vs HINTS ($\tau=25$)	Break-even solves (router)	Saving per solve vs solver only
Poisson	128^2	82 s	8 s	5.64 ms	1419	1.83 s
	256^2	98 s	34 s	18.1 ms	1883	28.82 s
	512^2	504 s	229 s	11.4 ms	20139	–
ConvDiff	128^2	79 s	8 s	6.92 ms	1157	1.63 s
	256^2	106 s	33 s	24.0 ms	1376	30.05 s
	512^2	493 s	254 s	34.2 ms	7423	–

1040 E.5 Complete results on the 256×256 and 512×512 grids

1041 The tables of Section E.4 summarise the larger grids at $\varepsilon = h^2$ for two pairings; the following tables
1042 repeat the full per-tolerance results of the 128^2 study (Tables 2, 17 and 19 to 22) on the 256×256
1043 grid (32 test instances, all six pairings) and on the 512×512 grid (16 instances; Jacobi, GS, SOR
1044 and multigrid pairings; solver-only runs capped at 8000 iterations and reported as lower bounds).
1045 Correctors and routers are retrained per grid with the recipe of Section E; the corrector’s sensor grid
1046 stays at 64×64 (band $|k| \leq 31$).

Table 29: 256×256 : median wall-clock time to $\varepsilon = h^2 = 1.5 \times 10^{-5}$ (32 instances; paired median speedup over solver-only in parentheses; † n : n instances did not reach the tolerance within the 40,000-iteration cap, in which case the median time at the cap is given as a lower bound).

Equation	Solver	Solver only	HINTS ($\tau=25$)	HINTS (best τ)	Greedy oracle	Cost-aware oracle	Learned router (ours)
Poisson	Jacobi	$>7.61 \text{ s}^{\dagger 32}$	5.95 ms ($> 10^3 \times$)	2.47 ms ($> 10^3 \times$; $\tau=5$)	2.30 ms ($> 10^3 \times$)	2.32 ms ($> 10^3 \times$)	2.38 ms ($> 10^3 \times$)
	Jacobi (0.67)	$>7.74 \text{ s}^{\dagger 32}$	6.41 ms ($> 10^3 \times$)	3.43 ms ($> 10^3 \times$; $\tau=5$)	2.93 ms ($> 10^3 \times$)	2.77 ms ($> 10^3 \times$)	2.83 ms ($> 10^3 \times$)
	GS	28.83 s	22.0 ms (1316 $\times$)	6.07 ms (4681 $\times$; $\tau=5$)	3.85 ms (7702 $\times$)	3.78 ms (7797 $\times$)	3.92 ms (7591 $\times$)
	SymGS	26.53 s	37.3 ms (712 $\times$)	8.71 ms (3052 $\times$; $\tau=5$)	4.18 ms (7002 $\times$)	4.19 ms (7038 $\times$)	4.22 ms (7027 $\times$)
	SOR (1.5)	9.60 s	40.7 ms (235 $\times$)	9.06 ms (1065 $\times$; $\tau=5$)	3.69 ms (2650 $\times$)	3.51 ms (2748 $\times$)	3.80 ms (2558 $\times$)
ConvDiff	Jacobi	$>12.73 \text{ s}^{\dagger 32}$	9.37 ms ($> 10^3 \times$)	4.95 ms ($> 10^3 \times$; $\tau=10$)	4.43 ms ($> 10^3 \times$)	4.81 ms ($> 10^3 \times$)	4.76 ms ($> 10^3 \times$)
	Jacobi (0.67)	$>12.55 \text{ s}^{\dagger 32}$	9.31 ms ($> 10^3 \times$)	5.68 ms ($> 10^3 \times$; $\tau=10$)	5.93 ms ($> 10^3 \times$)	5.94 ms ($> 10^3 \times$)	5.76 ms ($> 10^3 \times$)
	GS	30.05 s	31.0 ms (963 $\times$)	10.5 ms (2830 $\times$; $\tau=5$)	7.20 ms (4211 $\times$)	7.15 ms (4238 $\times$)	7.05 ms (4326 $\times$)
	SymGS	27.77 s	42.3 ms (653 $\times$)	10.9 ms (2530 $\times$; $\tau=5$)	6.93 ms (4053 $\times$)	6.89 ms (4083 $\times$)	6.96 ms (4026 $\times$)
	SOR (1.5)	8.46 s	46.1 ms (182 $\times$)	10.6 ms (785 $\times$; $\tau=5$)	5.90 ms (1416 $\times$)	5.74 ms (1462 $\times$)	5.80 ms (1444 $\times$)

Table 30: 256×256 : paired median speedup of the learned router over HINTS (32 instances; bold: $\geq 1.1 \times$ with one-sided Wilcoxon $p < 0.01$).

Equation	Solver	vs. HINTS ($\tau=25$)			vs. best fixed τ		
		$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-8}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-8}$
Poisson	Jacobi	4.02$\times$	2.52$\times$	1.23$\times$	1.38$\times$ ($\tau=5$)	1.56$\times$ ($\tau=5$)	1.11$\times$ ($\tau=50$)
	Jacobi (0.67)	4.63$\times$	2.26$\times$	1.10 $\times$	1.55$\times$ ($\tau=5$)	1.73$\times$ ($\tau=5$)	1.10 $\times$ ($\tau=25$)
	GS	15.0$\times$	5.77$\times$	1.67$\times$	3.29$\times$ ($\tau=5$)	1.70$\times$ ($\tau=5$)	1.20$\times$ ($\tau=10$)
	SymGS	27.1$\times$	9.96$\times$	2.97$\times$	5.36$\times$ ($\tau=5$)	2.27$\times$ ($\tau=5$)	1.22$\times$ ($\tau=5$)
	SOR (1.5)	14.9$\times$	10.9$\times$	2.48$\times$	3.36$\times$ ($\tau=5$)	2.33$\times$ ($\tau=5$)	1.09 $\times$ ($\tau=10$)
ConvDiff	Jacobi	5.13$\times$	1.92$\times$	1.12$\times$	1.55$\times$ ($\tau=5$)	1.30$\times$ ($\tau=10$)	1.08 $\times$ ($\tau=50$)
	Jacobi (0.67)	5.64$\times$	1.80$\times$	1.06 $\times$	1.66$\times$ ($\tau=5$)	1.25$\times$ ($\tau=10$)	1.06 $\times$ ($\tau=25$)
	GS	15.0$\times$	5.52$\times$	1.95$\times$	3.31$\times$ ($\tau=5$)	1.53$\times$ ($\tau=5$)	1.17$\times$ ($\tau=10$)
	SymGS	25.3$\times$	6.26$\times$	2.63$\times$	4.99$\times$ ($\tau=5$)	1.69$\times$ ($\tau=5$)	1.18$\times$ ($\tau=5$)
	SOR (1.5)	14.8$\times$	7.99$\times$	2.50$\times$	3.24$\times$ ($\tau=5$)	1.96$\times$ ($\tau=5$)	1.19$\times$ ($\tau=5$)

Table 31: 256×256 : median number of iterations and corrector calls to reach $\varepsilon = h^2$.

Equation	Solver	HINTS ($\tau=25$)		Cost-aware oracle		Learned router	
		iters	NO calls	iters	NO calls	iters	NO calls
Poisson	Jacobi	25	1	6	1	6	1
	Jacobi (0.67)	25	1	8	1	8	1
	GS	27	1	4	1	4	1
	SymGS	26	1	3	1	3	1
	SOR (1.5)	50	2	4	1	4	1
ConvDiff	Jacobi	25	1	10	1	10	1
	Jacobi (0.67)	25	1	15	1	15	1
	GS	33	1	7	1	7	1
	SymGS	27	1	4	1	4	1
	SOR (1.5)	50	2	6	1	6	1

Table 32: 256×256 : measured single-thread per-iteration costs and macro-action sizes.

Equation	Solver	classical iteration	corrector iteration	m_{solver}	m_{NO}
Poisson	Jacobi	$167 \mu\text{s}$	$1004 \mu\text{s}$	6	1
	Jacobi (0.67)	$150 \mu\text{s}$	$971 \mu\text{s}$	6	1
	GS	$780 \mu\text{s}$	$1007 \mu\text{s}$	1	1
	SymGS	$1402 \mu\text{s}$	$931 \mu\text{s}$	1	1
	SOR (1.5)	$771 \mu\text{s}$	$960 \mu\text{s}$	1	1
ConvDiff	Jacobi	$286 \mu\text{s}$	$1130 \mu\text{s}$	4	1
	Jacobi (0.67)	$288 \mu\text{s}$	$1147 \mu\text{s}$	4	1
	GS	$855 \mu\text{s}$	$1077 \mu\text{s}$	1	1
	SymGS	$1551 \mu\text{s}$	$1114 \mu\text{s}$	1	1
	SOR (1.5)	$813 \mu\text{s}$	$1032 \mu\text{s}$	1	1

Table 33: 256×256 , Poisson: median wall-clock time to relative error ε for every policy and pairing (32 instances).

Solver	Method	$\varepsilon=10^{-2}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-5}$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
Jacobi	Solver only	5.65 s	$>7.61 \text{ s}^{132}$	$>7.61 \text{ s}^{132}$	$>7.61 \text{ s}^{132}$	$>7.61 \text{ s}^{132}$	$>7.61 \text{ s}^{132}$
	HINTS ($\tau=25$)	5.90 ms ($948\times$)	5.90 ms ($> 10^3\times$)	5.95 ms ($> 10^3\times$)	5.95 ms ($> 10^3\times$)	6.50 ms ($> 10^3\times$)	85.5 ms ($> 10^3\times$)
	HINTS ($\tau=10$)	3.00 ms ($1824\times$)	3.00 ms ($> 10^3\times$)	3.31 ms ($> 10^3\times$)	3.31 ms ($> 10^3\times$)	6.06 ms ($> 10^3\times$)	108.2 ms ($> 10^3\times$)
	HINTS ($\tau=5$)	2.03 ms ($2721\times$)	2.07 ms ($> 10^3\times$)	2.47 ms ($> 10^3\times$)	3.21 ms ($> 10^3\times$)	8.72 ms ($> 10^3\times$)	163.1 ms ($> 10^3\times$)
	HINTS ($\tau=50$)	10.4 ms ($536\times$)	10.4 ms ($> 10^3\times$)	10.6 ms ($> 10^3\times$)	10.6 ms ($> 10^3\times$)	11.1 ms ($> 10^3\times$)	72.9 ms ($> 10^3\times$)
	Greedy oracle (Alg. 1)	1.27 ms ($4345\times$)	1.28 ms ($> 10^3\times$)	2.30 ms ($> 10^3\times$)	2.68 ms ($> 10^3\times$)	5.50 ms ($> 10^3\times$)	67.2 ms ($> 10^3\times$)
	Cost-aware oracle	1.42 ms ($3889\times$)	1.42 ms ($> 10^3\times$)	2.32 ms ($> 10^3\times$)	2.74 ms ($> 10^3\times$)	5.34 ms ($> 10^3\times$)	67.0 ms ($> 10^3\times$)
Jacobi (0.67)	Learned router (ours)	1.46 ms ($3740\times$)	1.47 ms ($> 10^3\times$)	2.38 ms ($> 10^3\times$)	2.76 ms ($> 10^3\times$)	5.18 ms ($> 10^3\times$)	73.1 ms ($> 10^3\times$)
	Solver only	$>7.74 \text{ s}^{131}$	$>7.74 \text{ s}^{132}$	$>7.74 \text{ s}^{132}$	$>7.74 \text{ s}^{132}$	$>7.74 \text{ s}^{132}$	$>7.74 \text{ s}^{132}$
	HINTS ($\tau=25$)	6.02 ms ($> 10^3\times$)	6.02 ms ($> 10^3\times$)	6.41 ms ($> 10^3\times$)	6.45 ms ($> 10^3\times$)	8.13 ms ($> 10^3\times$)	16.8 ms ($> 10^3\times$)
	HINTS ($\tau=10$)	3.06 ms ($> 10^3\times$)	3.06 ms ($> 10^3\times$)	3.54 ms ($> 10^3\times$)	3.87 ms ($> 10^3\times$)	8.78 ms ($> 10^3\times$)	21.9 ms ($> 10^3\times$)
	HINTS ($\tau=5$)	2.08 ms ($> 10^3\times$)	2.10 ms ($> 10^3\times$)	3.43 ms ($> 10^3\times$)	4.50 ms ($> 10^3\times$)	13.7 ms ($> 10^3\times$)	33.6 ms ($> 10^3\times$)
	HINTS ($\tau=50$)	10.6 ms ($> 10^3\times$)	10.6 ms ($> 10^3\times$)	10.6 ms ($> 10^3\times$)	10.6 ms ($> 10^3\times$)	11.0 ms ($> 10^3\times$)	21.1 ms ($> 10^3\times$)
	Greedy oracle (Alg. 1)	1.29 ms ($> 10^3\times$)	1.30 ms ($> 10^3\times$)	2.93 ms ($> 10^3\times$)	3.59 ms ($> 10^3\times$)	7.67 ms ($> 10^3\times$)	16.2 ms ($> 10^3\times$)
GS	Cost-aware oracle	1.29 ms ($> 10^3\times$)	1.30 ms ($> 10^3\times$)	2.77 ms ($> 10^3\times$)	3.45 ms ($> 10^3\times$)	7.19 ms ($> 10^3\times$)	16.1 ms ($> 10^3\times$)
	Learned router (ours)	1.30 ms ($> 10^3\times$)	1.32 ms ($> 10^3\times$)	2.83 ms ($> 10^3\times$)	3.48 ms ($> 10^3\times$)	7.56 ms ($> 10^3\times$)	16.8 ms ($> 10^3\times$)
	Solver only	11.78 s	17.80 s	28.83 s	29.94 s	$>31.70 \text{ s}^{132}$	$>31.70 \text{ s}^{132}$
	HINTS ($\tau=25$)	20.4 ms ($574\times$)	20.4 ms ($871\times$)	22.0 ms ($1316\times$)	22.9 ms ($1307\times$)	40.4 ms ($> 10^3\times$)	43.5 ms ($> 10^3\times$)
	HINTS ($\tau=10$)	8.34 ms ($1398\times$)	8.34 ms ($2120\times$)	9.92 ms ($2899\times$)	10.9 ms ($2723\times$)	17.3 ms ($> 10^3\times$)	30.4 ms ($> 10^3\times$)
	HINTS ($\tau=5$)	4.49 ms ($2626\times$)	4.49 ms ($3981\times$)	6.07 ms ($4681\times$)	7.23 ms ($4133\times$)	14.0 ms ($> 10^3\times$)	31.1 ms ($> 10^3\times$)
	HINTS ($\tau=50$)	39.9 ms ($294\times$)	39.9 ms ($445\times$)	41.4 ms ($698\times$)	42.3 ms ($703\times$)	79.5 ms ($> 10^3\times$)	79.8 ms ($> 10^3\times$)
SymGS	Greedy oracle (Alg. 1)	1.34 ms ($8746\times$)	1.36 ms ($13154\times$)	3.85 ms ($7702\times$)	5.37 ms ($5649\times$)	11.3 ms ($> 10^3\times$)	25.4 ms ($> 10^3\times$)
	Cost-aware oracle	1.31 ms ($8992\times$)	1.33 ms ($13490\times$)	3.78 ms ($7797\times$)	5.28 ms ($5826\times$)	11.4 ms ($> 10^3\times$)	25.6 ms ($> 10^3\times$)
	Learned router (ours)	1.33 ms ($8750\times$)	1.36 ms ($13075\times$)	3.92 ms ($7591\times$)	5.56 ms ($5508\times$)	12.2 ms ($> 10^3\times$)	26.0 ms ($> 10^3\times$)
	Solver only	10.82 s	16.41 s	26.53 s	27.56 s	33.16 s	44.30 s
	HINTS ($\tau=25$)	36.1 ms ($302\times$)	36.1 ms ($457\times$)	37.3 ms ($712\times$)	37.6 ms ($732\times$)	71.9 ms ($462\times$)	71.9 ms ($616\times$)
	HINTS ($\tau=10$)	14.3 ms ($754\times$)	14.3 ms ($1143\times$)	15.8 ms ($1669\times$)	15.9 ms ($1721\times$)	28.5 ms ($1164\times$)	34.6 ms ($1277\times$)
	HINTS ($\tau=5$)	7.18 ms ($1523\times$)	7.18 ms ($2301\times$)	8.71 ms ($3052\times$)	8.77 ms ($3153\times$)	15.5 ms ($2137\times$)	29.8 ms ($1493\times$)
SOR (1.5)	HINTS ($\tau=50$)	72.5 ms ($149\times$)	72.5 ms ($226\times$)	73.3 ms ($359\times$)	74.3 ms ($372\times$)	144.3 ms ($229\times$)	144.4 ms ($306\times$)
	Greedy oracle (Alg. 1)	1.35 ms ($7971\times$)	1.36 ms ($11909\times$)	4.18 ms ($7002\times$)	4.90 ms ($5659\times$)	10.7 ms ($3086\times$)	24.3 ms ($1817\times$)
	Cost-aware oracle	1.33 ms ($8231\times$)	1.35 ms ($12187\times$)	4.19 ms ($7038\times$)	4.95 ms ($5652\times$)	10.5 ms ($3150\times$)	23.8 ms ($1863\times$)
	Learned router (ours)	1.33 ms ($8089\times$)	1.34 ms ($12258\times$)	4.22 ms ($7027\times$)	4.97 ms ($5654\times$)	10.8 ms ($3081\times$)	24.4 ms ($1821\times$)
	Solver only	3.93 s	5.94 s	9.60 s	9.97 s	11.97 s	15.97 s
	HINTS ($\tau=25$)	20.5 ms ($190\times$)	20.5 ms ($287\times$)	40.7 ms ($235\times$)	40.7 ms ($244\times$)	40.7 ms ($293\times$)	60.9 ms ($261\times$)
	HINTS ($\tau=10$)	8.39 ms ($461\times$)	8.39 ms ($700\times$)	16.4 ms ($577\times$)	16.5 ms ($598\times$)	17.7 ms ($683\times$)	27.2 ms ($592\times$)
SOR (1.5)	HINTS ($\tau=5$)	4.57 ms ($855\times$)	4.57 ms ($1299\times$)	9.06 ms ($1065\times$)	9.20 ms ($1104\times$)	14.2 ms ($832\times$)	27.4 ms ($577\times$)
	HINTS ($\tau=50$)	39.4 ms ($98.9\times$)	39.4 ms ($151\times$)	78.5 ms ($122\times$)	78.8 ms ($126\times$)	78.8 ms ($152\times$)	104.0 ms ($154\times$)
	Greedy oracle (Alg. 1)	1.30 ms ($3003\times$)	1.31 ms ($4507\times$)	3.69 ms ($2650\times$)	4.46 ms ($2252\times$)	10.4 ms ($1142\times$)	22.7 ms ($698\times$)
	Cost-aware oracle	1.29 ms ($3009\times$)	1.30 ms ($4527\times$)	3.51 ms ($2748\times$)	4.26 ms ($2320\times$)	10.3 ms ($1142\times$)	22.4 ms ($702\times$)
	Learned router (ours)	1.34 ms ($2896\times$)	1.36 ms ($4339\times$)	3.80 ms ($2558\times$)	4.64 ms ($2126\times$)	10.9 ms ($1083\times$)	24.2 ms ($654\times$)

Table 34: 256×256 , convection–diffusion: median wall-clock time to relative error ε for every policy and pairing (32 instances).

Solver	Method	$\varepsilon=10^{-2}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-5}$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
Jacobi	Solver only	8.83 s	$>12.73 \text{ s}^{126}$	$>12.73 \text{ s}^{132}$	$>12.73 \text{ s}^{132}$	$>12.73 \text{ s}^{132}$	$>12.73 \text{ s}^{132}$
	HINTS ($\tau=25$)	9.15 ms (967 $\times$)	9.15 ms ($> 10^3 \times$)	9.37 ms ($> 10^3 \times$)	9.46 ms ($> 10^3 \times$)	11.2 ms ($> 10^3 \times$)	500.8 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	4.33 ms (2010 $\times$)	4.37 ms ($> 10^3 \times$)	4.95 ms ($> 10^3 \times$)	5.24 ms ($> 10^3 \times$)	10.3 ms ($> 10^3 \times$)	631.6 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	2.73 ms (3051 $\times$)	2.80 ms ($> 10^3 \times$)	4.97 ms ($> 10^3 \times$)	6.76 ms ($> 10^3 \times$)	14.9 ms ($> 10^3 \times$)	869.7 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	17.0 ms (517 $\times$)	17.0 ms ($> 10^3 \times$)	17.3 ms ($> 10^3 \times$)	17.3 ms ($> 10^3 \times$)	18.5 ms ($> 10^3 \times$)	475.6 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	1.55 ms (5578 $\times$)	1.57 ms ($> 10^3 \times$)	4.43 ms ($> 10^3 \times$)	5.06 ms ($> 10^3 \times$)	9.42 ms ($> 10^3 \times$)	436.3 ms ($> 10^3 \times$)
	Cost-aware oracle	1.69 ms (5129 $\times$)	1.70 ms ($> 10^3 \times$)	4.81 ms ($> 10^3 \times$)	5.42 ms ($> 10^3 \times$)	9.60 ms ($> 10^3 \times$)	437.5 ms ($> 10^3 \times$)
	Learned router (ours)	1.73 ms (4987 $\times$)	1.77 ms ($> 10^3 \times$)	4.76 ms ($> 10^3 \times$)	5.42 ms ($> 10^3 \times$)	9.76 ms ($> 10^3 \times$)	435.1 ms ($> 10^3 \times$)
Jacobi (0.67)	Solver only	$>12.55 \text{ s}^{120}$	$>12.55 \text{ s}^{132}$	$>12.55 \text{ s}^{132}$	$>12.55 \text{ s}^{132}$	$>12.55 \text{ s}^{132}$	$>12.55 \text{ s}^{132}$
	HINTS ($\tau=25$)	9.03 ms ($> 10^3 \times$)	9.03 ms ($> 10^3 \times$)	9.31 ms ($> 10^3 \times$)	9.35 ms ($> 10^3 \times$)	14.9 ms ($> 10^3 \times$)	30.4 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	4.25 ms ($> 10^3 \times$)	4.26 ms ($> 10^3 \times$)	5.68 ms ($> 10^3 \times$)	7.16 ms ($> 10^3 \times$)	15.6 ms ($> 10^3 \times$)	34.5 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	2.68 ms ($> 10^3 \times$)	2.73 ms ($> 10^3 \times$)	7.87 ms ($> 10^3 \times$)	9.37 ms ($> 10^3 \times$)	21.7 ms ($> 10^3 \times$)	47.7 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	16.2 ms ($> 10^3 \times$)	16.2 ms ($> 10^3 \times$)	16.3 ms ($> 10^3 \times$)	16.4 ms ($> 10^3 \times$)	17.9 ms ($> 10^3 \times$)	33.8 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	1.53 ms ($> 10^3 \times$)	1.54 ms ($> 10^3 \times$)	5.93 ms ($> 10^3 \times$)	6.88 ms ($> 10^3 \times$)	13.1 ms ($> 10^3 \times$)	26.8 ms ($> 10^3 \times$)
	Cost-aware oracle	1.56 ms ($> 10^3 \times$)	1.58 ms ($> 10^3 \times$)	5.94 ms ($> 10^3 \times$)	6.88 ms ($> 10^3 \times$)	13.4 ms ($> 10^3 \times$)	27.5 ms ($> 10^3 \times$)
	Learned router (ours)	1.53 ms ($> 10^3 \times$)	1.61 ms ($> 10^3 \times$)	5.76 ms ($> 10^3 \times$)	6.65 ms ($> 10^3 \times$)	13.0 ms ($> 10^3 \times$)	26.9 ms ($> 10^3 \times$)
GS	Solver only	11.85 s	18.36 s	30.05 s	31.23 s	$>36.70 \text{ s}^{126}$	$>36.70 \text{ s}^{132}$
	HINTS ($\tau=25$)	23.5 ms (501 $\times$)	23.5 ms (773 $\times$)	31.0 ms (963 $\times$)	46.0 ms (666 $\times$)	47.0 ms ($> 10^3 \times$)	59.3 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	9.79 ms (1213 $\times$)	9.79 ms (1875 $\times$)	17.1 ms (1695 $\times$)	19.4 ms (1618 $\times$)	21.3 ms ($> 10^3 \times$)	36.7 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	5.27 ms (2247 $\times$)	5.29 ms (3468 $\times$)	10.5 ms (2830 $\times$)	11.4 ms (2674 $\times$)	19.4 ms ($> 10^3 \times$)	39.2 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	46.2 ms (257 $\times$)	46.2 ms (397 $\times$)	53.6 ms (565 $\times$)	71.9 ms (427 $\times$)	92.8 ms ($> 10^3 \times$)	94.2 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	1.55 ms (7777 $\times$)	1.57 ms (11258 $\times$)	7.20 ms (4211 $\times$)	8.15 ms (3852 $\times$)	16.2 ms ($> 10^3 \times$)	31.1 ms ($> 10^3 \times$)
	Cost-aware oracle	1.56 ms (7586 $\times$)	1.61 ms (10966 $\times$)	7.15 ms (4238 $\times$)	8.13 ms (3865 $\times$)	16.2 ms ($> 10^3 \times$)	31.0 ms ($> 10^3 \times$)
	Learned router (ours)	1.56 ms (7414 $\times$)	1.57 ms (10840 $\times$)	7.05 ms (4326 $\times$)	7.97 ms (3960 $\times$)	16.1 ms ($> 10^3 \times$)	31.4 ms ($> 10^3 \times$)
SymGS	Solver only	10.93 s	16.90 s	27.77 s	28.89 s	34.88 s	46.85 s
	HINTS ($\tau=25$)	39.2 ms (278 $\times$)	39.2 ms (429 $\times$)	42.3 ms (653 $\times$)	43.9 ms (651 $\times$)	78.0 ms (446 $\times$)	78.1 ms (594 $\times$)
	HINTS ($\tau=10$)	15.6 ms (697 $\times$)	15.6 ms (1076 $\times$)	18.9 ms (1464 $\times$)	20.4 ms (1401 $\times$)	30.9 ms (1118 $\times$)	41.4 ms (1143 $\times$)
	HINTS ($\tau=5$)	7.80 ms (1391 $\times$)	7.80 ms (2149 $\times$)	10.9 ms (2530 $\times$)	12.6 ms (2276 $\times$)	18.5 ms (1858 $\times$)	34.8 ms (1345 $\times$)
	HINTS ($\tau=50$)	78.3 ms (138 $\times$)	78.3 ms (213 $\times$)	81.4 ms (341 $\times$)	83.1 ms (345 $\times$)	156.3 ms (221 $\times$)	156.3 ms (298 $\times$)
	Greedy oracle (Alg. 1)	1.53 ms (6906 $\times$)	1.58 ms (10455 $\times$)	6.93 ms (4053 $\times$)	7.74 ms (3675 $\times$)	14.1 ms (2383 $\times$)	28.4 ms (1616 $\times$)
	Cost-aware oracle	1.52 ms (7162 $\times$)	1.56 ms (10557 $\times$)	6.89 ms (4083 $\times$)	7.71 ms (3756 $\times$)	14.1 ms (2414 $\times$)	28.4 ms (1633 $\times$)
	Learned router (ours)	1.54 ms (7007 $\times$)	1.55 ms (10689 $\times$)	6.96 ms (4026 $\times$)	7.92 ms (3739 $\times$)	14.8 ms (2372 $\times$)	29.6 ms (1569 $\times$)
SOR (1.5)	Solver only	3.31 s	5.14 s	8.46 s	8.79 s	10.59 s	14.22 s
	HINTS ($\tau=25$)	23.2 ms (141 $\times$)	23.2 ms (219 $\times$)	46.1 ms (182 $\times$)	46.1 ms (189 $\times$)	46.1 ms (228 $\times$)	69.0 ms (204 $\times$)
	HINTS ($\tau=10$)	9.72 ms (339 $\times$)	9.72 ms (523 $\times$)	19.1 ms (435 $\times$)	19.1 ms (453 $\times$)	23.2 ms (456 $\times$)	32.5 ms (443 $\times$)
	HINTS ($\tau=5$)	5.18 ms (622 $\times$)	5.22 ms (970 $\times$)	10.6 ms (785 $\times$)	11.9 ms (745 $\times$)	17.4 ms (609 $\times$)	31.2 ms (449 $\times$)
	HINTS ($\tau=50$)	45.7 ms (71.2 $\times$)	45.7 ms (110 $\times$)	91.0 ms (90.8 $\times$)	91.0 ms (94.4 $\times$)	91.0 ms (114 $\times$)	136.7 ms (102 $\times$)
	Greedy oracle (Alg. 1)	1.52 ms (2097 $\times$)	1.56 ms (3139 $\times$)	5.90 ms (1416 $\times$)	7.29 ms (1200 $\times$)	14.3 ms (733 $\times$)	28.1 ms (504 $\times$)
	Cost-aware oracle	1.52 ms (2172 $\times$)	1.57 ms (3151 $\times$)	5.74 ms (1462 $\times$)	7.13 ms (1230 $\times$)	14.0 ms (749 $\times$)	27.5 ms (516 $\times$)
	Learned router (ours)	1.53 ms (2088 $\times$)	1.57 ms (3051 $\times$)	5.80 ms (1444 $\times$)	7.21 ms (1218 $\times$)	14.2 ms (740 $\times$)	27.6 ms (510 $\times$)

Table 35: 256×256 : strong classical baselines (32 instances; paired median speedup of the learned router with its best stationary pairing over each method in parentheses).

Equation	Method	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$	iters to h^2
Poisson	FFT direct solve	1.32 ms (0.58 $\times$)	1.32 ms (0.58 $\times$)	1.32 ms (0.58 $\times$)	1.32 ms (0.58 $\times$)	1
	Multigrid V(2,2) alone	9.27 ms (3.92 $\times$)	14.1 ms (6.70 $\times$)	18.5 ms (8.63 $\times$)	27.0 ms (12.4 $\times$)	3
	CG	58.0 ms (24.5 $\times$)	73.1 ms (32.2 $\times$)	88.4 ms (35.5 $\times$)	102.5 ms (43.6 $\times$)	348
	PCG (SymGS)	146.5 ms (64.5 $\times$)	254.7 ms (112 $\times$)	297.2 ms (127 $\times$)	365.0 ms (161 $\times$)	170
	PCG (multigrid)	10.5 ms (3.94 $\times$)	15.2 ms (6.30 $\times$)	19.6 ms (8.55 $\times$)	24.5 ms (10.7 $\times$)	3
	HINTS ($\tau=25$), Jacobi	5.90 ms (2.52 $\times$)	5.95 ms (2.52 $\times$)	6.50 ms (4.82 $\times$)	85.5 ms (34.1 $\times$)	25
	Learned router, {NO, Jacobi}	1.47 ms	2.38 ms	5.18 ms	73.1 ms	6
	Learned router, {NO, Multigrid}	1.32 ms	5.97 ms	10.8 ms	16.6 ms	2
	Cost-aware oracle, {NO, Multigrid}	1.31 ms	6.09 ms	10.8 ms	16.2 ms	2
ConvDiff	FFT direct solve	1.56 ms (0.39 $\times$)	1.56 ms (0.39 $\times$)	1.56 ms (0.39 $\times$)	1.56 ms (0.39 $\times$)	1
	Multigrid V(2,2) alone	12.3 ms (2.73 $\times$)	18.8 ms (4.60 $\times$)	24.8 ms (5.87 $\times$)	36.1 ms (7.77 $\times$)	3
	BiCGSTAB	377.7 ms (78.9 $\times$)	486.6 ms (102 $\times$)	545.8 ms (113 $\times$)	605.9 ms (130 $\times$)	731
	BiCGSTAB (multigrid)	12.5 ms (2.92 $\times$)	24.0 ms (5.06 $\times$)	24.5 ms (5.28 $\times$)	36.1 ms (7.53 $\times$)	2
	GMRES(20)	1.85 s (387 $\times$)	3.00 s (644 $\times$)	3.75 s (797 $\times$)	5.14 s (1089 $\times$)	5030
	HINTS ($\tau=25$), Jacobi	9.15 ms (1.92 $\times$)	9.37 ms (1.92 $\times$)	11.2 ms (5.96 $\times$)	500.8 ms (28.0 $\times$)	25
	Learned router, {NO, Jacobi}	1.77 ms	4.76 ms	9.76 ms	435.1 ms	10
	Learned router, {NO, Multigrid}	1.60 ms	7.26 ms	12.4 ms	20.2 ms	2
	Cost-aware oracle, {NO, Multigrid}	1.55 ms	7.23 ms	12.7 ms	19.9 ms	2

Table 36: 512×512 : median wall-clock time to $\varepsilon = h^2 = 3.8 \times 10^{-6}$ (16 instances; Jacobi, GS, SOR and multigrid pairings; solver-only runs capped at 8000 iterations).

Equation	Solver	Solver only	HINTS ($\tau=25$)	HINTS (best τ)	Greedy oracle	Cost-aware oracle	Learned router (ours)
Poisson	Jacobi	$>9.85 \text{ s}^{116}$	87.0 ms ($> 10^3 \times$)	87.0 ms ($> 10^3 \times$; $\tau=25$)	78.2 ms ($> 10^3 \times$)	74.2 ms ($> 10^3 \times$)	78.8 ms ($> 10^3 \times$) ¹²
	GS	$>29.96 \text{ s}^{116}$	142.8 ms ($> 10^3 \times$)	142.8 ms ($> 10^3 \times$; $\tau=25$)	141.4 ms ($> 10^3 \times$)	130.0 ms ($> 10^3 \times$)	131.5 ms ($> 10^3 \times$)
	SOR (1.5)	$>29.74 \text{ s}^{116}$	182.7 ms ($> 10^3 \times$)	74.4 ms ($> 10^3 \times$; $\tau=5$)	61.1 ms ($> 10^3 \times$)	60.3 ms ($> 10^3 \times$)	60.7 ms ($> 10^3 \times$)
ConvDiff	Jacobi	$>13.71 \text{ s}^{116}$	153.8 ms ($> 10^3 \times$)	140.6 ms ($> 10^3 \times$; $\tau=50$)	148.0 ms ($> 10^3 \times$)	165.2 ms ($> 10^3 \times$)	148.5 ms ($> 10^3 \times$) ¹⁴
	GS	$>32.99 \text{ s}^{116}$	214.1 ms ($> 10^3 \times$)	192.7 ms ($> 10^3 \times$; $\tau=10$)	184.8 ms ($> 10^3 \times$)	185.9 ms ($> 10^3 \times$)	179.9 ms ($> 10^3 \times$)
	SOR (1.5)	$>32.91 \text{ s}^{116}$	206.6 ms ($> 10^3 \times$)	89.3 ms ($> 10^3 \times$; $\tau=5$)	83.3 ms ($> 10^3 \times$)	85.0 ms ($> 10^3 \times$)	83.6 ms ($> 10^3 \times$)

Table 37: 512×512 : paired median speedup of the learned router over HINTS (16 instances; bold: $\geq 1.1 \times$ with $p < 0.01$).

Equation	Solver	vs. HINTS ($\tau=25$)			vs. best fixed τ		
		$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-8}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-8}$
Poisson	Jacobi	6.37 $\times$	1.11 $\times$	1.00 $\times$	1.85 $\times$ ($\tau=5$)	1.11 $\times$ ($\tau=25$)	1.00 $\times$ ($\tau=50$)
	GS	19.3 $\times$	1.11 $\times$	1.07 $\times$	4.07 $\times$ ($\tau=5$)	1.11 $\times$ ($\tau=25$)	1.07 $\times$ ($\tau=25$)
	SOR (1.5)	19.2 $\times$	3.10 $\times$	1.37 $\times$	3.93 $\times$ ($\tau=5$)	1.24 $\times$ ($\tau=5$)	1.09 $\times$ ($\tau=10$)
ConvDiff	Jacobi	7.73 $\times$	1.04 $\times$	1.00 $\times$	1.94 $\times$ ($\tau=5$)	1.18 $\times$ ($\tau=50$)	1.00 $\times$ ($\tau=50$)
	GS	17.2 $\times$	1.05 $\times$	1.03 $\times$	3.68 $\times$ ($\tau=5$)	1.09 $\times$ ($\tau=10$)	1.03 $\times$ ($\tau=25$)
	SOR (1.5)	18.4 $\times$	2.48 $\times$	1.41 $\times$	3.72 $\times$ ($\tau=5$)	1.18 $\times$ ($\tau=5$)	1.08 $\times$ ($\tau=10$)

Table 38: 512×512 : median iterations and corrector calls to h^2 (left) and measured per-iteration costs (right).

Equation	Solver	HINTS ($\tau=25$)		Cost-aware oracle		Learned router		Equation	Solver	classical iteration	corrector iteration	m_{solver}	m_{NO}
		iters	NO calls	iters	NO calls	iters	NO calls						
Poisson	Jacobi	65	2	64	1	64	1	Poisson	Jacobi	1072 μs	3363 μs	3	1
	GS	38	1	35	1	35	1		GS	3497 μs	3300 μs	1	1
	SOR (1.5)	50	2	17	1	17	2		SOR (1.5)	3412 μs	3195 μs	1	1
ConvDiff	Jacobi	85	2	84	1	84	1	ConvDiff	Jacobi	1418 μs	3614 μs	3	1
	GS	51	2	44	1	44	2		GS	3943 μs	3667 μs	1	1
	SOR (1.5)	50	2	20	1	20	2		SOR (1.5)	3896 μs	3618 μs	1	1

Table 39: 512×512 , Poisson: median wall-clock time to relative error ε for every policy and pairing (16 instances).

Solver	Method	$\varepsilon=10^{-2}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-5}$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
Jacobi	Solver only	$>9.85 \text{ s}^{116}$	$>9.85 \text{ s}^{116}$	$>9.85 \text{ s}^{116}$	$>9.85 \text{ s}^{116}$	$>9.85 \text{ s}^{116}$	$>9.85 \text{ s}^{116}$
	HINTS ($\tau=25$)	33.1 ms ($> 10^3 \times$)	33.1 ms ($> 10^3 \times$)	87.0 ms ($> 10^3 \times$)	56.4 ms ($> 10^3 \times$)	127.7 ms ($> 10^3 \times$) ¹²	309.2 ms ($> 10^3 \times$) ¹⁷
	HINTS ($\tau=10$)	14.5 ms ($> 10^3 \times$)	15.2 ms ($> 10^3 \times$)	103.3 ms ($> 10^3 \times$)	67.0 ms ($> 10^3 \times$)	152.1 ms ($> 10^3 \times$) ¹²	363.9 ms ($> 10^3 \times$) ¹⁷
	HINTS ($\tau=5$)	9.18 ms ($> 10^3 \times$)	9.27 ms ($> 10^3 \times$)	126.3 ms ($> 10^3 \times$)	82.0 ms ($> 10^3 \times$)	192.2 ms ($> 10^3 \times$) ¹²	460.4 ms ($> 10^3 \times$) ¹⁷
	HINTS ($\tau=50$)	60.8 ms ($> 10^3 \times$)	60.8 ms ($> 10^3 \times$)	88.9 ms ($> 10^3 \times$)	75.1 ms ($> 10^3 \times$)	125.8 ms ($> 10^3 \times$) ¹²	293.9 ms ($> 10^3 \times$) ¹⁷
	Greedy oracle (Alg. 1)	4.57 ms ($> 10^3 \times$)	4.74 ms ($> 10^3 \times$)	78.2 ms ($> 10^3 \times$)	53.6 ms ($> 10^3 \times$)	116.6 ms ($> 10^3 \times$) ¹²	275.5 ms ($> 10^3 \times$) ¹⁷
	Cost-aware oracle	4.62 ms ($> 10^3 \times$)	4.74 ms ($> 10^3 \times$)	74.2 ms ($> 10^3 \times$)	47.2 ms ($> 10^3 \times$)	111.0 ms ($> 10^3 \times$) ¹²	261.5 ms ($> 10^3 \times$) ¹⁷
	Learned router (ours)	4.80 ms ($> 10^3 \times$)	4.86 ms ($> 10^3 \times$)	78.8 ms ($> 10^3 \times$) ¹²	52.6 ms ($> 10^3 \times$)	119.4 ms ($> 10^3 \times$) ¹⁴	282.9 ms ($> 10^3 \times$) ¹⁷
GS	Solver only	$>29.96 \text{ s}^{116}$	$>29.96 \text{ s}^{116}$	$>29.96 \text{ s}^{116}$	$>29.96 \text{ s}^{116}$	$>29.96 \text{ s}^{116}$	$>29.96 \text{ s}^{116}$
	HINTS ($\tau=25$)	92.5 ms ($> 10^3 \times$)	92.5 ms ($> 10^3 \times$)	142.8 ms ($> 10^3 \times$)	107.0 ms ($> 10^3 \times$)	210.1 ms ($> 10^3 \times$)	439.6 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	37.3 ms ($> 10^3 \times$)	37.3 ms ($> 10^3 \times$)	147.0 ms ($> 10^3 \times$)	96.0 ms ($> 10^3 \times$)	214.6 ms ($> 10^3 \times$)	465.9 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	19.5 ms ($> 10^3 \times$)	20.0 ms ($> 10^3 \times$)	162.5 ms ($> 10^3 \times$)	107.8 ms ($> 10^3 \times$)	238.2 ms ($> 10^3 \times$)	522.1 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	183.5 ms ($> 10^3 \times$)	183.5 ms ($> 10^3 \times$)	212.2 ms ($> 10^3 \times$)	190.8 ms ($> 10^3 \times$)	346.0 ms ($> 10^3 \times$)	478.7 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	4.59 ms ($> 10^3 \times$)	4.65 ms ($> 10^3 \times$)	141.4 ms ($> 10^3 \times$)	95.2 ms ($> 10^3 \times$)	221.0 ms ($> 10^3 \times$)	447.1 ms ($> 10^3 \times$)
	Cost-aware oracle	4.68 ms ($> 10^3 \times$)	4.87 ms ($> 10^3 \times$)	130.0 ms ($> 10^3 \times$)	88.6 ms ($> 10^3 \times$)	190.1 ms ($> 10^3 \times$)	433.0 ms ($> 10^3 \times$)
	Learned router (ours)	4.66 ms ($> 10^3 \times$)	4.70 ms ($> 10^3 \times$)	131.5 ms ($> 10^3 \times$)	89.1 ms ($> 10^3 \times$)	194.5 ms ($> 10^3 \times$)	417.8 ms ($> 10^3 \times$)
SOR (1.5)	Solver only	$>29.74 \text{ s}^{116}$	$>29.74 \text{ s}^{116}$	$>29.74 \text{ s}^{116}$	$>29.74 \text{ s}^{116}$	$>29.74 \text{ s}^{116}$	$>29.74 \text{ s}^{116}$
	HINTS ($\tau=25$)	93.2 ms ($> 10^3 \times$)	93.2 ms ($> 10^3 \times$)	182.7 ms ($> 10^3 \times$)	129.0 ms ($> 10^3 \times$)	187.1 ms ($> 10^3 \times$)	269.4 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	37.3 ms ($> 10^3 \times$)	37.7 ms ($> 10^3 \times$)	82.5 ms ($> 10^3 \times$)	78.6 ms ($> 10^3 \times$)	108.5 ms ($> 10^3 \times$)	214.9 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	18.7 ms ($> 10^3 \times$)	18.7 ms ($> 10^3 \times$)	74.4 ms ($> 10^3 \times$)	49.3 ms ($> 10^3 \times$)	107.4 ms ($> 10^3 \times$)	237.4 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	185.7 ms ($> 10^3 \times$)	185.7 ms ($> 10^3 \times$)	355.2 ms ($> 10^3 \times$)	209.1 ms ($> 10^3 \times$)	368.3 ms ($> 10^3 \times$)	376.4 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	4.55 ms ($> 10^3 \times$)	4.56 ms ($> 10^3 \times$)	61.1 ms ($> 10^3 \times$)	41.8 ms ($> 10^3 \times$)	88.7 ms ($> 10^3 \times$)	186.7 ms ($> 10^3 \times$)
	Cost-aware oracle	4.47 ms ($> 10^3 \times$)	4.62 ms ($> 10^3 \times$)	60.3 ms ($> 10^3 \times$)	41.1 ms ($> 10^3 \times$)	89.3 ms ($> 10^3 \times$)	185.9 ms ($> 10^3 \times$)
	Learned router (ours)	4.62 ms ($> 10^3 \times$)	4.69 ms ($> 10^3 \times$)	60.7 ms ($> 10^3 \times$)	41.5 ms ($> 10^3 \times$)	89.1 ms ($> 10^3 \times$)	188.5 ms ($> 10^3 \times$)

Table 40: 512×512 , convection–diffusion: median wall-clock time to relative error ε for every policy and pairing (16 instances).

Solver	Method	$\varepsilon=10^{-2}$	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-5}$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
Jacobi	Solver only	$>13.71 \text{ s}^{116}$	$>13.71 \text{ s}^{116}$	$>13.71 \text{ s}^{116}$	$>13.71 \text{ s}^{116}$	$>13.71 \text{ s}^{116}$	$>13.71 \text{ s}^{116}$
	HINTS ($\tau=25$)	45.3 ms ($> 10^3 \times$)	45.8 ms ($> 10^3 \times$)	153.8 ms ($> 10^3 \times$)	114.5 ms ($> 10^3 \times$)	214.1 ms ($> 10^3 \times$) ⁱ⁴	1.38 s ($> 10^3 \times$) ⁱ⁷
	HINTS ($\tau=10$)	20.5 ms ($> 10^3 \times$)	20.8 ms ($> 10^3 \times$)	170.0 ms ($> 10^3 \times$)	126.6 ms ($> 10^3 \times$)	237.8 ms ($> 10^3 \times$) ⁱ⁴	1.57 s ($> 10^3 \times$) ⁱ⁷
	HINTS ($\tau=5$)	12.5 ms ($> 10^3 \times$)	13.8 ms ($> 10^3 \times$)	250.2 ms ($> 10^3 \times$)	185.3 ms ($> 10^3 \times$)	335.6 ms ($> 10^3 \times$) ⁱ⁴	2.33 s ($> 10^3 \times$) ⁱ⁷
	HINTS ($\tau=50$)	93.0 ms ($> 10^3 \times$)	93.0 ms ($> 10^3 \times$)	140.6 ms ($> 10^3 \times$)	121.5 ms ($> 10^3 \times$)	195.2 ms ($> 10^3 \times$) ⁱ⁴	1.33 s ($> 10^3 \times$) ⁱ⁷
	Greedy oracle (Alg. 1)	5.84 ms ($> 10^3 \times$)	6.49 ms ($> 10^3 \times$)	148.0 ms ($> 10^3 \times$)	111.4 ms ($> 10^3 \times$)	202.0 ms ($> 10^3 \times$) ⁱ⁴	1.29 s ($> 10^3 \times$) ⁱ⁷
	Cost-aware oracle	5.85 ms ($> 10^3 \times$)	8.02 ms ($> 10^3 \times$)	165.2 ms ($> 10^3 \times$)	120.5 ms ($> 10^3 \times$)	232.9 ms ($> 10^3 \times$) ⁱ⁴	1.28 s ($> 10^3 \times$) ⁱ⁷
	Learned router (ours)	5.77 ms ($> 10^3 \times$)	6.18 ms ($> 10^3 \times$)	148.5 ms ($> 10^3 \times$) ⁱ⁴	109.8 ms ($> 10^3 \times$)	204.2 ms ($> 10^3 \times$) ⁱ⁴	1.36 s ($> 10^3 \times$) ⁱ⁷
GS	Solver only	$>32.99 \text{ s}^{116}$	$>32.99 \text{ s}^{116}$	$>32.99 \text{ s}^{116}$	$>32.99 \text{ s}^{116}$	$>32.99 \text{ s}^{116}$	$>32.99 \text{ s}^{116}$
	HINTS ($\tau=25$)	105.1 ms ($> 10^3 \times$)	105.1 ms ($> 10^3 \times$)	214.1 ms ($> 10^3 \times$)	151.5 ms ($> 10^3 \times$)	257.6 ms ($> 10^3 \times$)	504.5 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	42.5 ms ($> 10^3 \times$)	42.9 ms ($> 10^3 \times$)	192.7 ms ($> 10^3 \times$)	143.4 ms ($> 10^3 \times$)	265.1 ms ($> 10^3 \times$)	519.2 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	21.8 ms ($> 10^3 \times$)	22.0 ms ($> 10^3 \times$)	212.5 ms ($> 10^3 \times$)	157.4 ms ($> 10^3 \times$)	294.0 ms ($> 10^3 \times$)	582.6 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	209.5 ms ($> 10^3 \times$)	209.5 ms ($> 10^3 \times$)	295.3 ms ($> 10^3 \times$)	236.8 ms ($> 10^3 \times$)	414.1 ms ($> 10^3 \times$)	570.7 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	5.58 ms ($> 10^3 \times$)	5.70 ms ($> 10^3 \times$)	184.8 ms ($> 10^3 \times$)	134.4 ms ($> 10^3 \times$)	256.3 ms ($> 10^3 \times$)	493.9 ms ($> 10^3 \times$)
	Cost-aware oracle	5.69 ms ($> 10^3 \times$)	5.97 ms ($> 10^3 \times$)	185.9 ms ($> 10^3 \times$)	138.4 ms ($> 10^3 \times$)	254.8 ms ($> 10^3 \times$)	489.9 ms ($> 10^3 \times$)
	Learned router (ours)	5.65 ms ($> 10^3 \times$)	5.79 ms ($> 10^3 \times$)	179.9 ms ($> 10^3 \times$)	133.2 ms ($> 10^3 \times$)	247.3 ms ($> 10^3 \times$)	486.0 ms ($> 10^3 \times$)
SOR (1.5)	Solver only	$>32.91 \text{ s}^{116}$	$>32.91 \text{ s}^{116}$	$>32.91 \text{ s}^{116}$	$>32.91 \text{ s}^{116}$	$>32.91 \text{ s}^{116}$	$>32.91 \text{ s}^{116}$
	HINTS ($\tau=25$)	103.8 ms ($> 10^3 \times$)	103.8 ms ($> 10^3 \times$)	206.6 ms ($> 10^3 \times$)	206.6 ms ($> 10^3 \times$)	206.6 ms ($> 10^3 \times$)	308.3 ms ($> 10^3 \times$)
	HINTS ($\tau=10$)	41.1 ms ($> 10^3 \times$)	41.5 ms ($> 10^3 \times$)	91.5 ms ($> 10^3 \times$)	84.9 ms ($> 10^3 \times$)	121.2 ms ($> 10^3 \times$)	234.4 ms ($> 10^3 \times$)
	HINTS ($\tau=5$)	21.5 ms ($> 10^3 \times$)	22.1 ms ($> 10^3 \times$)	89.3 ms ($> 10^3 \times$)	66.2 ms ($> 10^3 \times$)	123.9 ms ($> 10^3 \times$)	242.4 ms ($> 10^3 \times$)
	HINTS ($\tau=50$)	203.2 ms ($> 10^3 \times$)	203.2 ms ($> 10^3 \times$)	406.5 ms ($> 10^3 \times$)	403.1 ms ($> 10^3 \times$)	406.5 ms ($> 10^3 \times$)	460.1 ms ($> 10^3 \times$)
	Greedy oracle (Alg. 1)	5.41 ms ($> 10^3 \times$)	6.82 ms ($> 10^3 \times$)	83.3 ms ($> 10^3 \times$)	60.8 ms ($> 10^3 \times$)	111.5 ms ($> 10^3 \times$)	212.8 ms ($> 10^3 \times$)
	Cost-aware oracle	5.22 ms ($> 10^3 \times$)	5.68 ms ($> 10^3 \times$)	85.0 ms ($> 10^3 \times$)	62.2 ms ($> 10^3 \times$)	114.0 ms ($> 10^3 \times$)	217.1 ms ($> 10^3 \times$)
	Learned router (ours)	5.48 ms ($> 10^3 \times$)	5.64 ms ($> 10^3 \times$)	83.6 ms ($> 10^3 \times$)	61.2 ms ($> 10^3 \times$)	112.5 ms ($> 10^3 \times$)	216.7 ms ($> 10^3 \times$)

Table 41: 512×512 : strong classical baselines (16 instances).

Equation	Method	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$	iters to h^2
Poisson	FFT direct solve	7.65 ms (0.13 $\times$)	7.65 ms (0.13 $\times$)	7.65 ms (0.13 $\times$)	7.65 ms (0.13 $\times$)	1
	Multigrid V(2,2) alone	42.8 ms (0.78 $\times$)	81.9 ms (1.49 $\times$)	90.2 ms (1.63 $\times$)	126.5 ms (2.21 $\times$)	4
	CG	689.5 ms (12.2 $\times$)	920.9 ms (16.9 $\times$)	1.04 s (18.1 $\times$)	1.18 s (20.7 $\times$)	776
	PCG (SymGS)	1.33 s (22.6 $\times$)	2.52 s (42.9 $\times$)	2.62 s (44.3 $\times$)	3.14 s (54.2 $\times$)	364
	PCG (multigrid)	44.2 ms (0.73 $\times$)	85.6 ms (1.64 $\times$)	85.5 ms (1.58 $\times$)	113.2 ms (1.87 $\times$)	4
	HINTS ($\tau=25$), SOR (1.5)	93.2 ms (1.61 $\times$)	182.7 ms (3.10 $\times$)	187.1 ms (3.10 $\times$)	269.4 ms (4.35 $\times$)	50
	Learned router, {NO, SOR (1.5)}	4.69 ms	60.7 ms	89.1 ms	188.5 ms	17
	Learned router, {NO, Multigrid}	4.76 ms	38.7 ms	52.5 ms	99.5 ms	3
ConvDiff	Cost-aware oracle, {NO, Multigrid}	4.86 ms	38.6 ms	50.6 ms	97.0 ms	2
	FFT direct solve	8.06 ms (0.10 $\times$)	8.06 ms (0.10 $\times$)	8.06 ms (0.10 $\times$)	8.06 ms (0.10 $\times$)	1
	Multigrid V(2,2) alone	52.4 ms (0.63 $\times$)	99.7 ms (1.23 $\times$)	107.7 ms (1.36 $\times$)	150.7 ms (1.87 $\times$)	4
	BiCGSTAB	3.79 s (43.1 $\times$)	5.56 s (68.3 $\times$)	5.83 s (70.6 $\times$) ⁱ¹	6.72 s (80.6 $\times$) ⁱ¹	1695
	BiCGSTAB (multigrid)	46.1 ms (0.82 $\times$)	93.5 ms (1.18 $\times$)	93.7 ms (1.12 $\times$)	144.8 ms (1.69 $\times$)	2
	HINTS ($\tau=25$), SOR (1.5)	103.8 ms (1.24 $\times$)	206.6 ms (2.48 $\times$)	206.6 ms (2.48 $\times$)	308.3 ms (3.75 $\times$)	50
	Learned router, {NO, SOR (1.5)}	5.64 ms	83.6 ms	112.5 ms	216.7 ms	20
	Learned router, {NO, Multigrid}	5.63 ms	53.7 ms	61.3 ms	102.6 ms	3
	Cost-aware oracle, {NO, Multigrid}	5.74 ms	50.9 ms	62.3 ms	104.1 ms	3

1047 E.6 Statistical significance and multi-trial robustness

1048 All wall-clock comparisons are paired: every policy solves the same 64 test instances, so we test
1049 the per-instance log time ratios with a one-sided Wilcoxon signed-rank test (alternative: the router
1050 is faster) and, as a parametric complement, a one-sided paired t -test on log times; instances that a
1051 baseline fails to bring below the tolerance within the iteration cap are counted against the router
1052 (ratio 0). Table 42 reports the p -values of the pairwise comparisons of Tables 2 and 17, together with
1053 a multi-trial analysis: the router of every pairing was retrained from scratch with five independent
1054 seeds (different training instances, exploration and initialisation; the corrector and the test set are
1055 fixed) and re-run on the test set. Because these trials ran in separate sessions, whose live timings
1056 are not comparable with the main run’s, they are compared in *work units* (measured per-iteration
1057 costs times executed operations, plus $5 \mu\text{s}$ per decision; the main run’s HINTS work units serve as the
1058 reference), which are determined by the decision sequence alone. We report the mean and standard
1059 deviation over seeds of the median work-unit time to h^2 , in parentheses the fraction of test instances
1060 on which the seed router’s iteration count to h^2 coincides with the main router’s (identical decision
1061 sequences up to the crossing), the range over seeds of the paired speedup over HINTS ($\tau=25$), and
1062 the number of seeds for which the router is significantly faster ($p < 0.01$) than both HINTS ($\tau=25$)
1063 and the best fixed period. The learned policy turns out to be insensitive to the training seed: the seed
1064 routers reproduce the main router’s decision sequence up to the h^2 crossing on essentially every test
1065 instance, so their work-unit times and speedups coincide and every seed passes both significance
1066 tests. Table 43 gives the corresponding tests for the ensembles (including the tests in the opposite
1067 direction, to show where an ensemble router is significantly *slower* than the best pairwise router or

1068 than its oracle), and Table 44 for the strong classical baselines of Section E.4. The iteration-based
1069 table (Table 18) already carries paired t -tests on the AUC.

Table 42: Significance of the pairwise comparisons on the 128×128 grid (64 paired instances; one-sided Wilcoxon / paired t -test p -values on live times, “ 10^{-k} ” denotes $p < 10^{-k}$) and robustness over five independent router-training seeds (work-unit times; the percentage is the share of instances whose decision sequence to h^2 is identical to the main router’s).

Equation	Solver	$\varepsilon = h^2$; p (Wilcoxon / t)			$\varepsilon = 10^{-8}$; p		Router over 5 training seeds		
		vs. solver only	vs. HINTS-25	vs. best τ	vs. HINTS-25	vs. best τ	time to h^2 (decisions as main router)	speedup vs. HINTS-25	seeds with $p < 0.01$
Poisson	Jacobi	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-8} / 10^{-7}$	$< 10^{-10} / < 10^{-10}$	$10^{-9} / 10^{-8}$	0.74 ± 0.00 ms (100%)	$2.59\text{--}2.59\times$	5/5
	Jacobi (0.67)	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-9} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-4} / 10^{-5}$	0.75 ± 0.00 ms (100%)	$2.58\text{--}2.58\times$	5/5
	GS	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-10} / < 10^{-10}$	0.90 ± 0.00 ms (100%)	$6.30\text{--}6.30\times$	5/5
	SymGS	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	1.06 ± 0.00 ms (100%)	$9.29\text{--}9.29\times$	5/5
	SOR (1.5)	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-9} / 10^{-10}$	0.89 ± 0.00 ms (100%)	$10.45\text{--}10.45\times$	5/5
ConvDiff	Jacobi	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / 10^{-7}$	–	–	–
	Jacobi (0.67)	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-5} / 10^{-6}$	–	–	–
	GS	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$10^{-10} / < 10^{-10}$	–	–	–
	SymGS	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	–	–	–
	SOR (1.5)	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	$< 10^{-10} / < 10^{-10}$	–	–	–

Table 43: Ensembles: one-sided Wilcoxon p -values at $\varepsilon = h^2$ (64 paired instances) for the ensemble router against the fastest member solver alone, against the best pairwise router in both directions, and against the cost-aware oracle over the same ensemble (alternative: the ensemble router is slower).

Equation	$\mathcal{W}$	vs. best solver only	vs. best pairwise router (faster)	vs. best pairwise router (slower)	vs. oracle($\text{NO} \cup \mathcal{W}$) (slower)
Poisson	$\{Jacobi, GS\}$	$< 10^{-10}$	10^{-7}	1.000	0.040
	$\{Jacobi, GS, SymGS\}$	$< 10^{-10}$	0.001	0.999	0.001
	$\{Jacobi, GS, SymGS, Jacobi(0.67)\}$	$< 10^{-10}$	0.856	0.144	10^{-4}
	$\{Jacobi, GS, SymGS, Jacobi(0.67), SOR(1.5)\}$	$< 10^{-10}$	1.000	10^{-8}	10^{-8}
ConvDiff	$\{Jacobi, GS\}$	$< 10^{-10}$	10^{-4}	1.000	10^{-5}
	$\{Jacobi, GS, SymGS\}$	$< 10^{-10}$	10^{-10}	1.000	0.492
	$\{Jacobi, GS, SymGS, Jacobi(0.67)\}$	$< 10^{-10}$	0.783	0.217	0.001
	$\{Jacobi, GS, SymGS, Jacobi(0.67), SOR(1.5)\}$	$< 10^{-10}$	0.047	0.953	0.566

Table 44: Strong baselines: one-sided Wilcoxon p -values that the learned router (best stationary pairing) is faster than each method at each tolerance; where the baseline’s median is lower the entry gives the p -value that the router is slower.

Equation	Method	$\varepsilon=10^{-3}$	$\varepsilon=h^2$	$\varepsilon=10^{-6}$	$\varepsilon=10^{-8}$
ConvDiff 128 ²	FFT direct solve	slower: $< 10^{-10}$	slower: $< 10^{-10}$	slower: $< 10^{-10}$	slower: $< 10^{-10}$
	Multigrid V(2,2) alone	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
	BiCGSTAB	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
	BiCGSTAB (multigrid)	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
	GMRES(20)	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
ConvDiff 256 ²	FFT direct solve	slower: 10^{-4}	slower: 10^{-6}	slower: 10^{-10}	slower: 10^{-10}
	Multigrid V(2,2) alone	10^{-10}	0.006	0.533	slower: 10^{-4}
	BiCGSTAB	10^{-10}	10^{-9}	10^{-6}	0.105
	BiCGSTAB (multigrid)	10^{-10}	0.005	0.562	slower: 10^{-4}
	GMRES(20)	10^{-10}	10^{-10}	10^{-10}	10^{-5}
ConvDiff 512 ²	FFT direct solve	0.768	slower: 10^{-5}	slower: 10^{-5}	slower: 10^{-5}
	Multigrid V(2,2) alone	10^{-5}	0.065	slower: 0.768	slower: 0.008
	BiCGSTAB	10^{-5}	10^{-5}	10^{-5}	10^{-5}
	BiCGSTAB (multigrid)	10^{-5}	0.088	slower: 0.490	slower: 0.009
Poisson 128 ²	FFT direct solve	slower: $< 10^{-10}$	slower: $< 10^{-10}$	slower: $< 10^{-10}$	slower: $< 10^{-10}$
	Multigrid V(2,2) alone	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
	CG	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
	PCG (SymGS)	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
	PCG (multigrid)	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$	$< 10^{-10}$
Poisson 256 ²	FFT direct solve	slower: 10^{-5}	slower: 10^{-6}	slower: 10^{-9}	slower: 10^{-10}
	Multigrid V(2,2) alone	10^{-10}	10^{-5}	0.165	slower: 0.009
	CG	10^{-10}	10^{-9}	10^{-5}	0.789
	PCG (SymGS)	10^{-10}	10^{-10}	10^{-7}	0.014
	PCG (multigrid)	10^{-10}	10^{-5}	0.195	slower: 0.007
Poisson 512 ²	FFT direct solve	0.353	slower: 10^{-4}	slower: 10^{-5}	slower: 10^{-5}
	Multigrid V(2,2) alone	10^{-5}	0.052	0.217	slower: 0.005
	CG	10^{-5}	10^{-5}	10^{-5}	10^{-5}
	PCG (SymGS)	10^{-5}	10^{-5}	10^{-5}	10^{-5}
	PCG (multigrid)	10^{-5}	0.037	slower: 0.702	slower: 0.005

1070 **F Limitations**

1071 A primary limitation of our approach is the higher on-time computational cost requires to learn
1072 the greedy routing strategy. In contrast, the simpler baselines such as HINTS incur no training
1073 overhead. While this cost is amortized during inference time and leads to improved solution quality,
1074 it may be prohibitive in settings with limited computational resources or when rapid deployment
1075 is required. On the deployment side, Section E shows that the gains survive cost accounting: with
1076 a corrector that covers the smooth half of the spectrum and a classical smoother that covers the
1077 rest, one or two corrector calls suffice and the router’s advantage over fixed schedules is uniform
1078 across solvers, equations and tolerances. The corrector we use is specific to the constant-coefficient
1079 periodic setting (a fixed Fourier trunk basis on a coarse sensor grid), its cost grows with the fourth
1080 power of the sensor-grid size, and undamped Jacobi remains limited far below truncation level by the
1081 near-Nyquist modes that neither component damps. Our wall-clock study is restricted to single-thread
1082 CPU execution and stationary smoothers; comparisons against optimal-complexity solvers such as
1083 multigrid, and hybrid ensembles that include them, are left to future work.

1084 Additionally, the effectiveness of the learned router depends on the neural operator exhibiting
1085 heterogeneous performance across samples. When the neural operators produces predictions of
1086 relatively uniform quality, the benefit of adaptive routing diminishes and it is more practical to set a
1087 fixed schedule based on the quality of the neural operator. In practice, achieving such heterogeneity
1088 can be sensitive to training choices, and neural operators themselves can be finicky to train.

1089 **G LLM Usage**

1090 LLMs, specifically ChatGPT and Gemini, supported the writing process in an iterative manner. We
1091 drafted paragraphs and asked the models for feedback on grammar and clarity. We then incorporated
1092 selected suggestions into the writing and repeated this process until we were satisfied with the writing.

1093 The code developed for the experiments was written by the authors with the help of occasional code
1094 completions. The central components (e.g., the hybrid solver implementation and the greedy-router
1095 training pipelines) were implemented exclusively by the authors.

1096 All substantive intellectual contributions, which include ideas, theorems, and analyses, are our own.
1097 LLMs were occasionally used to verify the correctness of proofs, but all proof strategies originated
1098 from the authors and relevant literature.

1099 **NeurIPS Paper Checklist**

1100 The checklist is designed to encourage best practices for responsible machine learning research,
1101 addressing issues of reproducibility, transparency, research ethics, and societal impact. Do not remove
1102 the checklist: **The papers not including the checklist will be desk rejected.** The checklist should
1103 follow the references and follow the (optional) supplemental material. The checklist does NOT count
1104 towards the page limit.

1105 Please read the checklist guidelines carefully for information on how to answer these questions. For
1106 each question in the checklist:

- 1107 • You should answer [Yes], [No], or [N/A].
- 1108 • [N/A] means either that the question is Not Applicable for that particular paper or the
1109 relevant information is Not Available.
- 1110 • Please provide a short (1–2 sentence) justification right after your answer (even for [N/A]).

1111 **The checklist answers are an integral part of your paper submission.** They are visible to the
1112 reviewers, area chairs, senior area chairs, and ethics reviewers. You will also be asked to include it
1113 (after eventual revisions) with the final version of your paper, and its final version will be published
1114 with the paper.

1115 The reviewers of your paper will be asked to use the checklist as one of the factors in their evaluation.
1116 While [Yes] is generally preferable to [No], it is perfectly acceptable to answer [No] provided a
1117 proper justification is given (e.g., error bars are not reported because it would be too computationally
1118 expensive” or “we were unable to find the license for the dataset we used”). In general, answering
1119 [No] or [N/A] is not grounds for rejection. While the questions are phrased in a binary way, we
1120 acknowledge that the true answer is often more nuanced, so please just use your best judgment and
1121 write a justification to elaborate. All supporting evidence can appear either in the main paper or the
1122 supplemental material, provided in appendix. If you answer [Yes] to a question, in the justification
1123 please point to the section(s) where related material for the question can be found.

1124 IMPORTANT, please:

- 1125 • **Delete this instruction block, but keep the section heading “NeurIPS Paper Checklist”,**
- 1126 • **Keep the checklist subsection headings, questions/answers and guidelines below.**
- 1127 • **Do not modify the questions and only use the provided macros for your answers.**

1128 **1. Claims**

1129 Question: Do the main claims made in the abstract and introduction accurately reflect the
1130 paper’s contributions and scope?

1131 Answer: [Yes]

1132 Justification: The abstract clearly delineates the paper’s main contributions and scope, and
1133 the introduction reiterates these claims in a structured, bullet-point form. All stated claims
1134 are directly supported by the theoretical and experimental results presented in the paper.

1135 Guidelines:

- 1136 • The answer [N/A] means that the abstract and introduction do not include the claims
1137 made in the paper.
- 1138 • The abstract and/or introduction should clearly state the claims made, including the
1139 contributions made in the paper and important assumptions and limitations. A [No] or
1140 [N/A] answer to this question will not be perceived well by the reviewers.
- 1141 • The claims made should match theoretical and experimental results, and reflect how
1142 much the results can be expected to generalize to other settings.
- 1143 • It is fine to include aspirational goals as motivation as long as it is clear that these goals
1144 are not attained by the paper.

1145 **2. Limitations**

1146 Question: Does the paper discuss the limitations of the work performed by the authors?

1147 Answer: [Yes]

1148 Justification: The paper discusses key limitations in Appendix E.

1149 Guidelines:

- 1150 • The answer [N/A] means that the paper has no limitation while the answer [No] means
1151 that the paper has limitations, but those are not discussed in the paper.
- 1152 • The authors are encouraged to create a separate “Limitations” section in their paper.
- 1153 • The paper should point out any strong assumptions and how robust the results are to
1154 violations of these assumptions (e.g., independence assumptions, noiseless settings,
1155 model well-specification, asymptotic approximations only holding locally). The authors
1156 should reflect on how these assumptions might be violated in practice and what the
1157 implications would be.
- 1158 • The authors should reflect on the scope of the claims made, e.g., if the approach was
1159 only tested on a few datasets or with a few runs. In general, empirical results often
1160 depend on implicit assumptions, which should be articulated.
- 1161 • The authors should reflect on the factors that influence the performance of the approach.
1162 For example, a facial recognition algorithm may perform poorly when image resolution
1163 is low or images are taken in low lighting. Or a speech-to-text system might not be
1164 used reliably to provide closed captions for online lectures because it fails to handle
1165 technical jargon.
- 1166 • The authors should discuss the computational efficiency of the proposed algorithms
1167 and how they scale with dataset size.
- 1168 • If applicable, the authors should discuss possible limitations of their approach to
1169 address problems of privacy and fairness.
- 1170 • While the authors might fear that complete honesty about limitations might be used by
1171 reviewers as grounds for rejection, a worse outcome might be that reviewers discover
1172 limitations that aren’t acknowledged in the paper. The authors should use their best
1173 judgment and recognize that individual actions in favor of transparency play an impor-
1174 tant role in developing norms that preserve the integrity of the community. Reviewers
1175 will be specifically instructed to not penalize honesty concerning limitations.

1176 3. Theory assumptions and proofs

1177 Question: For each theoretical result, does the paper provide the full set of assumptions and
1178 a complete (and correct) proof?

1179 Answer: [Yes]

1180 Justification: All theoretical results include clearly stated assumptions in the statement
1181 of theorems. Complete proofs are provided in Appendices A and B with appropriate
1182 cross-referencing from the main text.

1183 Guidelines:

- 1184 • The answer [N/A] means that the paper does not include theoretical results.
- 1185 • All the theorems, formulas, and proofs in the paper should be numbered and cross-
1186 referenced.
- 1187 • All assumptions should be clearly stated or referenced in the statement of any theorems.
- 1188 • The proofs can either appear in the main paper or the supplemental material, but if
1189 they appear in the supplemental material, the authors are encouraged to provide a short
1190 proof sketch to provide intuition.
- 1191 • Inversely, any informal proof provided in the core of the paper should be complemented
1192 by formal proofs provided in appendix or supplemental material.
- 1193 • Theorems and Lemmas that the proof relies upon should be properly referenced.

1194 4. Experimental result reproducibility

1195 Question: Does the paper fully disclose all the information needed to reproduce the main ex-
1196 perimental results of the paper to the extent that it affects the main claims and/or conclusions
1197 of the paper (regardless of whether the code and data are provided or not)?

1198 Answer: [Yes]

Justification: The paper provides sufficient detail to reproduce all experiments, including training procedures and implementation details described in the main text and Appendix C. Additionally, we release code with a comprehensive README to support the reproducibility of our results.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: We provide open access to code with detailed instructions in a comprehensive README, including environment setup and commands to train routers and reproduce the main experimental results. These files will automatically generate the data needed for training. Data generation has also been documented in Appendix C.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.

- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [\[Yes\]](#)

Justification: The paper specifies all key training and evaluation details in the Section 6 and Appendix C.

Guidelines:

- The answer [\[N/A\]](#) means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [\[Yes\]](#)

Justification: The paper reports standard deviations in the main results tables, and further provides statistical significance via t-test p values in Appendix D.

Guidelines:

- The answer [\[N/A\]](#) means that the paper does not include experiments.
- The authors should answer [\[Yes\]](#) if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

1307 Answer: [Yes]

1308 Justification: The paper provides details on compute resources in Appendix C.

1309 Guidelines:

- 1310 • The answer [N/A] means that the paper does not include experiments.
- 1311 • The paper should indicate the type of compute workers CPU or GPU, internal cluster,
- 1312 or cloud provider, including relevant memory and storage.
- 1313 • The paper should provide the amount of compute required for each of the individual
- 1314 experimental runs as well as estimate the total compute.
- 1315 • The paper should disclose whether the full research project required more compute
- 1316 than the experiments reported in the paper (e.g., preliminary or failed experiments that
- 1317 didn't make it into the paper).

1318 **9. Code of ethics**

1319 Question: Does the research conducted in the paper conform, in every respect, with the

1320 NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

1321 Answer: [Yes]

1322 Justification: This paper does not involve any human subjects and all data has been simu-

1323 lated. This research focuses on numerical methods for physical systems and does not raise

1324 concerns related to safety, security, discrimination, surveillance, deception & harassment,

1325 environment, human rights, and bias & fairness.

1326 Guidelines:

- 1327 • The answer [N/A] means that the authors have not reviewed the NeurIPS Code of
- 1328 Ethics.
- 1329 • If the authors answer [No], they should explain the special circumstances that require a
- 1330 deviation from the Code of Ethics.
- 1331 • The authors should make sure to preserve anonymity (e.g., if there is a special consid-
- 1332 eration due to laws or regulations in their jurisdiction).

1333 **10. Broader impacts**

1334 Question: Does the paper discuss both potential positive societal impacts and negative

1335 societal impacts of the work performed?

1336 Answer: [Yes]

1337 Justification: The paper discusses broader impacts in the introduction section. No direct

1338 negative societal impacts are anticipated.

1339 Guidelines:

- 1340 • The answer [N/A] means that there is no societal impact of the work performed.
- 1341 • If the authors answer [N/A] or [No], they should explain why their work has no societal
- 1342 impact or why the paper does not address societal impact.
- 1343 • Examples of negative societal impacts include potential malicious or unintended uses
- 1344 (e.g., disinformation, generating fake profiles, surveillance), fairness considerations
- 1345 (e.g., deployment of technologies that could make decisions that unfairly impact specific
- 1346 groups), privacy considerations, and security considerations.
- 1347 • The conference expects that many papers will be foundational research and not tied
- 1348 to particular applications, let alone deployments. However, if there is a direct path to
- 1349 any negative applications, the authors should point it out. For example, it is legitimate
- 1350 to point out that an improvement in the quality of generative models could be used to
- 1351 generate Deepfakes for disinformation. On the other hand, it is not needed to point out
- 1352 that a generic algorithm for optimizing neural networks could enable people to train
- 1353 models that generate Deepfakes faster.
- 1354 • The authors should consider possible harms that could arise when the technology is
- 1355 being used as intended and functioning correctly, harms that could arise when the
- 1356 technology is being used as intended but gives incorrect results, and harms following
- 1357 from (intentional or unintentional) misuse of the technology.

- 1358 • If there are negative societal impacts, the authors could also discuss possible mitigation
1359 strategies (e.g., gated release of models, providing defenses in addition to attacks,
1360 mechanisms for monitoring misuse, mechanisms to monitor how a system learns from
1361 feedback over time, improving the efficiency and accessibility of ML).

1362 11. Safeguards

1363 Question: Does the paper describe safeguards that have been put in place for responsible
1364 release of data or models that have a high risk for misuse (e.g., pre-trained language models,
1365 image generators, or scraped datasets)?

1366 Answer: [N/A]

1367 Justification: The paper does not release any models or datasets at all. It focuses on method-
1368 ological contributions for numerical solvers using simulated data. Therefore, safeguards are
1369 not applicable.

1370 Guidelines:

- 1371 • The answer [N/A] means that the paper poses no such risks.
1372 • Released models that have a high risk for misuse or dual-use should be released with
1373 necessary safeguards to allow for controlled use of the model, for example by requiring
1374 that users adhere to usage guidelines or restrictions to access the model or implementing
1375 safety filters.
1376 • Datasets that have been scraped from the Internet could pose safety risks. The authors
1377 should describe how they avoided releasing unsafe images.
1378 • We recognize that providing effective safeguards is challenging, and many papers do
1379 not require this, but we encourage authors to take this into account and make a best
1380 faith effort.

1381 12. Licenses for existing assets

1382 Question: Are the creators or original owners of assets (e.g., code, data, models), used in
1383 the paper, properly credited and are the license and terms of use explicitly mentioned and
1384 properly respected?

1385 Answer: [N/A]

1386 Justification: The paper does not use any external datasets or pretrained models. All
1387 experiments are conducted using simulated data and models trained in-house.

1388 Guidelines:

- 1389 • The answer [N/A] means that the paper does not use existing assets.
1390 • The authors should cite the original paper that produced the code package or dataset.
1391 • The authors should state which version of the asset is used and, if possible, include a
1392 URL.
1393 • The name of the license (e.g., CC-BY 4.0) should be included for each asset.
1394 • For scraped data from a particular source (e.g., website), the copyright and terms of
1395 service of that source should be provided.
1396 • If assets are released, the license, copyright information, and terms of use in the
1397 package should be provided. For popular datasets, `paperswithcode.com/datasets`
1398 has curated licenses for some datasets. Their licensing guide can help determine the
1399 license of a dataset.
1400 • For existing datasets that are re-packaged, both the original license and the license of
1401 the derived asset (if it has changed) should be provided.
1402 • If this information is not available online, the authors are encouraged to reach out to
1403 the asset's creators.

1404 13. New assets

1405 Question: Are new assets introduced in the paper well documented and is the documentation
1406 provided alongside the assets?

1407 Answer: [Yes]

1408 Justification: We release code for our method which is documented with a detailed
1409 README.

1410 Guidelines:

1411 • The answer [N/A] means that the paper does not release new assets.

1412 • Researchers should communicate the details of the dataset/code/model as part of their

1413 submissions via structured templates. This includes details about training, license,

1414 limitations, etc.

1415 • The paper should discuss whether and how consent was obtained from people whose

1416 asset is used.

1417 • At submission time, remember to anonymize your assets (if applicable). You can either

1418 create an anonymized URL or include an anonymized zip file.

1419 **14. Crowdsourcing and research with human subjects**

1420 Question: For crowdsourcing experiments and research with human subjects, does the paper

1421 include the full text of instructions given to participants and screenshots, if applicable, as

1422 well as details about compensation (if any)?

1423 Answer: [N/A]

1424 Justification: The paper does not involve crowdsourcing or any research with human subjects.

1425 All experiments are conducted using simulated data.

1426 Guidelines:

1427 • The answer [N/A] means that the paper does not involve crowdsourcing nor research

1428 with human subjects.

1429 • Including this information in the supplemental material is fine, but if the main contribu-

1430 tion of the paper involves human subjects, then as much detail as possible should be

1431 included in the main paper.

1432 • According to the NeurIPS Code of Ethics, workers involved in data collection, curation,

1433 or other labor should be paid at least the minimum wage in the country of the data

1434 collector.

1435 **15. Institutional review board (IRB) approvals or equivalent for research with human**

1436 **subjects**

1437 Question: Does the paper describe potential risks incurred by study participants, whether

1438 such risks were disclosed to the subjects, and whether Institutional Review Board (IRB)

1439 approvals (or an equivalent approval/review based on the requirements of your country or

1440 institution) were obtained?

1441 Answer: [N/A]

1442 Justification: This paper does not involve human subjects. All experiments are conducted

1443 using simulated data. Therefore, IRB approval is not applicable.

1444 Guidelines:

1445 • The answer [N/A] means that the paper does not involve crowdsourcing nor research

1446 with human subjects.

1447 • Depending on the country in which research is conducted, IRB approval (or equivalent)

1448 may be required for any human subjects research. If you obtained IRB approval, you

1449 should clearly state this in the paper.

1450 • We recognize that the procedures for this may vary significantly between institutions

1451 and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the

1452 guidelines for their institution.

1453 • For initial submissions, do not include any information that would break anonymity (if

1454 applicable), such as the institution conducting the review.

1455 **16. Declaration of LLM usage**

1456 Question: Does the paper describe the usage of LLMs if it is an important, original, or

1457 non-standard component of the core methods in this research? Note that if the LLM is used

1458 only for writing, editing, or formatting purposes and does *not* impact the core methodology,

1459 scientific rigor, or originality of the research, declaration is not required.

1460 Answer: [N/A]

1461 Justification: LLMs are primarily used for writing and editing. Further details are provided
1462 in Appendix F.
1463 Guidelines:
1464 • The answer [N/A] means that the core method development in this research does not
1465 involve LLMs as any important, original, or non-standard components.
1466 • Please refer to our LLM policy in the NeurIPS handbook for what should or should not
1467 be described.