Dropzyy 1.0 — QA Tester Interactive Verification Checklist

Fillable Digital AcroForm PDF: Testers can click checkboxes to tickmark Pass/Fail and type notes directly in this document.

Tester Name:		**Test Date:**		**Target URL:**	
Environment:	FastAPI + Mongo Atlas + SQLite	**Result:**	PASSED FAILED	**Sign-off:**	



Module 1: Authentication, Role-Based Access Control (RBAC) & Security

ID & Pri.	Scenario / Scope	Execution Steps	Expected Criteria	PASS	FAIL	Defect / Notes
AUTH-01 [CRIT]	**Customer Registration & OTP**	1. Click Sign In -> Register. 2. Enter valid email -> Send OTP. 3. Enter 6-digit OTP & password.	OTP received. Account created in SQLite and MongoDB Atlas dropzyy.users.			
AUTH-02 [CRIT]	**Supplier Login & Portal**	1. Sign in with supplier credentials. 2. Verify dashboard view.	JWT Bearer token assigned. Redirected to Supplier Dashboard with operating hours & calendar.			
AUTH-03 [CRIT]	**Admin RBAC Barrier**	1. Login as regular customer. 2. Try navigating to /api/admin/users or opening Admin view.	Blocked with HTTP 403 Forbidden. Regular customer cannot access administrative views.			
AUTH-04 [HIGH]	**Rate Limiter & Headers**	1. Inspect response headers in DevTools. 2. Submit 12 failed login attempts rapidly.	X-Content-Type-Options: nosniff present. 11th request triggers HTTP 429 Too Many Requests.			

Module 2: Restaurant Operating Hours & Live Scheduling

ID & Pri.	Scenario / Scope	Execution Steps	Expected Criteria	PASS	FAIL	Defect / Notes
SCHED-01 [CRIT]	**Operating Hours (In-Hours)**	1. Supplier sets hours (e.g. 08:00 AM - 10:00 PM). 2. View restaurant during these hours.	Displays green 'OPEN NOW' pill. Dashboard displays 'Store is OPEN'. Cart accepts orders.			
SCHED-02 [CRIT]	**Operating Hours (Outside-Hours)**	1. Set closing time 1 hour prior to current time. 2. Refresh catalog view.	Automatically displays red 'CLOSED' pill with 'Opens at ...'. Add to Cart is disabled.			
SCHED-03 [HIGH]	**Overnight Hours Support**	1. Set hours 08:00 PM to 02:00 AM. 2. Test at 11:00 PM and at 03:00 AM.	Correctly identified as OPEN at 11:00 PM, and automatically CLOSED at 03:00 AM.			

Module 3: Restaurant Availability Calendar Scheduling

ID & Pri.	Scenario / Scope	Execution Steps	Expected Criteria	PASS	FAIL	Defect / Notes
CAL-01 [CRIT]	**Mark Specific Date CLOSED**	1. Open Supplier Calendar. 2. Select today's date -> Click 'Mark as CLOSED'.	Date turns red. Store immediately turns 'Closed today (Calendar schedule) ■■'.			
CAL-02 [CRIT]	**Calendar Override Priority**	1. Ensure current time is within operating hours. 2. Mark date CLOSED in calendar.	Calendar closure strictly takes precedence over operating hours. Store remains closed all day.			
CAL-03 [HIGH]	**Reset Date to Default**	1. Click closed date -> 'Reset to Default'. 2. Check store status.	Date resets to gray neutral. Store status immediately recalculates based on daily operating hours.			
CAL-04 [CRIT]	**Global Customer Availability Sync**	1. Mark store closed via supplier account. 2. Open clean browser as customer.	GET /api/supplier/availability fetches rules. Customer sees closed badge without opening dashboard.			

Module 4: Restaurant Deletion & Catalog Management

ID & Pri.	Scenario / Scope	Execution Steps	Expected Criteria	PASS	FAIL	Defect / Notes
DEL-01 [CRIT]	**Admin Delete Restaurant**	1. Admin clicks 'Delete' on partner restaurant card. 2. Confirm dialog prompt.	DELETE /api/restaurants/{id}?store_name={name} returns 200. Deleted from SQLite & MongoDB Atlas.			
DEL-02 [CRIT]	**Anti-Resurrection Verification**	1. Delete restaurant via Admin. 2. Hard refresh browser (Ctrl + F5).	Restaurant and products DO NOT reappear. Not resurrected from DEFAULT_PRODUCTS or DB cache.			
DEL-03 [HIGH]	**Supplier Self-Delete Store**	1. Supplier logs in -> clicks 'Delete Store'. 2. Confirm warning dialog.	Company name cleared, role reverts to customer, all products removed from live catalog.			
DEL-04 [HIGH]	**Product Inventory CRUD**	1. Supplier adds product with price & image. 2. Edit price. 3. Delete product.	Instant catalog update on homepage and search. Persists in SQLite and MongoDB Atlas.			

Module 5: Cart, Checkout, Coupon Codes & Order Tracking

ID & Pri.	Scenario / Scope	Execution Steps	Expected Criteria	PASS	FAIL	Defect / Notes
ORD-01 [CRIT]	**Cart Line Items & Quantities**	1. Add open store items. 2. Increment to 3, decrement to 1, then 0.	Subtotal dynamically recalculates. Decreasing to 0 cleanly removes line item.			
ORD-02 [HIGH]	**Coupon Validation (KIRANA10)**	1. Enter coupon 'KIRANA10' -> Apply. 2. Enter invalid code 'FAKE999'.	'KIRANA10' deducts 10% discount. Invalid code displays clear error notification.			
ORD-03 [CRIT]	**Order Placement & Invoice PDF**	1. Complete checkout. 2. Confirm order. 3. Click 'Download PDF Invoice'.	Order placed with unique ORD ID. Branded PDF invoice downloads with itemized summary.			
ORD-04 [HIGH]	**Order Tracking & Refund Claim**	1. Open 'Booking Tracking & Refund Claims'. 2. File refund claim on order.	Order lifecycle updates (Placed -> Preparing -> Out for Delivery -> Delivered). Refund claim logged for Admin.			

Module 6: Dual Database Sync (MongoDB + SQLite) & Edge Cases

ID & Pri.	Scenario / Scope	Execution Steps	Expected Criteria	PASS	FAIL	Defect / Notes
SYNC-01 [CRIT]	**MongoDB Atlas Cloud Parity**	1. Add product or place order. 2. Query MongoDB collection dropzyy.products / orders.	Document replicated in MongoDB Atlas with matching fields, status, and UTC timestamp.			
SYNC-02 [HIGH]	**SQLite Relational Integrity**	1. Query SQLite dropzyy.db. 2. Check users, products, suppliers, orders tables.	Foreign key constraints and data types strictly valid.			

EDGE-01 **[HIGH]**	**Closed Store Order Prevention**	1. Navigate to a closed restaurant. 2. Attempt to add item or force checkout.	UI shows closed notice; checkout action blocked until store reopens.			
EDGE-02 **[MED]**	**Session Expiry Handling**	1. Clear sessionStorage dropzyy_user. 2. Trigger protected API request.	Handled gracefully with redirect to login or fallback to customer guest mode.			