

Smt. Chandibai Himathmal Mansukhani College

Contents

USCSP301 - USCS303: Operating System (OS) Practical – 02	2
Practical Date: 24 – 07 – 2021.....	2
Alogrithm :-	3
Step 1: Input the number of processes required to be scheduled using SJF, burst time for each process.	3
Step 2: Using enhanced bubble sort technique, sort the all given processes in ascending order according to burst time in a ready queue.	3
Step 3: Calculate the Finish Time, Turn Around Time and Waiting Time for each process which in turn help to calculate Average Waiting Time and Average Turn Around Time required by CPU to schedule given set of process using SJF.	3
Implementation:-	13
Input:-	17
Output.	17
Sample Output – 01	18
Sample Output – 02	19
Sample Output-03	20
Sample Output-04	21

USCSP301 - USCS303: Operating System (OS) Practical – 02

Practical Date: 24 – 07 – 2021

Practical Aim: Non-Preemptive CPU Scheduling algorithm where each process with the smallest burst time is executed time.

CPU scheduling algorithm are used for scheduling different process present in the ready queue with available resource in an optimal way so that each and every process get execute by CPU

Scheduling algorithm are broadly classified into two main type namely preemptive and non-preemptive .

FIRST COME FIRST OUT(FCFS) is also know as FIRST IN FIRST OUT (FIFO) SCHEDUAL algorithm is the and simplest CPU .

A process scheduling different process to be assigned to the CPU based on particular scheduling algorithm .there are six popular process scheduling algorithm which we are going to discuss in this chapter FIRST COME FIRST OUT(FCFS) scheduling

Smt. Chandibai Himathmal Mansukhani College

Alogrithm :-

Step 1: Input the number of processes required to be scheduled using SJF, burst time for each process.

Step 2: Using enhanced bubble sort technique, sort the all given processes in ascending order according to burst time in a ready queue.

Step 3: Calculate the Finish Time, Turn Around Time and Waiting Time for each process which in turn help to calculate Average Waiting Time and Average Turn Around Time required by CPU to schedule given set of process using SJF.

Step 3.1: for $i = 0$, Finish Time $T_0 = \text{Arrival Time } T_0 + \text{Burst Time } T_0$

Step 3.2: for $i \geq 1$, Finish Time $T_i = \text{Burst Time } T_i + \text{Finish Time } T_{i-1}$

Step 3.3: for $i = 0$, Turn Around Time $T_0 = \text{Finish Time } T_0 - \text{Arrival Time } T_0$

Step 3.4: for $i \geq 1$, Turn Around Time $T_i = \text{Finish Time } T_i - \text{Arrival Time } T_i$

Step 3.5: for $i = 0$, Waiting Time $T_0 = \text{Turn Around Time } T_0 - \text{Burst Time } T_0$

Step 3.6: for $i \geq 1$, Waiting Time $T_i = \text{Turn Around Time } T_i - \text{Burst Time } T_i$

Step 4: Process with less arrival time comes first and gets scheduled first by the CPU.

Step 5: Calculate the Average Waiting Time and Average Turn Around Time.

Step 6: Stop

Smt. Chandibai Himathmal Mansukhani College

Solved Example :-

Example 1: Consider the following example contain five processes .

Process Id	Burst Time
P0	6
P1	3
P2	8
P3	3
P4	4

Step 1: Processes get execute according to their lowest burst time first .

Process Id	Burst Time
P0	6
P1	3
P2	8
P3	3
P4	4

Smt. Chandibai Himathmal Mansukhani College

Step 2: Following shows the scheduling and execution of processes

Step 2.1: At start P1 shortest execution time which is 0-3 second.

System time	0
Processes scheduling finish time	P1
Finish time	$0+3=3$
Waiting time	$3-3=0$
Turn Around time	$3-0=3$

Step 2.2: next shortest execution time is for process P3 for duration 3-6 second.

System time	6
Processes scheduling finish time	P1,p3
Finish time	$3+3=6$
Waiting time	$6-3=3$
Turn Around time	$6-0=6$

Smt. Chandibai Himathmal Mansukhani College

Step 2.3: Next job with shortest execution time is P4 for a duration 6-10 second.

System time	10
Processes scheduling finish time	P1,p3,p4
Finish time	$6+4=10$
Waiting time	$10-4=6$
Turn Around time	$10-0=10$

Step 2.4: Next job with shortest execution time is p0 for duration of 10-16 second.

System time	10
Processes scheduling finish time	P1,p3,p3,p4,p0
Finish time	$10+6=16$
Waiting time	$16-6=10$
Turn Around time	$16-0=16$

Step 2.5 : Similarly next job with shortest execution time is P2 for duration of 16-24 second.

System time	16
Processes scheduling finish time	P1,p3,p3,p4,p0,p2

Smt. Chandibai Himathmal Mansukhani College

Finish time	$16+8=24$
Waiting time	$24-8=16$
Turn Around time	$24-0=24$

Step 3: Calculate average waiting time and average turn around time.

$$\begin{aligned}\text{Average waiting time} &= (0+3+6+10+16)/5 \\ &= 35/5 \\ &= 7\end{aligned}$$

$$\begin{aligned}\text{Average turn around time} &= (3+6+10+16+24)/5 \\ &= 59/5 \\ &= 11.8\end{aligned}$$

Smt. Chandibai Himathmal Mansukhani College

Step 4: After scheduling of all provided processes.

Process id	Burst time	Arrival time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time- Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P1	3	0	$0+3=3$	$3-0=3$	$3-3=0$
P3	3	0	$3+3=6$	$6-0=6$	$6-3=3$
P4	4	0	$6+4=10$	$10-0=10$	$10-4=6$
P0	6	0	$10+6=16$	$16-0=16$	$16-6=10$
P2	8	0	$16+8=24$	$24-0=24$	$24-8=16$
Average				11.8000000	7.0000000

Gnatt chart : -

P0	P1	P2	P3	P4	
0	3	6	10	16	24

Smt. Chandibai Himathmal Mansukhani College

Example 2: Consider the following example containing five processes arrive at same time.

Processes ID	Burst Time
P0	2
P1	1
P2	6

Solution :-

Process id	Burst time	Arrival time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time-Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P1	1	0	1	1	1
P0	2	0	3	3	3
P2	6	0	9	9	9
Average				4.33333	1.33333

P0	P1	P2	
0	1	3	9

Smt. Chandibai Himathmal Mansukhani College

Example 3: Consider the following example contain five processes arrive at same time .

Process ID	Burst time
P0	25
P1	15
P2	10
P3	25
P4	10
P5	25

Solution :-

Process id	Burst time	Arrival time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time- Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P2	10	0	10	10	0
P4	10	0	20	20	10
P1	15	0	35	35	20
P0	25	0	60	60	35
P3	25	0	85	85	60
P5	25	0	110	110	85
Average				53.3333	35.000000

Smt. Chandibai Himathmal Mansukhani College

P2	P4	P1	P0	P3	P5	
0	10	20	35	60	85	110

Example 4: Consider the following example contain five processes arrive at same time .

Process Id	Burst Time
P0	7
P1	3
P2	2
P3	10
P4	8

Step 4: After scheduling of all provided processes.

Process id	Burst time	Arrival time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time- Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P2	2	0	2	2	0
P1	3	0	5	5	2
P0	7	0	12	12	5

Smt. Chandibai Himathmal Mansukhani College

P4	8	0	20	20	12
P3	10	0	30	30	20
Average				13.80000	7.800000

P2	P1	P0	P4	P3	
0	2	5	12	20	30

Smt. Chandibai Himathmal Mansukhani College

Implementation:-

//Name: Yash Patil

//Batch:B2

//PRN: 2020016400809191

//Date:24/7/2021

//Prac-02: SJF(with no preemption)Algorithm

import java.util.Scanner;

public class P2_SJF_YP

{

int burstTime[];

int arrivalTime[]={0};

String[] processId;

int numberOfProcess;

void getProcessData(Scanner input){

System.out.println("enter the number of process for Scheduling:");

int inputNumberOfProcess=input.nextInt();

numberOfProcess=inputNumberOfProcess;

burstTime=new int[numberOfProcess];

arrivalTime=new int[numberOfProcess];

processId=new String[numberOfProcess];

String st="p";

for(int i=0;i < numberOfProcess;i++){

processId[i]=st.concat(Integer.toString(i));

System.out.print("enter the burst time for process-"+(i)+" :");

burstTime[i]=input.nextInt();

Smt. Chandibai Himathmal Mansukhani College

```
}  
}  
  
void sortAccordingBurstTime(int[] at,int[] bt,String[] pid){  
    boolean swapped;  
    int temp;  
    String stemp;  
    for (int i=0;i<numberOfProcess;i++){  
        swapped=false;  
        for (int j = 0;j<numberOfProcess-i-1;j++){  
            if(bt[j]>bt[j+1]){  
                temp=bt[j];  
                bt[j]=bt[j+1];  
                bt[j+1]=temp;  
                temp=at[j];  
                at[j]=at[j+1];  
                at[j+1]=temp;  
                stemp=pid[j];  
                pid[j]=pid[j+1];  
                pid[j+1]=stemp;  
                swapped=true;  
            }  
        }  
        if(swapped==false){  
            break;  
        }  
    }  
  
    void shortestJobFirstNPAlgorithm(){  
        int finishTime[]=new int[numberOfProcess];  
        int bt[]=burstTime.clone();
```

Smt. Chandibai Himathmal Mansukhani College

```
int at[]=arrivalTime.clone();
String pid[]=processId.clone();
int waitingTime[]=new int[numberOfProcess];
int turnAroundTime[]=new int[numberOfProcess];
sortAccordingBurstTime(at,bt,pid);
finishTime[0]=at[0]+bt[0];
turnAroundTime[0]=finishTime[0]-at[0];
waitingTime[0]=turnAroundTime[0]-bt[0];
for(int i=1;i<numberOfProcess;i++){
    finishTime[i]=bt[i]+finishTime[i-1];
    turnAroundTime[i]=finishTime[i]-at[i];
    waitingTime[i]=turnAroundTime[i]-bt[i];
}
float sum=0;
for(int n:waitingTime){
    sum+=n;
}
float averageWaitingTime=sum/numberOfProcess;
sum=0;
for(int n:turnAroundTime){
    sum+=n;
}
float averageTurnAroundTime=sum/numberOfProcess;
System.out.println("SJF (with no preemption) Scheduling Algorithm :");
System.out.format("%20s%20s%20s%20s%20s%20s\n","ProcessId","BurstTime"
,"ArrivalTime","FinishTime","TurnAroundTime","WaitingTime");
for(int i=0;i<numberOfProcess;i++){
    System.out.format("%20s%20d%20d%20d%20d%20d\n",pid[i],bt[i],at[i]
,finishTime[i],turnAroundTime[i],waitingTime[i]);
}
```

Smt. Chandibai Himathmal Mansukhani College

```
System.out.format("%8s%20f%20f\n",  
"Average",averageTurnAroundTime,averageWaitingTime);  
  
}  
  
public static void main(String[] args){  
Scanner input=new Scanner(System.in);  
P2_SJF_YP obj=new P2_SJF_YP();  
obj.getProcessData(input);  
obj.shortestJobFirstNPAlgorithm();  
}  
}
```


Smt. Chandibai Himathmal Mansukhani College

Input:-

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>javac P2_SJF_YP.java
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>java P2_SJF_YP
enter the number of process for Scheduling:
5
enter the burst time for process-0:3
enter the burst time for process-1:3
enter the burst time for process-2:4
enter the burst time for process-3:6
enter the burst time for process-4:8
```

Output.

```
SJF (with no preemption) Scheduling Algorithm :
ProcessId      BurstTime      ArrivalTime      FinishTime      TurnAroundTime      WatingTime
p0              3              0                3                3                0
p1              3              0                6                6                3
p2              4              0               10               10               6
p3              6              0               16               16              10
p4              8              0               24               24              16
Average              11.800000              7.000000

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>
```

Sample Output – 01

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>javac P2_SJF_YP.java

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>java P2_SJF_YP
enter the number of process for Scheduling:
5
enter the burst time for process-0:3
enter the burst time for process-1:3
enter the burst time for process-2:4
enter the burst time for process-3:6
enter the burst time for process-4:8
SJF (with no preemption) Scheduling Algorithm :

```

ProcessId	BurstTime	ArrivalTime	FinishTime	TurnAroundTime	WaitingTime
p0	3	0	3	3	0
p1	3	0	6	6	3
p2	4	0	10	10	6
p3	6	0	16	16	10
p4	8	0	24	24	16
		Average		11.800000	7.000000

```
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>
```

Sample Output – 02

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>javac P2_SJF_YP.java

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>java P2_SJF_YP
enter the number of process for Scheduling:
5
enter the burst time for process-0:7
enter the burst time for process-1:3
enter the burst time for process-2:2
enter the burst time for process-3:10
enter the burst time for process-4:8
SJF (with no preemption) Scheduling Algorithm :

```

ProcessId	BurstTime	ArrivalTime	FinishTime	TurnAroundTime	WaitingTime
p2	2	0	2	2	0
p1	3	0	5	5	2
p0	7	0	12	12	5
p4	8	0	20	20	12
p3	10	0	30	30	20
		Average	13.800000	7.800000	

```
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>
```

Sample Output-03

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>javac P2_SJF_YP.java
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>java P2_SJF_YP
enter the number of process for Scheduling:
6
enter the burst time for process-0:25
enter the burst time for process-1:15
enter the burst time for process-2:10
enter the burst time for process-3:25
enter the burst time for process-4:10
enter the burst time for process-5:25
SJF (with no preemption) Scheduling Algorithm :
  ProcessId      BurstTime  ArrivalTime  FinishTime  TurnAroundTime  WatingTime
    p2           10         0             10          10             0
    p4           10         0             20          20             10
    p1           15         0             35          35             20
    p0           25         0             60          60             35
    p3           25         0             85          85             60
    p5           25         0            110         110             85
              Average      53.333332      35.000000

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>
```

Smt. Chandibai Himathmal Mansukhani College

Sample Output-04

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>javac P2_SJF_YP.java

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>java P2_SJF_YP
enter the number of process for Scheduling:
3
enter the burst time for process-0:2
enter the burst time for process-1:1
enter the burst time for process-2:6
SJF (with no preemption) Scheduling Algorithm :
  ProcessId      BurstTime      ArrivalTime      FinishTime      TurnAroundTime      WaitingTime
    p1           1             0                1                1                0
    p0           2             0                3                3                1
    p2           6             0                9                9                3
              Average          4.333333          1.333333

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 02 23-07-2021\Q2_ReaderWriter_YP>
```