

# **Smt. Chandibai Himathmal Mansukhani College**

## Contents

<b>USCS3P01:USCS303 – Operating System (OS) Practical_01 .....</b>	<b>2</b>
<b>Practical – 01 : First Come First Serve (FCFS) Algorithm .....</b>	<b>2</b>
<b>Practical Date : - 16 / 07 /2021 .....</b>	<b>2</b>
<b>Practical Aim :- Implement FCFS Scheduling Algorithm in Java .....</b>	<b>2</b>
<b>Algorithm :- .....</b>	<b>3</b>
<b>Gantt Chart :- .....</b>	<b>6</b>
<b>Implementation :- .....</b>	<b>9</b>
<b>Input :- .....</b>	<b>12</b>
<b>Output :- .....</b>	<b>13</b>
<b>Sample Output – 01 :- .....</b>	<b>14</b>
<b>Sample Output – 02 :- .....</b>	<b>15</b>
<b>Sample Output – 03 :- .....</b>	<b>16</b>
<b>Sample Output 04 :- .....</b>	<b>17</b>

## **USCS3P01:USCS303 – Operating System (OS) Practical\_01**

### **Practical – 01 : First Come First Serve (FCFS) Algorithm**

Practical Date :- 16/ 07 /2021

Practical Aim :- Implement FCFS Scheduling Algorithm in Java

CPU Scheduling algorithms are used for scheduling different processes present in the ready queue with available resources(CPU cores) in an optimal way so that each and every process get executed by CPU.

Scheduling algorithms are broadly classified into two main types name Preemptive and Non-preemptive. First Come First Service (FCFS) is a Non-preemptive Scheduling algorithm where each process is executed according to its arrival time.

First Come First Serve (FCFS) is also know as First In First Out (FIFO) scheduling algorithm is the easiest and simplest CPU scheduling algorithm where the process which arrives first in the ready queue is executed first by the CPU.

New process is executed only when the current process is executed fully by the CPU

# **Smt. Chandibai Himathmal Mansukhani College**

## **Algorithm :-**

### **In Algorithm we need to know :**

- $\text{Finish Time} = \text{Previous Process Finish Time} + \text{Burst Time}$
- $\text{Turn Around Time} = \text{Finish Time} - \text{Arrival Time}$
- $\text{Waiting Time} = \text{Turn Around Time} - \text{Burst time}$

### **FCFS Algorithm :**

**Step 1 :** Input the number of processes required to be scheduled using FCFS , burst time for each process and its arrival time .

**Step 2 :** Using enhanced bubble sort technique , sort the all given processes in ascending order according to arrival time in a ready queue.

**Step 3 :** Calculate the Finish time , Turn Around Time and Waiting Time for each process which in turn help to calculate Average Waiting Time and Average Turn Around Time required by CPU to schedule given set of process using FCFS.

**Step 3.1 :** For  $i = 0$ ,  $\text{Finish Time } T_0 = \text{Arrival Time } T_0 + \text{Burst Time } T_0$

**Step 3.2 :** For  $i \geq 1$ ,  $\text{Finish Time } T_i = \text{Burst Time } T_i + \text{Finish Time } T_{i-1}$

**Step 3.3 :** For  $i = 0$ ,  $\text{Turn Around Time } T_0 = \text{Finish Time } T_0 - \text{Arrival Time } T_0$

**Step 3.4 :** For  $i = 1$ ,  $\text{Turn Around Time } T_i = \text{Finish Time } T_i - \text{Arrival Time } T_i$

**Step 3.5 :** For  $i = 0$ ,  $\text{Waiting Time } T_0 = \text{Turn Around Time } T_0 - \text{Burst Time } T_0$

**Step 3.6 :** For  $i = 1$ ,  $\text{Waiting Time } T_i = \text{Turn Around Time } T_i - \text{Burst Time } T_{i-1}$

**Step 4 :** Process with less arrival time comes first and gets scheduled first by the CPU.

**Step 5 :** Calculate the Average Waiting Time and Average Turn Around Time.

**Step 6 :** Stop.

# **Smt. Chandibai Himathmal Mansukhani College**

## **Solved Example :-**

**Example 1 :-** Consider the following example containing five processes arrive at same time.

Process ID	Burst Time
P0	6
P1	3
P2	8
P3	3
P4	4

**Step 1 :** Processes get executed according to their arrival time.

**Step 2 :** Following Shows the scheduling and execution of processes.

**Step 2.1 :** At start P0 arrives and get executed for 6 (i.e; 0 – 6 ) seconds.

Process ID	Burst Time
P0	6
P1	3
P2	8
P3	3
P4	4

**Step 2.2 :** P1 arrives after completion of P0 , P1 is executed for 3 (i.e; 6 – 9 )

Seconds.

System Time	:	0
Process Scheduled	:	P0
Waiting Time	:	$0 + 0 = 0$
Turn Around Time	:	$0 + 6 = 6$

**Step 2.2:** P1 arrives after completion of P0,P1 is executed for 3 (i.e; 6 – 9) seconds.

# Smt. Chandibai Himathmal Mansukhani College

System Time	:	6
Process Scheduled	:	P0, P1
Waiting Time	:	$6 + 0 = 6$
Turn Around Time	:	$3 + 6 = 9$

**Step 2.3:** P2 arrives after complete execution of process P1, for 8 (i.e;  $9 - 17$ ) seconds

System Time	:	17
Process Scheduled	:	P0, P1, P2, P3
Waiting Time	:	$8 + 9 = 17$
Turn Around Time	:	$3 + 17 = 20$

**Step 2.4:** P3 arrives and gets executed for 3 (i.e;  $17 - 20$ ) seconds.

System Time	:	17
Process Scheduled	:	P0, P1, P2, P3
Waiting Time	:	$8 + 9 = 17$
Turn Around Time	:	$3 + 17 = 20$

**Step 2.5:** Similarly, P4 arrives and gets executed for 4 (i.e;  $20 - 24$ ) seconds.

System Time	:	20
Process Scheduled	:	P0, P1, P2, P3, P4
Waiting Time	:	$3 + 17 = 20$
Turn Around Time	:	$4 + 20 = 24$

**Step 3:** Calculate Average Waiting and Average Turn Around Time

**Average Waiting Time**  $= (0 + 6 + 9 + 17 + 20) / 5 = 52 / 5 = 10.4$

**Average Turn Around Time**  $= (6 + 9 + 17 + 20 + 24) / 5 = 76 / 5 = 15.2$

**Step 4:** After scheduling of all provided processes:

Process ID	Burst Time	Arrival Time	Finish Time	Turn Around Time	Waiting Time
P0	6	0	$(-+6=)6$	$(6-0=)6$	$(6-6=)0$
P1	3	0	$(6+3=)9$	$(9-0=)9$	$(9-3=)6$
P2	8	0	$(9+8=)17$	$(17-0=)17$	$(17-8=)9$
P3	3	0	$(17+3=)20$	$(20-0=)20$	$(20-3=)17$
P4	4	0	$(20+4=)24$	$(24-0=)24$	$(24-4=)20$
<b>Average</b>				15.200000	10.400000

**Step 5:** Stop

# Smt. Chandibai Himathmal Mansukhani College

Gnatt Chart :-

P0	P1	P2	P3	P4	
0	6	9	17	20	24

**Example 2 :-** Consider the Following example containing five processes with varied arrival time.

Process ID	Burst Time	Arrival Time
P0	6	2
P1	3	5
P2	8	1
P3	3	0
P4	4	4

**Solution:-**

Process ID	Burst Time	Arival Time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time-Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P3	3	0	3	3	0
P2	8	1	11	10	2
P0	6	2	17	15	9
P4	4	4	21	17	13
P1	3	5	24	19	16
Average				12.800000	8.000000

P0	P1	P2	P3	P4	
0	3	11	17	21	24

# Smt. Chandibai Himathmal Mansukhani College

## Example:03

Consider the following example containing five processes arrive at same time.

Process ID	Burst Time	Arrival Time
P0	2	2
P1	1	5
P2	6	1

Solution:

Process ID	Burst Time	Arival Time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time-Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P0	2	0	2	2	0
P1	1	0	3	3	2
P2	6	0	9	9	3
Average				4.66667	1.66667

P0	P1	P2	
0	2	3	9

## Example:04

Consider the following example containing five processes with varied arrival time.

Process ID	Burst Time	Arrival Time
P0	4	3
P1	3	5
P2	2	0
P3	1	5
P4	3	4

# Smt. Chandibai Himathmal Mansukhani College

**Solution:**

Process ID	Burst Time	Arival Time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time-Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P2	2	0	2	2	0
P0	4	3	6	3	-1
P4	3	4	9	5	2
P1	3	5	12	7	4
P3	1	5	13	8	7
Average				5.000000	2.400000

P0	P1	P2	P3	P4	
0	2	6	9	12	13



# **Smt. Chandibai Himathmal Mansukhani College**

---

## **Implementation :-**

```
import java.util.Scanner;

public class P1_FCFS_YP
{
    int burstTime[];
    int arrivalTime[];
    String[] processId;
    int numberOfProcess;

    void getProcessData(Scanner input){
        System.out.println("enter the number of process for Scheduling:");
        int inputNumberOfProcess=input.nextInt();
        numberOfProcess=inputNumberOfProcess;
        burstTime=new int[numberOfProcess];
        arrivalTime=new int[numberOfProcess];
        processId=new String[numberOfProcess];
        String st="p";
        for(int i=0;i < numberOfProcess;i++){
            processId[i]=st.concat(Integer.toString(i));
            System.out.print("enter the burst time for process-"+(i)+":");
            burstTime[i]=input.nextInt();
            System.out.println("enter the arrival time for process-"+(i)+":");
            arrivalTime[i]=input.nextInt();
        }
    }

    void sortAccordingArrivalTime(int[] at,int[] bt,String[] pid){
        boolean swapped;
        int temp;
        String stemp;

        for (int i=0;i<numberOfProcess;i++){
            swapped=false;
```

# **Smt. Chandibai Himathmal Mansukhani College**

```
for (int j = 0;j<numberOfProcess-i-1;j++){
    if(at[j]>at[j+1]){
        temp=at[j];
        at[j]=at[j+1];
        at[j+1]=temp;
        temp=bt[j];
        bt[j]=bt[j+1];
        bt[j+1]=temp;
        stemp=pid[j];
        pid[j]=pid[j+1];
        pid[j+1]=stemp;
        swapped=true;
    }
}
if(swapped==false){
    break;
}
}

void firstComeFirstServeAlgorithm(){
    int finishTime[]=new int[numberOfProcess];
    int bt[]=burstTime.clone();
    int at[]=arrivalTime.clone();
    String pid[]=processId.clone();
    int waitingTime[]=new int[numberOfProcess];
    int turnAroundTime[]=new int[numberOfProcess];
    sortAccordingArrivalTime(at,bt,pid);
    finishTime[0]=at[0]+bt[0];
    turnAroundTime[0]=finishTime[0]-at[0];
    waitingTime[0]=turnAroundTime[0]-bt[0];
    for(int i=1;i<numberOfProcess;i++){
```

# **Smt. Chandibai Himathmal Mansukhani College**

```
finishTime[i]=bt[i]+finishTime[i-1];
turnAroundTime[i]=finishTime[i]-at[i];
waitingTime[i]=turnAroundTime[i]-bt[i];
}
float sum=0;
for(int n:waitingTime){
sum+=n;
}
float averageWaitingTime=sum/numberOfProcess;
sum=0;
for(int n:turnAroundTime){
sum+=n;
}
float averageTurnAroundTime=sum/numberOfProcess;
System.out.println("FCFS Scheduling algorithm :");
System.out.format("% 20s% 20s% 20s% 20s% 20s% 20s\n", "ProcessId", "BurstTime"
, "ArrivalTime", "FinishTime", "TurnAroundTime", "WaitingTime");
for(int i=0;i<numberOfProcess;i++){
System.out.format("% 20s% 20d% 20d% 20d% 20d% 20d\n", pid[i], bt[i], at[i]
, finishTime[i], turnAroundTime[i], waitingTime[i]);
}
System.out.format("% 80s% 20f% 20f\n", "Average", averageTurnAroundTime, averageWaitingTime);
}
public static void main(String[] args){
Scanner input=new Scanner(System.in);
P1_FCFS_YP obj=new P1_FCFS_YP();
obj.getProcessData(input);
obj.firstComeFirstServeAlgorithm();
}
}
```

# **Smt. Chandibai Himathmal Mansukhani College**

Input :-

Enter the number of process for scheduling:5

Enter the burst time for Process0:

Enter the arrival time for Process0:

Enter the burst time for Process1:

Enter the arrival time for Process1:

Enter the burst time for Process2:

Enter the arrival time for Process2:

Enter the burst time for Process3:

Enter the arrival time for Process3:

Enter the burst time for Process4:

Enter the arrival time for  
Process4:

# Smt. Chandibai Himathmal Mansukhani College

Output :-

Process ID	Burst Time	Arival Time	Finish Time (Prev.Finish Time + Burst Time)	Turn Around Time (Finish Time-Arrival Time)	Waiting Time (Turn Around Time-Burst Time)
P3	3	0	3	3	0
P2	8	1	11	10	2
P0	6	2	17	15	9
P4	4	4	21	17	13
P1	3	5	24	19	16
Average				12.800000	8.000000

## Sample Output – 01 :-

```
Command Prompt
C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>javac P1_FCFS_YP.java
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>java P1_FCFS_YP
enter the number of process for Scheduling:
5
enter the burst time for process-0:6
enter the arrival time for process-0:
0
enter the burst time for process-1:3
enter the arrival time for process-1:
0
enter the burst time for process-2:8
enter the arrival time for process-2:
0
enter the burst time for process-3:3
enter the arrival time for process-3:
0
enter the burst time for process-4:4
enter the arrival time for process-4:
0
FCFS Scheduling algorithm :
  ProcessId      BurstTime      ArrivalTime      FinishTime      TurnAroundTime      WatingTime
    p0           6             0                6                6                0
    p1           3             0                9                9                6
    p2           8             0               17               17                9
    p3           3             0               20               20               17
    p4           4             0               24               24               20
                        Average          15.200000          10.400000
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>
```

## Sample Output – 02 :-

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_05_B2\Pratical 01 16_07_2021\Q2_ReaderWriter_YP
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_05_B2\Pratical 01 16_07_2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_05_B2\Pratical 01 16_07_2021\Q2_ReaderWriter_YP>javac P1_FCFS_YP.java
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_05_B2\Pratical 01 16_07_2021\Q2_ReaderWriter_YP>java P1_FCFS_YP
enter the number of process for Scheduling:
5
enter the burst time for process-0:3
enter the arrival time for process-0:
0
enter the burst time for process-1:8
enter the arrival time for process-1:
1
enter the burst time for process-2:6
enter the arrival time for process-2:
2
enter the burst time for process-3:4
enter the arrival time for process-3:
4
enter the burst time for process-4:3
enter the arrival time for process-4:
5
FCFS Scheduling algorithm :
  ProcessId      BurstTime      ArrivalTime      FinishTime      TurnAroundTime      WatingTime
    p0           3             0                3                3                0
    p1           8             1               11               10                2
    p2           6             2               17               15                9
    p3           4             4               21               17               13
    p4           3             5               24               19               16
                    Average          12.800000          8.000000

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_05_B2\Pratical 01 16_07_2021\Q2_ReaderWriter_YP>
```

# Smt. Chandibai Himathmal Mansukhani College

## Sample Output – 03 :-

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USC53P01_USC5303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP
C:\Yash Patil\OS\Java files\USC53P01_USC5303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"
C:\Yash Patil\OS\Java files\USC53P01_USC5303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>javac P1_FCFS_YP.java
C:\Yash Patil\OS\Java files\USC53P01_USC5303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>java P1_FCFS_YP
enter the number of process for Scheduling:
3
enter the burst time for process-0:2
enter the arrival time for process-0:
0
enter the burst time for process-1:1
enter the arrival time for process-1:
0
enter the burst time for process-2:6
enter the arrival time for process-2:
0
FCFS Scheduling algorithm :
  ProcessId      BurstTime      ArrivalTime      FinishTime      TurnAroundTime      WatingTime
    p0           2             0                2                2                0
    p1           1             0                3                3                2
    p2           6             0                9                9                3
      Average          4.666667          1.666667

C:\Yash Patil\OS\Java files\USC53P01_USC5303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>
```



# Smt. Chandibai Himathmal Mansukhani College

## Sample Output 04 :-

```
Command Prompt
Microsoft Windows [Version 10.0.19042.1165]
(c) Microsoft Corporation. All rights reserved.

C:\Users\yashp>cd C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>set path="C:\Program Files\Java\jdk-16.0.2\bin"
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>javac P1_FCFS_YP.java
C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>java P1_FCFS_YP
enter the number of process for Scheduling:
5
enter the burst time for process-0:2
enter the arrival time for process-0:
0
enter the burst time for process-1:4
enter the arrival time for process-1:
3
enter the burst time for process-2:3
enter the arrival time for process-2:
4
enter the burst time for process-3:3
enter the arrival time for process-3:
5
enter the burst time for process-4:1
enter the arrival time for process-4:
5
FCFS Scheduling algorithm :
  ProcessId      BurstTime      ArrivalTime      FinishTime      TurnAroundTime      WatingTime
    p0           2             0                2                2                0
    p1           4             3                6                3               -1
    p2           3             4                9                5                2
    p3           3             5               12                7                4
    p4           1             5               13                8                7
                    Average          5.000000          2.400000

C:\Yash Patil\OS\Java files\USCS3P01_USCS303_OS_B2\Practical 01 16_07_2021\Q2_ReaderWriter_YP>
```