YASH RAJ AGARWAL Quick Revision

Slides 1–6; target approximately 4.5 minutes.

Motivation; objective; four verified sources and literature gap; actual architecture; synthetic data and grouping.

200 synthetic CSV rows; 40 duplicate rows removed; 160 unique examples (80 human-style, 80 AI-style); 20 synthetic problem groups; 96 training, 32 validation, 32 test samples.

Models: Logistic Regression, Decision Tree, Random Forest. Selected: Logistic Regression. Test metrics: all four 1.000; confusion matrix [[16,0],[0,16]]. Both labels are synthetic style categories written into a generator, not verified human or LLM provenance. The 20 group IDs vary a few filtering templates and do not represent 20 independent algorithmic tasks. Perfect scores describe template separation only.

What does this project actually classify?
Synthetic code-style labels. The generator assigns human and ai strings to templates. Neither label proves actual provenance.

How many records are used?
160 unique examples from 200 rows. Forty exact duplicates are removed after stripping boundary whitespace.

What is group splitting?
Keeping related records in one partition. GroupShuffleSplit keeps each problem_id exclusively in training, validation or test.

Are there 20 independent tasks?
No. The IDs reuse a few filter templates with naming and modulus variants.

Demonstration recovery
Start backend with .venv\Scripts\python.exe -m uvicorn backend.main:app and frontend with npm run dev --prefix frontend. If startup fails, show the captured real screenshots and experiment CSV. Never invent a live result.