AMAN SHARMA Quick Revision

Slides 13–18; target approximately 4.5 minutes.

API request flow; real screenshots; eight experiments; outputs; reliability limits; future data protocol.

200 synthetic CSV rows; 40 duplicate rows removed; 160 unique examples (80 human-style, 80 AI-style); 20 synthetic problem groups; 96 training, 32 validation, 32 test samples.

Models: Logistic Regression, Decision Tree, Random Forest. Selected: Logistic Regression. Test metrics: all four 1.000; confusion matrix [[16,0],[0,16]]. Both labels are synthetic style categories written into a generator, not verified human or LLM provenance. The 20 group IDs vary a few filtering templates and do not represent 20 independent algorithmic tasks. Perfect scores describe template separation only.

What happens on Analyze?
React posts JSON, FastAPI validates, saved inference returns JSON. The fitted transformer and classifier run; training and source execution do not.

What is feature ablation?
Removing feature groups and retraining. Validation comparisons reveal conditional reliance, though this trivial fixture gives identical class metrics.

Does the factorial probe prove generalization?
No. It is one unlabeled unseen task, so accuracy cannot be computed.

What if a human writes a docstring?
The model may raise the AI score. Docstrings are a synthetic class cue here; this is an example of why false accusations are possible.

Demonstration recovery
Start backend with .venv\Scripts\python.exe -m uvicorn backend.main:app and frontend with npm run dev --prefix frontend. If startup fails, show the captured real screenshots and experiment CSV. Never invent a live result.