

ASSIGNMENT 4

```
mysql> use placement;
```

Database changed

QUES 1:

```
mysql> select count(distinct job) as Number_of_Jobs from employees;
```

1 row in set (0.01 sec)

Number_of_Jobs
3

QUES 2:

```
mysql> select sum(salary) as Total_Payable_Salary from employees;
```

1 row in set (0.00 sec)

Total_Payable_Salary
532000

QUES 3:

```
mysql> select min(salary) as Minimum_Salary from employees;
```

1 row in set (0.00 sec)

Minimum_Salary
42000

QUES 4:

```
mysql> select max(salary) as Maximum_Salary_of_Programmer from employees where  
job='Programmer';
```

ASSIGNMENT 4

1 row in set (0.00 sec)

Maximum_Salary_of_Programmer
60000

QUES 5:

```
mysql> select avg(salary) as average_salary,count(*) as number_of_employees from  
employees where department_id=90;
```

1 row in set (0.00 sec)

average_salary	number_of_employees
75000.0000	1

QUES 6:

```
mysql> select max(salary) as highest_salary, min(salary) as lowest_salary,sum(salary) as  
total_salary,round(avg(salary),2) as average_salary from employees;
```

1 row in set (0.00 sec)

highest_salary	lowest_salary	total_salary	average_salary
75000	42000	532000	53200.00

QUES 7:

```
mysql> select job,count(*) from employees group by job;
```

4 rows in set (0.00 sec)

ASSIGNMENT 4

job	count(*)
Programmer	4
Manager	3
Data Analyst	3
NULL	4

QUES 8:

```
mysql> select max(salary)-min(salary) as salary_difference from employees ;
```

1 row in set (0.00 sec)

salary_difference
33000

QUES 9:

```
mysql> select manager_id, min(salary) as lowest_salary from employees where  
manager_id is not null group by manager_id order by lowest_salary asc;
```

manager_id	lowest_salary
1003	42000
1002	45000
1007	47000
1004	48000
1001	50000
1008	52000
1005	55000
1010	58000
1006	60000
1009	75000

ASSIGNMENT 4

QUES 10:

```
mysql> select department_id ,sum(salary) from employees group by department_id;
```

11 rows in set (0.00 sec)

10 rows in set (0.00 sec)

department_id	sum(salary)
NULL	NULL
10	50000
20	45000
30	42000
40	48000
50	55000
60	60000
70	47000
80	52000
90	75000
100	58000

QUES 11:

```
mysql> select job,round(avg(salary),2) from employees where job not in ('Programmer')  
group by job;
```

2 rows in set (0.00 sec)

job	round(avg(salary),2)
Manager	58333.33
Data Analyst	49000.00

QUES 12:

ASSIGNMENT 4

```
mysql> select min(salary),max(salary),sum(salary),avg(salary) from employees where  
department_id='90' order by job_id;
```

1 row in set (0.00 sec)

min(salary)	max(salary)	sum(salary)	avg(salary)
75000	75000	75000	75000.0000

QUES 13:

```
mysql> select job_id,max(salary) as maximum_salary from employees group by job_id  
having max(salary)>=4000;
```

10 rows in set (0.00 sec)

job_id	maximum_salary
101	50000
102	45000
103	42000
104	48000
105	55000
106	60000
107	47000
108	52000
109	75000
110	58000

QUES 14:

```
select department_id,avg(salary) as average_salary,count(*) as employee_count from  
employees group by department_id having count(*) > 10;
```

2 rows in set (0.00 sec)

ASSIGNMENT 4

department_id	average_salary	employee_count
NULL	NULL	2
20	45000.0000	2