

CSS Properties Introduced After 2025

1. animation-timeline

Syntax: `animation-timeline: scroll();`

Purpose: Links animation progress to scroll position.

Use Case: Scroll-based animations, reveal effects, storytelling UI.

Example:

```
.box {  
  animation: fade 1s linear;  
  animation-timeline: scroll();  
}
```

Browser Support: Chrome, Edge, partial Safari

Reference: Scroll-Linked Animations Specification

2. text-box-trim

Syntax: `text-box-trim: both;`

Purpose: Removes extra vertical spacing around text.

Use Case: Clean typography and precise alignment.

Example:

```
h1 { text-box-trim: both; }
```

Browser Support: Chrome, Edge

Reference: CSS Inline Layout

3. text-box-align

Syntax: `text-box-align: center;`

Purpose: Controls vertical alignment of trimmed text.

Use Case: Precise text layout in headings.

Example:

```
h1 { text-box-align: center; }
```

Browser Support: Chrome

Reference: CSS Inline Layout

4. text-box

Syntax: `text-box: trim-both;`

Purpose: Controls text box spacing and trimming.

Use Case: Typography control in UI design.

Example:

```
p { text-box: trim-both; }
```

Browser Support: Chrome

Reference: CSS Text Module

5. anchor-name

Syntax: `anchor-name: --anchor;`

Purpose: Defines an anchor element for positioning.

Use Case: Tooltips, dropdowns, floating UI.

Example:

```
button { anchor-name: --btn; }
```

Browser Support: Chrome, Safari
Reference: Anchor Positioning Spec

6. position-anchor

Syntax: `position-anchor: --btn;`
Purpose: Positions element relative to anchor.
Use Case: Popovers and contextual menus.
Example:

```
.tooltip { position-anchor: --btn; }
```

Browser Support: Chrome, Safari
Reference: Anchor Positioning

7. anchor()

Syntax: `top: anchor(bottom);`
Purpose: Reads anchor position coordinates.
Use Case: Dynamic positioning logic.
Example:

```
.tooltip { top: anchor(bottom); }
```

Browser Support: Chrome
Reference: Anchor Positioning

8. scrollbar-gutter

Syntax: `scrollbar-gutter: stable;`
Purpose: Prevents layout shift when scrollbar appears.

Use Case: Stable layouts in scrollable containers.

Example:

```
.box { scrollbar-gutter: stable; }
```

Browser Support: All major browsers

Reference: CSS Overflow Module

9. ::target-text

Syntax: ::target-text { }

Purpose: Styles highlighted linked text.

Use Case: Highlighting search or anchor links.

Example:

```
::target-text { background: yellow; }
```

Browser Support: Modern browsers

Reference: CSS Pseudo Elements

10. light-dark()

Syntax: background: light-dark(white, black);

Purpose: Automatic theme-based color switching.

Use Case: Dark mode support.

Example:

```
body { background: light-dark(#fff,#000); }
```

Browser Support: All modern browsers

Reference: CSS Color Module

11. Relative Color Syntax

Syntax: `color: hsl(from red h s 50%);`

Purpose: Modify colors dynamically.

Use Case: Theme systems and color transformations.

Example:

```
div { background: hsl(from blue h s 40%); }
```

Browser Support: Modern browsers

Reference: CSS Color Level 5

12. color-interpolation-method

Syntax: `color-interpolation-method: oklab;`

Purpose: Controls gradient blending method.

Use Case: Smooth and accurate gradients.

Example:

```
.grad { color-interpolation-method: oklab; }
```

Browser Support: Chrome

Reference: CSS Color 5

13. transition-behavior

Syntax: `transition-behavior: allow-discrete;`

Purpose: Enables transitions for discrete values.

Use Case: Animating visibility and state changes.

Example:

```
.box { transition-behavior: allow-discrete; }
```

Browser Support: Chrome
Reference: CSS Transitions Level 2

14. @starting-style

Syntax: @starting-style {}
Purpose: Defines initial transition state.
Use Case: Entry animations.
Example:

```
@starting-style {  
  .card { opacity: 0; }  
}
```

Browser Support: Chrome
Reference: CSS Transitions

15. field-sizing

Syntax: field-sizing: content;
Purpose: Auto sizes form inputs.
Use Case: Responsive form design.
Example:

```
input { field-sizing: content; }
```

Browser Support: Chrome
Reference: CSS UI Module

16. @scope

Syntax: @scope (.box) {}

Purpose: Limits style to specific area.

Use Case: Component styling.

Example:

```
@scope (.box) {  
  p { color:red; }  
}
```

Browser Support: Chrome, Firefox, Safari

Reference: CSS Cascade Level 6

17. interpolate-size

Syntax: interpolate-size: allow-keywords;

Purpose: Animates auto sizes.

Use Case: Expanding panels.

Example:

```
.box { interpolate-size: allow-keywords; }
```

Browser Support: Chrome

Reference: CSS Sizing Module

18. @property

Syntax: @property --x {}

Purpose: Defines typed custom properties.

Use Case: Safe CSS variables.

Example:

```
@property --color {  
  syntax: "<color>";  
  initial-value: red;  
}
```

Browser Support: All modern browsers
Reference: CSS Properties & Values API

19. align-content

Syntax: `align-content: center;`
Purpose: Vertical alignment in block layout.
Use Case: Layout control without flexbox.
Example:

```
.container { align-content: center; }
```

Browser Support: All modern browsers
Reference: CSS Box Alignment

20. content-visibility

Syntax: `content-visibility: auto;`
Purpose: Improves rendering performance.
Use Case: Large page optimization.
Example:

```
.section { content-visibility:auto; }
```

Browser Support: All major browsers
Reference: CSS Containment