

ASSINGMENT 9 – Documentation Generation -

Automatic documentation and code comments

Task Description :1 – Docstring , Inline comments , Google-style documentation

Task: Compare the three approaches. Discuss their advantages and disadvantages. Explain suitable use cases. Recommend the best documentation style for a mathematical utilities library

Prompt: Explain what the function does, describe the input parameter, and describe the return value. Keep the documentation simple and suitable for a beginner.

Input:

```
def find_max_docstring(numbers):
```

```
    """Return the maximum number from a list of numbers."""
```

```
    return max(numbers)
```

```
def find_max_inline(numbers):
```

```
    # Check and return the maximum value in the input list
```

```
    return max(numbers) # Built-in max function handles the comparison
```

```
def find_max_google(numbers):
```

```
    """Finds the maximum value in a list of numbers.
```

Args:

numbers (list of int/float): A list of numerical values to search.

Returns:

int/float: The largest number in the list.

Raises:

ValueError: If the input list is empty.

"""

if not numbers:

raise ValueError("The list of numbers cannot be empty.")

return max(numbers)

#example usage

numbers = [3, 5, 1, 8, 2]

print(find_max_docstring(numbers)) # Output: 8

print(find_max_inline(numbers)) # Output: 8

print(find_max_google(numbers)) # Output: 8

Explanation:

The purpose of this problem is to understand different ways of documenting Python code.

Output:

```
PS C:\Users\yashwanth\.vscode> python -u "C:\Users\yashwanth\.vscode\github\tempCodeRunnerFile.  
8  
8  
8  
PS C:\Users\yashwanth\.vscode>
```

Task Description :2 – Documentation for login()

Task: Write documentation using all three formats. Critically compare the approaches. Recommend which documentation style would be most useful for new developers joining a project.

Prompt : Generate a clear inline comment to the following Python function. The comment should explain what the function is doing without unnecessarily explaining obvious Python syntax.

```
def find_max(numbers):  
    return max(numbers)
```

Input:

```
def login_docstring(user, password, credentials):  
    """Verify if the provided password matches the stored password for the given user in  
    the credentials registry."""  
    return credentials.get(user) == password
```

```
def login_inline(user, password, credentials):  
    # Retrieve password for user and evaluate match  
    # Using .get() prevents KeyError if user is missing, returning None which safely  
    compares False  
    return credentials.get(user) == password
```

```
def login_google(user, password, credentials):
```

"""Authenticates a user against a provided credentials store.

Args:

user (str): The unique identifier/username of the user trying to log in.

password (str): The plain-text security password provided by the client.

credentials (dict): A dictionary mapping usernames (str) to their corresponding correct passwords (str).

Returns:

bool: True if the user exists and the password matches; False otherwise.

"""

```
return credentials.get(user) == password
```

#example usage

```
credentials = {'alice': 'password123', 'bob': 'securepass'}
```

```
print(login_docstring('alice', 'password123', credentials)) # Output: True
```

```
print(login_inline('alice', 'password123', credentials)) # Output: True
```

```
print(login_google('alice', 'password123', credentials)) # Output: True
```

Explanation:

This problem is similar to Problem 1, but the function represents a login/authentication operation.

Output:

```
PS C:\Users\yashwanth\.vscode> python -u "C:\Users\yashwanth\.vscode\github\tempCodeRunnerFi
True
True
True
PS C:\Users\yashwanth\.vscode>
```

Task Description :3 – Calculator Module

Task: Display the module documentation in the terminal. Generate the documentation as an HTML file using Python's pydoc. Open the generated HTML file in a browser and verify it methods.

Prompt: Generate Convert the following Python function into a properly documented Google-style function. Include a description, Args section, and Returns section.

```
def find_max(numbers):  
    return max(numbers)
```

Input:

```
"""A basic calculator module providing arithmetic operations with structured  
documentation.
```

```
"""
```

```
def add(a, b):
```

```
    """Returns the sum of two numbers.
```

Args:

a (int/float): The first number.

b (int/float): The second number.

Returns:

int/float: The sum of a and b.

```
"""
```

```
    return a + b
```

```
def subtract(a, b):
```

```
    """Returns the difference of two numbers.
```

Args:

a (int/float): The first number (minuend).

b (int/float): The second number (subtrahend).

Returns:

int/float: The difference of a and b.

```
    """
```

```
    return a - b
```

```
def multiply(a, b):
```

```
    """Returns the product of two numbers.
```

Args:

a (int/float): The first factor.

b (int/float): The second factor.

Returns:

int/float: The product of a and b.

```
    """
```

```
    return a * b
```

```
def divide(a, b):
```

```
"""Returns the quotient of two numbers.
```

Args:

a (int/float): The dividend.

b (int/float): The divisor.

Returns:

float: The quotient of a divided by b.

Raises:

ZeroDivisionError: If the divisor b is zero.

```
"""
```

```
if b == 0:
```

```
    raise ZeroDivisionError("Division by zero is not allowed.")
```

```
return a / b
```

```
#example usage
```

```
print(divide(10, 2)) # Output: 5.0
```

```
print(multiply(3, 4)) # Output: 12
```

```
print(subtract(10, 5)) # Output: 5
```

```
print(add(7, 3)) # Output: 10
```

Explanation:

This problem introduces automatic documentation generation.

Instead of manually creating a documentation website, Python's pydoc can read the docstrings from your program and generate documentation.

Output:

```
PS C:\Users\yashwanth\.vscode> python -u "C:\Users\yashwanth\.vscode\github\tempCodeRunnerFile.py"
PS C:\Users\yashwanth\.vscode> python -u "C:\Users\yashwanth\.vscode\github\tempCodeRunnerFile.py"
5.0
12
5
10
PS C:\Users\yashwanth\.vscode>
```

Task Description :4 – Conversion Utilities Module

Task: Use Copilot to automatically generate docstrings. Generate the documentation in the terminal. Export the documentation to HTML. Open the HTML documentation in a browser.

Prompt: Generate Compare docstrings, inline comments, and Google-style documentation for the following Python function:

```
def find_max(numbers):
```

```
    return max(numbers)
```

For each approach, explain:

1. Advantages
2. Disadvantages
3. Suitable use cases

Finally, recommend the most effective documentation style for a mathematical utilities library and justify your answer.

Input:

```
"""A conversion utility module providing functions to convert numbers between
decimal, binary, and hexadecimal bases.
```

```
"""
```

```
def decimal_to_binary(n):
```

```
    """Converts a decimal integer to its binary string representation.
```

Args:

n (int): The decimal integer to convert.

Returns:

str: The binary representation of the integer (prefixed with '0b').

Raises:

TypeError: If the input is not an integer.

"""

if not isinstance(n, int):

raise TypeError("Input must be an integer.")

return bin(n)

def binary_to_decimal(b):

"""Converts a binary string to its decimal integer representation.

Args:

b (str): The binary string to convert (can optionally start with '0b').

Returns:

int: The decimal integer value of the binary string.

Raises:

ValueError: If the input string is not a valid binary number.

TypeError: If the input is not a string.

"""

```
if not isinstance(b, str):  
    raise TypeError("Input must be a string.")  
return int(b, 2)
```

```
def decimal_to_hexadecimal(n):  
    """Converts a decimal integer to its hexadecimal string representation.
```

Args:

n (int): The decimal integer to convert.

Returns:

str: The lowercase hexadecimal representation of the integer (prefixed with '0x').

Raises:

TypeError: If the input is not an integer.

```
"""
```

```
if not isinstance(n, int):  
    raise TypeError("Input must be an integer.")  
return hex(n)
```

#example usage

```
print(decimal_to_binary(10)) # Output: '0b1010'  
print(binary_to_decimal('0b1010')) # Output: 10  
print(decimal_to_hexadecimal(255)) # Output: '0xff'
```

Explanation:

This problem combines programming + AI-assisted documentation + automatic documentation generation.

Output:

```
PS C:\Users\yashwanth\.vscode> python -u "C:\Users\yashwanth\.vscode\github\tempCodeRunnerFile.py"
0b1010
10
0xff
PS C:\Users\yashwanth\.vscode>
```

Task-5: Course Management Module

Prompt: Generate a Python module named `course.py` for a simple course management system.

Input:

```
"""A course management module providing utilities to add, remove, and retrieve course
details.
```

```
"""
```

```
# In-memory database to store course information
```

```
_course_db = {}
```

```
def add_course(course_id, name, credits):
```

```
    """Adds a new course to the registry.
```

Args:

course_id (str): The unique identifier for the course (e.g., 'CS101').

name (str): The name of the course.

credits (int): The number of academic credits for the course.

Raises:

ValueError: If the course_id already exists in the registry.

TypeError: If credits is not an integer or if course_id/name is not a string.

"""

```
if not isinstance(course_id, str) or not isinstance(name, str):
```

```
    raise TypeError("course_id and name must be strings.")
```

```
if not isinstance(credits, int):
```

```
    raise TypeError("credits must be an integer.")
```

```
if course_id in _course_db:
```

```
    raise ValueError(f"Course with ID {course_id} already exists.")
```

```
_course_db[course_id] = {
```

```
    "name": name,
```

```
    "credits": credits
```

```
}
```

```
def remove_course(course_id):
```

```
    """Removes an existing course from the registry.
```

Args:

course_id (str): The unique identifier of the course to be removed.

Raises:

KeyError: If the course_id is not found in the registry.

"""

```
if course_id not in _course_db:
```

```
        raise KeyError(f"Course with ID {course_id} does not exist.")
    del _course_db[course_id]
```

```
def get_course(course_id):
    """Retrieves the details of a specific course.
```

Args:

course_id (str): The unique identifier of the course to retrieve.

Returns:

dict: A dictionary containing the course 'name' and 'credits'.

Raises:

KeyError: If the course_id is not found in the registry.

```
"""
```

```
if course_id not in _course_db:
```

```
    raise KeyError(f"Course with ID {course_id} does not exist.")
```

```
    return _course_db[course_id]
```

#example usage

```
add_course('CS101', 'Introduction to Computer Science', 4)
```

```
print(get_course('CS101')) # Output: {'name': 'Introduction to Computer Science',
'credits': 4}
```

Explanation:

Review the course.py module and check whether the documentation for add_course(), remove_course(), and get_course() is complete and consistent.

Output:

```
p PS C:\Users\yashwanth\.vscode> python -u "C:\Users\yashwanth\.vscode\github\tempCodeRunnerFile.  
{'name': 'Introduction to Computer Science', 'credits': 4}  
PS C:\Users\yashwanth\.vscode>
```