3. Implement a java program to illustrate storing user defined classes in collection.

```
import java.util.*;

class Student {
   int id;
   String name;

   Student(int id, String name) {
      this.id = id;
      this.name = name;
   }
}

public class Demo {
   public static void main(String[] args) {

      ArrayList<Student> list = new ArrayList<>();

      Student s1 = new Student(1, "Deepak");
      Student s2 = new Student(2, "Rahul");

      list.add(s1);
      list.add(s2);

      for (Student s : list) {
         System.out.println(s.id + " " + s.name);
      }
   }
}
```

OUTPUT:

```
1 Deepak
2 Rahul
```

4. Implement a java program to illustrate the use of different types of string class constructors.

```
import java.lang.String;

public class StringConstructorDemo {
   public static void main(String[] args) {

       // 1. Empty String constructor

       String s1 = new String();
       System.out.println("s1 = " + s1);

       // 2. String from another string

       String s2 = new String("Hello");
       System.out.println("s2 = " + s2);

       // 3. String from character array

       char ch[] = {'J','A','V','A'};
       String s3 = new String(ch);
       System.out.println("s3 = " + s3);

       // 4. String from byte array

       byte b[] = {65,66,67};
       String s4 = new String(b);
       System.out.println("s4 = " + s4);
   }
}
```

OUTPUT:

```
s1 =
s2 = Hello
s3 = JAVA
s4 = ABC
```