Direction B — Provenance-routed hybrid (best-of-breed + WITNESS core)

User prompt
trusted

Agent LLM
proposes sink call f(args)

Context isolator
DRIFT-style: mask spans that conflict with the prompt

Tool outputs
untrusted

sink call

Provenance Router
prompt only (ROPE + AuthGraph planner): per sink arg -> lane 1..5

routes

Control Fence
IPIGuard / AuthGraph plan graph
undeclared tool or slot -> BLOCK

Counterfactual check (optional)
action-open tasks only ("do the to-do list in this file")
AttriGuard / AgentSentry replay, ~2x

1 User literal
value typed by user
deterministic match (ROPE prompt marker)

2 Trusted record
value from own records
deterministic match (ROPE record marker)

3 Delegated value
value read from a doc
WITNESS core: enumerate, eliminate, pin, confirm

4 Derived value
"the cheapest hotel"
typed Q-LLM, enum-bound (FIDES / CaMeL) + fact support (AuthorityFlow)

5 Free text
email body, message
capacity label (FIDES) + sanitiser (CausalArmor); no high-impact sink

per-argument verdicts

Call decision
all ALLOW -> run any BLOCK -> block otherwise ESCALATE

LLM veto (shared)
may only downgrade

ALLOW executes with canonical values

ESCALATE closed-choice confirm / ABSTAIN

BLOCK denial returned to agent (replan)

Per-argument label log -> two-sided LIS audit
same label schema as Direction A, plus the lane each argument was routed to

trusted input · untrusted input · novel (ours) · adopted from prior work · LLM, optional / veto-only