DO

Document Organizer

COPY-ONLY DOCUMENT RE-ORGANIZER

UAT TEST CASES

UAT Test Cases

User acceptance tests for local folders, Azure Blob Storage and Amazon S3

Document ID DO-UAT-06 · **Version** 2.1 · **Date** 22-Oct-2026

Prepared by Yasin Jariwala

Audience Testers, product owner, operations, cloud and security teams

Document control

Document	UAT Test Cases
Document ID	DO-UAT-06
Version	2.1
Date	22-Oct-2026
Prepared by	Yasin Jariwala
Product	Document Organizer v2.1
Audience	Testers, product owner, operations, cloud and security teams
Classification	Public
Source	github.com/yasin679/Document_Organizer · docs/uat-test-cases.md

Version history

Version	Date	Author	Changes
1.0	06-Oct-2026	Yasin Jariwala	First release
2.0	13-Oct-2026	Yasin Jariwala	General-purpose release: Amazon S3 and S3-compatible storage, copy between providers, container hosting; tenant ID field removed
2.1	22-Oct-2026	Yasin Jariwala	Several mapping files per job; File name cells listing several files split into one entry per file; NULL placeholders treated as blank; repeats of missing records reported as MISSING

Related documents

ID	Document
DO-UG-01	User Guide
DO-IG-02	Installation and Administration Guide
DO-QS-03	Quick Start
DO-FAQ-04	FAQ and Troubleshooting
DO-TD-05	Technical Design
DO-RN-07	Release Notes v2.1

Contents

1 Introduction 3
1.1 Purpose 3
1.2 How to use this document 3
1.3 Test environment 3
1.4 Priority 3
2 Installation and sign-in 4
3 Users and roles 4
4 Job creation 4
5 Mapping file and column mapping 5
6 Rules and scan 5
7 Review, resolve and approve 6
8 Processing and recovery 7
9 Reconciliation and audit 8
10 Cloud storage 8
11 Security and hosting 9
12 Defect log 9
13 Sign-off 9

1 Introduction

1.1 Purpose

These test cases confirm that Document Organizer v2.1 works on your own machines, in your own hosting, and against your own Azure and AWS accounts before it is used with real documents. They cover every screen, every status, all three storage types, copying between providers, security controls and recovery after interruption.

1.2 How to use this document

1. Set up the test environment in section 1.3.
2. Run the cases in order. Later cases reuse jobs created earlier.
3. Write P (pass) or F (fail) in the last column. For a fail, note the Job ID and what you saw in section 12 (Defect log).
4. Sign off in section 13 when all mandatory cases pass.

1.3 Test environment

Item	Value
Machine	The machine or hosting platform you will use in production
Application	Document Organizer v2.1, for example http://localhost:5080 or your HTTPS address
Users	`admin` (Administrator), `uat.operator` (Operator), `uat.viewer` (Viewer)
Local data	Demo data (Dashboard > **Load demo data**)
Azure test account	A non-production storage account with containers `uat-source` and `uat-organized`
Azure access	Tester's account or managed identity: Reader on `uat-source`, Contributor on `uat-organized`
AWS test account	A non-production account with buckets `uat-source-<suffix>` and `uat-organized-<suffix>` in your usual region
AWS access	An IAM user or role with the least-privilege policy from DO-IG-02 section 4.4
Storage connections	One `AzureBlob` and one `S3` connection pointing at the test accounts, secrets outside Git

> **Expected demo counts**
>
> The demo mapping file and files are built to give exactly: 472 files discovered, 471 mapping records, 458 READY, 7 UNMAPPED, 3 MISSING, 2 AMBIGUOUS, 2 DUPLICATE, 5 INVALID (validation errors). Many cases below check these numbers.

1.4 Priority

Priority	Meaning
M	Mandatory for go-live
H	High: fix before wide roll-out
L	Low: can be accepted with a workaround

2 Installation and sign-in

ID	Pri	Test	Steps	Expected result	P/F
UAT-01	M	Start with admin password	Start the application with `DOCORG_ADMIN_PASSWORD` set to a 12-character password (`start.cmd` prompt, `start.sh`, or container environment)	Console or container log shows "Now listening on ..."; sign-in page opens	
UAT-02	M	Health check	Open `/healthz` without signing in	`{"status":"ok"}`	
UAT-03	M	Admin sign-in	Sign in as `admin` with that password	Dashboard opens; audit log shows Login	
UAT-04	M	Wrong password lockout	Sign in as `uat.viewer` with a wrong password 5 times	5th attempt says the account is locked for 10 minutes	
UAT-05	H	Admin password reset by restart	Stop, start again with a new `DOCORG_ADMIN_PASSWORD`	New password works; old one fails	
UAT-06	H	Session timeout	Leave the app idle for 31 minutes, then click a menu	Sign-in page shown	
UAT-07	M	Change own password	**Settings > My password**, enter a weak then a strong password	Weak is refused with the policy message; strong is accepted	

3 Users and roles

ID	Pri	Test	Steps	Expected result	P/F
UAT-08	M	Add users	As admin, add `uat.operator` (Operator) and `uat.viewer` (Viewer)	Both listed as Active; audit shows User created	
UAT-09	M	Viewer is read-only	Sign in as `uat.viewer`	No **New processing job**, **Load demo data**, **Approve** or Settings changes available	
UAT-10	M	Operator cannot manage users	Sign in as `uat.operator`, open Settings	Users and roles section is not available	
UAT-11	H	Disable user	As admin, disable `uat.viewer`, try to sign in	Sign-in refused; re-enable restores access	

4 Job creation

ID	Pri	Test	Steps	Expected result	P/F
UAT-12	M	Demo data	As operator, Dashboard > **Load demo data**	Message confirms demo files and mapping file created	
UAT-13	M	Local job	**New job** > **Fill in local demo folders**, label `UAT local`, **Check access and create job**	Job created in Draft with an ID `JOB-YYYYMMDD-NNNN`; step 2 opens	
UAT-14	M	Destination inside source refused	New job with the destination folder inside the source folder	Error "Destination folder cannot be inside the source folder"; no job created	
UAT-15	M	Azure check access (read)	New job, source **Azure Blob Storage**, your connection, container `uat-source`, **Check access**	Green message: list and read access confirmed	
UAT-16	M	Azure check access (no rights)	Choose a container you have no role on, **Check access**	Red message explains the authorization problem	

ID	Pri	Test	Steps	Expected result	P/F
UAT-17	M	S3 check access (read)	New job, source **Amazon S3**, your connection, bucket `uat-source-<suffix>`, **Check access**	Green message: list and read access confirmed	
UAT-18	M	S3 check access (write)	Destination **Amazon S3**, bucket `uat-organized-<suffix>`, prefix `uat/`, **Check access**	Green message: write access confirmed; no test file left in the bucket	
UAT-19	H	S3 wrong region	Temporarily set the connection's `Region` to another region, restart, **Check access**	Red message names the bucket's real region	
UAT-20	H	Connection type filter	On **New job**, switch between Azure Blob Storage and Amazon S3	Each shows only connections of its own type; labels read Container and Bucket	

5 Mapping file and column mapping

ID	Pri	Test	Steps	Expected result	P/F
UAT-21	M	Upload mapping file	In job `UAT local`, step 2 > **Use demo mapping file**	Summary shows file name, rows and header row; first rows displayed	
UAT-22	H	Wrong file type	Upload a `.pdf` as the mapping file	Error "Mapping file must be .xlsx or .csv"	
UAT-23	M	Auto column mapping	Continue to step 3	All required fields mapped with a tick; sample values look right	
UAT-24	H	Change a column	Set Document type to another column, then back	Sample value changes; required field shows **Missing** when unmapped	
UAT-25	M	Your own mapping file	Upload a real export from your source system (or `samples/sample-mapping.csv`) in a separate draft job	Header row and columns detected; required fields mapped or easy to map	
UAT-25a	M	Several mapping files	In a draft job, select two exports at once (for example HR documents and payroll) and **Upload**	Both listed with their rows and fingerprints, plus a Total row	
UAT-25b	H	Different column names	Use a second file whose columns are named differently (for example `EmpCode`, `StoredFileName`); open step 3 and click its name	Each file has its own column mapping; required fields mapped for both	
UAT-25d	H	Different structure	Add an `.xlsx` with title rows above the header and extra columns, plus a semicolon `.csv` that has a Year column but no Uploaded on column	Both read; header row found below the titles; step 3 shows the note that the Year column gives the year	
UAT-25e	H	Same file twice	Upload a mapping file that is already in the job	Refused with "... has the same content as ..."; list unchanged	
UAT-25c	H	Remove and add	**Remove** one file, then add it again with **Add more mapping files**	List updates; after a scan, changing the files clears the results	

6 Rules and scan

ID	Pri	Test	Steps	Expected result	P/F
UAT-26	M	Default rules	Step 4: keep defaults, **Save and start scan**	Scan runs and finishes with Awaiting approval	
UAT-27	M	Demo counts	Read results summary	472 discovered, 458 ready, 7 unmapped, 3 missing, 2 ambiguous, 2 duplicate, 5 validation errors	

ID	Pri	Test	Steps	Expected result	P/F
UAT-28	M	Reference example path	Search tab **Everything** for `e00879_final`	Destination `E00879/Medical Certificate/2021/e00879_final_certifica`	
UAT-29	H	Template example	In step 4, change template to `{DocumentType}/{EmployeeCode}/{FileName}`	Example path updates; revert before saving	
UAT-30	H	Unknown token	Enter template `{Employee}/{FileName}` and save	Error naming the unknown token	
UAT-30a	M	Several files in one cell	Use a mapping file where one File name cell lists two existing files separated by a comma (for example `a.pdf,b.pdf`); scan	Two entries `ROW-n/1` and `ROW-n/2`, both READY; both copied	
UAT-30b	M	Placeholder file name	Put `NULL` in a File name cell; scan	That record is INVALID "Blank FileName", not MISSING	
UAT-30c	M	Repeat of a missing record	Two identical rows (same file, employee, type) naming a file that is not in the source; scan	Both MISSING; the second names the first; neither is DUPLICATE	
UAT-30d	H	`{MappingFile}` token	With two mapping files, template `{MappingFile}/{EmployeeCode}/{FileName}`	Example path and destinations start with the mapping file name	
UAT-30e	H	Keep all	Use a mapping file where two records (different employees) name the same file; in step 4 choose **Keep all**; scan, approve	No AMBIGUOUS; one READY item per record with its own destination; after copying the file is at both destinations; the reconciliation report has a row for each	
UAT-30f	H	Keep all, same path	As UAT-30e with template `{FileName}`	One copy READY, the other DUPLICATE "Destination path collision"	
UAT-31	M	Overwrite needs admin	As operator, open duplicate rule options	Overwrite is greyed out with "Not permitted by the administrator" unless an admin enabled it	

7 Review, resolve and approve

ID	Pri	Test	Steps	Expected result	P/F
UAT-32	M	Exception tabs	Click each tab: Unmapped, Missing, Ambiguous, Duplicate, Validation errors	Counts match tab labels; each row has a reason	
UAT-33	M	Validation report	Download validation report (Excel and CSV)	Files open; one row per item; summary sheet present	
UAT-34	M	Resolve ambiguous	Ambiguous tab > **Resolve** on one file, choose a record, add a note, **Assign**	Item becomes READY (459 ready); audit shows the resolution with the note	
UAT-35	H	Leave flagged	Resolve the other ambiguous file, click **Leave flagged**	Item stays AMBIGUOUS	
UAT-35a	M	Exclude ticked rows	All exceptions tab: tick two rows, **Exclude selected**, enter a note	Both EXCLUDED; counts update; Excluded tab shows original status, user, time and note	
UAT-35b	M	Exclude a whole reason	Open **Exceptions by reason**, **Exclude all** on one reason, enter a note	Every item of that reason EXCLUDED; the reason disappears from the list	
UAT-35c	H	Exclude everything in a view	Unmapped tab, search for part of a name, **Exclude all N in this view**	Only the items shown are excluded	
UAT-35d	H	Note required	Try to exclude without a note	Refused with a message; nothing changes	
UAT-35e	H	Kept after a new scan	Go back to step 4 and scan again	The same items are EXCLUDED again	
UAT-35f	M	Restore	Excluded tab: **Restore all N in this view**	Items return to their original status	

ID	Pri	Test	Steps	Expected result	P/F
UAT-35g	H	Viewer	Sign in as a viewer	Excluded tab visible; no tick boxes or exclude buttons	
UAT-35h	M	Maker-checker on	As admin, Settings: tick **Maker-checker (second approver)**, save	Saved; audit shows the change	
UAT-35i	M	Submit	As operator A, prepare and scan a job, tick the confirmation, **Submit for approval**	Job shows *Submitted for approval*; A sees no Approve button	
UAT-35j	H	Locked while submitted	As A or B, try to change rules, mapping, exclusions or resolve	Refused with *submitted for approval*	
UAT-35k	M	Reject	As operator B, **Reject...** with a reason	Job back to A with the reason shown	
UAT-35l	M	Approve by a second person	A submits again; B approves	Copy starts; audit names B as checker and A as maker	
UAT-35m	H	Checker who changed the job	B excludes an item, A submits, B tries to approve	Refused: B worked on the job	
UAT-35n	M	Change request	After copying, A excludes items	Request pending; nothing changes until B approves under **Change requests**	
UAT-36	M	Approval needs confirmation	Click **Approve and start copy** without ticking the checkbox	Message "Tick the confirmation box first"; nothing starts	
UAT-37	M	Approve	Tick, approve, confirm	Status Processing; audit shows Processing approved with user and time	

8 Processing and recovery

ID	Pri	Test	Steps	Expected result	P/F
UAT-37a	M	Time left while scanning	Scan a job with a large mapping file or source	Step 5 shows *Step n of 4*, the time left for steps with a known total, the speed and the time taken	
UAT-37b	M	Time left while copying	Approve a job with many files and watch step 7	After a few seconds: time left with a finishing time, files/s and MB/s; counts move every few seconds	
UAT-37c	H	Copy counts	Copy into a destination that already holds some of the files (rule Skip)	*Already at destination (skipped)* counts only those files; *Copied* + skipped + failed + still to copy = total	
UAT-38	M	Copy completes	Wait for the job to finish	Completed with exceptions; 459 processed, 0 failed	
UAT-39	M	Source untouched	Compare the demo source folder before and after	Same file count, names and dates	
UAT-40	M	Output structure	Open the destination folder	`EmployeeCode/DocumentType/Year/FileName` folders as previewed	
UAT-41	M	Pause and resume	Create a job on a larger source (thousands of files); **Pause** mid-copy, then **Resume**	Copy continues; final processed count equals ready count	
UAT-42	M	Restart mid-copy	During a copy, stop the application; start it again	Job shows Paused; **Resume** completes with no duplicates at the destination	
UAT-43	H	Retry failed	Remove write access to the destination mid-job, then **Retry failed** after restoring it	Only failed items are copied again	
UAT-44	H	Re-run same destination	Run a new job with the same source and destination, rule Skip and report	All items DUPLICATE "Destination already exists"; nothing overwritten	

9 Reconciliation and audit

ID	Pri	Test	Steps	Expected result	P/F
UAT-45	M	Reconciliation report	Step 8 > **Reconciliation Excel**	Summary lists every mapping file; item sheet has status, reason, mapping file, paths, hashes, times	
UAT-46	M	Integrity evidence	In the report, check the hash columns for processed items	Source and destination hashes equal	
UAT-46a	M	Exclusions in the report	Exclude one exception, download the reconciliation report	Row has status EXCLUDED and the last four columns filled (original status, by, at, note)	
UAT-46b	H	Close a completed job	On a job Completed with exceptions, exclude all remaining exceptions	Job becomes Completed	
UAT-47	M	Audit trail	Audit log, search by Job ID	Creation, mapping upload, rules, scan, resolution, approval, processing and export all listed	

10 Cloud storage

ID	Pri	Test	Steps	Expected result	P/F
UAT-48	M	Azure end-to-end	Upload 50 test files to `uat-source`, prepare a matching mapping file, run a job to `uat-organized`	Same results as local; source blobs unchanged	
UAT-49	M	Azure server-side copy	Check the Reason column of processed items in the reconciliation report	No "Copied by streaming" note (server-side copy used)	
UAT-50	H	Azure metadata	In the Azure Portal, open a copied blob's metadata	`docorgjobid`, `docorgrecordid`, `docorgemployeecode` present	
UAT-51	M	S3 end-to-end	Upload the same 50 files to `uat-source-<suffix>`, run a job to `uat-organized-<suffix>`	Same results as Azure; source objects unchanged	
UAT-52	M	S3 server-side copy	Check the Reason column in the reconciliation report	No "Copied by streaming" note (CopyObject used)	
UAT-53	H	S3 metadata	In the S3 console, open a copied object's metadata	`x-amz-meta-docorgjobid`, `x-docorgrecordid`, `x-docorgemployeecode` present	
UAT-54	M	Azure to S3	Run a job with source `uat-source` (Azure) and destination `uat-organized-<suffix>` (S3), prefix `from-azure/`	All ready files processed with "Copied by streaming"; hashes match; Azure source unchanged	
UAT-55	H	S3 to Azure	Run the reverse job, prefix `from-s3/`	Same as UAT-54 in the other direction	
UAT-56	H	Large file to S3	Include one file over 20 MB in UAT-54	Processed; S3 shows a multipart ETag (ending in `-N`); hashes match	
UAT-57	M	IAM role or managed identity	On the hosting platform, use a connection without keys (`Auth: Default` on AWS, `ManagedIdentity` on Azure) and repeat UAT-15 and UAT-17	Access confirmed; the sign-in method shown is the role or identity	
UAT-58	H	Changed source	After a scan, overwrite one source object, then approve	That item FAILED with a reason saying the source changed since the scan	
UAT-59	L	Archived objects	Set one Azure blob to Archive tier, or one S3 object to Glacier Flexible Retrieval, then scan	Item INVALID "archive tier"; not restored	

11 Security and hosting

ID	Pri	Test	Steps	Expected result	P/F
UAT-60	M	No secrets on screen	Open New job, Settings and reports for cloud jobs	No account key, SAS token or secret access key visible anywhere	
UAT-61	M	No secrets in Git	Run `git status` and `git diff` in the installation folder	No secrets in tracked files; they are only in environment variables or `appsettings.Production.json`	
UAT-62	H	CSV formula escape	Put `=1+1` in a mapping file Description, run a job, open the CSV report in Excel	Shown as text, not calculated	
UAT-63	M	Demo off in production	Set `EnableDemoData` to `false`, restart	**Load demo data** not shown	
UAT-64	H	Allowed local roots	Set `AllowedLocalRoots` to one folder; create a job outside it	Path refused	
UAT-65	M	HTTPS behind proxy	Hosted only: open the application through its HTTPS address with `BehindReverseProxy` true	Sign-in works; audit log shows the client's real IP address	

12 Defect log

#	UAT ID	Job ID	Description	Severity	Status
1					
2					
3					
4					
5					

13 Sign-off

Summary	Count
Cases run	
Passed	
Failed	
Mandatory cases failed	

Role	Name	Decision	Signature and date
Product owner		Accept / Reject	
Operations lead		Accept / Reject	
Cloud / Infrastructure		Accept / Reject	
Information security		Accept / Reject	