DO

Document Organizer

COPY-ONLY DOCUMENT RE-ORGANIZER

FAQ AND TROUBLESHOOTING

FAQ and Troubleshooting

Answers to common questions and fixes for common problems

Document ID DO-FAQ-04 · **Version** 2.1 · **Date** 22-Oct-2026

Prepared by Yasin Jariwala

Audience Operators, administrators and support teams

Document control

Document	FAQ and Troubleshooting
Document ID	DO-FAQ-04
Version	2.1
Date	22-Oct-2026
Prepared by	Yasin Jariwala
Product	Document Organizer v2.1
Audience	Operators, administrators and support teams
Classification	Public
Source	github.com/yasin679/Document_Organizer · docs/faq-and-troubleshooting.md

Version history

Version	Date	Author	Changes
1.0	06-Oct-2026	Yasin Jariwala	First release
2.0	13-Oct-2026	Yasin Jariwala	General-purpose release: Amazon S3 and S3-compatible storage, copy between providers, container hosting; tenant ID field removed
2.1	22-Oct-2026	Yasin Jariwala	Several mapping files per job; File name cells listing several files split into one entry per file; NULL placeholders treated as blank; repeats of missing records reported as MISSING

Related documents

ID	Document
DO-UG-01	User Guide
DO-IG-02	Installation and Administration Guide
DO-QS-03	Quick Start
DO-TD-05	Technical Design
DO-UAT-06	UAT Test Cases
DO-RN-07	Release Notes v2.1

Contents

1 Frequently asked questions 3
1.1 General 3
One file is named by several records. Can it go to each of them? 3
Can I get rid of thousands of exceptions at once? 3
1.2 Running jobs 4
1.3 Reports and audit 5
2 Troubleshooting 6
2.1 Starting and signing in 6
2.2 Azure Blob Storage 6
2.3 Amazon S3 and S3-compatible storage 7
2.4 Jobs and locations 8
2.5 Mapping file and matching 8

1 Frequently asked questions

1.1 General

Does the application ever move or delete the original documents?

No. Document Organizer only reads the source and writes a copy to the destination. The source container, bucket or folder needs read and list access only. The source stays exactly as it was, so a job can always be repeated.

Is this a recovery tool or an organizer?

It is an organizer. It does not restore deleted files. It takes documents that exist today, uses a mapping file to identify each one, and copies them into a clean structure: `EmployeeCode / DocumentType / Year / FileName`.

Which storage does it work with?

Azure Blob Storage, Amazon S3, S3-compatible services (MinIO, Wasabi, Cloudflare R2 and others), and local or network folders. Source and destination can be different types, so a job can also migrate documents, for example from Azure to S3.

Are documents sent anywhere else?

No. Documents go only from the source you choose to the destination you choose. When both are in the same Azure storage account, or use the same S3 connection, the storage service copies them server-side and the content never passes through the application server. Nothing is sent to any external service.

What does the mapping file need to contain?

One row per document with at least an employee code, a document type and a file name, plus an upload date or a year. Column names are matched automatically and can be changed in step 3. See `samples/sample-mapping.csv` in the repository.

Can I use more than one mapping file in a job?

Yes. In step 2, choose several files at once or add more later. Their records are combined in one scan. Each file has its own column mapping in step 3, so files with different column names can be mixed. Every record keeps the name of its mapping file in the reports, and the folder template token `{MappingFile}` can keep each file's documents in their own folder. Files can also differ in column order, extra columns, title rows, CSV delimiter, file type (`.xlsx` and `.csv` together) and date column (a file with only a Year column is fine).

One file is named by several records. Can it go to each of them?

Yes. In step 4, under **When a file matches several mapping records**, choose **Keep all** and scan. The file is copied once per record, each to its own destination, and each copy is its own row in the reconciliation report. With the default **Flag as ambiguous**, the file waits for a person to choose one record.

Can I get rid of thousands of exceptions at once?

Yes, by excluding them (User Guide section 10.3). Tick rows, use **Exclude all N in this view** on any tab or search, or exclude a whole reason from **Exceptions by reason** (for example all *Blank file name* errors). A

note is required. Excluded items are not copied, stay in the reports with status EXCLUDED and the note, are excluded again after a new scan, and can be restored. Nothing is deleted.

A File name cell lists several files separated by commas. Is that supported?

Yes. Each name becomes its own entry: record `ROW-68` with `a.pdf,b.pdf` becomes `ROW-68/1` (`a.pdf`) and `ROW-68/2` (`b.pdf`), each with its own status. Semicolons work the same way. A cell that is exactly the name of a source file (a real file name containing a comma) is never split. The option is under step 4 and is on by default.

Who can do what?

Viewers can see everything and download reports. Operators can also create and run jobs. Administrators can also change settings and manage users.

1.2 Running jobs

How long does a job take?

In testing, a mapping file of 66,000 rows with 60,000 files in a local folder was read and scanned in about 3 seconds. Copy speed depends on the storage: server-side copies inside one Azure account or one S3 connection are fastest; streaming between providers depends on the network. Cloud listings take longer for large containers (5,000 blobs per page on Azure, 1,000 objects per page on S3).

Can I close the browser while a job runs?

Yes. Jobs run inside the application, not in the browser. You can close the tab and come back later. Do not stop the application itself (the console window, service or container).

What happens if the server restarts in the middle of a copy?

The job is shown as **Paused**. Open it and click **Resume**. Files already copied are recognised by comparing their contents and are not copied again.

Can I change the rules after scanning?

Yes, until the job is approved. Go back to step 3 or 4 and save. The scan results are cleared and you scan again. After approval the rules are locked so each job's report always matches the rules used.

What if a file is already at the destination?

It depends on the duplicate rule you chose in step 4. **Skip and report** (default) leaves it alone and marks it DUPLICATE. **Rename with a suffix** writes `name_dup1.pdf`. **Compare hash** skips it if identical, otherwise renames. **Overwrite** replaces it, but only if an administrator has enabled overwrite in Settings.

How is the year worked out?

By default, from the UploadedOn date in the mapping file. You can instead use a Year column, a pattern in the file name, or a pattern in the folder, blob or object path. If no valid year is found, the record is INVALID and you decide what to do with it. The application never invents a year.

Why are some files AMBIGUOUS?

Two or more mapping records name the same file, for example `offer_letter.pdf` for two different employees. The application cannot know which is correct, so a person must choose in the Resolve panel. The choice and note go to the audit log.

The Missing count is very large. Are files lost?

Usually not. A large Missing count most often means the source prefix, bucket or folder was too narrow, so the scan did not see where those files are. Check the source location before reporting anything to the client. In version 2.0 and earlier, File name cells listing several files and cells containing `NULL` were also counted as missing; version 2.1 splits the first and reports the second as INVALID (blank file name).

Why is a repeated record MISSING and not DUPLICATE?

A repeated record (same file, employee and type as an earlier record) is DUPLICATE only when the earlier record found its file, because then the file is copied once. When the file is not in the source, both records are MISSING, and the reason of the second names the first, so the Missing count matches the records that need follow-up.

Can I run two jobs at the same time?

Yes. Avoid two jobs that write to the same destination prefix.

Can a job move documents from Azure to S3?

Yes. Choose Azure Blob Storage as the source and Amazon S3 as the destination. Each file is streamed from Azure to S3 (multipart for files over 8 MiB), verified, and tagged with the job ID, record ID and employee code. The Azure source is not changed.

1.3 Reports and audit

Which report do I send to the client?

The reconciliation report (Excel), downloaded from step 8. It has a summary sheet and one row per file and record with status, reason, source, destination, hashes and time copied.

How long is history kept?

Jobs and reports are kept for 365 days and the audit log for 7 years by default. Administrators can change both under Settings.

Can audit entries be edited or deleted?

No. There is no screen or API to change the audit log.

2 Troubleshooting

2.1 Starting and signing in

Problem	Likely cause	What to do
"dotnet is not recognized" or ".NET 8 is not installed"	.NET 8 is not installed, or the window was opened before installing	Install the .NET 8 SDK and open a new terminal
"SQLite library not found" (Linux)	The SQLite system library is missing	Install `libsqlite3-0` (Debian/Ubuntu) or `sqlite-libs` (RHEL/Fedora), or use the Docker image
Browser shows "This site can't be reached"	The application is not running, or the console window was closed	Start it again and keep it running
"address already in use" for port 5080	Another copy is already running	Stop the other copy, or change `Urls`
Admin password not accepted	Password was not set at start, or was shorter than 8 characters	Start again with `DOCORG_ADMIN_PASSWORD` set (or type it at the `start.cmd` prompt)
No temporary password appears	A password already exists in the database	Set a new one with `DOCORG_ADMIN_PASSWORD` at start-up
"The account is locked for 10 minutes"	5 wrong passwords	Wait 10 minutes, or ask an administrator to reset the password
Signed out unexpectedly	30 minutes without activity	Sign in again. Running jobs are not affected.
Signed out at once behind a load balancer, or every audit entry shows the proxy's address	Reverse proxy headers not trusted	Set `DocumentOrganizer__BehindReverseProxy=true`

2.2 Azure Blob Storage

Message or problem	Likely cause	What to do
`AuthorizationPermissionMismatch`	Your account lacks the Azure role on the container	Ask for Storage Blob Data Reader (source) or Contributor (destination). Wait up to 10 minutes after it is granted.
`AuthenticationFailed`	SAS token expired or wrong, or account key wrong	Get a new token or key and update the configuration
"Please run 'az login'"	Azure CLI sign-in has expired	Run `az login` and click **Check access** again

Message or problem	Likely cause	What to do
"No managed identity endpoint is reachable"	`ManagedIdentity` used outside Azure	Use `AzureCli` or `Sas` on a laptop
`ContainerNotFound`	Container name typed wrong	Check the name in the Azure Portal. Names are lower-case.
Azurite connection refused	Azurite is not running	Start `azurite-blob` in a separate terminal

2.3 Amazon S3 and S3-compatible storage

Message or problem	Likely cause	What to do
`NoSuchBucket`	Bucket name typed wrong, or the bucket is in another account	Check the name. Bucket names are lower-case.
"The bucket is in region 'X', but the connection uses 'Y'"	`Region` on the connection is wrong	Set `Region` to the region shown
`InvalidAccessKeyId`	The access key does not exist or was deactivated	Create a new access key and update the configuration
`SignatureDoesNotMatch`	The secret access key is wrong, or the server clock is far off	Check `SecretAccessKey`; make sure the server time is correct
`AccessDenied` on Check access	The IAM policy does not allow the action	Apply the policy in DO-IG-02 section 4.4
Destination items FAILED with `AccessDenied` / 403 on files that do not exist yet	`s3:ListBucket` missing on the destination, so S3 answers "denied" instead of "not found"	Add `s3:ListBucket` on the destination bucket
"No AWS credentials found"	`Auth` is `Default` and none of the credential sources is available	Set `AccessKeyId` and `SecretAccessKey`, set `AWS_ACCESS_KEY_ID` / `AWS_SECRET_ACCESS_KEY`, add a profile to `~/.aws/credentials`, or attach an IAM role
Connection refused to `localhost:9000`	The MinIO or moto emulator is not running	Start it, or remove the `LocalS3` connection
Wrong host or TLS error with an S3-compatible service	Virtual-hosted addresses not supported by that service	Set `ForcePathStyle` to `true` (the default when `ServiceUrl` is set)
INVALID "archive tier" for S3 objects	Objects are in Glacier Flexible Retrieval or Deep Archive	Restore them (S3 console or `aws s3api restore-object`), then scan again

2.4 Jobs and locations

Message or problem	Likely cause	What to do
"Destination must be different from the source", "Destination folder cannot be inside the source folder" or "Destination prefix cannot be inside the source prefix"	Destination is the same as, or inside, the source	Choose a different container, bucket, prefix or folder
"Connection 'X' is not an Amazon S3 connection" (or "...not an Azure Blob Storage connection")	The connection's `Provider` does not match the storage type chosen	Pick a connection of the right type, or correct `Provider` in the configuration
Path refused for local folder	Folder is outside `AllowedLocalRoots`	Ask an administrator to add the root, or use an allowed folder
A storage type is greyed out on the New job page	Turned off in Settings, or no connection of that type is configured	Ask an administrator
Many FAILED with HTTP 503 or `SlowDown`	The storage service is throttling	Lower **Parallel copies** in Settings, then **Retry failed**

2.5 Mapping file and matching

Problem	Likely cause	What to do
"No header row found in the file" or "could not be read as Excel"	The file has no column names in its first 20 rows, or is not a real `.xlsx` / `.csv`	Export the file again without changes
Required field shows **Missing** in column mapping	The column has a different name in this file	Pick the right column from the list
Almost everything UNMAPPED	Wrong mapping file for this source, the File name column is mapped wrongly, or the source also holds documents from other modules	Check the file and the File name mapping; add the other modules' exports as extra mapping files
Many MISSING whose file name contains commas	Version 2.0 or earlier, or **Several file names in one cell** turned off	Use version 2.1 with the option on (step 4), then scan again
Accented file names (`é`, `ü`) MISSING although the files exist	Version 2.0 or earlier read every CSV as UTF-8, so a CSV saved by Excel on Windows lost accented characters	Use version 2.1 and scan again
"... has the same content as ..., which is already added"	The same mapping file was uploaded twice	Nothing to do; the first copy is kept
"Enter a note saying why these items are excluded"	Exclude was clicked without a note	Type the reason; it goes into the reports and the audit log
"Exceptions can be excluded after a scan..."	The job is a draft, scanning or copying	Wait for the scan to finish, or pause the copy

Problem	Likely cause	What to do
Excluded items came back after a scan	Their status changed (for example a missing file arrived, so the record is READY)	Nothing; exclusions only re-apply when the status is the same
Scan refused: "Column ... is required" naming one of several files	That file's columns were not recognised	Step 3, click the file's name, map its columns
Almost everything MISSING	Source prefix, bucket or folder is wrong	Check the source location in step 1
Almost everything DUPLICATE	Destination already holds an earlier copy	Use a new destination prefix, or the Compare hash rule
Many INVALID "year could not be determined"	UploadedOn is blank or not a date	Use the Year column or a file-name pattern in step 4
INVALID "archive tier"	Azure Archive tier or S3 Glacier / Deep Archive	Rehydrate or restore the files, then scan again

Still stuck?

Note the Job ID (for example `JOB-20261013-0001`), the step, and the exact message. The audit log for the job shows every action taken on it. Bugs and questions can be raised as issues on the GitHub repository.