DO

Document Organizer

COPY-ONLY DOCUMENT RE-ORGANIZER

RELEASE NOTES V2.0

Release Notes v2.0

What is new, what changed, verified results and known limitations

Document ID DO-RN-07 · **Version** 2.0 · **Date** 13-Oct-2026

Prepared by Yasin Jariwala

Audience Everyone installing, upgrading or evaluating Document Organizer

Document control

Document	Release Notes v2.0
Document ID	DO-RN-07
Version	2.0
Date	13-Oct-2026
Prepared by	Yasin Jariwala
Product	Document Organizer v2.0
Audience	Everyone installing, upgrading or evaluating Document Organizer
Classification	Public
Source	github.com/yasin679/Document_Organizer · docs/release-notes.md

Version history

Version	Date	Author	Changes
1.0	06-Oct-2026	Yasin Jariwala	First release
2.0	13-Oct-2026	Yasin Jariwala	General-purpose release: Amazon S3 and S3-compatible storage, copy between providers, container hosting; tenant ID field removed

Related documents

ID	Document
DO-UG-01	User Guide
DO-IG-02	Installation and Administration Guide
DO-QS-03	Quick Start
DO-FAQ-04	FAQ and Troubleshooting
DO-TD-05	Technical Design
DO-UAT-06	UAT Test Cases

Contents

1 Release summary 3

2 New in v2.0 3

2.1 Amazon S3 and S3-compatible storage 3

2.2 Copy between providers 4

2.3 Hosting and packaging 4

2.4 Configuration 4

2.5 User interface 4

2.6 Documentation 4

3 Fixed in v2.0 5

4 Verified results 5

5 Changes that affect upgrades from v1.0 5

6 Known issues and limitations 6

7 Installation notes 6

8 Roadmap 6

1 Release summary

Item	Value
Product	Document Organizer
Version	2.0
Release date	13-Oct-2026
Status	Ready for UAT
Source	https://github.com/yasin679/Document_Organizer
Platform	.NET 8 on Windows, Linux or macOS; Docker image for any container platform

Document Organizer copies employee documents into a clean, consistent structure, `EmployeeCode / DocumentType / Year / FileName`, using a mapping file to identify each file. Version 2.0 is a general-purpose release: it works with **Azure Blob Storage**, **Amazon S3** (and S3-compatible storage) and **local or network folders**, in any combination, and can be hosted anywhere. It is copy-only: source documents are never moved, changed or deleted.

2 New in v2.0

2.1 Amazon S3 and S3-compatible storage

- **Amazon S3** as a source and destination, alongside Azure Blob Storage and folders.
- Works with **S3-compatible services** (MinIO, Wasabi, Cloudflare R2 and others) through `ServiceUrl`, with path-style addressing.
- **Credentials:** access key, or the standard AWS chain: environment variables, EKS web identity (IRSA), `~/.aws/credentials` profile, ECS / EKS Pod Identity container role, EC2 instance role (IMDSv2).
- **Server-side copy** (CopyObject) between buckets on the same connection, with the source ETag as a condition.
- **Multipart upload** for files over 8 MiB; each part carries an MD5 check; failed uploads are aborted.
- **Conditional writes** (`If-None-Match: *`) so an existing object is never replaced unless Overwrite is allowed.
- Objects in **Glacier Flexible Retrieval** and **Deep Archive** are reported as INVALID (archive tier) and never restored automatically.
- A wrong bucket region is reported with the bucket's real region.
- The destination bucket is created on **Check access** if it does not exist and the credentials allow it.
- **Content-MD5** integrity checks use the S3 ETag where it equals the MD5 (single-part uploads without KMS or customer-key encryption).
- Implemented on the S3 REST API with Signature Version 4; no AWS SDK is required.

2.2 Copy between providers

- Source and destination can be **different storage types**: Azure to S3, S3 to Azure, either to or from a folder.
- Files are streamed, verified (SHA-256 or Content-MD5) and tagged with traceability metadata on the destination.
- Source metadata is carried across providers, with names adjusted to each provider's rules.

2.3 Hosting and packaging

- **Dockerfile:** small runtime image, non-root user, port 8080, data on a volume.
- **docker-compose.yml:** the application plus Azurite (Azure emulator) and MinIO (S3 emulator) for a trial without any cloud account.
- `/healthz` endpoint for container and load-balancer health checks.
- `BehindReverseProxy` setting to trust `X-Forwarded-For` / `X-Forwarded-Proto` behind HTTPS proxies and load balancers.
- `start.sh` for Linux and macOS, next to `start.cmd` for Windows.
- **GitHub Actions** workflow that builds the application and runs the end-to-end tests against Azurite and moto on every push.
- `.gitignore`, `.gitattributes`, `.env.example` and a sample mapping file (`samples/sample-mapping.csv`).

2.4 Configuration

- Storage connections are **typed** with `Provider: AzureBlob` or `Provider: S3` (inferred if omitted).
- Any connection can be marked `UseForDemo`; **Load demo data** then also uploads the sample files there.
- Secrets can live in `appsettings.Production.json`, which is excluded from Git, or in environment variables.

2.5 User interface

- **New job** offers three storage types. Only connections of the chosen type are listed, and the box is labelled Container or Bucket accordingly.
- **Settings** has a switch for Amazon S3 and shows each connection's type.
- The jobs table shows the **destination** of each job.
- Demo shortcuts are shown for every demo connection that was loaded.
- The rule "Keep blob metadata" is now **Keep object metadata** and applies to every cloud destination.

2.6 Documentation

All seven guides were rewritten for v2.0 and are kept in the repository under `docs/`, as Markdown (readable on GitHub) and as PDF.

3 Fixed in v2.0

#	Issue	Fix
1	Copies from Azure Blob Storage to a non-Azure destination (for example a local folder) failed every file with "Source file changed after the scan"	Azure's list and properties calls return the ETag in different forms (unquoted and quoted). ETags are now stored in one form and compared without quotes. Azure-to-Azure copies were not affected.
2	Source metadata copied to Azure could be rejected if a name contained characters Azure does not allow	Metadata names are adjusted to the destination's rules

4 Verified results

Test	Result
End-to-end automated test: 7 jobs covering folder, Azure (Azurite), S3, Azure → folder, S3 → folder, Azure → S3, S3 → Azure	159 checks pass
S3 against an emulator that enforces Signature V4, about 10,000 requests	All accepted; wrong secret rejected with `SignatureDoesNotMatch`
20 MB file to S3; key with spaces, accents and `+&=@#`	Multipart in 3 parts, byte-identical; exact key preserved
Second run into the same destination	Every item DUPLICATE; nothing overwritten
66,000-row mapping file with 60,040 files (local folder)	Read, matched and validated in about 3 seconds
v1.0 scale test (176,000 rows, 60,000 files; restart during copy and resume)	Exactly 60,000 processed, no duplicates

5 Changes that affect upgrades from v1.0

Change	Effect	What to do
SignUpID removed	The SignUpID field on New job, the SignUpID column mapping, the `{SignUpId}` template token and the SignUpID report columns are gone. The mapping file no longer needs a tenant column.	Remove `{SignUpId}` from any saved templates. Extra columns in a mapping file are simply ignored.
Metadata keys renamed	Copied files are tagged `docorgjobid`, `docorgrecordid` and `docorgemployeecode`	Update anything that reads the old keys
Connection `Provider`	New optional setting; inferred when missing	Add `"Provider": "AzureBlob"` to existing connections for clarity

Change	Effect	What to do
Product-neutral naming	No customer-specific branding, names or examples remain in the application or documents	None
Demo data	New fictional data set (employee codes starting with `E`); demo mapping file `demo-mapping.xlsx`	Load the demo data again
Default connections	`appsettings.json` now ships `Azurite` and `LocalS3` emulator connections	Remove them in production

The database is upgraded automatically on start; existing jobs, users and the audit log are kept.

6 Known issues and limitations

#	Item	Workaround or plan
1	Not yet tested with real Azure (Azure CLI, managed identity) or real AWS (IAM roles); automated tests use emulators	Run UAT cases DO-UAT-06 before using real documents
2	Local user accounts only	Single sign-on (OpenID Connect) on the roadmap
3	Archived objects (Azure Archive, S3 Glacier Flexible Retrieval and Deep Archive) are not restored	Restore them in the storage service, then scan again
4	Server-side copy only within one Azure storage account or one S3 connection	Other combinations stream through the application
5	One application instance per data folder	Do not run two instances against the same data volume
6	The Docker image has not been built in the release pipeline yet	Build it locally (`docker compose up --build`) and run UAT-01 and UAT-02

7 Installation notes

- New installation: follow the Installation and Administration Guide (DO-IG-02).
- Requires the .NET 8 SDK (or ASP.NET Core 8 Runtime for a published build), or Docker.
- Set `EnableDemoData` to `false` and remove the emulator connections before production use.
- Keep secrets out of Git: environment variables or `appsettings.Production.json`.

8 Roadmap

Item	Planned
Sign-in	Single sign-on with OpenID Connect (Microsoft Entra ID, Okta, Google)
Storage	Google Cloud Storage; optional restore of archived objects with approval

Item	Planned
Dashboard	Filters by job label, storage type and date
Packaging	Published container image and release builds on GitHub
Intelligence	OCR and document classification, always with human approval