

HALAH System and Workflow

The HALAH implementation provides a role-based patient consent management environment that operationalises the proposed multi-party healthcare data-sharing framework. The subsystem is organised around four principal functions: patient consent creation, guardian cryptographic approval, authorised doctor data access, and independent audit of the consent lifecycle. Rather than treating consent as a single approval event, the implementation represents consent as a lifecycle in which a consent request is created, independently authorised by designated parties, and cryptographically activated on a public blockchain. It is then continuously checked for validity, subsequently used to control access to specific electronic medical record (EMR) modules, and finally revoked by the patient.

The activation and revocation of a consent are not confined to the application. Instead, they are executed as real transactions on the **Ethereum Sepolia** test network. Consequently, the essential state changes of a consent can be verified by any third party on a public block explorer. The overall workflow implemented by the system is therefore consistent with the proposed authorisation model as

*Create Consent → Guardian Approval → Multi-signature Validation → On-chain Consent Activation
→ Doctor Access → Consent Revocation → Independent Audit*

This sequence provides an end-to-end demonstration of how the conceptual consent model is translated into an operational healthcare data-sharing process. Each stage is documented below with a screenshot of the running system and, where the stage produces a blockchain transaction, with the corresponding transaction on Sepolia Etherscan.

1. HALAH System

The main HALAH subsystem presents itself as a Patient Consent Management Platform for History Access by Authorised Healthcare Providers. The subsystem provides a role-oriented environment in which different participants interact with the same consent lifecycle according to their respective authorisation responsibilities.

The implementation does not expose the underlying blockchain and cryptographic mechanisms as isolated technical components. Instead, these mechanisms are incorporated into the user workflow. Consequently, the subsystem presents the system from the perspective of the healthcare participants while the underlying implementation performs identity verification, consent-state checking, multi-party approval, cryptographic validation, on-chain anchoring and audit recording.

This design corresponds to the overall HALAH architecture, in which decentralised identifiers (DIDs) provide identity pointers, the consent object defines the authorisation conditions, cryptographic signatures provide evidence of approval, and the blockchain-based ledger provides lifecycle traceability.




Figure 1. Compilation of ConsentSBTV3 in Remix: the compiler reports a successful compilation and the contract is selected for deployment.

As shown in the figure above, the consent token contract, **ConsentSBTV3**, was first compiled in Remix without errors; the deployment record lists solc 0.8.34 with the optimiser enabled. The contract was then deployed to the Sepolia test network from the project test wallet through MetaMask. The contract implements a soulbound ERC-721 token. Transfers between accounts are blocked. Consequently, an activated consent can never be traded or moved; burning is possible only through the ERC-5484 consensual-burn interface. Each token stores the pseudonymous patient and requester addresses, a hash of the purpose, the validity window, a two-letter jurisdiction code and a revocation flag. The purpose is stored only as a keccak256 hash, and no medical content is written to the chain; the plaintext purpose and the EMR data remain in the application.




Figure 2. Deployment of ConsentSBTV3 from Remix through MetaMask on the Sepolia network.

As shown in the figure above, the deployment is an ordinary Ethereum transaction that the wallet owner must explicitly confirm: the project test wallet (displayed as BNHP Ministry Test Wallet) shows the target network (Sepolia), the estimated network fee and the account nonce before the contract is created. This is important because it demonstrates that consent activation in HALAH ultimately rests on the same transaction-signing discipline as any other blockchain operation.




Figure 3. Remix after deployment: the contract appears under Deployed Contracts and the source verification service reports Verification Successful.

As shown in the figure above, the deployed instance is listed in Remix under Deployed Contracts, and the source code was submitted for verification, which completed with Verification Successful. This is important because it ties the published bytecode on Sepolia to the audited Solidity source, so any party can confirm which rules the consent registry actually enforces.




Figure 4. The deployed contract on Sepolia Etherscan, with the creator wallet, the MedicalConsent (CONSENT) token tracker and the first mint transaction.

As shown in the figure above, the deployed contract is publicly listed at [0x0EC3617581DEC63A7f2bb162DC14d088916ADc73](https://etherscan.io/address/0x0EC3617581DEC63A7f2bb162DC14d088916ADc73) together with its creator wallet and the token tracker MedicalConsent (CONSENT). Consequently, the existence of the consent registry itself, and every activation or revocation recorded on it, can be inspected independently of the HALAH application.

The application itself was run in GitHub Codespaces, a browser-based execution environment. Before the demonstration, a readiness check was executed, which confirmed the network (Sepolia, chainId 11155111), the signer balance, the presence of contract code at the configured address, and the signer's ownership of the contract; its full output is preserved in the deployment record in the project evidence.

```
READY - run the app and complete a 2/2 guar
gnature to mint on-chain.
@yasir12345678900 → /workspaces/HealthRWA-S
Personal-try (claude/pensive-tesla-u9uk4j)
```

Figure 5. The final verdict of the Sepolia readiness check executed in GitHub Codespaces before the demonstration: READY.

As shown in the figure above, the check reports READY, so every subsequent step of the demonstration operates against the live contract. The subsystem therefore serves as the entry point for demonstrating the complete authorisation process rather than functioning merely as a conventional patient-record application.

2. Create Smart Consent Contract: Patient Subsystem

The first functional subsystem is the Create Smart Consent Contract module. This module represents the patient-side initiation of a consent transaction and corresponds directly to the construction of the proposed consent object.

The subsystem requires the patient to specify the Patient DID, Authorised Doctor DID, Data Access Scope, Designated Guardian DIDs, the Jurisdiction, and the temporal validity of the consent. These fields collectively operationalise the proposed consent representation:

$$C = (I, A, P, T, L, E)$$

where the identity of the patient is represented through a DID, the authorised actor is explicitly specified, the permitted data scope is constrained to selected EMR modules, the temporal fields define when the authorisation becomes valid and when it expires, the jurisdiction field constrains where the consent may be exercised, and the enforcement state records whether the consent is active or revoked.

Create Smart Consent Contract

Patient DID (Identity Pointer)
did:patient:5f01823-c8e8-9e40-c911-54b7b1ad843a

Authorised Doctor DID
did:hospital:001

Jurisdiction (VL)
AU

Data Access Scope (EMR Modules)
Observation * Medication * Condition * Procedure *

Designated Guardian DIDs (Comma Separated)
did:parent:A, did:parent:B

Contract Temporal Validity
Start Time (YYYY-MM-DD HH:MM:SS)
2026-09-24 10:55:49
Expiry Time (YYYY-MM-DD HH:MM:SS)
2026-10-31 23:59:59

Initial Consent

Consent contract created and logged (off-chain).

[CONSENT CREATED - OFF-CHAIN]
• Consent ID: 04da25f5-b16f-4d9a-af39-a78f0a83b17f
• TxHash: OFF-CHAIN - anchoring happens after guardian 2/2 approval
• Block Number: pending

My Consents

04da25f5... → did:hospital:001 PENDING_SIGNATURE 0/2 sigs - token: - **Revoke**

Figure 6. The patient subsystem after consent creation: four EMR modules, two designated guardians, jurisdiction AU, and the state `PENDING_SIGNATURE`.

As shown in the figure above, the Patient DID provides the identity pointer for the data subject, while the Authorised Doctor DID limits the intended healthcare recipient. This is important because the implementation does not represent consent as a general permission to access a patient's medical information. Instead, the authorisation is

bound to a specific identity and therefore supports subject-specific and actor-specific access control.

The Data Access Scope is particularly important to the proposed framework. Instead of granting access to the complete EMR, the patient selects particular modules; in the demonstrated transaction all four modules (Observation, Medication, Condition and Procedure) were selected. This implements the principle of purpose- and scope-limited consent and corresponds to the P component of the consent object. The implementation additionally validates the input before the consent is stored: a consent with an empty data scope is rejected, and every guardian entry must be a well-formed DID.

The Designated Guardian DIDs establish the additional parties required to participate in the authorisation process. Their presence in the consent-creation subsystem demonstrates that multi-party consent is incorporated at the point at which the consent contract is constructed rather than being added after authorisation.

Finally, the Start Time and Expiry Time implement temporal constraints on the consent, and the Jurisdiction field records the legal territory (AU in the demonstrated transaction). Consequently, authorisation is not represented as a permanent or universal permission. Instead, the consent has a defined lifecycle and territory and can subsequently be evaluated by the Consent Engine according to both. At this point the consent exists only in the application ledger, in the state `PENDING_SIGNATURE`; nothing is written to the blockchain until the guardians have approved.

Two consent lifecycles appear in the demonstration and should be distinguished. The evaluated consent, f050c29a, was carried through the complete lifecycle — activation as **token #1**, granted access, refused access and final revocation — and all transaction evidence in this chapter follows it. Because a revoked consent cannot be photographed in its earlier states, the screenshots of consent creation, guardian approval and granted access were captured from a second lifecycle with the same configuration — the same four-module scope, the same guardians, jurisdiction, purpose and doctor — executed for a different demonstration patient (consent 04da25f5, anchored as **token #2** in block 11,771,581). The two lifecycles were executed with the same code and the same contract.

From a system perspective, this module therefore corresponds primarily to **Consent Object Construction and Patient Initiation**.

3. Guardian Cryptographic Approval

The second part is the Guardian Cryptographic Approval. As shown in the figure below, it operationalises the multi-party authorisation component of the proposed framework.

Guardian Cryptographic Approval

Enter Target Consent ID

04da25f5-b16f-4d9a-af39-a78f0a83b17f

Found active transaction for Patient: did:patient:5f81f823-c8e8-9e40-c911-54b7b1ad843a

Select Your Guardian DID Identity

did:parent:A

Sign Consent via VC

EIP-712 signature verified (signer 0x3Af549b0...). Multi-sig: 1/2

Figure 7. The guardian subsystem at the first approval: the EIP-712 signature of did:parent:A is verified and the multi-signature count is 1/2.

As shown in the figure above, the first guardian (did:parent:A) approves the consent and the subsystem reports EIP-712 signature verified (signer 0x3Af549b0...) with the multi-signature count 1/2. The consent remains pending, because the approval condition has not yet been satisfied. The second guardian then repeats the same procedure.

Guardian Cryptographic Approval

Enter Target Consent ID

04da25f5-b16f-4d9a-af39-a78f0a83b17f

Found active transaction for Patient: did:patient:5f81f823-c8e8-9e40-c911-54b7b1ad843a

Select Your Guardian DID Identity

did:parent:B

Sign Consent via VC

EIP-712 signature verified (signer 0x39B12b87...). Multi-sig: 2/2

{ SBT MINTED - LOCAL LEDGER }

- Soulbound Token ID: SBT-LOCAL-04da25f5
- Status: 2/2 guardian approval reached - on-chain anchoring result shown below.

Anchoring on Sepolia in the background (15-30 s). You may navigate away - the result is written to the ledger automatically. Refresh or open Auditor to see it.

Figure 8. The guardian subsystem at the moment of the second approval: the EIP-712 signature is verified, the 2/2 threshold is reached, the SBT is minted in the local ledger and the Sepolia anchoring starts in the background.

As shown in the figure above, the guardian first enters the target Consent ID, after which the system retrieves the corresponding active transaction and displays the associated patient DID. The guardian then selects their own Guardian DID identity and approves the consent with an EIP-712 typed-data signature, which binds the approval to this specific consent, this guardian and this network (chainId 11155111). The system verifies each signature by recovering the signer address and comparing it

with the address associated with that guardian DID. A signature produced for another consent, another guardian or another chain is rejected, and the interface refuses a second signature from the same guardian.

The subsystem subsequently reports:

EIP-712 signature verified (signer 0x39B12b87...). Multi-sig: 2/2

This is an important implementation-level demonstration because the consent is not activated merely because the patient created it. Instead, the system requires the predefined guardian approval condition to be satisfied. The implementation therefore enforces the logical authorisation rule:

$$ALLOW = VI \wedge VA \wedge VP \wedge VT \wedge VL$$

where identity verification, authorisation verification, purpose verification, temporal verification and jurisdictional verification must all be satisfied before access can be granted. For the demonstrated two-guardian configuration, the approval process can also be represented as:

$$\sum_{g \in G} \text{Sign}(g, C) \geq |G| = 2$$

where G represents the designated guardians and every listed guardian must provide a valid signature for activation. Once the required signatures have been obtained, the subsystem displays SBT MINTED together with the Soulbound Token identifier, and a background job submits the mint transaction to Sepolia. While the background job is running, the subsystem reports the intermediate state explicitly.

The screenshot shows a web interface titled "Guardian Cryptographic Approval". It includes a text input field for "Enter Target Consent ID" with the value "04da25f5-b16f-4d9a-af39-a78fa83b17f". Below this, a blue box states "Found active transaction for Patient: did:patient:5f01f823-c8e8-9e40-c911-54b7b1ad843a". A green box indicates "Threshold 2/2 reached but NOT anchored on Sepolia yet (token: SBT-LOCAL-04da25f5). Click below and wait ~30 s without touching anything." There are two buttons: "Sync from Sepolia (find existing mint)" and "Anchor on Sepolia now (background)". A blue box shows "Anchoring in progress - refresh in ~30 s." Below this is a dropdown menu for "Select Your Guardian DID Identity" with the selected value "did:parent:B". A green button "Sign Consent via VC" is present. At the bottom, a green box states "This guardian has already signed this consent (one signature per guardian)."

Figure 9. The guardian subsystem while the mint transaction is pending: the 2/2 threshold is reached but not yet anchored, the anchoring runs in the background, and a repeated signature from the same guardian is refused.


As shown in the figure above, the subsystem reports that the threshold has been reached but the consent is not yet anchored, offers a manual synchronisation with the chain, and refuses a second signature from the same guardian. This is important

because the one-signature-per-guardian rule prevents a single guardian from satisfying the multi-signature threshold alone. When the guardian later re-enters the Consent ID, the subsystem reports Already anchored on Sepolia together with the on-chain token number (token #2 for the photographed lifecycle, token #1 for the evaluated consent).

The screenshot displays the 'Guardian Cryptographic Approval' interface. At the top, there is a header 'Guardian Cryptographic Approval'. Below it, a section titled 'Enter Target Consent ID' contains a text input field with the value '04da25f5-b16f-4d9a-af39-a78f0a83b17f'. A blue feedback message states 'Found active transaction for Patient: did:patient:5f01f823-c8e8-9e40-c911-54b7b1ad843a'. Below this, a green message indicates 'Already anchored on Sepolia - token #2'. The next section, 'Select Your Guardian DID Identity', features a dropdown menu currently showing 'did:parent:B'. At the bottom, there is a green button labeled 'Sign Consent via VC'.

Figure 10. The guardian subsystem revisited after the background job has completed: 'Already anchored on Sepolia - token #2'.

As shown in the figure above, the anchored state persists across sessions and navigation, because it is read back from the ledger rather than from the page. This provides a visible representation of the transition from a pending consent transaction to an activated, publicly recorded consent state. The SBT therefore functions in the implementation as a persistent cryptographic representation of the completed consent authorisation rather than as a transferable asset.



The guardian subsystem consequently corresponds to **Multi-Party Approval, Cryptographic Verification and Consent Activation** in the proposed architecture.

The third module is the Secure Patient Data Access module and represents the healthcare-provider side of the authorisation process.

The doctor enters an authorised Consent ID, after which the system retrieves and displays the associated consent information. The subsystem shows the patient DID, Consent ID, purpose, and current consent state:

State = ACTIVE

This is important because the doctor does not directly access patient data based solely on possession of a Consent ID. The system first evaluates whether the underlying authorisation remains valid, and it does so for every component of the consent object. The decision matrix displayed to the doctor reports the outcome of each check individually.

Enter Authorised Consent ID

f050c29a-3d92-4131-8605-63bcb1ff8d92

Consent Information

Patient

did:pat...

Consent ID

f050c2...

Purpose

Treat...

Requester jurisdiction (VL check)

AU

Decision matrix - ALLOW = VI AND VA AND VP AND VT AND VL

VI	VA	VP	VT	VL	ALLOW
PASS	PASS	PASS	PASS	PASS	PASS

Consent State: ACTIVE

Figure 12. The doctor subsystem with requester jurisdiction AU (the evaluated consent f050c29a, captured before its revocation): all five checks report PASS, ALLOW = PASS, and the consent state is ACTIVE.

As shown in the figure above, the five checks VI (identity), VA (authorisation), VP (purpose), VT (time) and VL (jurisdiction) all report PASS, and consequently ALLOW = PASS. The subsystem then presents the Authorised Data Scope, showing that only the EMR modules specified in the original consent are available. In the demonstrated transaction, the authorised modules are:

Scope = { Observation, Medication, Condition, Procedure }

The doctor must subsequently select the modules to request; the request must be a non-empty subset of the authorised scope. The system displays the requested modules and performs cryptographic verification before granting access. In this version, the verification also generates and verifies a Groth16 zero-knowledge proof, whose public inputs are a Poseidon commitment and the current time, and whose private witnesses are a secret and the expiry time; the proof establishes that the commitment is satisfied and that the current time does not exceed the expiry. Because the prover and the verifier currently run on the same server, the proof demonstrates the integration of the zero-knowledge toolchain rather than an additional privacy guarantee (Section 11). The audit ledger records the proof mode (groth16) with every access granted in the demonstrated lifecycles, and the subsystem then shows the message Cryptographic Verification Successful — Access Granted.

Patient

did:patient:5f01f...

Consent ID

04da25f5-b16f-4...

Purpose

Treatment

Requester jurisdiction (VL check)

AU

Decision matrix - ALLOW = VI AND VA AND VP AND VT AND VL

VI

VA

VP

VT

VL

ALLOW

PASS

PASS

PASS

PASS

PASS

PASS

Consent State: ACTIVE

Authorised Medical Records

OBSERVATION

	DATE	PATIENT	ENCOUNTER	CATEGORY	CODE	DESCRIPTION	VALUE	UNITS
238	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	8302-2	Body Height	172.9	cm
239	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	72514-3	Pain severity - 0-10 verbal num	0.0	[score]
240	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	29463-7	Body Weight	85.1	kg
241	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	39156-5	Body mass index (BMI) [Ratio]	28.5	kg/m2
242	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	8462-4	Diastolic Blood Pressure	80.0	mm[Hg]
243	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	8480-6	Systolic Blood Pressure	115.0	mm[Hg]
244	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	8867-4	Heart rate	88.0	/min
245	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	vital-signs	9279-1	Respiratory rate	13.0	/min
246	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	social-history	72166-2	Tobacco smoking status	Never s	None
247	2016-08-12T03:15:24Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	survey	76501-6	Within the last year have you b	No	None

Download CSV

MEDICATION

	START	STOP	PATIENT	PAYER	ENCOUNTER	CODE	
10	2015-08-07T02:26:12Z	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-958e-92483fe3e582	1049504	A
11	2015-08-07T02:26:12Z	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-958e-92483fe3e582	245134	T
12	2015-08-07T02:26:12Z	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-958e-92483fe3e582	835603	t
13	2015-08-07T02:26:12Z	2016-08-12T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-958e-92483fe3e582	1860491	1
14	2016-08-12T02:26:12Z	2017-08-18T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	1049504	A
15	2016-08-12T02:26:12Z	2017-08-18T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	245134	T
16	2016-08-12T02:26:12Z	2017-08-18T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	835603	t
17	2016-08-12T02:26:12Z	2017-08-18T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	1860491	1
18	2017-08-18T02:26:12Z	2018-08-24T02:26:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	d31fcc3-1767-390d-966a-22a5156f4219	5f01f823-c8e8-9e40-eba1-0e85ddb2ddbb	1049504	A

Figure 13. The doctor subsystem after verification (the photographed lifecycle 04da25f5, per Section 2): access granted and the authorised medical records displayed per EMR module; the Observation module's Download CSV control is visible.

CONDITION							
	START	STOP	PATIENT	ENCOUNTER	SYSTEM	CODE	DESCRIPTION
24	1977-03-16	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-3d12-6259d9e41d28	http://snomed.info/sct	40055000	Chronic sinusitis (disorder)
25	1987-07-17	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-5cb5-c909fa7070c	http://snomed.info/sct	224299000	Received higher education (finding)
26	1993-01-01	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-a174-4b0d42609415	http://snomed.info/sct	162864005	Body mass index 30+ - obesity (finding)
27	1993-12-20	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-e3e7-db542cc62f06	http://snomed.info/sct	428251008	History of appendectomy (situation)
28	1995-05-10	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-b64e-6f71fdd9cc0	http://snomed.info/sct	161744009	Past pregnancy history of miscarriage (situation)
29	1997-09-19	2016-01-01	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-94a5-c564d96e7a37	http://snomed.info/sct	706893006	Victim of intimate partner abuse (finding)
30	2005-04-23	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1340-b2438b25d99a	http://snomed.info/sct	267020005	History of tubal ligation (situation)
31	2014-02-02	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-fb96-afce40df3554	http://snomed.info/sct	82423001	Chronic pain (finding)
32	2014-02-02	None	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-fb96-afce40df3554	http://snomed.info/sct	278860009	Chronic low back pain (finding)
33	2014-08-01	2017-01-01	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-ec33-e038d0a52a26	http://snomed.info/sct	160903007	Full-time employment (finding)

Download CSV

PROCEDURE							
	START	STOP	PATIENT	ENCOUNTER	SYSTEM	CODE	DESCRIPTION
170	2016-08-12T02:26:12Z	2016-08-12T02:41:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	http://snomed.info/sct	430193006	Medication
171	2016-08-12T02:26:12Z	2016-08-12T03:15:24Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	http://snomed.info/sct	710824005	Assessment
172	2016-08-12T03:15:24Z	2016-08-12T03:26:34Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	http://snomed.info/sct	428211000124100	Assessment
173	2016-08-12T03:26:34Z	2016-08-12T03:48:35Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b18-d4c6bb1aa9c4	http://snomed.info/sct	763302001	Assessment
174	2016-08-19T02:26:12Z	2016-08-19T02:38:17Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-f486-ee6219a882da	http://snomed.info/sct	76601001	Intramuscular
175	2016-11-18T02:26:12Z	2016-11-18T02:43:39Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-c961-c9e35afa9c77	http://snomed.info/sct	76601001	Intramuscular
176	2017-02-17T02:26:12Z	2017-02-17T02:37:40Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-f45f-17f268bac16c	http://snomed.info/sct	76601001	Intramuscular
177	2017-05-19T02:26:12Z	2017-05-19T02:37:14Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-1b5b-214bb8245e13	http://snomed.info/sct	76601001	Intramuscular
178	2017-08-18T02:26:12Z	2017-08-18T02:41:12Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-eba1-0e85ddb2d8db	http://snomed.info/sct	430193006	Medication
179	2017-08-18T02:26:12Z	2017-08-18T02:57:42Z	5f01f823-c8e8-9e40-c911-54b7b1ad843a	5f01f823-c8e8-9e40-eba1-0e85ddb2d8db	http://snomed.info/sct	710824005	Assessment

Figure 14. The remaining authorised modules of the same request: the Condition and Procedure records, with the Condition module's export control visible.

The two figures above demonstrate the transition from consent verification to data-access authorisation; the checks are recorded in the audit ledger as STATE_CHECK events, one for every evaluated access request, so validity is re-established at each request rather than assumed. This distinction is central to the HALAH design. Consent and data access are not treated as identical events. Instead, the flow proceeds as follows:

Consent → Verification → AccessDecision

The doctor is therefore authorised only when the requested resources are consistent with the consent object and the consent remains active. The final Authorised Medical Records section presents the actual data modules available to the doctor. Because the subsystem separates the OBSERVATION, MEDICATION, CONDITION and PROCEDURE modules, it provides a direct visual demonstration of fine-grained EMR access control.

Thus, the doctor subsystem corresponds to **Consent-State Validation, Scope Enforcement and Authorised Data Access**.

5. Negative Demonstration: Jurisdiction Violation

The fourth part is the negative demonstration. This is important because a consent framework must be evaluated not only on whether it grants legitimate access, but also on whether it refuses illegitimate access. The same doctor therefore repeated the request for the evaluated consent while declaring the requester jurisdiction as SA, whereas the consent was issued for AU.

The screenshot displays a web interface for a doctor subsystem. At the top, there is a field labeled "Enter Authorised Consent ID" containing the value "f050c29a-3d92-4131-8605-63bcb1ff8d92". Below this, the "Consent Information" section shows three boxes: "Patient" with "did:pat...", "Consent ID" with "f050c2...", and "Purpose" with "Treat...". A dropdown menu for "Requester jurisdiction (VL check)" is set to "SA". Below this, a "Decision matrix" table is shown with the header "Decision matrix - ALLOW = VI AND VA AND VP AND VT AND VL". The table has six columns: VI, VA, VP, VT, VL, and ALLOW. The rows show the results: VI is PASS, VA is PASS, VP is PASS, VT is PASS, VL is FAIL, and ALLOW is FAIL. At the bottom, a green bar indicates "Consent State: ACTIVE".

VI	VA	VP	VT	VL	ALLOW
PASS	PASS	PASS	PASS	FAIL	FAIL

Consent State: ACTIVE

Figure 15. The doctor subsystem with requester jurisdiction SA: VL reports FAIL and consequently ALLOW = FAIL, although the consent state remains ACTIVE.

As shown in the figure above, the decision matrix immediately reports VL = FAIL and consequently ALLOW = FAIL, even though the consent itself is still ACTIVE, the guardian signatures remain valid and all other checks pass. This is important because it demonstrates that the access decision is taken over the complete consent tuple rather than over the consent state alone.




Figure 16. The refused request: 'Security Exception: Access Denied by ZK-Policy. Failed checks: VL'.

As shown in the figure above, when the doctor submits the request, access is refused and the failed check is named explicitly. The corresponding audit-ledger entry records the result DENIED together with the complete decision matrix, so that the refusal is itself auditable. This is important because the jurisdiction check is included in the access decision rather than merely displayed.

This demonstration corresponds to **Jurisdictional Constraint Enforcement and Fail-Closed Access Control**.

6. Consent Revocation

The fifth module is the Consent Revocation module. This module operationalises the enforcement component of the consent object, which requires that a patient can withdraw consent and that the withdrawal takes effect for every subsequent request. In the patient's My Consents view, each consent is listed with its state, signature count and token. The patient then selects Revoke, after which the system updates the application state and submits a revoke transaction to the contract on Sepolia.

My Consents

2502632b... → did:hospital:001	REVOKED	0/2 sigs - token: -	REVOKED
aca837a1... → did:hospital:001	REVOKED	0/2 sigs - token: -	REVOKED
cd9a24bd... → did:hospital:001	REVOKED	2/2 sigs - token: SBT-LOCAL- cd9a24bd	REVOKED
011bbb21... → did:hospital:001	REVOKED	2/2 sigs - token: SBT-8	REVOKED
0975c645... → did:hospital:001	PENDING_SIGNATURE	0/2 sigs - token: -	<button>Revoke</button>
f050c29a... → did:hospital:001	ACTIVE	2/2 sigs - token: SBT-1	<button>Revoke</button>

Revoking on Sepolia - waiting for block confirmation...

Figure 17. The patient subsystem during revocation: 'Revoking on Sepolia - waiting for block confirmation...'.

As shown in the figure above, the withdrawal is submitted as a blockchain transaction and the subsystem waits for the block confirmation before reporting the final state.

My Consents			
2502632b... → did:hospital:001	REVOKED	0/2 sigs - token: -	REVOKED
aca837a1... → did:hospital:001	REVOKED	0/2 sigs - token: -	REVOKED
cd9a24bd... → did:hospital:001	REVOKED	2/2 sigs - token: SBT-LOCAL- cd9a24bd	REVOKED
011bbb21... → did:hospital:001	REVOKED	2/2 sigs - token: SBT-8	REVOKED
0975c645... → did:hospital:001	PENDING_SIGNED	0/2 sigs - token: -	<button>Revoke</button>
f050c29a... → did:hospital:001	REVOKED	2/2 sigs - token: SBT-1	REVOKED

Figure 18. The patient subsystem after revocation: the evaluated consent f050c29a is REVOKED with token #1 (displayed as SBT-1). The other rows are earlier trial consents.

As shown in the figure above, the revoked consent is displayed as REVOKED together with its on-chain token number. The revocation was confirmed on Sepolia in block 11,771,307, and from that point the contract itself reports the token as no longer valid, so any verifier that reads the chain observes the withdrawal.

Secure Patient Data Access

Enter Authorised Consent ID

Consent Information

Patient did:patient:fe62...	Consent ID f050c29a-3d92-...	Purpose Treatment
---------------------------------------	--	-----------------------------

Requester jurisdiction (VL check)

AU

Decision matrix - ALLOW = VI AND VA AND VP AND VT AND VL

VI	VA	VP	VT	VL	ALLOW
PASS	FAIL	PASS	PASS	PASS	FAIL

Consent is not active. Current state: REVOKED

The Doctor cannot access patient data because the consent is not currently valid.

Figure 19. The doctor subsystem after revocation: VA reports FAIL and the consent is reported as 'not active. Current state: REVOKED'.

As shown in the figure above, when the doctor subsequently enters the same Consent ID, the authorisation check VA fails and the subsystem reports that the consent is not active. Consequently, revocation is not merely a change of display: it removes the authorisation on which every later access decision depends.




Figure 20. The revocation transaction on Sepolia Etherscan: status Success, block 11,771,307, decoded input 'Function: revoke(uint256 tokenId)' with tokenId = 1.

As shown in the figure above, the revocation is again a publicly verifiable transaction, whose decoded input names the contract function revoke and the token identifier. The transaction can be inspected at [Etherscan: revoke transaction](#). The revocation subsystem therefore corresponds to **Enforcement State Management and Consent Withdrawal**.

7. Blockchain Audit & Consent Lifecycle for Auditor

The sixth major module is the Blockchain Audit & Consent Lifecycle module. This subsystem provides an independent view of the complete consent process and corresponds to the auditability and accountability component of the HALAH framework.




Figure 21. The Consent Lifecycle reconstruction for the evaluated consent: the guardian signatures, MINT_SBT and ONCHAIN_MINT on the left, and the STATE_CHECK, DENIED, REVOKE_CONSENT and ONCHAIN_REVOKE events on the right.

As shown in the figure above, the lifecycle view presents each event as a card with its timestamp, actor, role, action and result, so the chronological sequence of the authorisation process can be read directly.




Figure 22. The auditor subsystem with the evaluated consent selected: aggregate indicators and the Detailed Audit Records, in which the on-chain events carry their transaction hashes and block numbers.

As shown in the figure above, the system first provides aggregate indicators including:

Total Events = 60 Consent Events = 8 Access Requests = 9 On-chain Anchors = 5

These indicators give the auditor an immediate overview of the recorded system activity and of how many events are anchored on the public chain. The five anchors comprise the mint and revocation of the evaluated consent (token #1), the mint of the photographed lifecycle (token #2), and the mint and revocation of an earlier trial consent on the previous contract; the nine access requests comprise the granted, refused and reproduced requests of the two lifecycles together with three granted requests recorded for the earlier trial consents. More importantly, the Consent Lifecycle section reconstructs the sequence of events associated with a particular consent. The reconstructed records include CREATE_CONSENT performed by the patient, followed by SIGN_CONSENT performed by each guardian, followed by MINT_SBT and ONCHAIN_MINT performed by the smart contract; in the figure the detailed table is scrolled to the on-chain events, whose rows carry the transaction hashes. The subsequent STATE_CHECK system events demonstrate that the Consent Engine continuously evaluates the state of the authorisation. The doctor then generates DATA_ACCESS with the result GRANTED, later DATA_ACCESS with the result DENIED when the jurisdiction check fails, and finally the patient generates REVOKE_CONSENT followed by ONCHAIN_REVOKE performed by the smart contract.

This produces an explicit chain of evidence as

*Patient → Guardian_A → Guardian_B → SmartContract(mint) → ConsentEngine → Doctor(GRANTED)
→ Doctor(DENIED) → Patient(revoke) → SmartContract(revoke)*

The audit subsystem therefore allows an auditor to reconstruct not only who accessed the data, but also why that access was permitted or refused, because each access event can be associated with the preceding consent creation, guardian approvals, on-chain activation, state checks and the decision matrix that was in force at that moment.

This corresponds to the proposed requirement for **traceability, accountability and non-repudiable consent evidence**.

8. Detailed Audit Records

The Detailed Audit Records component provides a lower-level view of the events represented in the lifecycle subsystem.

Where the lifecycle view is primarily designed to communicate the chronological sequence of the authorisation process, the detailed audit view provides the underlying event-level evidence. Each event can be associated with attributes such as actor, role, action, result, timestamp, consent context and, for on-chain events, the transaction hash and block number. As shown in the auditor figure above, the ONCHAIN_MINT and ONCHAIN_REVOKE rows carry the hashes of the two Sepolia transactions presented in Sections 3 and 6, so the ledger and the public chain describe the same events.

This separation is useful because different stakeholders require different levels of information. A clinician may only need to know that a consent is active and valid, whereas an auditor may need to establish precisely when an approval occurred, which identity performed it, and what authorisation decision followed.

The subsystem therefore implements the distinction between operational access information and forensic/audit information.

9. Complete Blockchain Audit Ledger and Independent Verification

The Complete Blockchain Audit Ledger provides the most comprehensive representation of the recorded consent history. This component demonstrates that the audit mechanism is not limited to successful data-access events. Instead, the system records the broader lifecycle of the consent, including creation, signatures, state validation, smart-contract actions, refused requests and revocations. Consequently, the ledger provides the evidentiary foundation for evaluating several properties of the proposed framework:

Accountability + Traceability + Integrity + Non-repudiation

A ledger kept by the application could in principle contain fabricated entries. Consequently, the implementation provides an independent verification tool. The tool re-reads the ledger and, for every event that carries a transaction hash, fetches the corresponding receipt directly from Sepolia and checks that the transaction exists, succeeded, and was included in the recorded block; for every consent anchored on the current contract it then reads the token back and compares the on-chain revocation state with the local state; the earlier trial token resides on the superseded contract and is reported and skipped.



Figure 23. The final verdict of the independent verification, re-executed after the second lifecycle: RESULT: ALL CHECKS PASSED.

As shown in the figure above, the verification was re-executed after the second lifecycle and reports ALL CHECKS PASSED: every recorded transaction was found on Sepolia in its recorded block, and for both tokens on the current contract the revocation state stored by the application matches the state stored by the contract (token #1 revoked, token #2 not revoked). Accordingly, the demonstrated sequence shows that the doctor receives a GRANTED result only while the consent is in the ACTIVE state, and a DENIED or 'not active' result otherwise. This provides an implementation-level demonstration that access decisions are linked to the consent lifecycle rather than being independent application events, and that the recorded lifecycle is consistent with the public chain.

10. Correspondence Between Subsystems and the HALAH Framework

The subsystems collectively implement the principal stages of the proposed framework:

HALAH Framework Component	Implementation Subsystem	Main Function
Consent Object Construction	Create Smart Consent Contract	Defines patient, authorised doctor, data scope, guardians, jurisdiction and temporal validity
Identity & Authorisation	Guardian Cryptographic Approval	Verifies guardian identities and EIP-712 signatures
Multi-party Consent	Guardian Cryptographic Approval	Implements the 2-of-2 approval condition
Consent Activation	Guardian Cryptographic Approval	Mints the SBT on Sepolia and marks the consent as fully activated

HALAH Framework Component	Implementation Subsystem	Main Function
Consent-State Management	Secure Patient Data Access	Checks whether the consent is ACTIVE
Scope Enforcement	Secure Patient Data Access	Restricts access to authorised EMR modules
Cryptographic Access Control	Secure Patient Data Access	Verifies the request, including a Groth16 proof, before granting data
Jurisdictional Constraint (L)	Secure Patient Data Access	Refuses requests whose declared jurisdiction differs from the consent
Healthcare Data Access	Secure Patient Data Access	Provides the authorised Observation, Medication, Condition and Procedure records
Enforcement / Revocation (E)	My Consents (Patient)	Revokes the consent locally and on-chain
Lifecycle Traceability	Blockchain Audit & Consent Lifecycle	Reconstructs the chronological consent process
Accountability	Detailed Audit Records	Provides event-level evidence with transaction hashes
Ledger Integrity	Complete Ledger + independent verification	Confirms the recorded history against Sepolia

This mapping demonstrates that the implementation is not merely a collection of independent user-subsystem modules. Rather, the modules correspond to successive stages of the proposed authorisation protocol.

11. Overall System Demonstration

Taken together, the subsystems demonstrate an end-to-end implementation of the proposed HALAH authorisation workflow on a public blockchain. The patient first establishes the consent conditions through the Smart Consent Contract subsystem. The designated guardians then independently authenticate and provide the required cryptographic approvals. Once the multi-signature condition is satisfied, the consent is activated and represented by an SBT minted on Sepolia. The authorised doctor subsequently submits an access request, which is evaluated against the patient's identity, consent state, authorised data scope, temporal validity and jurisdiction. Only when these conditions are satisfied does the system provide access to the specified EMR modules; an out-of-jurisdiction request is refused with the failed check named. The patient finally revokes the consent, the revocation is recorded on-chain, and the complete sequence is exposed through the auditor subsystem and re-verified independently against the chain.

C → MS → SBT_chain → StateCheck → AccessDecision → EMR → Revoke_chain → Audit → Verify

where C denotes consent creation, MS multi-signature approval, SBT_chain on-chain consent activation, StateCheck lifecycle validation, AccessDecision authorisation enforcement over the full consent tuple, EMR authorised medical-record access, Revoke_chain on-chain revocation, Audit immutable lifecycle recording, and Verify independent verification against Sepolia.

The demonstrated prototype makes several simplifications that are acceptable for a research demonstration but would require strengthening before deployment. The guardian signing keys are derived deterministically from the guardian DIDs so that the prototype can sign without wallets; in production each guardian would sign the same typed data with a wallet-held key registered against their DID. The doctor's identity and jurisdiction are declared in the interface rather than authenticated, and the Groth16 proof is generated and verified by the same server, so it currently demonstrates the integration of the zero-knowledge toolchain rather than an additional privacy guarantee. These aspects define the immediate future work of the project.

From a research-implementation perspective, the most significant feature of the presented subsystems is therefore the continuity between consent specification, multi-party authorisation, public on-chain activation and revocation, access enforcement and independently verifiable audit evidence. The user subsystems provide a visible representation of this continuity, allowing the proposed HALAH model to be demonstrated as an operational authorisation workflow on a public network rather than only as a conceptual framework.

Appendix: Verification Links

Contract:

<https://sepolia.etherscan.io/address/0x0EC3617581DEC63A7f2bb162DC14d088916ADc73>

Consent activation (mint of token #1):

<https://sepolia.etherscan.io/tx/0x8be1b99e9b7054d427bdee0a0b5cc56ae99030a399f4b11d3629ed5d98daf13d>

Consent activation (mint of token #2, photographed lifecycle):

<https://sepolia.etherscan.io/tx/0x25ef5e2f0046735dcb01ff7b68875b760bdf88ad0fa3fedc9bfb910769d4c210>

Consent revocation (token #1):

<https://sepolia.etherscan.io/tx/0x017efb9dc6acad9733fa05c19408c0166c9c0645e83b6ffdc41c4b3b85ddceaa>

Full audit-ledger export: evidence/sepolia_audit_ledger_2026-09-24.csv;
deployment and run record: evidence/sepolia_deploy_v3_2026-09-24.txt available in the project repository.