



# ATLANTIC DSG FLUID

Fully Synthetic DSG Fluid



## DESCRIPTION

ATLANTIC DSG FLUID is a fully synthetic lubricant formulated from premium quality base oils, specifically designed for the dual clutch transmissions (DCT) found in modern passenger vehicles. It guarantees smooth and reliable performance of these gearboxes.

## APPLICATIONS

ATLANTIC DSG FLUID is primarily designed for the DSG (Direct Shift Gearbox) used in VAG vehicles. However, it is also compatible with various other 6-speed DCT transmissions, including those found in Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, and BMW Drivelogic 7-speed systems, among others.

## PERFORMANCE FEATURES AND BENEFITS

- Frictional properties: very smooth gear shifting, no vibration
- Anti-wear protection: greatly prolongs the lifespan of the transmission
- Extended oil life: offers outstanding thermal and oxidation resistance

## RECOMMENDATIONS / SPECIFICATIONS

API GL-4, BENTLEY G 052 524-B2, CHRYSLER 68044345EA, DTFR 13C130, FERRARI TF DCT-F3, FIAT 9.55550-DA11/9.55550-MZ2/9.55550-MZ6, BMW 83220306816/83220397244/83220440214/83222147477/83222148578/83222148579/83222167666/83222409710/ BMW 83222433157/83225B3AC81/DCTF-1/DCTF-2/DTF 1/FFL-4/MTF LT-3/MTF LT-5, CHERY 730DHB/DHC 7DCT300/738DHA 7DCT380/9009011085, FORD F-DC/WSS-M2C200-D2/FORD WSS-M2C200-D3/WSS-M2C200-E1/WSS-M2C218-A1/WSS-M2C936-A, GM DEXRON DCT/FFL-4, GREAT WALL GW7DCT1/GWM 7DCT450, HONDA MTF III, HYUNDAI 04300-2N110 WDHO-1, KIA 04300-2N110 WDHO-1, KUNLUN DCTF-7S, MB 236.21/236.22/236.24/236.25/239.21/239.22, MB SLS A0019898603, MCLAREN FFL-4, MITSUBISHI DIAMOND QUEEN SSTF-1, NISSAN 999MP-6TRT00P/DCT FLUID/GR6/GT-R R35/LV MTF-1, NISSAN R35 SPECIAL, PSA 1618078480/9730 A8/9734 S2/JWS 2271, PUNCH DT2, SINOPEC DCTF-GS, STELLANTIS 16 934 837 80, SUZUKI 99000-22B27-036, TOYOTA 0888581001/ TOYOTA JWS 2271/LF/LV 75W MT, ZF 0671090545, RENAULT 7711579456/7711785243/ RENAULT BOT450 EDC 6-Speed/DC4/DW5/DW6, PORSCHE 999.917.080.01/999.917.546.00/TF 0870/ PORSCHE 000.043.20/000.043.207.29/000.043.207.30/000.043.210.44/000.043.305.63/971.094.307.02A/999.917.080.00/ VOLVO 1161520-7/1161839/32240415/32240419/BOT341 #1161838/D1/D2, VW G 052 171/G 052 178/G 052 182/G 052 512/ VW G 052 513/G 052 524/G 052 527/G 052 529/G 052 726/G 052 798/G 055 512/G 055 524/G 055 529/G 055 549/G 060 726/G 070 726/G009317/TL 521 82

Check owners' manual before use

## TYPICAL TECHNICAL PROPERTIES

|   |              |
|---|--------------|
| PRODUCTS CODE:  | TO-ATF-25019 |
| Color, VISUAL   | AMBER        |
| Density at 15°C, g/ml, ASTM D4052                           | 0.848        |
| Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445  | 33.6         |
| Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445 | 6.87         |
| Viscosity Index, ASTM D2270                                 | 170          |
| Flash Point(COC), °C, ASTM D92                              | 200          |
| Pour Point, °C, ASTM D97                                    | -45          |
| Brookfield viscosity at -40°C, mPa.s, ASTM D2983            | 11,000       |

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/ATF/0029 /0\*, 20.01.25, Page 1/1

\* supersedes all previous versions

**Packing :** 700 ml ,800 ml , 1L , 2L, 3L, 4L, 5L, 6.5L, 7L, 8L,16L,18L, 20L, 25L, 200L, 205L, 208L, 210L