



ATLANTIC SYNTHECH ENGINE OIL

SAE 0W-30 LL 1 FE A5/B5



(Fully Synthetic Motor Oils)

DESCRIPTION

ATLANTIC SYNTHECH ENGINE OIL LL 1 FE SAE 0W-30 A5/B5 is a fully synthetic lubricant made with specially chosen high-quality base oils. It was designed to meet the specific needs of Volvo passenger cars. This oil provides increased lubrication and improves fuel economy, leading to lower fuel consumption and a longer engine life.

APPLICATIONS

We recommend ATLANTIC SYNTHECH ENGINE OIL 1 FE SAE 0W-30 A5/B5 for newer gasoline and diesel Volvo cars with 5-cylinder engines.

PERFORMANCE FEATURES AND BENEFITS

- It keeps your engine clean for optimal performance.
- It provides excellent fuel economy and reduces CO2 emissions.
- It flows well at low temperatures for quick and smooth engines and easy cold starts.

RECOMMENDATIONS / SPECIFICATIONS

International Standards : API SN/CF, ACEA A5/B5, A7/B7

Meets or exceeds: BMW LONGLIFE-01 FE, RENAULT RN 0700, VOLVO VCC 95200377, VW 503 00, VW 506 00, VW 506 01

TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	0W-30
PRODUCTS CODE:	PCMO-24014
Density at 15°C, g/ml, ASTM D4052	0.841
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	5750 @-35°C
Kinematic Viscosity at 40°C, mm²/s, ASTM D445	53.7
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	10.1
Viscosity Index, ASTM D2270	178
Flash Point(COC), °C, ASTM D92	226
Pour Point, °C, ASTM D97	-45
Total Base Number (TBN), mg KOH/g, ASTM D2896	10
Sulphated Ash, %wt, ASTM D874	1.09

Note: These characteristics are typical of current production. While future production will conform to Atlantic's specification, variations in these characteristics may occur.

ATL/PDS/AL/097/01*, 04.07.24, Page 1/1

* supersedes all previous versions

Packing : 700 ml ,800 ml , 1L , 2L, 3L, 4L, 5L, 6.5L, 7L, 8L,16L,18L, 20L, 25L, 200L, 205L, 208L, 210L